

Landscape Irrigation Products2020 Catalog















Preserving beauty while conserving water.

That's intelligent.

At Rain Bird, we believe it is our responsibility to develop products and technologies that use water efficiently. Our commitment also extends to education, training and services for our industry and our communities. Through innovative product development, Rain Bird is helping sustain healthier landscapes—and a healthier planet. A lush lawn or colorful garden can also be highly water-efficient. Every Rain Bird product is a testament to that truth. From water-saving nozzles to sprays with pressureregulating stems to leading-edge Smart Control Technology, Rain Bird products make the most of every drop, delivering superior results with less water. Keeping the world and your backyard beautiful. That's The Intelligent Use of Water." The need to conserve water has never been greater. We want to do even more, and with your help, we can.

The Intelligent Use of Water™

Water efficient irrigation technology for every landscape application

When you design and install Rain Bird complete irrigation solutions, you can be confident knowing that the system will perform better and last longer for many years to come. No matter what your irrigation needs are, Rain Bird has a solution that will help save water for every application in your next green project.



Spray Bodies Page 5



Central Controls

Page 101



Spray & Rotary **Nozzles**

Page 14



Drip Irrigation

Page 111



Rotors

Page 38



Pump Stations

Page 164



Valves

Page 62



Drainage Products

Page 172



Controllers

Page 83



Resources

Page 183





Together, we can make a difference

At Rain Bird, we believe that saving water is a responsibility that we all share. Our industry can have a tremendous impact on water conservation by installing more efficient systems and teaching customers how to use them correctly. By working together, we can really make a difference.

Rain Bird's 25 Ways offers practical, effective tips and advice drawn from the company's 80-plus years of experience in the irrigation industry. Available at 25ways.rainbird.com, these resources can be used anywhere and by anyone who wants to improve their watering efficiency.

Water Saving Tips from Rain Bird

Visit 25ways.rainbird.com for a complete list of water saving tips and techniques in each of the following categories.



Improve Your Existing System




Water Only At The Right Times



Don't Overwater



Use The Right Products



Keep Your Water In Place



Update Your Landscape



Spray Bodies

Major Products														
Primary Applications	1802, 1804, 1806	1812	1800 PRS	1800 SAM	1800 SAM-PRS	1800 SAM- PRS-45	US-400	1300/ 1400 Bubblers	PA-80 PA-8S PA-8S-NP PA-8S-PRS PA-8S-P45	RD-04, RD-06	RD-12	RD1800 SAM- PRS	RD1800 SAM- PRS-F	RD1800 SAM- PRS-45-F
Turfgrass	•		•	•	•	•	•			•		•	•	•
Slopes				•	•	•	•					•	•	•
Ground Cover/Shrubs					•	•	•	•	•				•	
High Pressure Systems			•		•	•		•	•	•	•	•	•	•
Low Pressure Systems														
High Wind Areas	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Non-Potable Water									•			•	•	•
Vandalism/Damage Prone													•	•
Dirty Water														



Water Saving Tips

- The patented, built-in PRS regulator maintains optimal operating pressure and restricts water loss by up to 70% if a nozzle is removed or damaged. It also ends water waste by eliminating misting and fogging caused by high pressure.
- Save water, stop low head drainage, and reduce water hammer by preventing water from draining out of pipes after irrigation with 1800/RD1800
 Series Sprays featuring Seal-A-Matic™ (SAM) check valves.
- Exclusive Flow Shield Technology available in the RD1800 Series provides up to 90% reduction in water loss when a nozzle is removed, preventing potentially costly and unacceptable run-off.



UNI-Spray[™] Series

Compact and reliable spray heads for any application

Features

- Small exposed cover makes the unit virtually invisible for more attractive landscapes
- Constructed of durable materials including corrosion resistant stainless steel, assuring long product life even in high pressure or surge conditions
- Pressure-activated wiper seal prevents excessive flow-by and water waste and keeps debris from entering upon retraction
- Two-piece ratchet mechanism allows easy nozzle pattern alignment and provides added durability
- Three Year Trade Warranty

Operating Range (for pre-installed nozzle choices)

- Spacing:
 - 8' HE-VAN Series: 6 to 8 feet (1.8 to 2.4m)
 - 10' HE-VAN Series: 8 to 10 feet (2.4 to 3.0m)
 - 12' HE-VAN Series: 9 to 12 feet (2.7 to 3.7m)
 - 15' HE-VAN Series: 12 to 15 feet (3.7 to 4.6m)
- Pressure: 15 to 70 psi (1.0 to 4.8 bar)
- Optimum pressure: 30 psi (2.1 bar)
- Adjustable nozzle arc range: 0° 360°

Specifications

Flow-by: 0 at 10 psi (0.75 bar) or greater;
 0.20 gpm (0.04 m³/h; 0.60 l/m) otherwise

Models*


• US400: 4" pop-up height (10.2cm)

Models with High-Efficiency Nozzles Pre-Attached*


- US408HE: 4" pop-up height (10.2cm) with HE-VAN-08 attached
- US410HE: 4" pop-up height (10.2cm) with HE-VAN-10 attached
- US412HE: 4" pop-up height (10.2cm) with HE-VAN-12 attached
- US415HE: 4" pop-up height (10.2cm) with HE-VAN-15 attached



High Efficiency Variable Arc Nozzles (8, 10, 12, or 15 feet) are available pre-installed







^{*} The UNI-Spray accepts all Rain Bird nozzles

1800[®] Series

The #1 irrigation spray head in the world

- · Co-molded wiper seal provides unmatched resistance to grit, pressure and the environment
- · Constructed of time-proven UV-resistant plastic and corrosion resistant stainless steel parts, ensuring long product life
- Precision controlled flush at pop-down clears debris from unit, assuring positive stem retraction in all soil types
- Two-piece ratchet mechanism allows easy nozzle pattern alignment and provides added durability
- · Five Year Trade Warranty

Operating Range

- Spacing: 2.5 to 24 feet (0.8 to 7.3m)**
- Pressure: 15 to 70 psi (1.0 to 4.8 bar)


Specifications

• Flow-by: 0 gpm at 8 psi (0.6 bar) or greater; 0.10 gpm (0.02 m³/h; 0.36 l/m) otherwise

Dimensions/Models

- · ½" (15/21) NPT female threaded inlet
- · Models and height:
- 1802: 4" (10.2 cm) body height; 2" pop-up height (5.1 cm)
- 1804: 6" (15.2 cm) body height; 4" pop-up height (10.2 cm)
- 1806: 93/8" (23.8 cm) body height; 6" pop-up height (15.2 cm)
- 1812: 16" (40.6 cm) body height; 12" pop-up height (30.5 cm)
- Exposed surface diameter: 21/4" (5.7 cm)
- * 1806 and 1812-SAM, SAMPRS, and SAM-PRS-45 units do not have a side inlet
- ** 2.5 to 15 feet with standard Rain Bird Spray Head Nozzles (SQ, U-Series, HE-VAN) 8 to 24 feet with Rain Bird Rotary Nozzles







1804 SAM-PRS

SAM: Seal-A-Matic™ check valve PRS: Pressure regulator

Pop-up Height 1802: 2" pop-up height (5.1 cm) 1804: 4" pop-up height (10.2 cm) 1806: 6" pop-up height (15.2 cm) 1812: 12" pop-up height (30.5 cm)

1800 Series Spray Bodies





1800°-SAM, 1800°-PRS, 1800°-SAM-PRS, 1800°-SAM-P45 Series

4", 6", 12" (10.2 cm, 15.2 cm, 30.5 cm)

Features

- 1800°-SAM Series: Built-in Seal-A-Matic™ (SAM) check valve. Eliminates the need for under-the-head check valves. Traps water in lateral pipes in elevation changes of up to 14 feet (4.2 m). Reduces wear on system components by minimizing water hammer during start-up
- 1800°-PRS Series: Maintains constant outlet pressure at 30 psi (2.1 bar). PRS pressure regulator built into the stem simplifies system design. Eliminates misting and fogging caused by high pressure. Saves time and money
- 1800°-SAM-PRS Series: Incorporates all 1800 Series SAM and PRS features. Meets the needs of all spray areas, regardless of changing elevation or water pressures
- 1800°-SAM-P45 Series: Maintains constant outlet pressure at 45 psi (3.1 bar) at varying inlet pressures. Ensures maximum spray body and nozzle performance, even with varying inlet pressures. Maintains constant pressure regardless of nozzle used

Specifications

- SAM capability: holds up to 14 feet (4.2 m) of head; 6 psi (0.4 bar)
- PRS models regulate nozzle pressure to an average 30 or 45 psi (2.1 or 3.1 bar) with inlet pressures of up to 70 psi (4.8 bar)
- Flow-by: 0 gpm at 8 psi (0.6 bar) or greater;
 0.10 gpm (0.02 m³/h; 0.36 l/m) otherwise
- · Installation: side or bottom inlet
- · Side inlet installation not recommended in freezing climates
- Five Year Trade Warranty

1800-SAM Models

- 1804-SAM: 4" pop-up height (10.2 cm)
- 1806-SAM: 6" pop-up height (15.2 cm)
- 1812-SAM: 12" pop-up height (30.5 cm)

1800-PRS Models

- 1804 PRS: 4" pop-up height (10.2 cm)
- 1806 PRS: 6" pop-up height (15.2 cm)
- 1812 PRS: 12" pop-up height (30.5 cm)

1800-SAM-PRS Models

- 1804-SAM-PRS: 4" pop-up height (10.2 cm)
- 1806-SAM-PRS: 6" pop-up height (15.2 cm)
- 1812-SAM-PRS: 12" pop-up height (30.5 cm)

1800-SAM-P45 Models

- 1804-SAM-P45: 4" pop-up height (10.2 cm)
- 1806-SAM-P45: 6" pop-up height (15.2 cm)
- 1812-SAM-P45: 12" pop-up height (30.5 cm)



Operating Range

- Spacing: 2.5 to 24 feet (0.8 to 7.3m)*
- Pressure: 15 to 70 psi (1.0 to 4.8 bar)










Built in Seal-A-Matic check valve prevents low-head drainage, ideal for use in changing



Patented pressure regulator in stem compensates for high or fluctuating water pressure to ensure maximum performance



Top-of-the-line spray head includes all the features of the SAM and PRS series, ideal regardless of pressure or elevation

* 2.5 to 18 feet with standard Rain Bird Spray Head Nozzles (SQ, MPR. VAN. U-Series). 13 to 24 feet with Rain Bird Rotary Nozzles

Service

Stream

Indication

RD1800[™] Series Spray Heads

4", 6", 12" (10.2 cm; 15.2 cm; 30.5 cm)

To one EPA Colored Col

When using 30psi and 45psi pressure regulating spray heads

Features

- Patented, Triple-Blade Wiper Seal precisely balances flushing, flow-by and debris protection to optimize performance and durability at pop-up and retraction. Precision-controlled flushing at pop-up and retraction clears debris, ensuring positive stem retraction in all soil types
- Unique debris pockets hold grit in place, removing it from circulation and preventing long-term damage. Parts resistant to corrosion in treated recycled water containing chlorine
- RD1800™ SAM PRS Series: Incorporates all RD1800 Series SAM and PRS features. Meets the needs of all spray areas, regardless of changing elevation or water pressures
- RD1800™ Flow-Shield™ Series: Provides low flow vertical water jet visible from +200′ line of sight when a nozzle has been removed
- RD1800[™] Non-Potable Water Series: Provides an alternative to clip-on caps and molded purple covers. Easy-to-read English "DO NOT DRINK", Spanish "NO BEBA" warnings, and international do not drink symbol

Operating Range

- Spacing: 2.5 to 24 feet (0.8 to 7.3 m)
- Pressure: 15 to 100 psi (1.0 to 6.9 bar)

Specifications

- SAM capability: Holds up to 14 feet (4.2 m) of head; 6 psi (0.3 bar)
- Flow-by: SAM Models: 0 at 15 psi (1.0 bar) or greater; 0.5 gpm (0.1 m³/h; 0.03 l/s) otherwise
 - All Other Models: 0 at 10 psi (0.7 bar) or greater; 0.5 gpm (0.1 m³/h; 0.03 l/s) otherwise
- SAM-PRS models regulate nozzle pressure to an average 30 or 45 psi (2.1 or 3.1 bar) with inlet pressures of up to 100 psi (6.9 bar)
- Side inlets featured on non Seal-A-Matic[™] (SAM) models only
- Five-year trade warranty

Dimensions

• 1/2" (15/21) NPT female threaded inlet

Models		
4"	6"	12"
RD04	-	-
RD04-NP	-	-
RD04-S-P-30	RD06-S-P-30	RD12-S-P-30
RD04-S-P-30-NP	RD06-S-P-30-NP	RD12-S-P-30-NP
RD04-S-P-30-F	RD06-S-P30-F	RD12-S-P-30-F
RD04-S-P-30-F-NP	RD06-S-P-30-F-NP	RD12-S-P-30-F-NP
RD04-S-P-45-NP	RD06-S-P-45-NP	RD12-S-P-45-NP
RD04-S-P-45-F	RD06-S-P-45-F	RD12-S-P-45-F
RD04-S-P-45-F-NP	RD06-S-P-45-F-NP	RD12-S-P-45-F-NP



Exclusive

Flow-Shield™

Technology

RD1800 Series




Standard Cover



Non-Potable Cover





RD-04: 4 (10 cm) pop-up height RD-06: 6"(15 cm) pop-up height RD-12: 12" (30.5 cm) pop-up height

Notes:

Flow-Shield™ Technology available in P30 and P45 models only.

Specify sprinkler bodies and nozzles separately.



1800® NP Cover

Non-Potable 1800 Spray Head Cover

Features

- Designed for excellent retention on 1800 Series Spray Body covers
- Purple plastic cover for easy identification of non-potable water system
- Marked with "Do Not Drink!" warning in both English and Spanish
- Snaps onto all 1800[®] Series Spray Body covers

Model

1800-NPCAP



PA

Plastic Shrub Adapter

Features

- Adapts Rain Bird Nozzles for use with ½" (15/21) NPT threaded risers
- Accepts protective, nonclogging 1800 Series filter screen (shipped with nozzle) and PCS Series screens
- Durable, non-corrosive plastic construction
- Non-Potable Plastic Shrub Adapter

Specifications

- $\frac{1}{2}$ " (15/21) female inlet threads
- Fine top threads accept all Rain Bird nozzles

Model

PA-8SPA-8S-NP





PA-8S-NP

....

PA-80

Plastic Adapter

Features

- Adapts Rain Bird Spray Bodies for use with any 1/2" (15/21) FPT bubbler or spray nozzle
- Rugged, UV-resistant thermoplastic construction
- · Easy to install; no tools required

Dimensions

Height: 1½" (3.8 cm); 0.8" (2.0 cm) above 1800 cap

Model

PA-80



1800®-EXT

Plastic Extension

Features

- UV-resistant thermoplastic construction for long life
- Fits all Rain Bird Spray Bodies and Nozzles. Exception: Cannot be used with bubblers

Model

1800-EXT



PA-8S-PRS & PA-8S-P45

30 psi and 45 psi Pressure Regulating Shrub Adapters

Features

- Adapts nozzles for use with 1/2" (15/21) NPT threaded risers
- Patented PRS pressure regulator built into the stem. No parts to be installed at the site. Saves time and money
 - Maintains constant pressure at 30 psi (2,1 bar) or 45 psi (3,1 bar)
 - Restricts water loss by up to 70% if nozzle is removed or damaged.
 Saves water and money. Reduces liability. Recommended for vandal-prone areas
- · Fits all Rain Bird plastic nozzles
- Rugged thermoplastic construction resists UV rays

Operating Range

- Pressure: 15 to 70 psi (1.0 to 4.8 bar)
- Flow: 0.2 to 4.0 gpm (0.05 to 0.91 m³/h; 0.06 to 15.0 l/m)

Specifications

- $\frac{1}{2}$ " (15/21) female inlet threads
- · Fine top threads accept all Rain Bird nozzles
- Height: 5¹/₄" (13.3 cm)

Models

- PA-8S-PRS
- PA-8S-P45



PA-8S-PRS & PA-8S-P45

1800 PCS

Pressure Compensating Screens

Features


- Compensates* for pressure variations
- · Eliminates fogging and water waste caused by high pressures
- Nozzles can be matched with screens to create short-throw, reducedradius patterns and/or flush-mounted bubblers
- Color-coded for easy identification
- Use with all 1800 Series plastic nozzles (MPR, VAN, U-Series, Strips and Bubblers)

Operating Range

- Flow: 0.20 to 0.90 gpm (0.05 to 0.20 m³/h; 0.6 to 3.6 l/m)
- Pressure: 15 to 70 psi (1.0 to 4.8 bar)

Models

- PCS-020: 0.2 gpm (0.05 m³/h; 0.6 l/m) Brown
- PCS-025: 0.25 gpm (0.06 m³/h; 1.2 l/m) Pink
- PCS-030: 0.3 gpm (0.07 m³/h; 1.2 l/m) Silver
- PCS-040: 0.4 gpm (0.09 m³/h; 1.8 l/m) Orange
- PCS-060: 0.6 gpm (0.14 m³/h; 2.4 l/m) Black
- PCS-090: 0.9 gpm (0.20 m^3/h ; 3.6 l/m) White





1800 PCS Screens

Flow (gpm) m³/h (I/m) Distance	0	0 (Brown) 0.2 5 (60) meters	0.	25 (Pink) 25 5 (72) meters		(Silver) .3 (84) meters	0	(Orange) 0.4 (108) meters	0	0 (Black) 1.6 (144) meters	(0 (White) 0.9 (216) meters
U-8Q U-8H	6	(1.8) (1.2)	7 5	(2.1) (1.5)								
U-8F					1	(0.3)	3	(0.9)	7	(2.1)		
U-10Q U-10H	5	(1.5)	6	(1.8)	10' 5	(3.1) (1.5)	6	(1.8)	8	(2.4)	9	(2.7)
U-10F U-12Q	2'	(0.6)	4	(1.2)	7'	, ,	12'		4	(1.2)	9	(2.7)
U-12H	2	(0.6)	4	(1.2)	3'	(2.1) (0.9)	4'	(3.7) (1.2)	7'	(2.1)	11'	(3.4)
U-12F U-15Q			3'	(0.9)	6'	(1.8)	3' 11'	(0.9) (3.4)	6' 15'	(1.8) (4.6)	8'	(2.4)
U-15H				(0.5)	2'	(1.8) (0.6)	3'	(0.9)	5' 4'	(1.5)	9' 6'	(2.7)
U-15F 4 (90°)	1'	(0.3)			3'	(0.9)	4'	(1.2)		(1.2)	0	(1.8)
4 (180°) 4 (270°)			1'	(0.3)	2' 1'	(0.6) (0.3)	3' 2'	(0.9) (0.6)	4' 4'	(1.2) (1.2)		
4 (330°)				(0.4)	1'	(0.3)	2'	(0.6)	4'	(1.2)		
6 (90°) 6 (180°)			2'	(0.6)	3' 2'	(0.9) (0.6)	6' 4'	(1.8) (1.2)	6'	(1.8)		
6 (270°) 6 (330°)					0.5' 0.5'	(0.2)	1' 1'	(0.3)	3' 3'	(0.9) (0.9)	6' 6'	(1.8) (1.8)
8 (90°)					1'	(0.3)	3'	(0.9)	8'	(2.4)		
8 (180°) 8 (270°)					0.5'	(0.2)	2' 0.5'	(0.6)	4' 3'	(1.2) (0.9)	8' 5'	(2.4) (1.5)
8 (330°)					3'	(0.0)	0.5' 5'	(0.2) (1.5)	3' 10'	(0.9)	5'	(1.5)
10 (90°) 10 (180°)					3	(0.9)	1'	(0.3)	5'	(3.1) (1.5)	7'	(2.1)
10 (270°) 10 (360°)					0.5'	(0.2)	1' 1'	(0.3)	4' 4'	(1.2) (1.2)	6' 6'	(1.8) (1.8)
12 (90°)	3'	(0.9)			8' 1'	(2.4) (0.3)	10'	(3.1)	12'	(3.7)		
12 (180°) 12 (270°)					0.5'	(0.3)	2' 1'	(0.6) (0.3)	5' 3'	(1.5) (0.9)	8' 6'	(2.4) (1.8)
12 (360°) 15 (90°)					2'	(0.6)	1' 5'	(0.3)	3' 11'	(0.9) (3.4)	5' 15'	(1.5) (4.6)
15 (180°)					1'	(0.3)	3'	(0.9)	6'	(1.8)	9'	(2.7)
15 (270°) 15 (360°)											6'	(1.8)
18 (90°) 18 (180°)					0.5'	(0.2)	2' 1'	(0.6)	6' 3'	(1.8) (0.9)	12' 5'	(3.7) (1.5)
18 (270°)							0.5'	(0.2)	1'	(0.3)	3'	(0.9)
18 (330°) 5Q							0.5'	(0.2)	1'	(0.3)	3'	(0.9)
5T	5'	(1 E)	6'	(1.0)								
5H 5F		(1.5)		(1.8)	5'	(1.5)						
8Q 8T	8' 6'	(2.4) (1.8)	10' 6.5'	(3.1) (2.0)	7'	(2.1)	8'	(2.4)				
8H	5'	(1.5)	6'	(1.8)	7'	(2.1)	8'	(2.4)	01	(2.4)		
8F 10Q	6'	(1.8)	8'	(2.4)	2' 8'	(0.6) (2.4) (2.7)	3' 10'	(0.9) (3.1)	8'	(2.4)		
10T 10H	4' 3'	(1.2)	5' 4'	(1.5) (1.2)	9' 6'	(2.7) (1.8)	10' 8'	(3.1) (2.4)	10'	(3.1)		
10F		` '	71				1'	(0.3)	4'	(1.2)	8'	(2.4)
12Q 12T	3' 2'	(0.9) (0.6)	7' 4'	(2.1) (1.2)	8' 6'	(2.4) (1.8)	11' 10'	(3.4) (3.1)	12' 11'	(3.7)	12'	(3.7)
12H 12TT					4' 2'	(1.2) (0.6)	6' 4'	(1.8) (1.2)	10' 6'	(3.1)	12' 9'	(3.7) (2.7)
12TQ					2'	(0.6)	3'	(0.9)	6'	(1.8)	8'	(2.4) (2.1)
12F 15Q	3'	(0.9)	4' 2'	(1.2)	5' 5'	(1.5)	2' 9' 7'	(0.6) (2.7)	5' 12'	(1.5) (3.7)	7' 15'	(4.6)
15T 15H		,	2'	(1.2) (0.6)	5' 3'	(1.5) (1.5) (0.9)	7' 4'	(2.1) (1.2)	12'	(3.7) (2.1)	14' 11'	(4.3) (3.4)
15TT					1'	(0.3)	2'	(0.6)	7' 4'	(1.2)	8'	(2.4)
15TQ 15F											6' 4'	(1.8)
5Q-B 5H-B	2'	(0.6)	3	(0.9)	4 ¹ 1'	(1.2) (0.3)	5' 2'	(1.5)	5'	(1.5)		()
5F-B 5CST-B							1'	(0.6)	2'	(1.5) (0.6)	3'	(0.9)
5CST-B 9SST	1'	(0.3)	2	(0.6)	3'	(0.9)	5'	(1.5)			7' x 12'	(2.1 x 3.
15CST							4' x 12'	(1.2 x 3.7)	4' x 24'	(1.2 x 7.3)	4' x 30'	(1.2 x 9.
15SST 15EST					3' x 12'	(0.9 x 3.7)	2' x 10' 4' x 15'	(0.6x 3.1) (1.2 x 4.6)	3' x 20'	(0.9 x 6.1)	4' x 26'	(1.2 x 7.
15LCS	1' x 5'	(0.3 x 1.5) (0.3 x 1.5)	1' x 7' 1' x 7'	(0.3 x 2.1) (0.3 x 2.1)	1' x 12' 1' x 12'	(0.3 x 3.7)						
15RCS Bold green type indications Bold green type indications Bold green combinations Bold green type indications Bold green type indications	1' x 5' ates recommend nation to achieve	(0.3 x 1.5) led Bo	1' x 7' Id blue type indi tisfactory nozzle mbination	(0.3 x 2.1)	1' x 12' Black type indic	(0.3 x 3.7) rates a nozzle/scre w reduction of mo				tested at 50 psi (3. nents. Distances ma		

www.rainbird.com

11




SA Series

Swing Assemblies Connect Heads to Lateral Pipes.

Features


- Quality alternative to locally assembled swing pipe/spiral barb fittings that do not carry a manufacturer's warranty
- Comprehensive range of products support a variety of landscape solutions



Specifications

• The operating range of the Rain Bird Swing Assemblies matches or exceeds the operating range for most $\frac{1}{2}$ " (1.3 cm) sprays and $\frac{3}{4}$ " (1.9 cm) rotors


• Operating pressure: Up to 80 psi (5.5 bar)



• Maximum flow: 8 gpm (0.5 l/sec)



SA Series



Swing Pipe Flexible Sprinkler Assembly

SA Series Swing Assemblies Specifications								
Model Number	Length		Inlet		Outlet			
	US	METRIC	US	METRIC	US	METRIC		
SA-6050	6"	15.2 cm	1/2"	1.3 cm	1/2"	1.3 cm		
SA-125050	12"	30.5 cm	1/2"	1.3 cm	1/2"	1.3 cm		
SA-127575	12"	30.5 cm	3/4"	1.9 cm	3/4"	1.9 cm		
SA-185050	18"	45.7 cm	1/2"	1.3 cm	1/2"	1.3 cm		

SPX Series Swing Pipe

Swing Pipe and Spiral Barb Fittings

Swing Pipe with Spiral Barb Fittings Provides a Flexible Swing Assembly for Sprays and Rotors

Features and Benefits

SPX-FLEX100

- Superior flexibility allows pipe to be efficiently routed around hardscape, terraces, and uneven terrain to turn landscape design into reality
- Textured surface makes product easier to handle, contributing to labor efficiency, especially under wet conditions
- Resists kinking
- Quick and easy installation lowers material and labor costs
- Installs quickly leaving time for additional system installations and incremental revenue opportunities

Specifications

- Inside diameter: 0.49" (1.24 cm)
- Operating pressure: Up to 80 psi (5.5 bar)
- Temperature: Up to 110° F (43° C)

Models

• SPX-FLEX-100: 100' (30 m) coil





SPX-FLEX100

SB Series Spiral Barb Fittings

A Natural Product Complement to SPX Series Swing Pipe

Features and Benefits

- Fittings are made of robust acetal material to make connecting swing pipe fast and easy
- Easy twist-in insertion no glue or clamps needed for installation
- Aggressive barb lip makes a secure connection that is less likely to leak



- Broad range of shapes and sizes allow the contractor to choose the best fitting for the application
- Extended length and aggressive barb lip prevent blow outs, reducing likelihood of contractor call backs

Specifications

- Operating pressure: Up to 80 psi (5.5 bar)
- Temperature: Up to 110° F (43° C)

Models

- SB-CPLG: ½" barb x ½" barb coupling
- SBA-050: ½" M NPT x ½" barb adapter
- SBE-075: ¾" M NPT x ½" barb elbow
- SBE-050: ½" M NPT x ½" barb elbow
- SB-TEE: ½" barb x ½" barb x ½" barb tee



Spray & Rotary Nozzles

Major Products							
	Rotary Nozzles	Variable A	ARC Sprays		Fixed ARC Sprays		
Primary Applications	R-VAN	HE-VAN	VAN	U-Series	SQ Nozzles	MPR	
	Best	Best	Standard	Best	Standard	Standard	
Turfgrass	•	•	•	•	•	•	
Slopes	•						
Narrow Strips	•				•	•	
Small Areas	•	•			•		
Landscape Beds	•	•	•	•	•	•	
High Efficiency	•	•		•			
High Winds	•	•		•			
High Pressure	•	•					



Water Saving Tips

- Rotary Nozzles have efficient water distribution through rotating streams that uniformly deliver water at a low precipitation rate, significantly reducing runoff and erosion.
- HE-VAN nozzles are fully adjustable from 0 to 360 degrees with high uniformity and efficiency. HE-VAN nozzles can reduce the number of variations that need to be carried to cover just about any field challenge. Available in radii from 8' to 15', this high efficient nozzle has you covered.
- U-Series Nozzles are dual-orifice nozzles that have better, more uniform water distribution. Water flowing from both orifices combines to form a continuous water stream and eliminates gaps for more uniform coverage throughout the entire watering area.



What is a High-Efficiency Nozzle?

Typical nozzles - Un-Even Watering

With typical nozzles, part of the lawn may not have enough water and other parts may be over-watered. A large portion of water may be lost to evaporation / misting, and over-spray.

High-efficiency nozzles - Even Watering

High-efficiency nozzles provide better coverage. Better coverage means shorter zone run-times while keeping grass healthy. Shorter run-times means you will save up to 25%+ water vs. typical nozzles. Rain Bird's high-efficiency nozzles are also engineered to produce large water droplets to reduce wind drift.

Standard or Low Precipitation Rate?

Low Precipitation Rate Nozzles

Low precipitation rate nozzles are best used in sloped or compacted soil areas to minimize run-off. The low watering rate makes run-times longer.

Standard Precipitation Rate Nozzles

Standard precipitation rate nozzles are best used for shorter distance irrigation, and when watering times may be limited due to city ordinances.

Low Precipitation Rate		Standard Precipitation Rate						
High-Efficiency Rotary Nozzles	High-Efficie	ency Nozzles	Standard Nozzles					
	2		j					
R-VAN	HE-VAN	U-Series	VAN	MPR and SQ				
Adjustable Arc (45° - 270°) Full Circle (360°	Adjustable Arc	Fixed Arc	Adjustable Arc	Fixed Arc				



R-VAN Nozzles

High Efficiency, Multi-Stream

Rain Bird® R-VAN Adjustable Rotary Nozzles save more water, are easier to use, and are lower priced compared to leading rotating nozzles. R-VANs thick streams and large water droplets cut through the wind to deliver water where you want it. R-VANs are easier to use thanks to its hand-adjustable arc and radius.

Features

- · Matched precipitation across radius, arcs, and pattern types
- · Low precipitation rate reduces run-off and erosion
- · Adjust arc and radius without tools
- A pull-up to flush feature clears the nozzle of dirt and debris
- Maintains efficient performance at high operating pressures without misting or fogging
- Compatible with all models of Rain Bird spray bodies, risers and adapters
- Installing with Rain Bird 5000 MPR Series Rotors allows for matched precipitation from 8'to 35' (2.4m to 10.7m)
- · Three year trade warranty

Operating Specifications

- Pressure Range: 30 to 55 psi (2.1 to 3.8 bar)
- Recommended Operating Pressure: 45 psi (3.1 bar)
- Spacing: 8' to 24' (2.4 to 7.3m)
- Adjustments: Arc and radius should be adjusted while water is running

Models

8' - 14' (2.4 to 4.6m)

- R-VAN14: 45° 270° Adjustable Arc
- R-VAN14-360: 360° Full Circle

13' - 18' (4.0 to 5.5m)

- R-VAN18: 45° 270° Adjustable Arc
- R-VAN18-360: 360° Full Circle

17' - 24' (5.2 to 7.3m)

- R-VAN24: 45° 270° Adjustable Arc
- R-VAN24-360: 360° Full Circle

Strip Nozzles

- R-VAN-LCS: 5'x 15'(1.5 x 4.6m) Left Corner Strip
- R-VAN-RCS: 5'x 15'(1.5 x 4.6m) Right Corner Strip
- R-VAN-SST: 5'x 30'(1.5 x 9.1m) Side Strip
- $^{\scriptscriptstyle 1}$ Rain Bird recommends using 1800 P45 Spray Bodies to maintain optimum nozzle performance

R-VAN Nozzles meet the requirements of the ASABE/ICC 802-2014 standard


The average DU(LQ) of the applicable products exceed 0.65 distribution uniformity.

Product	Туре	Radius	DU(LQ)
R-VAN	Multi-stream	8 - 24 ft.	> 0.70

To view the complete document of compliance for Rain Bird products that have been tested to meet the requirements of the ASABE/ICC 802-2014 standard and the California MWELO as to: www.rainbird.com/aaency/california/MWELO.htm



R-VAN Nozzles



Pull Up HARD to Flush

For Optimum Performance, Use Rain Bird 1800 45 PSI Regulated or RD1800 45 PSI Regulated Spray Bodies



How to Specify

R-VAN 18-360

Radius Range 8'- 14' (2.4 to 4.6m) R-VAN14: 45° - 270°

R-VAN14-360: 360° 13'-18' (4.0 to 5.5m) R-VAN18: 45°-270° R-VAN18-360: 360°

17' - 24' (5.2 to 7.3m) R-VAN24: 45° - 270° R-VAN24-360: 360°

Strip Nozzles

R-VAN-LCS: 5' x 15' (1.5 x 4.6m) R-VAN-RCS: 5' x 15' (1.5 x 4.6m) R-VAN-SST: 5' x 30' (1.5 x 9.1m)

Model R-VAN Adjustable Rotary Nozzle





13' to 18'

17' to 24' (5.2m to 7.3m)

Strip Nozzles



45° - 270°



360°



45° - 270°



360°





45° - 270°



360°









5' x 30' 5' x 15' 5' x 15' Left Corner Strip Side Strip Right Corner Strip

8' - 14' Adjustable Arc Nozzles (45° to 270°)

R-VAN14 8'	R-VAN14 8'-14'							
Nozzle	Pressure	Radius	Flow	Precip	Precip			
	psi	ft.	gpm	In/h	In/h			
270°	30	13	0.84	0.64	0.76			
	35	13	0.87	0.66	0.74			
	40	14	0.92	0.60	0.71			
	45	14	0.94	0.62	0.70			
	50	15	1.11	0.63	0.73			
	55	15	1.17	0.67	0.77			
210°	30 35 40 45 50 55	13 13 14 14 15	0.65 0.68 0.72 0.73 0.86 0.91	0.64 0.66 0.60 0.62 0.63 0.67	0.76 0.74 0.71 0.70 0.73 0.77			
180°	30 35 40 45 50 55	13 13 14 14 15	0.56 0.58 0.61 0.63 0.74 0.78	0.64 0.66 0.60 0.62 0.63 0.67	0.76 0.74 0.71 0.70 0.73 0.77			
90°	30	13	0.28	0.64	0.76			
	35	13	0.29	0.66	0.74			
	40	14	0.31	0.62	0.71			
	45	14	0.32	0.61	0.70			
	50	15	0.37	0.63	0.73			
	55	15	0.39	0.67	0.77			

R-VAN14 2.4	4 to 4.6m				METRIC
Nozzle	Pressure bar	Radius m	Flow I/m	Precip mm/h	Precip mm/h
270°	2.1 2.4 2.8 3.1 3.4	4.0 4.0 4.3 4.3 4.6	3.18 3.29 3.48 3.56 4.20	16 17 15 16	19 19 18 18 19
210°	3.8 2.1 2.4 2.8 3.1 3.4 3.8	4.6 4.0 4.3 4.3 4.6 4.6	4.43 2.46 2.57 2.73 2.76 3.26 3.44	17 16 17 15 16 16	20 19 19 18 18 19 20
180°	2.1 2.4 2.8 3.1 3.4 3.8	4.0 4.0 4.3 4.3 4.6 4.6	2.12 2.20 2.31 2.38 2.80 2.95	16 17 15 16 16	19 19 18 18 19
90°	2.1 2.4 2.8 3.1 3.4 3.8	4.0 4.0 4.3 4.3 4.6 4.6	1.06 1.10 1.17 1.21 1.40 1.48	16 17 16 15 16	19 19 18 18 19

8' - 14' Full Circle Nozzles (360°)

R-VAN14-360	8' - 14'				
Nozzle	Pressure psi	Radius ft.	Flow gpm	Precip In/h	Precip In/h
360°	30	13	1.10	0.63	0.72
	35	13	1.12	0.64	0.74
	40	14	1.22	0.60	0.69
	45	14	1.27	0.62	0.72
	50	15	1.41	0.60	0.70
	55	15	1.45	0.62	0.72

Note: All R-VAN nozzles tested on 4" (10.2 cm) pop-ups

- Square spacing based on 50% diameter of throw
- ▲ Triangular spacing based on 50% diameter of throw

R-VAN14-360	2.4 to 4.6	m			METRIC
Nozzle	Pressure	Radius	Flow	Precip	Precip
	bar	m	I/m	mm/h	mm/h
360°	2.1	4.0	4.16	16	18
	2.4	4.0	4.24	16	19
	2.8	4.3	4.62	15	18
	3.1	4.3	4.81	16	18
	3.4	4.6	5.34	15	18
	3.8	4.6	5.49	16	18

Performance data taken in zero wind conditions

R-VAN24 and R-VAN24-360: "Do not reduce the radius below 17' (5,2 m) R-VAN18 and R-VAN18-360: "Do not reduce the radius below 13' (4,0 m)

R-VAN14 and R-VAN18-360: "Do not reduce the radius below 8' (2,4 m)



13' - 18' Adjustable Arc Nozzles (45° to 270°)

R-VAN18 13	′- 18′				
Nozzle	Pressure	Radius	Flow	Precip	Precip
	psi	ft.	gpm	In/h	In/h
270°	30	16	1.26	0.65	0.75
	35	16	1.35	0.64	0.74
	40	17	1.42	0.63	0.73
	45	17	1.51	0.64	0.73
	50	18	1.57	0.60	0.69
	55	18	1.62	0.60	0.69
210°	30 35 40 45 50 55	16 16 17 17 18	0.98 1.05 1.10 1.17 1.22 1.26	0.63 0.68 0.63 0.64 0.62 0.64	0.73 0.78 0.73 0.77 0.72 0.74
180°	30	16	0.85	0.65	0.75
	35	16	0.91	0.64	0.74
	40	17	0.98	0.63	0.73
	45	17	1.01	0.64	0.73
	50	18	1.07	0.60	0.69
	55	18	1.09	0.60	0.69
90°	30	16	0.42	0.65	0.75
	35	16	0.47	0.64	0.74
	40	17	0.50	0.63	0.73
	45	17	0.50	0.64	0.73
	50	18	0.54	0.60	0.69
	55	18	0.58	0.60	0.69

R-VAN18 4.0	0 to 5.5m				METRIC
Nozzle	Pressure bar	Radius m	Flow I/m	Precip mm/h	Precip mm/h
270°	2.1 2.4 2.8 3.1 3.4 3.8	4.9 4.9 5.2 5.2 5.5 5.5	4.77 5.11 5.38 5.72 5.94 6.13	17 16 16 16 15	19 19 19 19 18
210°	2.1 2.4 2.8 3.1 3.4 3.8	4.9 4.9 5.2 5.2 5.5 5.5	3.71 3.97 4.16 4.43 4.62 4.77	16 17 16 16 16	19 20 19 20 18
180°	2.1 2.4 2.8 3.1 3.4 3.8	4.9 4.9 5.2 5.2 5.5 5.5	3.22 3.44 3.71 3.82 4.05 4.13	17 16 16 16 15	19 19 19 19 18
90°	2.1 2.4 2.8 3.1 3.4 3.8	4.9 4.9 5.2 5.2 5.5 5.5	1.59 1.78 1.89 1.89 2.04 2.20	17 16 16 16 15	19 19 19 19 18

13' - 18' Full Circle Nozzles (360°)

R-VAN18-360	13' - 18'				
Nozzle	Pressure psi	Radius ft.	Flow gpm	Precip In/h	Precip In/h
360°	30 35 40 45 50	16 16 17 17 18	1.65 1.67 1.80 1.85 2.05 2.11	0.62 0.63 0.60 0.62 0.61 0.63	0.72 0.73 0.69 0.71 0.70 0.72

Note: All R-VAN nozzles tested on 4" (10.2 cm) pop-ups

- Square spacing based on 50% diameter of throw
- ▲ Triangular spacing based on 50% diameter of throw

R-VAN18-360	4.0 to 5.5	METRIC			
Nozzle	Pressure bar	Radius m	Flow I/m	Precip mm/h	Precip mm/h
360°	2.1	4.9	6.25	16	18
	2.4	4.9	6.32	16	19
	2.8	5.2	6.81	15	18
	3.1	5.2	7.00	16	18
	3.4	5.5	7.76	15	18
	3.8	5.5	7.99	16	18

Performance data taken in zero wind conditions

R-VAN24 and R-VAN24-360: "Do not reduce the radius below 17' (5,2 m) R-VAN18 and R-VAN18-360: "Do not reduce the radius below 13' (4,0 m) R-VAN14 and R-VAN18-360: "Do not reduce the radius below 8' (2,4 m)

Did you know?

You can use R-VAN Nozzles and 5000 Series MPR Rotors on the same zone!

- Matched precipitation rate (MPR) from 8' to 35'
- Superior coverage >0.70 DU[LQ]
- Thick, wind-resistant streams near to far



17' - 24' Adjustable Arc Nozzles (45° to 270°)

R-VAN24 17	"- 24 '				
Nozzle	Pressure	Radius	Flow	Precip	Precip
	psi	ft.	gpm	In/h	In/h
270°	30	19	1.80	0.64	0.74
	35	20	1.95	0.63	0.72
	40	22	2.31	0.61	0.71
	45	23	2.52	0.61	0.71
	50	24	2.82	0.63	0.73
	55	24	2.88	0.64	0.74
210°	30 35 40 45 50	19 20 22 23 24 24	1.40 1.52 1.80 1.96 2.19 2.24	0.64 0.63 0.61 0.61 0.63 0.64	0.74 0.72 0.71 0.71 0.73 0.74
180°	30	19	1.20	0.64	0.74
	35	20	1.30	0.63	0.72
	40	22	1.54	0.61	0.71
	45	23	1.68	0.61	0.71
	50	24	1.88	0.63	0.73
	55	24	1.92	0.64	0.74
90°	30	19	0.60	0.64	0.74
	35	20	0.65	0.63	0.72
	40	22	0.77	0.61	0.71
	45	23	0.84	0.61	0.71
	50	24	0.94	0.63	0.73
	55	24	0.96	0.64	0.74

R-VAN24 5	i.2 to 7.3m				METRIC
Nozzle	Pressure bar	Radius m	Flow I/m	Precip mm/h	Precip mm/h
270°	2.1 2.4 2.8 3.1 3.4 3.8	5.8 6.1 6.7 7.0 7.3 7.3	6.81 7.38 8.74 9.54 10.67 10.90	16 16 15 15 16 16	19 18 18 18 19
210°	2.1 2.4 2.8 3.1 3.4 3.8	5.8 6.1 6.7 7.0 7.3 7.3	5.30 5.75 6.81 7.42 8.29 8.48	16 16 15 15 16	19 18 18 18 19
180°	2.1 2.4 2.8 3.1 3.4 3.8	5.8 6.1 6.7 7.0 7.3 7.3	4.54 4.92 5.83 6.36 7.12 7.27	16 16 15 15 16	19 18 18 18 19
90°	2.1 2.4 2.8 3.1 3.4 3.8	5.8 6.1 6.7 7.0 7.3 7.3	2.27 2.46 2.91 3.18 3.56 3.63	16 16 15 15 16	19 18 18 18 19

17' - 24' Full Circle Nozzles (360°)

R-VAN24-360	17' - 24'				
Nozzle	Pressure	Radius	Flow	Precip	Precip
	psi	ft.	gpm	In/h	In/h
360°	30	19	2.35	0.63	0.72
	35	20	2.52	0.61	0.70
	40	22	3.13	0.62	0.72
	45	23	3.48	0.63	0.73
	50	24	3.61	0.60	0.70
	55	24	3.74	0.62	0.72

Note: All R-VAN nozzles tested on 4" (10.2 cm) pop-ups

- Square spacing based on 50% diameter of throw
- ▲ Triangular spacing based on 50% diameter of throw

R-VAN24-360	5.2 to 7.3	m			METRIC
Nozzle	Pressure bar	Radius m	Flow I/m	Precip mm/h	Precip mm/h
360°	2.1	5.8	8.90	16	18
	2.4	6.1	9.54	15	18
	2.8	6.7	11.85	16	18
	3.1	7.0	13.17	16	19
	3.4	7.3	13.67	15	18
	3.8	7.3	14.16	16	18

Performance data taken in zero wind conditions

R-VAN24 and R-VAN24-360: "Do not reduce the radius below 17' (5,2 m) R-VAN18 and R-VAN18-360: "Do not reduce the radius below 13' (4,0 m) R-VAN14 and R-VAN18-360: "Do not reduce the radius below 8' (2,4 m)

R-VAN Requires Half the Models to Cover 45° to 360°





Offering Valuable Bottom-Line Savings

- Shorter zone run times save water and energy
- Lower precipitation rates reduce wasteful runoff and costly erosion
- Fewer nozzles needed to cover any area, reducing your inventory costs

R-VAN-SST

psi

30

35

40

45

50

55

Nozzle

Side

Strip



Strip Nozzles (Left Corner, Side, Right Corner)

R-VAN-LCS 5'x 15'								
Nozzle	Pressure psi	Size ft.	Flow gpm	Precip In/h	Precip In/h			
Left Corner Strip	30 35 40 45 50 55	4'x14' 5'x15' 5'x15' 5'x15' 5'x15' 6'x16'	0.18 0.22 0.23 0.24 0.25 0.28	0.62 0.56 0.59 0.62 0.64 0.56	0.62 0.56 0.59 0.62 0.64 0.56			

Precip Precip

In/h

0.62

0.56

0.59

0.62

0.64

0.56

In/h

0.62

0.64

0.56

0.44 0.56

0.46 0.59

Flow

gpm

0.36

5'x30' 0.48 0.62

0.50

0.56

5' x 30'

ft.

4'x28'

5'x30'

5'x30'

5'x30'

6'x32'

Pressure Size

R-VAN-I	LCS 1.5	x 4.6m		ı	METRIC
Nozzle	Pressure bar	Size m		Precip mm/h	
	2.1 2.4	1.2x4.3 1.5x4.6	0.00	16 14	16 14
Strip	2.8 3.1 3.4 3.8	1.5x4.6 1.5x4.6 1.5x4.6 1.8x4.9	0.91 0.95	15 16 16 14	15 16 16 14

R-VAN-SST 1.5 x 9.1m METRIC								
Nozzle	Pressure bar	Size m	Flow I/m	Precip mm/h				
Side	2.1	1.2x8.5	1.36	16	16			
Strip	2.4	1.5x9.1	1.67	14	14			
	2.8	1.5x9.1	1.74	15	15			
	3.1	1.5x9.1	1.82	16	16			
	3.4	1.5x9.1	1.89	16	16			
	3.8	1 8x9 8	2 12	14	14			

R-VAN-	SST 1.5		ı	METRIC	
Nozzle	Pressure bar	Size m	Flow I/m	Precip mm/h	
Side	2.1	1.2x8.5	1.36	16	16
Strip	2.4	1.5x9.1	1.67	14	14
	2.8	1.5x9.1	1.74	15	15
	3.1	1.5x9.1	1.82	16	16
•	3.4	1.5x9.1	1.89	16	16
	3.8	1.8x9.8	2.12	14	14

R-VAN-RCS 5' x 15'									
Nozzle	Pressure psi	Size ft.	Flow gpm	Precip In/h	Precip In/h				
Right	30	4'x14'	0.18	0.62	0.62				
Corner	35	5'x15'	0.22	0.56	0.56				
Strip	40	5'x15'	0.23	0.59	0.59				
	45	5'x15'	0.24	0.62	0.62				
	50	5'x15'	0.25	0.64	0.64				
	55	6'x16'	0.28	0.56	0.56				

Note: All R-VAN nozzles tested on 4" (10.2 cm) pop-ups Performance data taken in zero wind conditions

R-VAN-F	RCS 1.5	x 4.6m		ı	METRIC
Nozzle	Pressure bar	Size m	Flow I/m	Precip mm/h	
Right	2.1	1.2x4.3	0.68	16	16
	2.4	1.5x4.6	0.83	14	14
Strip	2.8	1.5x4.6	0.87	15	15
	3.1	1.5x4.6	0.91	16	16
Щ.	3.4	1.5x4.6	0.95	16	16
	3.8	1.8x4.9	1.06	14	14

- Straight-line spacing based on 50% overlap of throw for LCS, SST, and RCS
- ▲ Triangular spacing based on 50% overlap of throw for LCS, SST, and RCS

Easy Adjustments

Adjustable Arc Nozzles

R-VAN14, R-VAN18, R-VAN24

RADIUS ADJUSTMENT



ARC ADJUSTMENT



Full Circle Nozzles

R-VAN14-360, R-VAN18-360, RVAN24-360

RADIUS ADJUSTMENT



Strip Nozzles

R-VAN-LCS, R-VAN-RCS, R-VAN-SST

SIZE ADJUSTMENT





Improving Watering Efficiencies Up to 30%

- · Gentle, rotating streams create uniform coverage at lower precipitation rates
- Multi-stream technology optimizes absorption for healthier lawns
- · Larger droplets and thicker streams cut through wind and keep water in target zone

HE-VAN Series Nozzles

High-Efficiency Variable Arc Spray Nozzles

Features

- HE-VAN's even coverage allows you to shorten run times by up to 35%, saving you water and money, while still maintaining a healthy lawn.
 HE-VAN has more than a 40 percent even-coverage improvement over existing variable arc nozzles
- HE-VAN nozzles have a unique stream pattern, designed for superior coverage and wind resistance. Low-trajectory spray and large water droplets prevent misting and airborne evaporation so the right amount of water is delivered to the right place. Gentle close-in watering eliminates dry-spots around the spray head
- HE-VAN nozzles throw to the exact specified radius, delivering the cleanest edge of any VAN on the market today
- Reduced zone run times, compared to competitive nozzles, help stay within tight watering windows, conserve water, and save money
- With full adjustability from 0° to 360°, you'll be able to efficiently water landscapes of all shapes, while saving time and stocking fewer nozzles
- Matched precipitation rates allow you to install Rain Bird HE-VAN, MPR and U-Series nozzles on the same zone
- HE-VAN nozzles have a tactile click to keep the arc setting from drifting over time
- · Three year trade warranty


Operating Range

- Spacing: 6 to 15 feet (1.8 to 4.6m) ¹
- Pressure: 15 to 30 psi (1.0 to 2.1 bar)
- Optimum pressure: 30 psi (2.1 bar)²

Models

- HE-VAN-08: 6 to 8 feet (1.8 to 2.4 m)
- HE-VAN-10: 8 to 10 feet (2.4 to 3.0 m)
- HE-VAN-12: 9 to 12 feet (2.7 to 3.7 m)
- HE-VAN-15: 12 to 15 feet (3.7 to 4.6 m)
- ¹ These ranges are based on proper pressure at nozzle
- ² Rain Bird recommends using 1800/RD 1800 PRS Spray Bodies to maintain optimum nozzle performance in higher pressure situations





To view the complete document of compliance for Rain Bird products that have been tested to meet the requirements of the ASABE/ICC 802-2014 standard and the California MWELO go to: www.rainbird.com/agency/california/MWELO.htm



Fits on all Rain Bird® 1800® Series Spray Heads, UNI-Spray™ Series Spray Heads and Rain Bird Shrub Adapters

For Optimum Performance, Use Rain Bird 1800 30 PSI Regulated or RD1800 30 PSI Regulated Spray Bodies



How to Specify HE-VAN-15 Radius Range 8: 6 to 8 feet (1.8 to 2.4 m) 10: 8 to 10 feet (2.4 to 3.0 m) 12: 9 to 12 feet (2.7 to 3.7 m) 15: 12 to 15 feet (3.7 to 4.6 m) Feature VAN: Variable Arc Model High Efficiency Nozzle







/AN				
Pressure	Radius	Flow	Precip	Precip
psi	ft.	gpm	ln/h	In/h
15	5	0.83	3.19	3.68
20	6	0.96	2.56	2.95
25	7	1.07	2.10	2.42
30	8	1.17	1.76	2.03
15	5	0.62	3.19	3.68
20	6	0.72	2.56	2.95
25	7	0.80	2.10	2.42
30	8	0.88	1.76	2.03
15	5	0.41	3.19	3.68
20	6	0.48	2.56	2.95
25	7	0.53	2.10	2.42
30	8	0.59	1.76	2.03
15	5	0.21	3.19	3.68
20	6	0.24	2.56	2.95
25	7	0.27	2.10	2.42
30	8	0.29	1.76	2.03
	Pressure psi 15 20 25 30 15 20 25 30 15 20 25 30 15 20 25 30 25 30 25 25 25 25	Pressure psi ft. 15 5 20 6 25 7 30 8 15 5 20 6 25 7 30 8 15 5 20 6 25 7 30 8 15 5 20 6 25 7 30 8 15 5 20 6 25 7 30 8	Pressure psi Radius ft. Flow gpm 15 5 0.83 20 6 0.96 25 7 1.07 30 8 1.17 15 5 0.62 20 6 0.72 25 7 0.80 30 8 0.88 15 5 0.41 20 6 0.48 25 7 0.53 30 8 0.59 15 5 0.21 20 6 0.24 25 7 0.27	Pressure psi Radius ft. Flow gpm Precip ln/h 15 5 0.83 3.19 20 6 0.96 2.56 25 7 1.07 2.10 30 8 1.17 1.76 15 5 0.62 3.19 20 6 0.72 2.56 25 7 0.80 2.10 30 8 0.88 1.76 15 5 0.41 3.19 20 6 0.48 2.56 25 7 0.53 2.10 30 8 0.59 1.76 15 5 0.21 3.19 20 6 0.24 2.56 25 7 0.53 2.10 30 8 0.59 1.76 15 5 0.21 3.19 20 6 0.24 2.56 25 7 0.27

8 Series HE-\	/AN				ı	METRIC
24° Trajectory	Pressure bar	Radius m	Flow m ³ /h	Flow I/m	Precip mm/h	Precip mm/h
360° Arc	1.03	1.52	0.19	3.14	82	95
JOU AIC	1.38	1.83	0.19	3.62	66	76
(•)	1.72	2.13	0.25	4.05	54	62
	2.07	2.44	0.27	4.43	45	52
270° Arc	1.03	1.52	0.14	2.35	82	95
	1.38	1.83	0.16	2.72	66	76
	1.72	2.13	0.18	3.04	54	62
	2.07	2.44	0.20	3.33	45	52
180° Arc	1.03	1.52	0.10	1.57	82	95
	1.38	1.83	0.11	1.81	66	76
	1.72	2.13	0.12	2.02	54	62
	2.07	2.44	0.13	2.22	45	52
90° Arc	1.03	1.52	0.05	0.78	82	95
	1.38	1.83	0.05	0.91	66	76
	1.72	2.13	0.06	1.01	54	62
	2.07	2.44	0.07	1.11	45	52

10 Series HE	-VAN				
27° Trajectory Nozzle	Pressure	Radius	Flow	Precip	Precip
	psi	ft.	gpm	In/h	In/h
360° Arc	15	7	1.26	2.48	2.86
	20	8	1.46	2.19	2.53
	25	9	1.63	1.94	2.24
	30	10	1.78	1.72	1.98
270° Arc	15	7	0.95	2.48	2.86
	20	8	1.09	2.19	2.53
	25	9	1.22	1.94	2.24
	30	10	1.34	1.72	1.98
180° Arc	15	7	0.63	2.48	2.86
	20	8	0.73	2.19	2.53
	25	9	0.81	1.94	2.24
	30	10	0.89	1.72	1.98
90° Arc	15	7	0.32	2.48	2.86
	20	8	0.36	2.19	2.53
	25	9	0.41	1.94	2.24
	30	10	0.45	1.72	1.98

27° Trajectory						
Nozzle	Pressure bar	Radius m	Flow m ³ /h	Flow I/m	Precip mm/h	Precip mm/h
360° Arc	1.03	2.13	0.29	4.78	64	74
	1.38	2.44	0.34	5.52	56	65
(•)	1.72	2.74	0.37	6.17	50	57
	2.07	3.05	0.41	6.76	44	51
270° Arc	1.03	2.13	0.22	3.59	64	74
	1.38	2.44	0.25	4.14	56	65
—	1.72	2.74	0.28	4.63	50	57
	2.07	3.05	0.31	5.07	44	51
180° Arc	1.03	2.13	0.15	2.39	64	74
	1.38	2.44	0.17	2.76	56	65
	1.72	2.74	0.19	3.09	50	57
	2.07	3.05	0.21	3.38	44	51
90° Arc	1.03	2.13	0.07	1.20	64	74
	1.38	2.44	0.08	1.38	56	65
	1.72	2.74	0.09	1.54	50	57
	2.07	3.05	0.10	1.69	44	51

Note: All HE-VAN nozzles tested on 4" (10.2 cm) pop-ups

Square spacing based on 50% diameter of throw

▲ Triangular spacing based on 50% diameter of throw

Performance data taken in zero wind conditions **Note:** Radius reduction over 25% of the normal throw of the nozzle is not recommended

10 Series HE-VAN

12 Series HE	-VAN				
23°Trajectory					
Nozzle	Pressure psi	Radius ft.	Flow gpm	Precip In/h	Precip In/h
360° Arc	15	9	1.67	1.99	2.30
	20	10	1.93	1.86	2.15
•	25	11	2.16	1.72	1.99
	30	12	2.37	1.58	1.83
270° Arc	15	9	1.25	1.99	2.30
	20	10	1.45	1.86	2.15
	25	11	1.62	1.72	1.99
	30	12	1.77	1.58	1.83
180° Arc	15	9	0.84	1.99	2.30
	20	10	0.97	1.86	2.15
	25	11	1.08	1.72	1.99
	30	12	1.18	1.58	1.83
90° Arc	15	9	0.42	1.99	2.30
	20	10	0.48	1.86	2.15
	25	11	0.54	1.72	1.99
	30	12	0.59	1.58	1.83

12 Series HE	-VAN				I	METRIC
23° Trajectory						
Nozzle	Pressure bar	Radius m	Flow m³/h	Flow I/m	Precip mm/h	Precip mm/h
360° Arc	1.0	2.7	0.38	6.33	50.5	58.3
	1.4	3.0	0.44	7.31	47.3	54.6
•	1.7	3.4	0.49	8.18	43.7	50.4
	2.1	3.7	0.54	8.96	40.2	46.4
270° Arc	1.0	2.7	0.28	4.75	50.5	58.3
	1.4	3.0	0.33	5.48	47.3	54.6
	1.7	3.4	0.37	6.16	43.7	50.4
	2.1	3.7	0.40	6.72	40.2	46.4
180° Arc	1.0	2.7	0.19	3.17	50.5	58.3
	1.4	3.0	0.22	3.66	47.3	54.6
	1.7	3.4	0.25	4.09	43.7	50.4
	2.1	3.7	0.27	4.48	40.2	46.4
90° Arc	1.0	2.7	0.09	1.58	50.5	58.3
	1.4	3.0	0.11	1.83	47.3	54.6
	1.7	3.4	0.12	2.04	43.7	50.4
	2.1	3.7	0.13	2.24	40.2	46.4

15 Series HE	-VAN				
25° Trajectory Nozzle	Pressure psi	Radius ft.	Flow	Precip In/h	Precip In/h
360° Arc	15	11	gpm 2.62	2.08	2.40
300 AIC	20 25	12 14	3.02 3.38	2.02 1.66	2.33
	30	15	3.70	1.58	1.83
270° Arc	15 20 25 30	11 12 14 15	1.96 2.27 2.53 2.78	2.08 2.02 1.66 1.58	2.40 2.33 1.92 1.83
180° Arc	15 20 25 30	11 12 14 15	1.31 1.51 1.69 1.85	2.08 2.02 1.66 1.58	2.40 2.33 1.92 1.83
90° Arc	15 20 25 30	11 12 14 15	0.65 0.76 0.84 0.93	2.08 2.02 1.66 1.58	2.40 2.33 1.92 1.83

15 Series HE	-VAN				l	METRIC
25° Trajectory Nozzle	Pressure bar	Radius m	Flow m³/h	Flow I/m	Precip mm/h	Precip mm/h
360° Arc	1.0	3.4	0.59	9.91	52.9	61.1
	1.4	3.7	0.69	11.44	51.3	59.3
	1.7	4.3	0.77	12.79	42.2	48.7
	2.1	4.6	0.84	14.01	40.2	46.5
270° Arc	1.0	3.4	0.45	7.43	52.9	61.1
	1.4	3.7	0.51	8.58	51.3	59.3
	1.7	4.3	0.58	9.59	42.2	48.7
	2.1	4.6	0.63	10.51	40.2	46.5
180° Arc	1.0	3.4	0.30	4.95	52.9	61.1
	1.4	3.7	0.34	5.72	51.3	59.3
	1.7	4.3	0.38	6.39	42.2	48.7
	2.1	4.6	0.42	7.00	40.2	46.5
90° Arc	1.0	3.4	0.15	2.48	52.9	61.1
	1.4	3.7	0.17	2.86	51.3	59.3
	1.7	4.3	0.19	3.20	42.2	48.7
	2.1	4.6	0.21	3.50	40.2	46.5

Note: All HE-VAN nozzles tested on 4" (10.2 cm) pop-ups

■ Square spacing based on 50% diameter of throw

A Triangular spacing based on 50% diameter of throw

Performance data taken in zero wind conditions

Note: Radius reduction over 25% of the normal throw of the nozzle is not recommended



U-Series Nozzles

Dual orifice spray nozzles that use 30% less water¹

Features

- Additional orifice for close-in watering minimizes brown spots around the spray head and eliminates gaps in coverage so the entire watering area is more uniformly covered
- Superior coverage for efficient watering. Use up to 30% less water
- Matched precipitation rate with Rain Bird HE-VAN and MPR nozzles
- · Five year trade warranty

Operating Range


- Spacing: 5 to 15 feet (1.7 to 4.6 m)²
- Pressure: 15 to 30 psi (1.0 to 2.1 bar)
- Optimum pressure: 30 psi (2.1 bar)3

Models

- U-8 Series: 8-foot Quarter, Half, Full nozzles
- U-10 Series: 10-foot Quarter, Half, Full nozzles
- U-12 Series: 12-foot Quarter, Half, Full nozzles
- U-15 Series: 15-foot Quarter, Half, Full nozzles
- When U-Series dual-orifice nozzles are installed instead of standard nozzles on every spray body in the zone. Results may vary based on site-specific conditions such as sprinkler spacing, wind, temperature, soil and grass type.
- ² These ranges are based on proper pressure at nozzle.
- ³ Rain Bird recommends using 1800/RD1800 PRS Spray Bodies to maintain optimum nozzle performance in higher pressure situations.



U-Series nozzles offer better, more uniform water distribution. Water flowing from both orifices combines to form a continuous water stream. Eliminates gaps for more uniform coverage throughout the entire watering area



U-Series Nozzles meet the requirements of the ASABE/ICC 802-2014 standard The average DU(LQ) of the applicable products exceed 0.65 distribution uniformity. Product Type Radius DU(LQ) U-Series Spray, Fixed Arc 6 - 15 ft. > 0.70

To view the complete document of compliance for Rain Bird products that have been tested to meet the requirements of the ASABE/ICC 802-2014 standard and the California MWELO go to: www.rainbird.com/agency/california/MWELO.htm






U-Series Nozzle with screen

For Optimum Performance, Use Rain Bird 1800 30 PSI Regulated or RD1800 30 PSI Regulated Spray Bodies







U8 Series					
10° Trajectory					
	Pressure	Radius	Flow	Precip	Precip
Nozzle	psi	ft.	gpm	In/h	In/h
U-8F	15	5	0.74	2.85	3.29
	20	6	0.86	2.30	2.66
(•)	25	7	0.96	1.89	2.18
	30	8	1.05	1.58	1.83
U8H	15	5	0.37	2.85	3.29
	20	6	0.42	2.25	2.59
	25	7	0.47	1.85	2.13
	30	8	0.52	1.58	1.83
U8Q	15	5	0.18	2.77	3.20
	20	6	0.21	2.25	2.59
	25	7	0.24	1.89	2.18
	30	8	0.26	1.58	1.83

U8 Series					I	METRIC
10° Trajectory Nozzle	Pressure	Radius	Flow	Flow	Precip	Precip
	bar	m	m³/h	I/m	mm/h	mm/h
U-8F	1.0	1.7	0.16	2.8	72	84
	1.5	2.1	0.20	3.4	58	68
	2.0	2.4	0.23	3.9	48	55
	2.1	2.4	0.24	4.0	40	46
U-8H	1.0	1.7	0.08	1.4	72	84
	1.5	2.1	0.10	1.7	57	66
	2.0	2.4	0.12	1.9	47	54
	2.1	2.4	0.12	2.0	40	46
U-8Q	1.0	1.7	0.04	0.7	70	81
	1.5	2.1	0.05	0.8	57	66
	2.0	2.4	0.06	1.0	48	55
	2.1	2.4	0.06	1.0	40	46

U10 Series					
12°Trajectory	Pressure	Radius	Flow	Precip	_ Precip
Nozzle	psi	ft.	gpm	ln/h	ln/h
U-10F	15	7	1.16	2.07	2.39
	20	8	1.34	2.01	2.32
(°)	25	9	1.50	1.62	1.87
	30	10	1.64	1.58	1.83
U-10H	15	7	0.58	2.07	2.39
	20	8	0.67	2.01	2.32
	25	9	0.75	1.62	1.87
	30	10	0.82	1.58	1.83
U-10Q	15	7	0.29	2.07	2.39
	20	8	0.33	2.01	2.32
	25	9	0.37	1.62	1.87
	30	10	0.41	1.58	1.83

1.5	2.6	0.08
2.0	3.0	0.08
2.1	3.1	0.09

bar

1.0

1.5

2.0

2.1

1.0

1.5

2.0

2.1

1.0

U10 Series 12° Trajectory

Nozzle

U-10F

U-10H

U-10Q

Note: All U-Series nozzles tested on 4" (10.2 cm) pop-ups

■ Square spacing based on 50% diameter of throw

A Triangular spacing based on 50% diameter of throw

Performance data taken in zero wind conditions Radius refers to recommended product spacing. Actual radii along arc may vary

Pressure Radius Flow

2.1

2.6

3.0

3.1

2.1

2.6

3.0

3.1

2.1

m

Flow

I/m

4.4

5.3

6.1

6.2

2.2

2.6

3.1

3.1

1.1

1.3

1.5

1.6

m³/h

0.26

0.30

0.34

0.37

0.13

0.15

0.17

0.19

0.07

Precip Precip

mm/h

60

55

48

46

60

55

48

46

60

55

48

46

mm/h

52

47

41

40

52

47

41

40

52

47

41

40



U12 Series					
23° Trajectory	Pressure	Radius	Flow	Precip	Precip
Nozzle	psi	ft.	gpm	In/h	In/h
U-12F	15	9	1.80	2.14	2.47
	20	10	2.10	2.02	2.34
(•)	25	11	2.40	1.91	2.21
	30	12	2.60	1.74	2.01
U-12H	15	9	0.90	2.14	2.47
	20	10	1.05	2.02	2.34
	25	11	1.20	1.91	2.21
	30	12	1.30	1.74	2.01
U-12Q	15	9	0.45	2.14	2.47
	20	10	0.53	2.02	2.34
	25	11	0.60	1.91	2.21
	30	12	0.65	1.74	2.01

U12 Series					ı	METRIC
23° Trajectory						
Nozzle	Pressure bar	Radius m	Flow m³/h	Flow I/m	Precip mm/h	Precip mm/h
U-12F	1.0	2.7	0.40	6.8	55	63
	1.5	3.2	0.48	8.3	47	54
(•)	2.0	3.6	0.59	9.7	46	53
	2.1	3.7	0.60	9.8	44	51
U-12H	1.0	2.7	0.20	3.4	55	63
	1.5	3.2	0.24	4.2	47	54
	2.0	3.6	0.30	4.8	46	53
	2.1	3.7	0.30	4.9	44	51
U-12Q	1.0	2.7	0.10	1.7	55	63
	1.5	3.2	0.12	2.1	47	54
	2.0	3.6	0.15	2.4	46	53
•	2.1	3.7	0.15	2.5	44	51

U15 Series					
23°Trajectory	Pressure	Radius	Flow	Precip	Precip
Nozzle	psi	ft.	gpm	In/h	In/h
U-15F	15	11	2.60	2.07	2.39
	20	12	3.00	2.01	2.32
	25	14	3.30	1.62	1.87
	30	15	3.70	1.58	1.83
U-15H	15	11	1.30	2.07	2.39
	20	12	1.50	2.01	2.32
	25	14	1.65	1.62	1.87
Ŭ	30	15	1.85	1.58	1.83
U-15Q	15	11	0.65	2.07	2.39
	20	12	0.75	2.01	2.32
	25	14	0.82	1.62	1.87
	30	15	0.92	1.58	1.83

Note: All U-Series nozzles tested	on 4" (10.2 cm)	pop-ups
-----------------------------------	-----------------	---------

- Square spacing based on 50% diameter of throw
- ▲ Triangular spacing based on 50% diameter of throw

U15 Series					1	METRIC
23° Trajectory	Pressure	Radius	Flow	Flow	Precip	_ Precip
Nozzle	bar	m	m³/h	l/m	mm/h	mm/h
U-15F	1.0	3.4	0.60	9.8	52	60
	1.5	3.9	0.72	11.8	47	55
	2.0	4.5	0.84	13.7	41	48
	2.1	4.6	0.84	14.0	40	46
U-15H	1.0	3.4	0.30	4.9	52	60
	1.5	3.9	0.36	5.9	47	55
	2.0	4.5	0.42	6.9	41	48
ŭ	2.1	4.6	0.42	7.0	40	46
U-15Q	1.0	3.4	0.15	2.5	52	60
	1.5	3.9	0.18	2.9	47	55
	2.0	4.5	0.21	3.4	41	48
	2.1	4.6	0.21	3.5	40	46

Radius refers to recommended product spacing. Actual radii along arc may vary

VAN Series Nozzles

Variable Arc Nozzles

Features

- A simple twist of the center collar with no special tools increases or decreases the arc setting making it ideal for watering odd shaped areas
- Quickly identify radius with Top Color-coded[™] nozzles even when system is not operating
- 12, 15, and 18-VAN have matched precipitation rates with Rain Bird MPR Nozzles
- Three year trade warranty


Operating Range

- Spacing: 3 to 18 feet (0.9 m to 5.5 m)1
- Pressure: 15 to 30 psi (1.0 to 2.1 bar)
- Optimum pressure: 30 psi (2.1 bar)²

Models

- 4-VAN Series: 3 to 4 feet (0.9 to 1.2 m)
- 6-VAN Series: 4 to 6 feet (1.2 to 1.8 m)
- 8-VAN Series: 6 to 8 feet (1.8 to 2.4 m)
- 10-VAN Series: 7 to 10 feet (2.1 to 3.1 m)
- 12-VAN Series: 9 to 12 feet (2.7 to 3.7 m)
- 15-VAN Series: 11 to 15 feet (3.4 to 4.6 m)
- 18-VAN Series: 14 to 18 feet (4.3 to 5.5 m)
- To Will belies. The To Teet (ins to sis

² Rain Bird recommends using 1800 PRS Spray Bodies to maintain optimum nozzle performance in higher pressure situations.



Note: All VAN nozzles tested on 4" (10.2 cm) pop-ups

- Square spacing based on 50% diameter of throw
- ▲ Triangular spacing based on 50% diameter of throw



For Optimum Performance, Use Rain Bird 1800-SAM-PRS 30 PSI Regulated or RD1800-SAM-PRS 30 PSI





How to Specify

8 VAN

Radius Range 4: 3-4 feet (0.9-1.2 m) 6: 4-6 feet (1.2-1.8 m) 8: 6-8 feet (1.8-2.4 m) 10: 7-10 feet (2.1-3.0 m) 12: 9-12 feet (2.7-3.7 m) 15: 11-15 feet (3.4-4.6 m) 18: 14-18 feet (4.3-5.5 m) Nozzle Type VAN: Variable Arc Nozzle

0° Trajectory Pressure Radius Flow Flow Precip Precip Nozzle bar m m³/h l/m mm/h mm/l
330° Arc 1.0 0.9 0.14 2.3 189 218
1.5 1.0 0.17 2.8 183 215
2.0 1.2 0.20 3.3 152 176
2.1 1.2 0.20 3.3 152 176
270° Arc 1.0 0.9 0.12 2.0 198 229
1.5 1.0 0.14 2.3 187 216
(-\gamma) 2.0 1.2 0.16 2.7 148 171
2.1 1.2 0.17 2.8 157 181
180° Arc 1.0 0.9 0.07 1.2 173 200
1.5 1.0 0.09 1.5 180 208
2.0 1.2 0.10 1.7 139 161
2.1 1.2 0.10 1.7 139 161
90° Arc 1.0 0.9 0.05 0.8 247 285
1.5 1.0 0.06 0.9 240 277
2.0 1.2 0.06 1.1 167 193
2.1 1.2 0.07 1.1 194 224

Performance data taken in zero wind conditions

Note: Radius reduction over 25% of the normal throw of the nozzle is not recommended

¹ These ranges are based on proper pressure at nozzle.



6 Series VAN	ı				
0° Trajectory Nozzle	Pressure	Radius	Flow	Precip	Precip
	psi	ft.	gpm	In/h	In/h
330° Arc	15	4	0.85	5.58	6.44
	20	5	0.96	4.03	4.65
	25	5	1.09	4.58	5.29
	30	6	1.20	3.50	4.04
270° Arc	15	4	0.79	6.34	7.32
	20	5	0.88	4.52	5.22
	25	5	1.00	5.13	5.92
	30	6	1.10	3.92	4.53
180° Arc	15	4	0.42	5.05	5.83
	20	5	0.49	3.77	4.35
	25	5	0.55	4.24	4.90
	30	6	0.60	3.21	3.71
90° Arc	15	4	0.26	6.26	7.23
	20	5	0.30	4.62	5.33
	25	5	0.34	5.24	6.05
	30	6	0.37	3.96	4.57

6 Series VAN						METRIC
0° Trajectory	Pressure	Radius	Flow	Flow	Precip	Precip
Nozzle	bar	m	m³/h	I/m	mm/h	mm/h
330° Arc	1.0	1.2	0.19	3.2	144	166
	1.5	1.5	0.23	3.8	112	129
	2.0	1.8	0.27	4.5	91	105
	2.1	1.8	0.27	4.5	91	105
270° Arc	1.0	1.2	0.18	3.0	167	193
	1.5	1.5	0.21	3.5	124	143
	2.0	1.8	0.24	4.1	99	114
	2.1	1.8	0.25	4.2	103	119
180° Arc	1.0	1.2	0.10	1.6	139	161
	1.5	1.5	0.11	1.9	98	113
	2.0	1.8	0.13	2.2	80	92
	2.1	1.8	0.14	2.3	86	99
90° Arc	1.0	1.2	0.06	1.0	167	193
	1.5	1.5	0.07	1.2	124	143
	2.0	1.8	0.08	1.4	99	114
	2.1	1.8	0.08	1.4	99	114

8 Series VAN					
5° Trajectory Nozzle	Pressure	Radius	Flow	Precip	Precip
	psi	ft.	gpm	In/h	In/h
330° Arc	15	6	1.21	3.53	4.07
	20	7	1.36	2.91	3.36
	25	7	1.55	3.32	3.83
	30	8	1.70	2.79	3.22
270° Arc	15	6	1.11	3.95	4.55
	20	7	1.24	3.24	3.74
	25	7	1.41	3.69	4.25
	30	8	1.55	3.10	3.58
180° Arc	15	6	0.84	4.49	5.18
	20	7	0.97	3.81	4.40
	25	7	1.09	4.28	4.94
	30	8	1.19	3.58	4.13
90° Arc	15	6	0.51	5.46	6.29
	20	7	0.59	4.64	5.35
	25	7	0.66	5.19	5.98
	30	8	0.72	4.33	5.00

8 Series VAN					ı	METRIC
5° Trajectory	Pressure	Radius	Flow	Flow	Precip	Precip
Nozzle	bar	m	m³/h	I/m	mm/h	mm/h
330° Arc	1.0	1.8	0.27	4.6	91	105
	1.5	2.1	0.32	5.4	79	91
	2.0	2.3	0.38	6.3	78	90
	2.1	2.4	0.39	6.4	74	86
270° Arc	1.0	1.8	0.25	4.2	103	119
	1.5	2.1	0.30	4.9	91	105
	2.0	2.3	0.34	5.8	86	99
	2.1	2.4	0.35	5.9	81	94
180° Arc	1.0	1.8	0.19	3.2	117	135
	1.5	2.1	0.23	3.8	104	120
	2.0	2.3	0.26	4.4	98	113
	2.1	2.4	0.27	4.5	94	109
90° Arc	1.0	1.8	0.12	1.9	148	171
	1.5	2.1	0.14	2.3	127	147
	2.0	2.3	0.16	2.7	121	140
	2.1	2.4	0.16	2.7	111	128

Note: All VAN nozzles tested on 4" (10.2 cm) pop-ups

- Square spacing based on 50% diameter of throw
- ▲ Triangular spacing based on 50% diameter of throw

Performance data taken in zero wind conditions

Note: Radius reduction over 25% of the normal throw of the nozzle is not recommended

Did you know?

You can use HE-VAN nozzles to have better coverage and save water vs. VAN nozzles.

- Stronger streams and larger water droplets for increased wind resistance.
- Superior close-in watering and edges provide better coverage.
- Shortened run times saves up to 35% in water



10 Series VA	N				
10° Trajectory Nozzle	Pressure	Radius	Flow	Precip	Precip
	psi	ft.	gpm	In/h	In/h
360° Arc	15	7	1.93	3.80	4.39
	20	8	2.32	3.50	4.04
	25	9	2.52	3.00	3.46
	30	10	2.60	2.50	2.89
270° Arc	15	7	1.45	3.80	4.39
	20	8	1.75	3.50	4.04
	25	9	1.89	3.00	3.46
	30	10	2.10	2.70	3.12
180° Arc	15	7	0.97	3.80	4.39
	20	8	1.20	3.50	4.04
	25	9	1.26	3.00	3.46
	30	10	1.45	2.80	3.23
90° Arc	15	7	0.48	3.80	4.39
	20	8	0.58	3.50	4.04
	25	9	0.63	3.00	3.46
	30	10	0.75	2.90	3.35

10 Series VA	N				ı	METRIC
10° Trajectory Nozzle	Pressure	Radius	Flow	Flow	Precip	Precip
	bar	m	m³/h	I/m	mm/h	mm/h
360° Arc	1.0	2.1	0.44	7.3	96	111
	1.5	2.4	0.53	9.0	89	103
	2.0	2.7	0.57	9.8	76	88
	2.1	3.1	0.59	9.8	63	73
270° Arc	1.0	2.1	0.33	5.5	96	111
	1.5	2.4	0.4	6.8	89	103
	2.0	2.7	0.43	7.8	76	88
	2.1	3.1	0.48	7.9	68	79
180° Arc	1.0	2.1	0.22	3.7	96	111
	1.5	2.4	0.27	4.6	89	103
	2.0	2.7	0.29	5.3	76	88
	2.1	3.1	0.33	5.5	71	82
90° Arc	1.0	2.1	0.11	1.8	96	111
	1.5	2.4	0.13	2.3	89	103
	2.0	2.7	0.14	2.7	76	88
	2.1	3.1	0.17	2.8	73	85

12 Series VA	N				
15° Trajectory Nozzle	Pressure	Radius	Flow	Precip	Precip
	psi	ft.	gpm	In/h	In/h
360° Arc	15	9	1.56	1.86	2.14
	20	10	1.86	1.79	2.06
	25	11	2.12	1.68	1.95
	30	12	2.36	1.58	1.82
270° Arc	15	9	1.17	1.86	2.14
	20	10	1.39	1.79	2.06
	25	11	1.59	1.68	1.94
	30	12	1.77	1.58	1.82
180° Arc	15	9	0.78	1.86	2.14
	20	10	0.93	1.79	2.06
	25	11	1.06	1.68	1.95
	30	12	1.18	1.58	1.82
90° Arc	15	9	0.39	1.86	2.14
	20	10	0.46	1.79	2.06
	25	11	0.53	1.68	1.95
	30	12	0.59	1.58	1.82

12 Series VA	N				ı	METRIC
15° Trajectory Nozzle	Pressure bar	Radius	Flow m³/h	Flow I/m	Precip mm/h	Precip
360° Arc	1.0	m 2.7	0.35	5.80	48	mm/h 55
JOO AIC	1.5	3.2	0.33	7.37	43	50
•	2.0	3.6	0.52	8.75	41	47
	2.1	3.7	0.54	9.02	40	46
270° Arc	1.0	2.7	0.26	4.35	48	55
	1.5	3.2	0.33	5.53	43	50
	2.0	3.6	0.39	6.56	41	47
	2.1	3.7	0.41	6.76	40	46
180° Arc	1.0	2.7	0.17	2.90	48	55
	1.5	3.2	0.22	3.69	43	50
	2.0	3.6	0.26	4.37	41	47
	2.1	3.7	0.27	4.51	40	46
90° Arc	1.0	2.7	0.09	1.45	48	55
	1.5	3.2	0.11	1.84	43	50
	2.0	3.6	0.13	2.19	41	47
	21	3.7	0.14	2 25	40	46

Note: Radius reduction over 25% of the normal throw of the nozzle is not recommended

Note: All VAN nozzles tested on 4" (10.2 cm) pop-ups

■ Square spacing based on 50% diameter of throw

A Triangular spacing based on 50% diameter of throw

Did you know?

You can use HE-VAN nozzles to have better coverage and save water vs. VAN nozzles.

- Stronger streams and larger water droplets for increased wind resistance.
- Superior close-in watering and edges provide better coverage.
- Shortened run times saves up to 35% in water





15 Series VA	N				
23° Trajectory Nozzle	Pressure	Radius	Flow	Precip	Precip
	psi	ft.	gpm	In/h	In/h
360° Arc	15	11	2.60	2.07	2.39
	20	12	3.00	2.01	2.32
	25	14	3.30	1.62	1.87
	30	15	3.70	1.58	1.83
270° Arc	15	11	1.95	2.07	2.39
	20	12	2.25	2.01	2.32
	25	14	2.48	1.62	1.87
	30	15	2.78	1.58	1.83
180° Arc	15	11	1.30	2.07	2.39
	20	12	1.50	2.01	2.32
	25	14	1.65	1.62	1.87
	30	15	1.85	1.58	1.83
90° Arc	15	11	0.65	2.07	2.39
	20	12	0.75	2.01	2.32
	25	14	0.82	1.62	1.87
	30	15	0.92	1.58	1.83

15 Series VA	N				ı	METRIC
23° Trajectory	Pressure	Radius	Flow	Flow	Precip	Precip
Nozzle	bar	m	m³/h	I/m	mm/h	mm/h
360° Arc	1.0	3.4	0.60	9.8	52	60
	1.5	3.9	0.72	11.8	47	55
	2.0	4.5	0.84	13.7	41	48
	2.1	4.6	0.84	14.0	40	46
270° Arc	1.0	3.4	0.45	7.4	52	60
	1.5	3.9	0.54	8.8	47	55
	2.0	4.5	0.63	10.3	41	48
	2.1	4.6	0.63	10.5	40	46
180° Arc	1.0	3.4	0.30	4.9	52	60
	1.5	3.9	0.36	5.9	47	55
	2.0	4.5	0.42	6.9	41	48
	2.1	4.6	0.42	7.0	40	46
90° Arc	1.0	3.4	0.15	2.5	52	60
	1.5	3.9	0.18	2.9	47	55
	2.0	4.5	0.21	3.4	41	48
	2.1	4.6	0.21	3.5	40	46

18 Series VAN									
26° Trajectory Nozzle	Pressure	Radius	Flow	Precip	Precip				
	psi	ft.	gpm	In/h	In/h				
360° Arc	15	14	4.21	2.07	2.39				
	20	15	4.70	2.01	2.32				
	25	17	4.86	1.62	1.87				
	30	18	5.32	1.58	1.83				
270° Arc	15	14	3.16	2.07	2.39				
	20	15	3.52	2.01	2.32				
	25	17	3.65	1.62	1.87				
	30	18	3.99	1.58	1.83				
180° Arc	15	14	2.11	2.07	2.39				
	20	15	2.35	2.01	2.32				
	25	17	2.43	1.62	1.87				
	30	18	2.66	1.58	1.83				
90° Arc	15	14	1.05	2.07	2.39				
	20	15	1.17	2.01	2.32				
	25	17	1.22	1.62	1.87				
	30	18	1.33	1.58	1.83				

18 Series VA	N				I	METRIC
26° Trajectory Nozzle	Pressure bar	Radius m	Flow m³/h	Flow I/m	Precip mm/h	Precip mm/h
360° Arc	1.0	4.3	0.96	15.9	52	60
	1.5	4.8	1.07	18.0	47	55
(•)	2.0	5.4	1.20	19.8	41	48
	2.1	5.5	1.21	20.1	40	46
270° Arc	1.0	4.3	0.72	12.0	52	60
	1.5	4.8	0.80	13.5	47	55
└ �)	2.0	5.4	0.90	14.8	41	48
	2.1	5.5	0.91	15.1	40	46
180° Arc	1.0	4.3	0.48	8.0	52	60
	1.5	4.8	0.54	9.0	47	55
<i>ڪ</i>	2.0	5.4	0.60	9.9	41	48
	2.1	5.5	0.61	10.1	40	46
90° Arc	1.0	4.3	0.24	4.0	52	60
	1.5	4.8	0.27	4.5	47	55
	2.0	5.4	0.30	5.0	41	48
	2.1	5.5	0.30	5.0	40	46

Note: All VAN nozzles tested on 4" (10.2 cm) pop-ups

- Square spacing based on 50% diameter of throw
- ▲ Triangular spacing based on 50% diameter of throw

Performance data taken in zero wind conditions

Note: Radius reduction over 25% of the normal throw of the nozzle is not recommended

Did you know?

You can use HE-VAN nozzles to have better coverage and save water vs. VAN nozzles.

- Stronger streams and larger water droplets for increased wind resistance.
- Superior close-in watering and edges provide better coverage.
- Shortened run times saves up to 35% in water



MPR Spray Nozzles

Matched Precipitation Rate Nozzles

Features

- Matched precipitation rates across sets and patterns in 5 Series, 8 Series, 10 Series, 12 Series, and 15 Series for even water distribution and design flexibility
- MPR Nozzles are installed by more contractors than all other brands combined
- Quickly identify radius and arc with Top Color-coded™ nozzles even when system is not operating
- Three year trade warranty

Operating Range

- Spacing: 3 to 15 feet (0.9 to 4.6 m)¹
- Pressure: 15 to 30 psi (1 to 2.1 bar)
- Optimum pressure: 30 psi (2.1 bar)²

Models

- 5 Series: Ouarter, Half, Full Nozzles
- 5 Series: Bubbler Nozzles
- 8 Series: Quarter, Half, Full Nozzles
- 8 FLT Series: Designed for lower trajectory applications, such as windy areas
- 10 Series Nozzles
- 12 Series Nozzles
- 15 Series: Quarter, Half, Full Nozzles
- 15 Strip Series Nozzles
- ¹ These ranges are based on proper pressure at nozzle.
- ² Rain Bird recommends using 1800 PRS Spray Bodies to maintain optimum nozzle performance in higher pressure situations.



MPR Nozzle and Screen

How to Specify

5 F

Pattern F: Full H: Half

Q: Quarter

MPR Radius Range 5: 3-5 feet (1.1-1.5 m) 8: 5-8 feet (1.7-2.4 m) 10: 7-10 feet (2.1-3.1) 12: 19-2 feet (2.7-3.7 m) 15: 11-15 feet (3.4-4.6 m)







Rain Bird® MPR Nozzles, The Industry Standard



5 Series MPI	R				
5° Trajectory Nozzle	Pressure	Radius	Flow	Precip	Precip
	psi	ft.	gpm	In/h	In/h
5F •	15	3	0.29	3.10	3.58
	20	4	0.33	1.99	2.29
	25	4	0.37	2.23	2.57
	30	5	0.41	1.58	1.83
5H	15	3	0.14	3.00	3.46
	20	4	0.16	1.93	2.22
	25	4	0.18	2.17	2.50
	30	5	0.20	1.54	1.78
5Q	15	3	0.07	3.00	3.46
	20	4	0.08	1.93	2.22
	25	4	0.09	2.17	2.50
	30	5	0.10	1.54	1.78

5 Series MPI	R					METRIC
5° Trajectory Nozzle	Pressure	Radius	Flow	Flow	Precip	Precip
	bar	m	m³/h	I/m	mm/h	mm/h
5F •	1.0	1.1	0.06	1.1	79	91
	1.5	1.3	0.08	1.4	51	58
	2.0	1.5	0.09	1.6	57	65
	2.1	1.5	0.09	1.6	40	46
5H	1.0	1.1	0.03	0.5	76	88
	1.5	1.3	0.04	0.7	49	56
	2.0	1.5	0.04	0.7	55	64
	2.1	1.5	0.05	0.9	39	45
5Q	1.0	1.1	0.02	0.4	76	88
	1.5	1.3	0.02	0.4	49	56
	2.0	1.5	0.02	0.4	55	64
	2.1	1.5	0.02	0.4	39	45

8 Series MPR								
10° Trajectory	Pressure	Radius	Flow	Precip	_ Precip			
Nozzle	psi	ft.	gpm	In/h	ln/h			
8F	15	5	0.74	2.85	3.29			
	20	6	0.86	2.30	2.66			
	25	7	0.96	1.89	2.18			
	30	8	1.05	1.58	1.82			
8H	15	5	0.37	2.85	3.29			
	20	6	0.42	2.25	2.59			
	25	7	0.47	1.85	2.13			
	30	8	0.52	1.56	1.81			
8Q	15	5	0.18	2.77	3.20			
	20	6	0.21	2.25	2.59			
	25	7	0.24	1.89	2.18			
•	30	8	0.26	1.56	1.81			

Note: All MPR nozzles tested of	on 4" (10.2 cm) pop-ups
---------------------------------	-------------------------

Square spacing based on 50% diameter of throw

8 Series MPR	2				ı	METRIC
10° Trajectory Nozzle	Pressure bar	Radius m	Flow m ³ /h	Flow I/m	Precip mm/h	Precip
8F	1.0	1.7	0.16	2.8	72	84
	1.5	2.1	0.10	3.4	58	68
	2.0	2.4	0.23	3.9	48	55
	2.1	2.4	0.24	4.0	40	46
8H	1.0	1.7	0.08	1.4	72	84
	1.5	2.1	0.10	1.7	57	66
	2.0	2.4	0.12	1.9	47	54
	2.1	2.4	0.12	2.0	40	46
8Q	1.0	1.7	0.04	0.7	70	81
	1.5	2.1	0.05	0.8	57	66
	2.0	2.4	0.06	1.0	48	55
· ·	2.1	2.4	0.06	1.0	40	46

Note: Radius reduction over 25% of the normal throw of the nozzle is not recommended

[▲] Triangular spacing based on 50% diameter of throw

10 Series MPR					
15° Trajectory Nozzle	Pressure	Radius	Flow	Precip	Precip
	psi	ft.	gpm	In/h	In/h
10F	15	7	1.16	2.28	2.63
	20	8	1.30	1.96	2.26
	25	9	1.44	1.71	1.98
	30	10	1.58	1.52	1.75
10H	15	7	0.58	2.28	2.63
	20	8	0.65	1.96	2.26
	25	9	0.72	1.71	1.98
	30	10	0.79	1.52	1.75
10Q	15	7	0.29	2.28	2.63
	20	8	0.33	1.96	2.26
	25	9	0.36	1.71	1.98
	30	10	0.39	1.52	1.75

10 Series MPR METRIC						
15° Trajectory Nozzle	Pressure	Radius	Flow	Flow	Precip	Precip
	bar	m	m³/h	I/m	mm/h	mm/h
10F	1.0	2.1	0.26	4.2	58	67
	1.5	2.4	0.29	4.8	50	58
	2.0	3.0	0.35	6.0	39	45
	2.1	3.1	0.36	6.0	37	43
10H	1.0	2.1	0.13	2.4	58	67
	1.5	2.4	0.14	2.4	50	58
	2.0	3.0	0.18	3.0	39	45
	2.1	3.1	0.18	3.0	37	43
10Q	1.0	2.1	0.06	1.2	58	67
	1.5	2.4	0.07	1.2	50	58
	2.0	3.0	0.09	1.2	39	45
	2.1	3.1	0.09	1.2	37	43

12 Series MPR						
30° Trajectory	Pressure	Radius	Flow	Precip	_ Precip	
Nozzle	psi	ft.	gpm	In/h	In/h	
12F	15	9	1.80	2.14	2.47	
	20	10	2.10	2.02	2.34	
•	25	11	2.40	1.91	2.21	
	30	12	2.60	1.74	2.01	
12H	15	9	0.90	2.14	2.47	
	20	10	1.05	2.02	2.34	
	25	11	1.20	1.91	2.21	
	30	12	1.30	1.74	2.01	
12Q	15	9	0.45	2.14	2.47	
	20	10	0.53	2.02	2.34	
	25	11	0.60	1.91	2.21	
•	30	12	0.65	1.74	2.01	

Square spacing based on 50% diameter of throw

12 Series MPR METRIC						
30° Trajectory Nozzle	Pressure	Radius	Flow	Flow	Precip	Precip
	bar	m	m³/h	l/m	mm/h	mm/h
12F	1.0	2.7	0.40	6.8	55	63
	1.5	3.2	0.48	8.3	47	54
•	2.0	3.6	0.59	9.7	46	53
	2.1	3.7	0.60	9.8	44	51
12H	1.0	2.7	0.20	3.4	55	63
	1.5	3.2	0.24	4.2	47	54
	2.0	3.6	0.30	4.9	46	53
_	2.1	3.7	0.30	4.9	44	51
12Q	1.0	2.7	0.10	1.7	55	63
	1.5	3.2	0.12	2.1	47	54
	2.0	3.6	0.15	2.4	46	53
•	2.1	3.7	0.15	2.5	44	51

Note: Radius reduction over 25% of the normal throw of the nozzle is not recommended

[▲] Triangular spacing based on 50% diameter of throw



15 Series MF	PR				
30° Trajectory	Pressure	Radius	Flow	Precip	Precip
Nozzle	psi	ft.	gpm	In/h	In/h
15F	15	11	2.60	2.07	2.39
	20	12	3.00	2.01	2.32
	25	14	3.30	1.62	1.87
	30	15	3.70	1.58	1.83
15H	15	11	1.30	2.07	2.39
	20	12	1.50	2.01	2.32
	25	14	1.65	1.62	1.87
	30	15	1.85	1.58	1.83
15Q	15	11	0.65	2.07	2.39
	20	12	0.75	2.01	2.32
—	25	14	0.82	1.62	1.87
	30	15	0.92	1.58	1.83

- Square spacing based on 50% diameter of throw
- ▲ Triangular spacing based on 50% diameter of throw

15 Series MPR METRIC						METRIC
30° Trajectory	Pressure	Radius	Flow	Flow	Precip	_ Precip
Nozzle	bar	m	m³/h	l/m	mm/h	mm/h
15F	1.0	3.4	0.60	9.8	52	60
	1.5	3.9	0.72	11.8	47	55
	2.0	4.5	0.84	13.7	41	48
	2.1	4.6	0.84	14.0	40	46
15H	1.0	3.4	0.30	4.9	52	60
	1.5	3.9	0.36	5.9	47	55
	2.0	4.5	0.42	6.8	41	48
	2.1	4.6	0.42	7.0	40	46
15Q	1.0	3.4	0.15	2.5	52	60
	1.5	3.9	0.18	2.9	47	55
—	2.0	4.5	0.21	3.4	41	48
	2.1	4.6	0.21	3.5	40	46

Note: Radius reduction over 25% of the normal throw of the nozzle is not recommended

5 Series MPR Stream Bubbler Nozzles					
0° Trajectory Nozzle	Pressure	Radius	Flow		
	psi	ft.	gpm		
5F-B	15	5	1.50		
	20	5	1.50		
	25	5	1.50		
	30	5	1.50		
5H-B	15	5	1.00		
	20	5	1.00		
	25	5	1.00		
	30	5	1.00		
5Q-B	15	5	0.50		
	20	5	0.50		
	25	5	0.50		
	30	5	0.50		
5CST-B	15	5	0.50		
	20	5	0.50		
	25	5	0.50		
	30	5	0.50		

Note: Indicates adjusted radius at psi shown
Note: Flow at adjusted radius of 5 feet (1.5 m)

5 Series MPR S	METRIC			
0° Trajectory				
Nozzle	Pressure bar	Radius m	Flow m³/h	Flow I/m
5F-B	1.0	1.5	0.35	5.7
	1.5	1.5	0.35	5.7
	2.0	1.5	0.35	5.7
	2.1	1.5	0.35	5.7
5H-B	1.0	1.5	0.23	3.8
	1.5	1.5	0.23	3.8
&	2.0	1.5	0.23	3.8
	2.1	1.5	0.23	3.8
5Q-B	1.0	1.5	0.12	1.9
	1.5	1.5	0.12	1.9
0	2.0	1.5	0.12	1.9
	2.1	1.5	0.12	1.9
5CST-B	1.0	1.5	0.12	1.9
	1.5	1.5	0.12	1.9
-0-	2.0	1.5	0.12	1.9
	2.1	1.5	0.12	1.9

Did you know?

You can use HE-VAN or U-Series nozzles to have better coverage and save water vs. VAN nozzles.

- Stronger streams and larger water droplets for increased wind resistance.
- Superior close-in watering and edges provide better coverage.
- Shortened run times saves up to 35% in water



15 Strip Series			
30° Trajectory	Pressure	WxL	Flow
Nozzle	psi	ft.	gpm
15EST	15	4 x 13	0.45
	20	4 x 14	0.50
	25	4 x 14	0.56
	30	4 x 15	0.61
15CST	15	4 x 26	0.89
	20	4 x28	1.00
	25	4x 28	1.11
	30	4 x 30	1.21
15RCS	15	3 x 11	0.35
	20	3 x 12	0.40
	25	4 x 14	0.45
	30	4 x 15	0.49
15LCS	15	3 x 11	0.35
	20	3 x 12	0.40
	25	4 x 14	0.45
	30	4 x 15	0.49
15SST	15	4 x 26	0.89
	20	4 x 28	1.00
	25	4 x 28	1.11
	30	4 x 30	1.21
9SST	15	9 x 15	1.34
	20	9 x 16	1.47
	25	9 x 18	1.60
	30	9 x 18	1.73

W = Width of coverage pattern	L = Length of coverage pattern
--------------------------------------	---------------------------------------

Note: Radius reduction over 25% of the normal throw of the nozzle is not recommended

15 Strip Series	5			METRIC
30° Trajectory	Pressure	WxL	Flow	Flow
Nozzle	bar	m VV X L	m³/h	I/m
15EST	1.0	1.2 x 4.0	0.10	1.7
	1.5	1.2 x 4.3	0.11	2.0
•	2.0	1.2 x 4.3	0.13	2.3
	2.1	1.2 x 4.6	0.14	2.3
15CST	1.0	1.2 x 7.9	0.20	3.4
	1.5	1.2 x 8.5	0.23	4.0
•	2.0	1.2 x 8.5	0.25	4.5
	2.1	1.2 x 9.2	0.27	4.6
15RCS	1.0	0.8 x 3.2	0.08	1.3
	1.5	1.0 x 3.9	0.09	1.6
—	2.0	1.2 x 4.5	0.11	1.8
	2.1	1.2 x 4.6	0.11	1.9
15LCS	1.0	0.8 x 3.2	0.08	1.3
	1.5	1.0 x 3.9	0.09	1.6
	2.0	1.2 x 4.5	0.11	1.8
	2.1	1.2 x 4.6	0.11	1.9
15SST	1.0	1.2 x 7.9	0.20	3.4
	1.5	1.2 x 8.5	0.23	4.0
•	2.0	1.2 x 8.5	0.25	4.5
	2.1	1.2 x 9.2	0.27	4.6
9SST	1.0	2.7 x 4.6	0.30	5.1
	1.5	2.7 x 4.9	0.33	5.8
	2.0	2.7 x 5.5	0.36	6.5
	2.1	2.7 x 5.5	0.39	6.5

Performance data taken in zero wind conditions

8 FLT Series MPR					
5° Trajectory Nozzle	Pressure	Radius	Flow	Precip	Precip
	psi	ft.	gpm	In/h	In/h
8H-FLT	15	6	0.56	3.36	3.88
	20	7	0.65	2.91	3.36
	25	7	0.72	2.60	3.01
	30	8	0.79	2.38	2.75
8Q-FLT	15	6	0.28	3.32	3.83
	20	7	0.32	2.87	3.32
	25	7	0.36	2.57	2.97
	30	8	0.39	2.35	2.71

Note: All MPR nozzles tested on 4" (10.2 cm) pop-ups

- Square spacing based on 50% diameter of throw
- ▲ Triangular spacing based on 50% diameter of throw

8 FLT Series MPR METRIC						
5° Trajectory Nozzle	Pressure	Radius	Flow	Flow	Precip	Precip
	bar	m	m³/h	I/m	mm/h	mm/h
8H-FLT	1.0	1.7	0.12	2.1	87	101
	1.5	2.1	0.15	2.6	71	82
	2.0	2.4	0.18	2.9	62	71
	2.1	2.4	0.18	3.0	60	70
8Q-FLT	1.0	1.7	0.06	1.1	86	100
	1.5	2.1	0.07	1.3	71	81
	2.0	2.4	0.09	1.4	61	71
	2.1	2.4	0.09	1.5	60	69

Performance data taken in zero wind conditions

Note: Radius reduction over 25% of the normal throw of the nozzle is not recommended





SQ Nozzle Installed on PolyFlex Riser with Nozzle Adapter



One Nozzle...Two Throws

With a simple turn of the nozzle to the next preset stop, the Rain Bird SQ Nozzle adjusts from a 2.5' (0.8 m) throw to a 4' (1.2 m) throw. It's like having two nozzles in one.



Can be used on...

The SQ Nozzle is an ideal solution for a wide range of difficult-to-design areas, thanks to its compatibility with popular irrigation products.



SQ Series, Square Pattern Nozzles

The Most Precise and Efficient, Low-Volume Spray Solution for Irrigation of Small Areas with Dense Plantings

Features

- Square spray pattern and pressure compensation offer increased efficiency and control, reducing overspray, property damage and liability
- Simplify design and installation with the flexibility of applications: one nozzle throws 2.5' or 4' (0.8 m or 1.2 m) and can be used on a variety of spray heads and risers
- Meets micro irrigation system requirement for less than 26 gph flow rate at 30 psi
- Square spray pattern with edge-to-edge coverage allows you to easily design and install in small spaces
- Pressure compensation design delivers uniform flow over the pressure range
- Available in 3 models—quarter, half and full patterns with matched precipitation rate
 - Virtually no-mist performance from 20 psi to 50 psi
 - Two throw distances in each nozzle. One simple click adjusts to 2.5' or 4' (0.8 m or 1.2 m)
 - Shipped with blue filter screen (0.02" x 0.02") to maintain precise distance of flow, and to prevent clogging
- Compatible with all 1800 Sprays, Xeri-Pops, New PolyFlex Riser Adapter, UNI-Spray and SCH 80 risers

Operating Range

- Pressure: 20 to 50 psi (1.4 to 3.5 bar)
- Flow rates: 6, 12 and 24 gph (22.7, 45.4 and 90.8 l/h)
- · Required filtration: 40 mesh

Note: See page 121 for SQ Series performance charts.

Models

- SQ-QTR: SQ Nozzle, quarter pattern
- · SQ-HLF: SQ Nozzle, half pattern
- SQ-FUL: SQ Nozzle, full pattern
- SQ-ADP12: SQ Nozzle Adapter with 12" PolyFlex Riser
- SQ-ADP24: SQ Nozzle Adapter with 24" PolyFlex Riser
- SQ-ADP: SQ PolyFlex Riser Adapter only
- * Note: A PA-8S Plastic Shrub Adapter (see page 10) is needed when using an SQ Series Nozzle mounted on a SCH 80 riser.

1300A-F

Adjustable Full-Circle Bubbler

Features


- Stainless Steel adjustment screw regulates flow and radius for spacing between from 1 to 3 feet (0.3 m to 0.9 m) apart
- · Non-corrosive plastic and stainless steel construction for long life
- Shipped with SR-050 1/2" (15/21) inlet filter screen for easy installation and resistance to debris
- Operates over a wide range of pressures
- Five year trade warranty

Operating Range

- Flow: 1.0 to 2.3 gpm (3.6 to 8.4 l/m)
- Spacing: 1 to 3 feet (0.3 to 0.9 m)¹
- Pressure: 10 to 60 psi (0.7 to 4.1 bar)²

Model

- 1300A-F
- ¹ These ranges are based on proper pressure at nozzle
- ² Rain Bird recommends using 1800 PRS Spray Bodies to maintain optimum nozzle performance in higher pressure situations



1300A-F	M	ETRIC	
Nozzle	Pressure bar	Flow m³/h	Flow I/m
F	0.7	0.23	3.6
	1.0	0.26	4.2
	1.5	0.30	4.8
	2.0	0.34	5.4
	2.5	0.39	6.0
	3.0	0.43	7.2
	3.5	0.48	7.8
	4.0	0.52	8.4
	4.1	0.53	8.4



1300A-F

1400 Series

Pressure Compensating Full-Circle Bubblers

Features

- Low flow rates allow water to be absorbed as needed.
 Reduces runoff
- Flow will not fluctuate at pressures between 20 and 90 psi (1.4 to 6.2 bar)
- Flow is not adjustable for increased vandal resistance
- Shipped with special SR-050 ½" (15/21) bubbler filter screen for easy installation and resistance to debris
- Trickle pattern on models 1401 and 1402; umbrella pattern on models 1404 and 1408
- Five-year trade warranty



1400 Series

Operating Range

- Flow: 0.25 to 2.00 gpm (1.2 to 7.2 l/m)
- Spacing: 1 to 3 feet (0.3 to 0.9 m)*
- Pressure: 20 to 90 psi (1.4 to 6.2 bar)

Models

- 1401: 0.25 gpm (0.06 m³/h; 0.9 l/m); full-circle, trickle pattern
- 1402: 0.50 gpm (0.11 m³/h; 1.8 l/m); full-circle, trickle pattern
- 1404: 1.00 gpm (0.23 m³/h; 3.6 l/m); full-circle, umbrella pattern
- 1408: 2.00 gpm (0.46 m³/h; 7.2 l/m); full-circle, umbrella pattern
- * These ranges are based on proper pressure at nozzle. Rain Bird recommends using 1800/ RD1800 PRS Spray Bodies to maintain optimum nozzle performance in higher pressure situations.

Pressure-Compensating Modules

Point-Source Medium-Flow Emitters for Watering Larger Shrubs and Trees



PCT-05, PCT-07, PCT-10

· ½" FPT inlet that easily threads onto a ½" PVC riser

Operating Range

- Flow: 5, 7, 10 gph (18.93, 26.50, 37.95 l/h)
- Pressure: 10 to 50 psi (0.7 to 3.5 bar)
- Required filtration: 100 mesh (150 micron)

Refer to page 118 for more information



Rotors

Major Products	Closed Case Rotors				Open Case Rotor	
Primary Applications	3500 Series	5000 Series	Falcon™ 6504 Series	8005 Series	2045A Maxi-Paw™ Series	XLR Water Jet Series
Turfgrass 15' to 35'	•	•				
Turfgrass 25' to 50'		•	•	•	•	
Turfgrass more than 50'			•			•
Residential	•	•			•	
Commercial		•	•		•	•
Vandalism/Damage Prone Areas						
Slopes	•	•	•	•	•	•
Ground Cover/Shrubs	•	•				
Athletic Fields			•			•
Pressure Regulating		•				
High Wind Areas	•	•	•		•	•
Taller Turfgrass		•		•		•
Non-Potable Water	•	•	•	•	•	•



Water Saving Tips

- Rain Curtain[™] nozzle technology is the standard in water-saving nozzle performance. Rain Curtain[™] performance is available in all Rain Bird Rotors.
- 5000 Series Rotors with PRS reduce water waste from 15%-45%.
 By eliminating pressure variation and/ or over pressurization, you'll save water and deliver greener results.
- All rotors with Seal-a-Matic[™] (SAM) check valves prevent drainage from heads at lower elevations, stop water waste and eliminate landscape damage due to flooding and/ or erosion.

3500 Series

Compact Residential Rotor. Big on Value and Convenience

Features

- Rain Curtain™ nozzles deliver even distribution over the entire radius including large wind resistant droplets and gentle close-in watering resulting in greener turf using less water
- Oversized wiper seal prevents leaks and protects internals from debris
- Arc adjustment through the top of the rotor requiring only a flat-blade screwdriver
- · 3 year trade warranty

Options


- SAM Seal-A-Matic[™] check valve holds up to 7 ft (2.1 m) of elevation change
- · Purple Cover (NP) for non-potable water

Operating Specifications

- Precipitation rate: 0.37 to 0.83 inches per hour (9 to 21 mm/h)
- Radius: 15 to 35 feet (4.6 to 10.7 m)
- Radius may be reduced up to 25% with radius reduction screw
- Pressure: 25 to 55 psi (1.7 to 3.8 bar)
- Flow rate: 0.54 to 4.6 gpm (2.0 to 17.4 l/m)
- · ½" NPT female bottom threaded inlet
- Reversing full- and part-circle adjustment 40° 360°
- · Nozzle trajectory of 25°

Models

- 3504-PC: 4" part/reverse full circle
- 3504-PC-SAM: 4" part/reverse full circle with SAM
- 3504-PC-SAM-NP: 4" part/reverse full circle with SAM and NP cover
- 3500-S-PC-SAM: 4" part/reverse full circle shrub model with SAM







Superior Distribution Uniformity

The 3500 Series Rotors with Rain Curtain™ Technology are engineered to deliver a uniform spray pattern, giving you a consistently green lawn throughout.

3500 Series Rotors meet the requirements of the ASABE/ICC 802-2014 standard

The average DU(LQ) of the applicable products exceed 0.65 distribution uniformity.

Product	Туре	Radius	DU(LQ)
3500	Rotors	15 - 35 ft.	> 0.75

To view the complete document of compliance for Rain Bird products that have been tested to meet the requirements of the ASABE/ICC 802-2014 standard and the California MWELO go to: www.rainbird.com/agency/california/MWELO.htm



3504 Series Nozzle Performance								
Pressure	Nozzle	Radius	Flow	Precip	Precip			
psi		ft.	gpm	In/h	In/h			
25	0.75	15	0.54	0.46	0.53			
	1.0	20	0.77	0.37	0.43			
	1.5	23	1.06	0.39	0.45			
	2.0	27	1.40	0.37	0.43			
	3.0	29	2.17	0.50	0.57			
	4.0	31	2.97	0.59	0.69			
35	0.75	17	0.67	0.45	0.52			
	1.0	21	0.92	0.40	0.46			
	1.5	23	1.28	0.47	0.54			
	2.0	27	1.69	0.45	0.52			
	3.0	31	2.60	0.52	0.60			
	4.0	33	3.58	0.63	0.73			
45	0.75	17	0.77	0.51	0.59			
	1.0	21	1.06	0.46	0.53			
	1.5	24	1.48	0.49	0.57			
	2.0	27	1.93	0.51	0.59			
	3.0	31	3.00	0.60	0.69			
	4.0	35	4.13	0.65	0.75			
55	0.75	18	0.85	0.51	0.58			
	1.0	22	1.18	0.47	0.54			
	1.5	24	1.65	0.55	0.64			
	2.0	28	2.15	0.53	0.61			
	3.0	32	3.25	0.61	0.71			
	4.0	35	4.60	0.72	0.83			

- Square spacing based on 50% diameter of throw
- ▲ Triangular spacing based on 50% diameter of throw

Performance data collected in zero wind conditions

Performance data derived from tests that conform with ASABE Standards; ASABE S398.1. See page 186 for complete ASABE Test Certification Statement.

3504 Series Nozzle Performance METRIC								
Pressure	Nozzle	Radius	Flow	Flow	Precip	Precip		
bar		m	m³/h	I/m	mm/h	mm/h		
1.7	0.75 1.0 1.5 2.0 3.0 4.0	4.6 6.1 7.0 8.2 8.8 9.4	0.12 0.17 0.24 0.32 0.49 0.67	2.04 2.91 4.01 5.30 8.21 11.24	12 9 10 9 13	14 11 11 11 15		
2.0	0.75	4.8	0.13	2.24	12	13		
	1.0	6.2	0.19	3.14	10	11		
	1.5	7.0	0.26	4.35	11	12		
	2.0	8.2	0.34	5.74	10	12		
	3.0	9.1	0.53	8.87	13	15		
	4.0	9.7	0.73	12.17	16	18		
2.5	0.75	5.2	0.16	2.58	12	13		
	1.0	6.4	0.21	3.55	10	12		
	1.5	7.0	0.30	4.94	12	14		
	2.0	8.2	0.39	6.51	12	13		
	3.0	9.4	0.60	10.03	13	16		
	4.0	10.1	0.83	13.82	16	19		
3.0	0.75 1.0 1.5 2.0 3.0 4.0	5.2 6.4 7.3 8.2 9.4 10.6	0.17 0.24 0.33 0.43 0.67 0.92	2.86 3.93 5.49 7.17 11.13 15.32	13 12 12 13 15	15 13 14 15 17		
3.5	0.75	5.4	0.19	3.09	13	15		
	1.0	6.6	0.26	4.27	12	14		
	1.5	7.3	0.36	5.97	13	15		
	2.0	8.4	0.47	7.79	13	15		
	3.0	9.6	0.71	11.90	15	18		
	4.0	10.7	1.00	16.66	18	20		
3.8	0.75	5.5	0.19	3.22	13	15		
	1.0	6.7	0.27	4.47	12	14		
	1.5	7.3	0.37	6.25	14	16		
	2.0	8.5	0.49	8.14	13	15		
	3.0	9.8	0.74	12.30	16	18		
	4.0	10.7	1.04	17.41	18	21		

5000 Series

Engineered to be the Industry's Most Reliable and Best Performing Rotor

Features


- Oversized wiper seal prevents leaks and protects internals from debris
- Rain Curtain™ nozzles deliver even distribution over the entire radius including large wind resistant droplets and gentle close-in watering resulting in greener turf using less water
- A history of proven performance and reliability tested in millions of installations
- Self-flushing arc adjustment port that prevents buildup of debris
- 5 year trade warranty

Operating Specifications

- Precipitation rate: 0.20 to 1.50 in/hr (5 to 38 mm/h)
- Radius: 25 to 50 feet (7.6 to 15.2 m)
- · Radius may be reduced up to 25% with radius reduction screw
- Pressure: 25 to 65 psi (1.7 to 4.5 bar)
- Flow Rate: 0.76 to 9.63 gpm (3.0 to 36.6 l/m; 0.17 to 2.19 m³/h)
- Reversing full- and part-circle adjustment from 40° 360°
- Standard nozzle trajectory of 25°. Low angle nozzle trajectory of 10°.
 MPR nozzles varied nozzle trajectory between 12° 25°.

Optional Features

- Plus (+) Flow shutoff "The Green Top." Reduce downtime on jobs by flushing and nozzling rotors without running back and forth to the controller or valves
- PRS (R) with flow optimizer technology. The 45 psi pressure regulator lowers water bills, provides exact flow of each rotor, equalizes lateral lines, and eliminates misting and fogging
- SAM Seal-A-Matic™ check valve holds up to 7 feet (2.1 m) of elevation change
- Stainless steel (SS) riser helps deter vandalism on public turf areas (available on 4 and 6" models)
- Purple cover (NP) for non-potable systems







0.20 to 1.50 in/hr (5 to 37 mm/h)



25 to 65 psi (1.7 to 4.5 bar)



0.76 to 9.63 gpm (3.0 to 36.6 l/m) (0.17 to 2.19 m³/h)



Shrub: 4" (10.2 cm) 6" (15.2 cm) 12" (30.5 cm)

Shrub: 7 ³/₄" (19.7cm) 4": 7 ³/₈" (18.5 cm) 6": 9 ⁵/₈" (24.5 cm) 12": 16 ⁷/₈" (42.9 cm)

3/4" NPT

5000 Series

5000 Series Rotors meet the requirements of the ASABE/ICC 802-2014 standard

The average DU(LQ) of the applicable products exceed 0.65 distribution uniformity.

Product	Туре	Radius	DU(LQ)
5000 Series	Rotors	25 - 50 ft.	> 0.70

To view the complete document of compliance for Rain Bird products that have been tested to meet the requirements of the ASABE/ICC 802-2014 standard and the California MWELO go to: www.rainbird.com/agency/california/MWELO.htm





5000 Series (cont.)

S Shrub Model

PC Part Circle & Reversing Full Circle

+ Flow Shut-off

FC Non-Reversing Full Circle

Models

Part-circle units (PC) are adjustable from 40° –360°. Full-circle units (FC) are 360 degrees only.

- 5000SPCSAM: 5000S Shrub Part Circle SAM
- 5000+SPCSAM: 5000S Shrub Plus Part Circle SAM
- 5000+SPCSAMNP: 5000S Shrub Plus Part Circle SAM Non Potable
- 5000+SPCSAMR: 5000S Shrub Plus PRS Part Circle SAM
- 5000+SPCSAMRN: 5000S Shrub Plus PRS Part Circle SAM Non Potable
- 5004PC: 5004 Part Circle
- 5004PC20: 5004 Part Circle w/2.0 Nozzle
- 5004PC30: 5004 Part Circle w/3.0 Nozzle
- 5004PCSAM: 5004 Part Circle SAM
- 5004PCSAM20: 5004 Part Circle SAM w/2.0 Nozzle
- 5004PCNP: 5004 Part Circle Non Potable
- 5004PCR: 5004 Part Circle PRS
- 5004+PC: 5004 Plus Part Circle
- 5004+PC20: 5004 Plus Part Circle w/2.0 Nozzle
- 5004+PC30: 5004 Plus Part Circle w/3.0 Nozzle
- 5004+PCSAM: 5004 Plus Part Circle SAM
- 5004+PCR 5004: Plus Part Circle PRS
- 5004+PCSAMR: 5004 Plus Part Circle SAM PRS
- 5004+PCSAMR20: 5004 Plus Part Circle SAM PRS w/2.0 Nozzle
- 5004+PCSAMR30: 5004 Plus Part Circle SAM PRS w/3.0 Nozzle
- 5004+PCSAMRNP: 5004 Plus Part Circle SAM PRS Non Potable
- 5004+PCSAMRSS: 5004 Plus Part Circle SAM PRS Stainless Steel
- 5004+PCSAMRNS: 5004 Plus Part Circle SAM PRS Stainless Steel Non Potable
- 5004FC 5004: Full Circle
- 5004+FC 5004: Plus Full Circle
- 5004+FCSAM: 5004 Plus Full Circle SAM
- 5004+FCSAMR: 5004 Plus Full Circle SAM PRS
- 5004+FCSAMRSS: 5004 Plus Full Circle Stainless Steel SAM PRS

SAM Check valve

SS Stainless Steel

R Pressure Regulation

NP Non-Potable Cover

- 5006PC: 5006 Part Circle
- 5006PC30: 5006 Part Circle w/ 3.0 Nozzle
- · 5006+PC: 5006 Plus Part Circle
- 5006+PCSAM: 5006 Plus Part Circle SAM
- 5006+PCSAMNP: 5006 Plus Part Circle SAM Non Potable
- 5006+PCSAMR: 5006 Plus Part Circle SAM PRS
- 5006+PCSAMRNP: 5006 Plus Part Circle SAM PRS Non Potable
- 5006+PCSAMRSS: 5006 Plus Part Circle SAM PRS Stainless Steel
- 5006+PCSAMRNS: 5006 Plus Part Circle SAM PRS Stainless Steel Non Potable
- 5012+PCSAMR: 5012 Plus Part Circle SAM PRS
- 5012+PCSAMRNP: 5012 Plus Part Circle SAM PRS Non Potable

5000 Seri	es Std. An	gle Rain C	urtain™ N	ozzle Perfo	ormance
Pressure	Nozzle	Radius	Flow	Precip	Precip
psi		ft.	gpm	In/h	In/h
25	1.5	33	1.12	0.20	0.23
	2.0	35	1.50	0.24	0.27
	2.5	35	1.81	0.28	0.33
	3.0	36	2.26	0.34	0.39
	4.0	36	2.91	0.43	0.49
	5.0	37	3.72	0.52	0.60
	6.0	37	4.25	0.60	0.69
	8.0	33	5.90	1.26	1.50
35	1.5	34	1.35	0.22	0.26
	2.0	36	1.81	0.27	0.31
	2.5	37	2.17	0.31	0.35
	3.0	38	2.71	0.36	0.42
	4.0	40	3.50	0.42	0.49
	5.0	41	4.47	0.51	0.59
	6.0	43	5.23	0.54	0.63
	8.0	41	7.06	0.94	1.10
45	1.5 2.0 2.5 3.0 4.0 5.0 6.0 8.0	35 37 37 39 42 43 44	1.54 2.07 2.51 3.09 4.01 5.09 6.01 8.03	0.24 0.29 0.35 0.37 0.44 0.48 0.59 0.92	0.28 0.34 0.41 0.43 0.51 0.56 0.69 1.06
55	1.5	35	1.71	0.27	0.31
	2.0	37	2.30	0.32	0.37
	2.5	37	2.76	0.39	0.45
	3.0	40	3.47	0.42	0.48
	4.0	42	4.44	0.48	0.56
	5.0	45	5.66	0.54	0.62
	6.0	50	6.63	0.51	0.59
	8.0	47	8.86	0.80	0.93
65	1.5	34	1.86	0.31	0.36
	2.0	35	2.52	0.40	0.46
	2.5	37	3.01	0.42	0.49
	3.0	40	3.78	0.45	0.53
	4.0	42	4.83	0.53	0.61
	5.0	45	6.16	0.59	0.68
	6.0	50	7.22	0.55	0.64
	8.0	48	9.63	0.84	0.97

Performance data collected in zero wind conditions

Performance data derived from tests that conform with ASABE Standards; ASABE S398.1. See page 186 for complete ASABE Test Certification Statement.

5000 Serie	s Std. Ang	Jle Rain C	urtain™ N	lozzle Per	formance	METRIC
Pressure	Nozzle	Radius	Flow	Flow	Precip	Precip
bar		m	m³/h	I/m	mm/h	mm/h
2.0	1.5	10.2	0.28	4.8	5	6
	2.0	10.8	0.36	6.0	6	7
	2.5	10.9	0.44	7.2	7	9
	3.0	11.2	0.55	9.0	9	10
	4.0	11.6	0.71	12.0	11	12
	5.0	12.1	0.91	15.0	13	15
	6.0	12.4	1.05	17.4	15	17
	8.0	11.8	1.45	24.0	32	37
2.5	1.5	10.4	0.31	5.4	6	7
	2.0	11.0	0.41	6.6	7	8
	2.5	11.3	0.50	8.4	8	9
	3.0	11.2	0.62	10.2	9	11
	4.0	12.3	0.81	13.2	11	13
	5.0	12.7	1.03	17.4	13	15
	6.0	13.2	1.21	20.4	14	16
	8.0	13.3	1.63	27.0	24	28
3.0	1.5	10.6	0.34	6.0	6	7
	2.0	11.2	0.45	7.8	7	8
	2.5	11.3	0.56	9.6	9	10
	3.0	12.1	0.69	11.4	9	11
	4.0	12.7	0.89	15.0	11	13
	5.0	13.5	1.13	18.6	12	14
	6.0	13.4	1.34	22.2	13	17
	8.0	13.4	1.79	30.0	23	27
3.5	1.5 2.0 2.5 3.0 4.0 5.0 6.0 8.0	10.7 11.3 11.3 12.2 12.8 13.7 14.2 14.9	0.37 0.49 0.60 0.74 0.97 1.23 1.45 1.93	6.0 8.4 10.2 12.6 16.2 20.4 24.0 32.4	7 8 9 10 12 13 13	8 9 11 12 14 15 15
4.0	1.5	10.6	0.40	6.6	7	8
	2.0	11.1	0.52	9.0	8	10
	2.5	11.3	0.64	10.8	10	12
	3.0	12.2	0.80	13.2	11	12
	4.0	12.8	1.04	17.4	13	15
	5.0	13.7	1.32	22.2	14	16
	6.0	14.9	1.55	25.8	14	16
	8.0	15.2	2.06	34.2	21	25
4.5	1.5 2.0 2.5 3.0 4.0 5.0 6.0 8.0	10.4 10.7 11.3 12.2 12.8 13.7 14.6 15.2	0.42 0.55 0.68 0.84 1.10 1.40 1.64 2.19	7.2 9.0 11.4 13.8 18.0 23.4 28.2 36.6	8 10 11 11 13 15 15	9 11 12 13 15 17 18 22

Square spacing based on 50% diameter of throw

[▲] Triangular spacing based on 50% diameter of throw



5000 Seri	es Low An	gle Nozzle	e Perform	ance	
Pressure	Nozzle	Radius	Flow	Precip	Precip
psi		ft.	gpm	In/h	In/h
25	1.0 LA	25	0.76	0.23	0.27
	1.5 LA	27	1.15	0.30	0.35
	2.0 LA	29	1.47	0.34	0.39
	3.0 LA	29	2.23	0.51	0.59
35	1.0 LA	28	0.92	0.23	0.26
	1.5 LA	30	1.38	0.30	0.34
	2.0 LA	31	1.77	0.35	0.41
	3.0 LA	33	2.68	0.47	0.55
45	1.0 LA	29	1.05	0.24	0.28
	1.5 LA	31	1.58	0.32	0.37
	2.0 LA	32	2.02	0.38	0.44
	3.0 LA	35	3.07	0.48	0.56
55	1.0 LA	29	1.17	0.27	0.31
	1.5 LA	31	1.76	0.35	0.41
	2.0 LA	33	2.24	0.40	0.46
	3.0 LA	36	3.41	0.51	0.58
65	1.0 LA	29	1.27	0.29	0.34
	1.5 LA	31	1.92	0.38	0.44
	2.0 LA	33	2.45	0.43	0.50
	3.0 LA	36	3.72	0.55	0.64

- Square spacing based on 50% diameter of throw
- ▲ Triangular spacing based on 50% diameter of throw Performance data collected in zero wind conditions

Performance data derived from tests that conform with ASABE Standards; ASABE S398.1. See page 186 for complete ASABE Test Certification Statement.

5000 Seri	ies Low <i>A</i>	Ingle No	zzle Per	formance	e	METRIC
Pressure	Nozzle	Radius	Flow	Flow	Precip	Precip
bar		m	m³/h	I/m	mm/h	mm/h
1.7	1.0 LA	7.6	0.17	3.0	6	7
	1.5 LA	8.2	0.26	4.2	8	9
	2.0 LA	8.8	0.33	5.4	9	10
	3.0 LA	8.8	0.51	8.4	13	15
2.0	1.0 LA	8.0	0.18	3.0	6	6
	1.5 LA	8.6	0.28	4.8	8	9
	2.0 LA	9.1	0.36	6.0	9	10
	3.0 LA	9.3	0.55	9.0	13	15
2.5	1.0 LA	8.6	0.20	3.6	5	6
	1.5 LA	9.2	0.32	5.4	8	9
	2.0 LA	9.5	0.41	6.6	9	10
	3.0 LA	10.1	0.62	10.2	12	14
3.0	1.0 LA	8.8	0.22	3.6	6	7
	1.5 LA	9.4	0.35	6.0	8	9
	2.0 LA	9.7	0.45	7.8	10	11
	3.0 LA	10.6	0.68	11.4	12	14
3.5	1.0 LA	8.8	0.24	4.2	6	7
	1.5 LA	9.4	0.38	6.6	9	10
	2.0 LA	9.9	0.49	8.4	10	11
	3.0 LA	10.8	0.74	12.6	13	15
4.0	1.0 LA	8.8	0.26	4.2	7	8
	1.5 LA	9.4	0.41	6.6	9	11
	2.0 LA	10.1	0.52	9.0	10	12
	3.0 LA	11.0	0.80	13.2	13	15
4.5	1.0 LA	8.8	0.27	4.8	7	8
	1.5 LA	9.4	0.44	7.2	10	11
	2.0 LA	10.1	0.56	9.0	11	13
	3.0 LA	11.0	0.84	13.8	14	16

Tools **Holdup Tool with Rotor Tool Bubble Level Features Features** • Flat blade screwdriver and pull-up tool all in one • Combination holdup tool/bubble level makes proper installation easier • Works with 3500, 5000, Falcon® 6504, and 8005 • Works with 5000, Falcon® 6504, and 8005 Model Model ROTORTOOL HOLDUPTOOL ROTORTOOL HOLDUPTOOL



5000 PRS Std. Angle Rain Curtain™ Nozzle Performance								
Pressure psi	Nozzle	Radius ft.	Flow gpm	Precip In/h	Precip In/h			
25	1.5 2.0 2.5 3.0 4.0 5.0 6.0 8.0	33 35 35 36 36 37 37 33	1.12 1.5 1.81 2.26 2.91 3.72 4.25 5.9	0.2 0.24 0.28 0.34 0.43 0.52 0.60 1.26	0.23 0.27 0.33 0.39 0.49 0.66 0.69 1.5			
35	1.5 2.0 2.5 3.0 4.0 5.0 6.0 8.0	34 36 37 38 40 41 43	1.35 1.81 2.17 2.71 3.5 4.47 5.23 7.06	0.22 0.27 0.31 0.36 0.42 0.51 0.54 0.94	0.26 0.31 0.35 0.41 0.49 0.59 0.63 1.1			
45	1.5 2.0 2.5 3.0 4.0 5.0 6.0 8.0	35 37 37 39 42 43 44	1.54 2.07 2.51 3.09 4.01 5.09 6.01 8.03	0.24 0.29 0.35 0.37 0.44 0.48 0.55 0.92	0.28 0.34 0.41 0.43 0.51 0.56 0.63 1.06			
55 – 75	1.5 2.0 2.5 3.0 4.0 5.0 6.0 8.0	35 37 37 39 42 43 44	1.59 2.14 2.6 3.2 4.15 5.27 6.22 8.31	0.25 0.3 0.37 0.39 0.45 0.5 0.57	0.29 0.35 0.42 0.44 0.52 0.58 0.65 0.84			

- Square spacing based on 50% diameter of throw
- ▲ Triangular spacing based on 50% diameter of throw

Performance data collected in zero wind conditions

Performance data derived from tests that conform with ASABE Standards; ASABE S398.1. See page 186 for complete ASABE Test Certification Statement.

5000 PRS	Std. Angl	e Rain Cu	rtain™ N	ozzle Perf	ormance	METRIC
Pressure	Nozzle	Radius	Flow	Flow	Precip	Precip
bar		m	m³/h	I/m	mm/h	mm/h
1.7	1.5 2.0 2.5 3.0 4.0 5.0 6.0 8.0	10.1 10.7 10.7 11.0 11.3 11.9 11.9	0.25 0.34 0.41 0.51 0.66 0.84 0.97 1.34	4.2 5.4 6.6 8.4 10.8 13.8 16.2 22.2	5 6 7 8 10 12 14 22	6 7 8 10 12 14 16 26
2.0	1.5	10.2	0.28	4.8	5	6
	2.0	10.8	0.36	6.0	6	7
	2.5	10.9	0.44	7.2	7	9
	3.0	11.2	0.55	9.0	9	10
	4.0	11.6	0.71	12.0	11	12.6
	5.0	12.1	0.91	15.0	13	15
	6.0	12.4	1.05	17.4	15	17
	8.0	11.8	1.45	24.0	32	37
2.5	1.5 2.0 2.5 3.0 4.0 5.0 6.0 8.0	10.4 11.0 11.3 11.2 12.3 12.7 13.2 13.3	0.31 0.41 0.50 0.62 0.81 1.03 1.21 1.63	5.4 6.6 8.4 10.2 13.2 17.4 20.4 27.0	6 7 8 9 11 13 14 24	7 8 9 11 13 15 16
3.0	1.5	10.6	0.34	6.0	6	7
	2.0	11.2	0.45	7.8	7	8
	2.5	11.3	0.56	9.6	9	10
	3.0	12.1	0.69	11.4	9	11
	4.0	12.7	0.89	16.8	11	13
	5.0	13.5	1.13	18.6	12	14
	6.0	13.9	1.34	22.2	14	16
	8.0	14.1	1.79	30.0	23	27
3.5 – 5.2	1.5	10.6	0.35	6.0	6	7
	2.0	11.2	0.47	7.8	8	9
	2.5	11.3	0.58	10.2	9	11
	3.0	12.1	0.71	12.0	10	11
	4.0	12.7	0.92	15.6	12	13
	5.0	13.5	1.17	19.2	13	15
	6.0	13.9	1.39	22.8	14	17
	8.0	14.1	1.85	31.2	18	21






5000 PRS Low Angle Nozzle Performance									
Pressure psi	Nozzle	Radius ft.	Flow gpm	Precip In/h	Precip In/h				
25	1.0 LA 1.5 LA 2.0 LA 3.0 LA	25 27 29 29	0.76 1.15 1.47 2.23	0.22 0.3 0.34 0.51	0.26 0.35 0.39 0.59				
35	1.0 LA 1.5 LA 2.0 LA 3.0 LA	28 30 31 33	0.92 1.38 1.77 2.68	0.21 0.3 0.35 0.47	0.25 0.34 0.41 0.55				
45	1.0 LA 1.5 LA 2.0 LA 3.0 LA	29 31 32 35	1.05 1.58 2.02 3.07	0.23 0.32 0.38 0.48	0.26 0.37 0.44 0.56				
55 – 75	1.0 LA 1.5 LA 2.0 LA 3.0 LA	29 31 32 35	1.09 1.64 2.09 3.18	0.25 0.33 0.39 0.5	0.29 0.38 0.45 0.58				

- Square spacing based on 50% diameter of throw
- ▲ Triangular spacing based on 50% diameter of throw

Performance data collected in zero wind conditions

Performance data derived from tests that conform with ASABE Standards; ASABE S398.1. See page 186 for complete ASABE Test Certification Statement.

5000 PRS Low Angle Nozzle Performance METRIC								
Pressure	Nozzle	Radius	Flow	Flow	Precip	Precip		
bar		m	m³/h	I/m	mm/h	mm/h		
1.7	1.0 LA	7.6	0.17	3.0	6	7		
	1.5 LA	8.2	0.26	4.2	8	9		
	2.0 LA	8.8	0.33	5.4	9	10		
	3.0 LA	8.8	0.51	8.4	13	15		
2.0	1.0 LA	8.0	0.18	3.0	6	6		
	1.5 LA	8.6	0.28	4.8	8	9		
	2.0 LA	9.1	0.36	6.0	9	10		
	3.0 LA	9.3	0.55	9.0	13	15		
2.5	1.0 LA	8.6	0.20	3.6	5	6		
	1.5 LA	9.2	0.32	5.4	8	9		
	2.0 LA	9.5	0.41	6.6	9	10		
	3.0 LA	10.1	0.62	10.2	12	14		
3.0	1.0 LA	8.8	0.22	3.6	6	7		
	1.5 LA	9.4	0.35	6.0	8	9		
	2.0 LA	9.7	0.45	7.8	10	11		
	3.0 LA	10.6	0.68	11.4	12	14		
3.5 – 5.2	1.0 LA	8.8	0.23	3.6	6	7		
	1.5 LA	9.4	0.36	6.0	8	10		
	2.0 LA	9.7	0.47	7.8	10	12		
	3.0 LA	10.6	0.70	12.0	13	15		



Flow 45 50 55 65 70 75 80 **GPM** 6 0 0.33 0.66 1.54 0.96 1.25 1.81 2.06 0 0.43 1.62 2.33 2.67 8 0.85 1.24 1.98 10 0 0.55 1.07 1.57 2.05 2.52 2.96 3.39 **Total Zone Flow in GPM** 12 0 0.66 1.27 1.86 2.43 2.97 3.50 4.01 14 4.70 0 0.77 1.49 2.18 2.84 3.48 4.10 16 0 0.87 1.69 2.48 3.24 3.97 4.67 5.35 18 0 0.98 1.90 2.79 3.64 4.46 5.25 6.01 20 0 1.10 2.12 3.10 4.05 4.96 5.83 6.68 22 4.46 0 1.21 2.33 3.42 5.47 6.44 7.37 24 0 1.30 2.54 3.72 4.85 7.00 8.01 5.94

How much water can you save each minute using Rain Bird®

5000 PRS Rotors with Flow Optimizer Technology?

Total gallons of water saved per minute of run time Ex: At 70 psi a zone with 20 gpm of flow would save 4.96 gallons a minute with 5000 PRS

4.04

4.34

4.65

5.27

5.66

6.07

26

28

30

0

0

1.41

1.53

1.63

2.76

2.96

3.17

6.45

6.93

7.43

7.60

8.16

8.74

8.70

9.35

10.02

5000 Series MPR Nozzles


Perfectly Balanced Coverage with the 5000 Series Rotor

Features

- Rain Curtain[™] nozzles deliver even distribution over the entire radius including large wind resistant droplets and gentle close-in watering resulting in greener turf using less water
- Precipitation rate is automatically matched with a uniform radius that does not require stream deflection
- Matched 0.6"/hour precipitation rates enable large and small turf areas to be zoned together by mixing rotors and Rain Bird R-VAN rotary nozzles

Models

 5000MPRMPK: 5000/5000 Plus Series MPR nozzle tree multi pack- 25′, 30′, 35′ radius in Quarter, Third, Half, Full arc





Installing Rotors with 5000 series MPR nozzles and Rain Bird R-VAN Rotary Nozzles in the same zone allows for matched precipitation from 8' to 35' (2.4m to 10.7m)



5000 Series MPR Nozzles

5000 MPR Nozzles meet the requirements of the ASABE/ICC 802-2014 standard

The average DU(LQ) of the applicable products exceed 0.65 distribution uniformity.

Product	Type	Radius	DU(LQ)
5000 MPR	Rotors	25 - 35 ft.	> 0.70

To view the complete document of compliance for Rain Bird products that have been tested to meet the requirements of the ASABE/ICC 802-2014 standard and the California MWELO go to: www.rainbird.com/agency/california/MWELO.htm

5000-MPR-25 (Red)								
Nozzle	Pressure	Radius	Flow	Precip	Precip			
	psi	ft.	gpm	In/h	In/h			
Quarter	25	23	0.74	0.54	0.62			
	35	24	0.88	0.59	0.68			
	45	25	1.00	0.62	0.71			
	55	25	1.11	0.68	0.79			
	65	25	1.21	0.75	0.86			
Third	25	23	1.00	0.55	0.63			
	35	24	1.21	0.61	0.70			
	45	25	1.38	0.64	0.74			
	55	25	1.53	0.71	0.82			
	65	25	1.67	0.77	0.89			
Half	25	23	1.44	0.52	0.61			
	35	24	1.73	0.58	0.67			
	45	25	1.98	0.61	0.70			
	55	25	2.21	0.68	0.79			
	65	25	2.41	0.74	0.86			
Full	25	23	2.78	0.51	0.58			
	35	24	3.34	0.56	0.64			
	45	25	3.82	0.59	0.68			
	55	25	4.25	0.65	0.76			
	65	25	4.63	0.71	0.82			

5000-MPR-25 (Red) METRIC								
Nozzle	Pressure	Radius	Flow	Flow	Precip	Precip		
	bar	m	m³/h	I/m	mm/h	mm/h		
Quarter	1.7	7.0	0.17	3.0	13.7	15.8		
	2.4	7.3	0.20	3.6	14.9	17.3		
	3.1	7.6	0.23	3.6	15.6	18.1		
	3.8	7.6	0.25	4.2	17.4	20.1		
	4.5	7.6	0.27	4.8	18.9	21.9		
Third	1.7	7.0	0.23	3.6	13.9	16.0		
	2.4	7.3	0.27	4.8	15.4	17.8		
	3.1	7.6	0.31	5.4	16.2	18.7		
	3.8	7.6	0.35	6.0	18.0	20.7		
	4.5	7.6	0.38	6.6	19.6	22.6		
Half	1.7	7.0	0.33	5.4	13.3	15.4		
	2.4	7.3	0.39	6.6	14.7	17.0		
	3.1	7.6	0.45	7.2	15.5	17.9		
	3.8	7.6	0.50	8.4	17.3	20.0		
	4.5	7.6	0.55	9.0	18.9	21.8		
Full	1.7	7.0	0.63	10.8	12.8	14.8		
	2.4	7.3	0.76	12.6	14.2	16.4		
	3.1	7.6	0.87	14.4	14.9	17.3		
	3.8	7.6	0.97	16.2	16.6	19.2		
	4.5	7.6	1.05	17.4	18.1	20.9		



5000-MPR	5000-MPR-30 (Green)								
Nozzle	Pressure	Radius	Flow	Precip	Precip				
	psi	ft.	gpm	In/h	In/h				
Quarter	25	29	1.03	0.47	0.54				
	35	30	1.23	0.53	0.61				
	45	30	1.40	0.60	0.69				
	55	30	1.56	0.67	0.77				
	65	30	1.69	0.72	0.83				
Third	25	29	1.34	0.46	0.53				
	35	30	1.62	0.52	0.60				
	45	30	1.85	0.59	0.69				
	55	30	2.06	0.66	0.76				
	65	30	2.24	0.72	0.83				
Half	25	29	2.15	0.49	0.57				
	35	30	2.59	0.55	0.64				
	45	30	2.96	0.63	0.73				
	55	30	3.30	0.71	0.82				
	65	30	3.60	0.77	0.89				
Full	25	29	4.24	0.49	0.56				
	35	30	5.08	0.54	0.63				
	45	30	5.78	0.62	0.71				
	55	30	6.39	0.68	0.79				
	65	30	6.92	0.74	0.85				

5000-MPF	METRIC					
Nozzle	Pressure	Radius	Flow	Flow	Precip	Precip
	bar	m	m³/h	I/m	mm/h	mm/h
Quarter	1.7	8.8	0.23	3.6	12.0	13.8
	2.4	9.1	0.28	4.8	13.4	15.4
	3.1	9.1	0.32	5.4	15.2	17.6
	3.8	9.1	0.35	6.0	17.0	19.6
	4.5	9.1	0.38	6.6	18.4	21.2
Third	1.7	8.8	0.30	4.8	11.7	13.5
	2.4	9.1	0.37	6.0	13.2	15.2
	3.1	9.1	0.42	7.2	15.1	17.4
	3.8	9.1	0.47	7.8	16.8	19.4
	4.5	9.1	0.51	8.4	18.3	21.1
Half	1.7	8.8	0.49	8.4	12.5	14.4
	2.4	9.1	0.59	9.6	14.1	16.2
	3.1	9.1	0.67	11.4	16.1	18.6
	3.8	9.1	0.75	12.6	17.9	20.7
	4.5	9.1	0.82	13.8	19.6	22.6
Full	1.7	8.8	0.96	16.2	12.3	14.2
	2.4	9.1	1.15	19.2	13.8	15.9
	3.1	9.1	1.31	21.6	15.7	18.1
	3.8	9.1	1.45	24.0	17.4	20.0
	4.5	9.1	1.57	26.4	18.8	21.7

5000-MPR-35 (Beige)								
Nozzle	Pressure	Radius	Flow	Precip	Precip			
	psi	ft.	gpm	In/h	In/h			
Quarter	25	32	1.40	0.53	0.61			
	35	34	1.67	0.56	0.64			
	45	35	1.92	0.60	0.70			
	55	35	2.13	0.67	0.77			
	65	35	2.31	0.73	0.84			
Third	25	32	1.77	0.50	0.58			
	35	34	2.15	0.54	0.62			
	45	35	2.46	0.58	0.67			
	55	35	2.74	0.65	0.75			
	65	35	2.99	0.70	0.81			
Half	25	32	2.75	0.52	0.60			
	35	34	3.33	0.55	0.64			
	45	35	3.81	0.60	0.69			
	55	35	4.23	0.66	0.77			
	65	35	4.62	0.73	0.84			
Full	25	32	5.36	0.50	0.58			
	35	34	6.62	0.55	0.64			
	45	35	7.58	0.60	0.69			
	55	35	8.43	0.66	0.76			
	65	35	9.18	0.72	0.83			

[■] Square spacing based on 50% diameter of throw

5000-MPF	METRIC					
Nozzle	Pressure	Radius	Flow	Flow	Precip	Precip
	bar	m	m³/h	I/m	mm/h	mm/h
Quarter	1.7	9.8	0.32	5.4	13.4	15.4
	2.4	10.4	0.38	6.6	14.1	16.3
	3.1	10.7	0.44	7.2	15.3	17.7
	3.8	10.7	0.48	7.8	17.0	19.6
	4.5	10.7	0.52	9.0	18.4	21.3
Third	1.7	9.8	0.40	6.6	12.7	14.6
	2.4	10.4	0.49	8.4	13.6	15.8
	3.1	10.7	0.56	9.6	14.7	17.0
	3.8	10.7	0.62	10.2	16.4	18.9
	4.5	10.7	0.68	11.4	17.9	20.7
Half	1.7	9.8	0.62	10.2	13.1	15.2
	2.4	10.4	0.76	12.6	14.1	16.3
	3.1	10.7	0.87	14.4	15.2	17.6
	3.8	10.7	0.96	16.2	16.9	19.5
	4.5	10.7	1.05	17.4	18.4	21.3
Full	1.7	9.8	1.22	20.4	12.8	14.8
	2.4	10.4	1.50	25.2	14.0	16.2
	3.1	10.7	1.72	28.8	15.1	17.5
	3.8	10.7	1.91	31.8	16.8	19.4
	4.5	10.7	2.09	34.8	18.3	21.2

Performance data derived from tests that conform with ASABE Standards; ASABE S398.1. See page 186 for complete ASABE Test Certification Statement.

[▲] Triangular spacing based on 50% diameter of throw Performance data collected in zero wind conditions

Falcon® 6504 Series

Reliable and Economical

Features

- · Ratcheting stem just like standard spray bodies
- 3-port, color-coded Rain Curtain nozzles for optimal long range,mic range, and close-in watering
- SAM Seal-A-Matic check valve
- Self-adjusting stator does not require replacement when changing nozzles
- · Heavy-duty, stainless steel retract spring ensures positive pop-dow
- 5 year warranty

Options

- Stainless steel (SS) riser helps deter vandalism on public turf areas
- Purple cover (NP) for non-potable systems
- High Speed (HS) "Tan Top" version for dust suppression

Operating Specifications

- Precipitation rate: 0.37 to 1.26 inches per hour (9 to 32 mm/h)
- Radius: 37 to 65 feet (11.3 to 19.8 m)
- Pressure: 30 to 90 psi (2.1 to 6.2 bar)
- Flow: 2.9 to 21.7 gpm (0.66 to 4.93 m³/h; 10.8 to 82.2 l/m)
- 1" female NPT or BSP threaded inlet
- SAM Seal-A-Matic[™] check valve holds up to 10 feet (3.1 m) of elevation change
- Rain Curtain™ Nozzles: Included with rotor, other sizes available upon request; 10-grey, 12-beige, 14-light green, 16-dark brown, 18-dark blue
- · Nozzle outlet trajectory is 25°

Models

- 6504-FC: Full-circle
- 6504-PC: Part-circle
- 6504-FC-NP: Full-circle, non-potable cover
- 6504-PC-NP: Part-circle, non-potable cover
- 6504-FC-SS: Full-circle, stainless steel
- 6504-PC-SS: Part-circle, stainless steel
- 6504-PC-SS-HS: Part-circle, stainless steel, high speed rotation
- 6504-FC-SS-NP: Full-circle, stainless steel, non-potable cover
- 6504-PC-SS-NP: Part-circle, stainless steel, non-potable cover

Note: BSP thread versions available for most models

Falcon 6504 Series Rotors meet the requirements of the ASABE/ICC 802-2014 standard

The average DU(LQ) of the applicable products exceed 0.65 distribution uniformity.

Product	Туре	Radius	DU(LQ)
6504 Series	Rotors	39 - 65 ft.	> 0.80

To view the complete document of compliance for Rain Bird products that have been tested to meet the requirements of the ASABE/ICC 802-2014 standard and the California MWELO go to: www.rainbird.com/agency/california/MWELO.htm



Falcon® 6504 Series



 \triangle

0.37 to 1.26 in/hr (9 to 32 mm/h)



30 to 90 psi (2.1 to 6.2 bar)




2.9 to 21.7 gpm (10.8 to 82.2 l/m) (0.66 to 4.93 m³/h)



4" (10.2 cm)

8½" (21.6 cm)

1" NPT or BSP





Precip

In/h

0.49

0.63

0.46 0.72

0.66

0.82

0.92 0.90

1.08

1.10

0.49

0.62

0.69

0.85

0.89

1.02

1.13

1.15

0.56

0.68

0.84 0.94

0.98

1.12

1.15

1.10

0.61

0.81

0.83

0.95

0.99

1.21

1.17

1.19

0.72

0.85

0.83

1.10

1.06

1.31

1.18 1.28

1.27

Precip

In/h

0.42

0.54

0.40

0.62

0.58

0.71

0.79

0.78

0.93

0.95

0.42

0.53

0.60

0.74

0.77

0.88

0.98

0.99

0.48

0.59

0.72

0.82

0.85

0.97

1.00

0.95

0.53

0.70

0.72

0.82

0.86

1.05

1.01

1.03

0.62

0.74

0.72

0.95

0.92

1.13



Falcon® 6504 Nozzle Performance							
Pressure psi	Nozzle	Radius ft.	Flow gpm	Precip In/h	Precip In/h		
30	4 6	39 43	2.9 4.2	0.37 0.44	0.42 0.50		
	4 6 8 10 12 14 16	41 45 49 51 53 55 55	3.3 4.9 6.6 8.1 9.7 11.3 12.6	0.38 0.47 0.53 0.60 0.66 0.72 0.80 0.76	0.44 0.54 0.61 0.69 0.77 0.83 0.93 0.87		
	4 6 8 10 12 14 16	41 47 51 53 55 59 61	3.7 5.5 7.4 9.1 11.0 12.7 14.3 15.4	0.42 0.44 0.55 0.62 0.70 0.70 0.74 0.85	0.49 0.51 0.63 0.72 0.81 0.81 0.85 0.98		
	4 6 8 10 12 14 16	41 47 51 55 57 61 63 63	4.0 6.0 8.2 10.0 12.2 14.0 15.7 17.1	0.46 0.52 0.61 0.64 0.72 0.72 0.76 0.83	0.53 0.60 0.70 0.73 0.83 0.84 0.88		
70	4 6 8 10 12 14 16	41 49 51 57 59 61 63 65	4.4 6.3 8.9 10.8 13.2 15.2 16.9 18.3	0.50 0.51 0.66 0.64 0.73 0.79 0.82 0.83	0.58 0.58 0.76 0.74 0.84 0.91 0.95		
	4 6 8 10 12 14 16 18 18	43 49 53 55 61 61 63 65	4.6 6.9 9.4 11.6 14.0 16.2 18.1 19.6 21.7	0.48 0.55 0.64 0.74 0.72 0.84 0.88 0.89	0.55 0.64 0.74 0.85 0.84 0.97 1.01 1.03		

	16	59	18.4	1.02	1.1					
	18	59	20.0	1.11	1.2					
90	18	61	21.3	1.10	1.2					
Perform	Performance data collected in zero wind conditions									
Performance data derived from tests that conform with ASABE Standards; ASABE S398.1. See page 186 for complete ASABE Test Certification Statement.										

High-Speed Falcon® 6504 Nozzle Performance

Radius

ft.

37

39

41

43

47

47

49

53

51

53

41

45

49

49

53

53

53

55

41

45

47

49

53

53

55

59

41

43

49

51

55

53

57

59

39

43

51

49

55

53

Flow

gpm

3.0

4.3

3.5

6.0

6.6

8.1

9.9

11.4

12.6

13.9

3.7

5.6

7.5

9.2

11.2

12.9

14.3

15.6

4.2

6.2

8.3

10.2

12.4

14.2

15.7

17.2

4.6

6.7

9.0

11.1

13.5

15.3

17.1

18.6

4.9

7.1

9.7

11.9

14.4

16.5

Pressure Nozzle

4 6

4

6

8

10

12

14

16

18

4

6

8

10

14

16

18

4

6

8

10

12

14

18

4

6

8

10

12

14

16

18

4

6

8

10

12

14

16

12

psi

30

40

50

60

70

80

Precipitation rates based on half-circle operation

[■] Square spacing based on 50% diameter of throw

[▲] Triangular spacing based on 50% diameter of throw

Falcon® 6	504 Noz	zle Perfo	rmance			METRIC
Pressure bar	Nozzle	Radius m	Flow m³/h	Flow I/m	Precip mm/h	Precip mm/h
2.1	4 6	11.9 13.1	0.66 0.95	10.98 15.90	9 11	11 13
2.5	4 6 8 10	13.1 12.3 13.5 14.9 15.5 16.2 16.8 16.8 18.0	0.95 0.72 1.05 1.50 1.84 2.20 2.57 2.86 3.11	15.90 11.92 17.56 25.20 30.60 36.60 42.60 47.40 51.60	11 10 12 13 15 17 18 20	13 11 13 16 18 19 21 24 22
3.0		12.5 14.1 15.1 15.8 16.4 17.2 17.4 18.0	0.78 1.16 1.56 1.92 2.31 2.68 3.00 3.25	13.02 19.34 26.04 31.99 38.44 44.63 49.95 54.11	10 12 14 15 17 18 20 20	12 13 16 18 20 21 23 23
3.5	4 6 8 10	12.5 14.9 15.5 16.2 16.8 18.0 18.6 18.1	0.85 1.26 1.69 2.08 2.52 2.91 3.27 3.53	14.09 20.96 28.24 34.70 41.98 48.45 54.53 58.78	11 11 14 16 18 18 19 22	13 13 16 18 21 21 22 25
4.0	4 6 8	12.5 14.4 15.5 16.6 17.3 18.5 19.1	0.89 1.34 1.83 2.23 2.72 3.12 3.50 3.81	14.91 22.33 30.44 37.17 45.28 52.01 58.37 63.45	11 13 15 16 18 18 19 21	13 15 17 19 21 21 22 24

Pressure	Nozzle	Radius	Flow	Flow	Precip	Precip
bar		m	m³/h	I/m	mm/h	mm/h
4.5	6 8 10	12.5 14.6 15.5 17.1 17.7 18.6 19.2 19.5	0.96 1.40 1.95 2.37 2.89 3.32 3.71 4.03	15.94 23.33 32.43 39.44 48.17 55.38 61.82 67.12	12 13 16 16 18 19 20 21	14 15 19 19 21 22 23 24
5.0	10	12.7 14.9 15.7 17.2 18.1 18.6 19.2 19.8	1.01 1.47 2.05 2.50 3.04 3.51 3.91 4.23	16.84 24.50 34.16 41.64 50.72 58.49 65.11 70.51	13 13 17 17 19 20 21 22	15 15 19 19 21 23 24 25
5.5	4	13.1	1.04	17.39	12	14
	6	14.9	1.56	25.79	14	16
	8	16.1	2.13	35.54	16	19
	10	16.8	2.63	43.84	19	22
	12	18.6	3.18	52.92	18	21
	14	18.6	3.67	61.23	21	25
	16	19.2	4.10	68.40	22	26
	18	19.8	4.44	74.07	23	26
6.0	18	19.8	4.79	79.77	24	28
6.2		19.8	4.93	82.13	25	29

- Square spacing based on 50% diameter of throw
- ▲ Triangular spacing based on 50% diameter of throw

Performance data collected in zero wind conditions

Performance data derived from tests that conform with ASABE Standards; ASABE S398.1. See page 186 for complete ASABE Test Certification Statement.

Low Flow Kit







Standard Flow Kit



Falcon® 6504 Rain Curtain™ Nozzles



High-Spe	ed Falco	n® 6504 ∣	Nozzle F	Performa	nce	METRIC
Pressure bar	Nozzle	Radius m	Flow m³/h	Flow I/m	Precip mm/h	Precip mm/h
2.1	4	11.3	0.68	11.35	11	12
2.5	6	11.9	0.98	15.90	14	16
2.5	4	12.0	0.75	12.54	10	12
	6 8	12.7 14.2	1.22 1.49	20.16 25.20	15 15	18 17
		14.2	1.83	30.60	18	21
		14.8	2.24	37.20	20	24
	14	16.0	2.58	43.20	20	23
	16	15.4	2.85	47.40	24	28
	18	16.0	3.15	52.80	24	28
3.0	4	12.5	0.81	13.51	10	12
	6	13.3	1.33	22.18	15	17
	8	14.5	1.57	26.18	15	17
	10	14.5	1.93	32.12	18	21
		15.4	2.35	39.20	20	23
	14	16.2	2.71	48.09	21	24
		15.8	3.00	49.95	24	28
3.5		16.4 12.5	3.29 0.85	54.87 14.15	25 11	28 13
3.5	6	13.7	1.28	21.37	14	16
	8	14.9	1.72	28.62	16	18
		14.9	2.11	35.11	19	22
		16.2	2.56	42.74	20	23
	14	16.2	2.95	49.20	23	26
	16	16.2	3.27	54.53	25	29
	18	16.9	3.57	59.51	25	29
4.0	4	12.5	0.93	15.52	12	14
	6	13.7	1.38	23.02	15	17
		14.4	1.85	30.81	18	21
		14.9	2.27	37.86	20	24
		16.2	2.76	46.03	21	24
	14 16	16.2 16.6	3.17 3.50	52.77 58.37	24 25	28 29
		17.7	3.83	63.90	23 24	29

Pressure	Nozzle	Radius	Flow	Flow	Precip	Precip
bar		m	m³/h	I/m	mm/h	mm/h
4.5	4	12.5	1.00	16.69	13	15
	6	13.4	1.48	24.46	16	19
	8	14.6	1.97	32.81	18	21
	10	15.3	2.42	40.40	21	24
	12	16.5	2.95	49.13	22	25
	14	16.2	3.36	55.94	26	30
	16	17.1	3.73	62.22	26	30
	18	18.0	4.07	67.89	25	29
5.0	4	12.3	1.06	17.70	14	16
	6	13.1	1.56	25.74	18	21
	8	15.1	2.08	34.73	18	21
	10	15.4	2.57	42.78	22	25
	12	16.8	3.12	51.96	22	26
	14	16.2	3.54	59.06	27	31
	16	17.5	3.96	65.96	26	30
	18	18.0	4.30	71.74	27	31
5.5	4 6 8	11.9 13.1 15.5 14.9 16.8 16.2 18.0 18.0	1.11 1.61 2.20 2.70 3.27 3.74 4.17 4.53	18.52 26.84 36.65 44.97 54.43 62.35 69.53 75.58	16 19 18 24 23 29 26 28	18 22 21 28 27 33 30 32
6.0	18	18.4	4.75	79.16	28	32
6.2	18	18.6	4.84	80.62	28	32

- Square spacing based on 50% diameter of throw
- ▲ Triangular spacing based on 50% diameter of throw

Performance data collected in zero wind conditions

Performance data derived from tests that conform with ASABE Standards; ASABE S398.1. See page 186 for complete ASABE Test Certification Statement.

8005 Series

Protect Your Turf with High Performance, Vandal and Abuse Resistant Rotors from 39' to 81'

Features

- Vandal resistance, brass reinforced turret for increased side impact durability
- Memory Arc® returns the rotor to its original arc setting
- · Non-strippable drive mechanism prevents damage from vandals
- Easy, wet, dry arc adjustment with slotted screwdriver through top of rotor from 50° to 330° part-circle, 360° non-reversing full-circle. Full and part circle operation in one unit
- Left and right side trips adjustable for ease of installation without turning the case and loosening the pipe connection
- SAM Seal-A-Matic check valve
- 3-port, color-coded Rain Curtain nozzles for optimal long-range, midrange, and close-in watering
- 5 year warranty

Options

- Stainless steel (SS) riser helps deter vandalism on public turf areas
- Purple cover (NP) for non-potable systems
- · Optional Sod Cup

Operating Specifications

- Radius: 39 to 81 feet (11.9 to 24.7 m)
- Precipitation rate: 0.48 to 1.23 inches per hour (12 to 31 mm/h)
- Pressure: 50 to 100 psi (3.5 to 6.9 bar)
- Flow: 3.8 to 36.3 gpm (0.86 to 8.24 m3/h; 14.4 to 137.4 l/m)
- · 1" NPT or BSP female threaded inlet
- SAM Seal-A-Matic[™] check valve holds up to 10 feet (3.1 m) of elevation change
- Nozzle outlet trajectory is 25°
- Rain Curtain™ Nozzles: Included with rotor, other sizes available upon request; 10-grey, 12-beige, 14-light green, 16-dark brown, 18-dark blue

Models

- 8005: 1" NPT female threaded inlet
- 8005-NP: 1" NPT female threaded inlet; non-potable cover
- 8005-SS: 1" NPT female threaded inlet; stainless steel
- 8005-SS-NP: 1" NPT female threaded inlet; stainless steel and nonpotable cover

Note: BSP threads versions available for most models

** **Note:** Pop-up height is measured from cover to the primary nozzle port. Overall body height is measured popped down

8005 Series Rotors meet the requirements of the ASABE/ICC 802-2014 standard

The average DU(LQ) of the applicable products exceed 0.65 distribution uniformity.

Product	Туре	Radius	DU(LQ)
8005 Series	Rotors	39 - 81 ft.	> 0.75

To view the complete document of compliance for Rain Bird products that have been tested to meet the requirements of the ASABE/ICC 802-2014 standard and the California MWELO go to: www.rainbird.com/agency/california/MWELO.htm





0.48 to 1.23 in/hr (12 to 31 mm/h)



50 to 100 psi (3.5 to 6.9 bar)



3.8 to 36.3 gpm (14.4 to 137.4 l/m) (0.86 to 8.24 m³/h)




5" (12.7 cm)

10¹/₈" (25.7 cm)

1" NPT or BSP

8005 Series







8005 Noz	zzle Perfor	mance			
Pressure psi	Nozzle	Radius ft.	Flow gpm	Precip In/h	Precip In/h
	 04 06 08 10 12 14 16 18 20 22 24 26 	39 45 49 53 57 59 61 63 65 65	3.8 5.6 6.6 9.3 11.1 12.6 14.3 16.1 18.6 20.7 22.3 24.3	0.48 0.53 0.53 0.64 0.66 0.70 0.74 0.78 0.85 0.94 1.08 1.11	0.56 0.62 0.61 0.74 0.76 0.81 0.85 0.90 0.98 1.09 1.25 1.28
60	 04 06 08 10 12 14 16 18 20 22 24 26 	39 45 49 53 59 61 65 65 67 71 69 73	3.8 6.1 8.4 10.1 12.0 14.3 15.9 17.8 20.1 23.2 24.7 26.7	0.48 0.58 0.67 0.69 0.66 0.74 0.72 0.81 0.86 0.89 1.00 0.96	0.56 0.67 0.78 0.80 0.77 0.85 0.84 0.94 1.00 1.02 1.15
	 04 06 08 10 12 14 16 18 20 22 24 26 	39 45 49 55 59 63 67 67 71 73 75	4.7 6.7 9.0 11.1 13.2 15.3 17.2 19.3 22.0 25.2 27.0 29.4	0.60 0.64 0.72 0.71 0.73 0.74 0.74 0.83 0.84 0.91 0.92 1.01	0.69 0.74 0.83 0.82 0.84 0.86 0.85 0.96 0.97 1.05 1.07
	 04 06 08 10 12 14 16 18 20 22 24 26 	39 45 49 55 61 63 67 69 71 75 77	5.0 7.1 9.8 11.8 14.2 16.4 18.6 20.9 23.9 27.3 29.2 31.5	0.63 0.68 0.79 0.75 0.73 0.80 0.80 0.91 0.93 0.95 0.97	0.73 0.78 0.91 0.87 0.85 0.92 0.92 0.98 1.05 1.08 1.10

Pressure psi	Nozzle	Radius ft.	Flow gpm	Precip In/h	Precip In/h
90	12 14 16 18 20 22 24 24	61 65 69 71 73 75 79	14.7 17.9 20.0 22.2 25.3 29.1 31.0 33.7	0.76 0.82 0.81 0.85 0.91 1.00 0.96 1.04	0.88 0.94 0.93 0.98 1.06 1.15 1.10
100	20222426	75 77 79 81	26.8 30.7 32.8 36.3	0.85 1.00 1.01 1.07	0.97 1.15 1.17 1.23

 ${\it Precipitation \, rates \, based \, on \, half-circle \, operation}$

- Square spacing based on 50% diameter of throw
- ▲ Triangular spacing based on 50% diameter of throw

Performance data collected in zero wind conditions

Performance data derived from tests that conform with ASABE Standards; ASABE S398.1. See page 186 for complete ASABE Test Certification Statement.







Sod Cup for 8005

8005 No	zzle Perfo	ormance				METRIC
Pressure bar	Nozzle	Radius m	Flow m³/h	Flow I/m	Precip mm/h	Precip mm/h
	4 6 8 10 12 14 16 18 20 22 24 26 26	11.9 13.7 14.9 16.1 17.5 18.0 18.7 19.2 19.9 20.0 19.3 20.0	0.86 1.28 1.59 2.10 2.52 2.89 3.28 3.69 4.25 5.08 5.11 5.57	14.38 21.34 25.50 35.43 42.27 48.18 54.59 61.43 70.83 79.07 85.10 92.67	12 14 14 16 16 18 19 20 21 25 27 28	14 16 16 19 19 21 22 23 25 29 32 32
	4 6 8 10 12 14 16 18 20 22 24 26 26	11.9 13.7 14.9 16.3 17.7 18.5 19.6 19.7 20.3 21.3 20.7 21.8	0.93 1.37 1.75 2.30 2.70 3.17 3.54 3.97 4.50 5.23 5.50 6.01	14.38 22.71 30.44 37.63 44.74 52.85 58.98 66.10 74.95 85.94 91.69 99.26	13 15 16 17 17 19 18 20 22 23 26 25	15 17 18 20 20 21 21 24 25 27 30 29
	4 6 8 10 12 14 16 18 20 22 24 26 26	11.9 13.7 14.9 16.5 18.0 18.9 20.1 20.1 21.1 22.0 22.0 22.6	1.00 1.45 1.92 2.40 2.87 3.37 4.22 4.79 5.51 5.88 6.42	16.18 24.28 32.99 40.22 47.81 56.12 62.77 70.36 79.87 91.80 98.08 106.44	14 15 17 18 18 19 19 21 22 23 24 25	16 18 20 20 20 22 22 24 25 26 28 29
	4 6 8 10 12 14 16 18 20 22 24 26	11.9 13.7 14.9 16.7 18.3 19.2 20.4 20.6 21.6 22.4 23.0 23.2	1.06 1.54 2.09 2.50 3.05 3.54 3.99 4.47 5.11 5.84 6.26 6.80	18.08 25.74 34.83 42.68 50.92 58.96 66.44 74.58 85.08 97.39 104.29 113.28	15 16 19 18 18 19 19 21 22 23 24 25	17 19 22 21 21 22 22 24 25 27 27

Pressure bar	Nozzle	Radius m	Flow m³/h	Flow I/m	Precip mm/h	Precip mm/h
5.5		11.9	1.13	18.90	16	18
	•	13.7	1.62	26.84	17	20
	Ü	14.9	2.25	37.02	20	23
		16.8	2.70	44.60	19	22
		18.5	3.23	53.66	19	22
		19.2	3.72	61.98	20	23
	16 18	20.4 21.0	4.22 4.74	70.28 78.97	20 21	23 25
	20	21.6	5.42	90.30	23	23 27
		22.8	6.19	103.15	24	28
		23.5	6.62	110.33	24	28
		24.1	7.14	119.05	25	28
6.0		18.6	3.30	55.07	19	22
	14	19.6	3.96	66.06	21	24
	16	20.9	4.45	74.12	20	24
		21.5	4.95	82.56	21	25
	20	22.1	5.65	94.18	23	27
		22.9	6.71	108.12	26	30
		23.9	6.92	115.31	24	28
		24.1	7.50	125.08	26	30
6.2		19.8 21.0	4.06 4.54	67.75 75.70	21 21	24 24
		21.7	5.04	75.70 84.02	21	2 4 25
6.5		22.5	5.89	98.19	23	27
0.5		23.4	6.84	112.73	25	29
		24.1	7.22	120.25	25	29
_	26	24.3	7.91	131.76	27	31
6.9		22.9	6.09	101.43	23	27
	22	23.5	6.97	116.19	25	29
		24.1	7.45	124.14	26	30
	26	24.7	8.24	137.39	27	31

- Square spacing based on 50% diameter of throw
- ▲ Triangular spacing based on 50% diameter of throw

Performance data collected in zero wind conditions

Performance data derived from tests that conform with ASABE Standards; ASABE S398.1. See page 186 for complete ASABE Test Certification Statement.



8005 Rain Curtain™ Nozzles



2045A Maxi-Paw™and 2045-PJ Maxi-Bird™

Dirty Water Applications - Spacing Up to 45 Feet (13.7 m)

Features

- Proven impact drive with straight-through flow for superior performance in dirty water
- Five standard trajectory and two low angle (LA) color-coded nozzles for matched precipitation and in a wide range of applications
- 360° full-circle OR arc adjustable from 20° to 340°
- Side and combination ½" or ¾" bottom inlet for design flexibility (Maxi-Paw)
- 3 year warranty

Operating Specifications

- Precipitation rate: 0.28 to 1.21 inches per hour (7 to 31 mm/h)
- Spacing: 22 to 45 feet (6.7 to 13.7 m)
- Flow rate: 1.5 to 8.4 gpm (0.34 to 1.91 m³/h; 0.9 to 0.53 l/s)
- Radius: 22 to 45 feet (6.7 to 13.7 m); 18 feet (5.4 m) with Radius Reduction Screw
- Pressure: 25 to 60 psi (1.7 to 4.1 bar)
- Combination ½" or ¾" female bottom inlet (Maxi-Paw)
- ' 1/2" FPT side inlet (Maxi-Paw)
- ' 1/2" NPT Riser-Mounted (Maxi-Bird)

Models

- · 2045A Maxi-Paw
- · 2045A Maxi-Paw-SAM
- 2045A Maxi-Paw-SAM-NP
- · 42064: Maxi-Paw Wrench for removing internal assembly from case
- · 2045-PJ Maxi-Bird




2045A Maxi-Paw



2045-PJ Maxi-Bird







Precip

mm/h

Flow

I/m

m³/h

METRIC

Precip

mm/h

Maxi-P <u>aw</u>	and M <u>ax</u> i	i-Bird Noz	zle Perf <u>or</u>	mance	
Pressure psi	Nozzle	Radius ft.	Flow gpm	Precip In/h	Precip In/h
	06 07 LA 07 08 10 LA 10	22 32 35 25 38 39	1.5 2.2 2.8 3.4 4.2 5.5	0.60 0.41 0.44 1.05 0.56 0.70	0.69 0.48 0.51 1.21 0.65 0.80
35	06 07 LA 07 08 10 LA 10	37 23 37 38 29 41 42	2.0 1.9 2.7 3.3 4.0 4.8 6.3	0.28 0.69 0.38 0.44 0.92 0.55 0.69	0.32 0.80 0.44 0.51 1.06 0.64 0.79
	06 07 LA 07 08 10 LA 10	38 25 39 40 31 42 44	2.3 2.1 3.0 3.7 4.5 5.4 7.1	0.31 0.65 0.38 0.45 0.90 0.59 0.71	0.35 0.75 0.44 0.51 1.04 0.68 0.82
	06 07 LA 07 08 10 LA 10	38 25 41 41 32 43 45	2.5 2.3 3.3 4.1 5.0 6.0 7.9	0.33 0.71 0.38 0.47 0.94 0.62 0.75	0.39 0.82 0.44 0.54 1.09 0.72 0.87
60	06 07 LA 07 08 10 LA 10	38 25 41 42 32 44 45	2.6 2.4 3.5 4.2 5.4 6.4 8.4	0.35 0.74 0.40 0.46 1.02 0.64 0.80	0.40 0.85 0.46 0.53 1.17 0.74 0.92

2.0	6	-	-	-	-	-	
	07 LA	6.8	0.38	6.0	16	19	
	• 7	10.4	0.55	9.0	10	12	
	8	11.0	0.68	11.4	11	13	
	10 LA	8.1	0.83	13.8	25	29	
	10	11.9	1.01	16.8	14	16	
	1 2	12.3	1.32	22.2	18	20	
2.5	6	11.3	0.46	7.8	7	8	
	07 LA	7.1	0.44	7.2	17	20	
	• 7	11.4	0.62	10.2	10	11	
	• 8	11.7	0.76	12.6	11	13	
	10 LA	8.9	0.92	15.6	23	27	
	10	12.5	1.11	18.6	14	16	
2.0	12	12.9 11.5	1.45 0.51	24.0 8.4	18 8	20 9	
3.0	● 6 ● 07 LA	7.5	0.51	7.8	o 17	9 19	
	• 7	7.5 11.8	0.47	11.4	10	11	
	• 8	12.1	0.83	13.8	11	13	
	10 LA	9.4	1.01	16.8	23	27	
	10 27	12.8	1.21	20.4	15	17	
	12	13.3	1.59	26.4		21	
3.5	6	11.6	0.55	9.0	8	9	
	07 LA	7.6	0.50	8.4	17	20	
	• 7	12.2	0.72	12.0	10	11	
	8	12.4	0.89	15.0	12	13	
	10 LA	9.6	1.09	18.0	23	27	
	10	13.0	1.30	21.6	15	18	
4.0	12	13.6	1.72	28.8	19	21	
4.0	● 6 ● 07 LA	11.6 7.6	0.58 0.54	9.6 9.0	9 18	10 21	
	• 7	12.5	0.34	13.2	10	11	
	• 8	12.3	0.78	15.2	12	14	
	10 LA	9.8	1.19	19.8	25	29	
	10 LA	13.3	1.42	23.4	16	19	
	12	13.7				23	

Maxi-Paw and Maxi-Bird Nozzle Performance

Pressure Nozzle Radius Flow

m

bar

LA = Low Angle

Precipitation rates based on half-circle operation

- Square spacing based on 50% diameter of throw
- ▲ Triangular spacing based on 50% diameter of throw

Performance data collected in zero wind conditions

Performance data derived from tests that conform with ASABE Standards; ASABE S398.1. See page 186 for complete ASABE Test Certification Statement.



2045A Maxi-Paw and 2045-PJ Standard Angle Nozzles



2045A Maxi-Paw and 2045-PJ Low Angle Nozzles



XLR Series Water Jets

The World's Most Advanced Long-Range Rotor

Features

- · Constant speed independent of operating pressure and flow rate
- · Water deflector distributes water uniformly for entire throw distance
- · Barrel and nozzle design optimized to maximize throw
- · Nozzle is 54% larger than competition
- Innovative material selection maximize efficiency of movement
- Full- and part-circle (20-340°) in one unit
- · Adjustable trajectory model provides ultimate in adaptability
- 9 nozzles options (sold separately)
- Only 2 field serviceable components built to last reliably
- · One-year trade warranty

Operating Specifications

- Radius: 81 177 feet (25.6 57.3 m)
- Pressure: 30 to 120 psi (2.1 to 8.3 bar)
- Flow: 35 to 379 gpm (7.9 to 86.1 m³/h)
- Inlet: 2" NPT, 2" BSP or 2" flange
- Nozzle trajectory: 24° fixed, 44° fixed or adjustable (15° to 45°)
- · Nozzles (sold separately):
 - 0.47 (12 mm)
 - 0.55 (14 mm)
 - 0.63 (16 mm)
 - 0.71 (18 mm)
 - 0.70 (20 mm)
 - 0.87 (22 mm)
 - 0.94 (24 mm)
 - 1.02 (26 mm)
 - 1.10 (28 mm)
- · Nozzle tool available (sold separately)

Options


- · Optional Jet-Breaker for improved distribution uniformity
- Inlet adapter kits available in flange, NPT and BSP configurations to convert existing inlet

Models


- IXLR24: 24° fixed trajectory with flange inlet
- · IXLR44: 44° fixed trajectory with flange inlet
- IXLRADJ: Adjustable trajectory (15-45°) with flange inlet
- · XLR24NPT: 24° fixed trajectory with NPT inlet
- XLRADJNPT: Adjustable trajectory (15-45°) with NPT inlet
- · XLR24BSP: 24° fixed trajectory with BSP inlet
- XLRADJBSP: Adjustable trajectory (15-45°) with BSP inlet







Improved distribution uniformity with Dynamic Jet-Breaker in low pressure condition and Solid-Set systems





XLR 24	XLR 24 Nozzle Throw Range Fixed 24° Trajectory																	
	().47"	C).55"	().63"	C	.71"	().79"	().87"	C	.94"	1	.02"	1	.10"
Pressure psi	Flow gpm	Radius ft.	Flow gpm	Radius ft.	Flow gpm	Radius ft.	Flow gpm	Radius ft.	Flow gpm	Radius ft.	Flow gpm	Radius ft.	Flow gpm	Radius ft.	Flow gpm	Radius ft.	Flow gpm	Radius ft.
30	35	81	48	88	62	96	78	98	97	99	117	101	139	102	164	103	189	104
40	40	93	55	100	71	107	90	114	112	120	135	122	161	125	190	127	219	130
50	45	103	62	110	80	117	101	125	125	133	151	137	180	141	212	146	245	151
60	50	109	67	117	87	124	111	133	137	141	165	147	197	152	232	159	268	166
70	54	113	73	121	94	129	119	138	148	147	178	154	212	160	251	168	289	176
80	57	118	78	126	101	135	128	144	158	153	191	160	227	167	268	176	309	185
90	61	122	83	131	107	141	135	150	168	158	202	166	241	174	284	184	328	193
100	64	125	87	135	113	145	143	154	177	163	213	171	254	180	300	189	346	198
110	67	128	91	138	118	148	150	157	186	166	224	175	266	184	314	193	363	202

XLR 24	Nozzl	e Throv	v Rang	e Fixe	d 24° T	rajecto	ry										М	ETRIC
	12	mm	14	mm	16	mm	18	mm	20	mm	22	mm	24	mm	26	mm	28	mm
Pressure bar	Flow m³/h	Radius m																
2.0	7.8	24.2	10.6	26.5	13.8	28.9	17.5	29.1	21.7	29.4	26.1	29.8	31.1	30.2	36.7	30.6	42.3	30.9
2.5	8.7	26.8	11.9	29.0	15.4	31.3	19.5	32.5	24.2	33.8	29.2	34.4	34.7	35.1	41.0	35.8	47.3	36.5
3.0	9.6	29.4	13.0	31.6	16.9	33.7	21.4	35.9	26.5	38.2	31.9	39.1	38.0	39.9	44.9	41.0	51.8	42.1
3.5	10.3	31.2	14.1	33.3	18.2	35.5	23.1	37.9	28.7	40.4	34.5	41.6	41.1	42.9	48.5	44.4	56.0	45.9
4.0	11.1	32.9	15.1	35.1	19.5	37.3	24.7	39.9	30.7	42.5	36.9	44.2	43.9	45.8	51.8	47.8	59.8	49.7
4.5	11.7	33.9	16.0	36.2	20.7	38.6	26.2	41.2	32.5	43.9	39.1	45.7	46.6	47.6	55.0	49.8	63.5	52.0
5.0	12.4	34.8	16.8	37.3	21.8	39.8	27.6	42.5	34.3	45.2	41.2	47.3	49.1	49.3	58.0	51.8	66.9	54.3
5.5	13.0	35.7	17.7	38.4	22.9	41.1	29.0	43.8	35.9	46.5	43.2	48.7	51.5	50.9	60.8	53.5	70.2	56.2
6.0	13.5	36.6	18.4	39.5	23.9	42.4	30.3	45.0	37.5	47.7	45.2	50.1	53.8	52.5	63.5	55.3	73.3	58.1
6.5	14.1	37.4	19.2	40.4	24.9	43.3	31.5	46.0	39.1	48.7	47.0	51.2	56.0	53.7	66.1	56.5	76.3	59.3
7.0	14.6	38.2	19.9	41.2	25.8	44.2	32.7	46.9	40.6	49.7	48.8	52.3	58.1	54.9	68.6	57.7	79.2	60.6







XLR 4	4 No	zzle 1	Thro	w Ra	nge /	Fixe	ed 44	₽° Tra	jecto	ory																	
		0.47	"		0.55	"		0.63			0.71	"		0.79	"		0.87	'		0.94	"		1.02	'		1.10	"
Pressure psi	Flow gpm	Radius ft.	Height ft.	Flow gpm	Radius ft.	Height ft.	Flow gpm	Radius ft.	Height ft.	Flow gpm	Radius ft.	Height ft.	Flow gpm	Radius ft.	Height ft.	Flow gpm	Radius ft.		Flow gpm	Radius ft.	Height ft.	Flow gpm	Radius ft.	Height ft.	Flow gpm		Height ft.
40	40	82	37	55	90	37	71	98	38	90	105	38	112	113	39	135	117	39	161	121	40	190	125	40	219	128	41
50	45	91	43	62	99	44	80	108	45	101	116	46	125	125	47	151	130	48	180	135	48	212	140	49	245	144	50
60	50	97	48	67	107	49	87	116	51	111	126	52	137	135	54	165	140	55	197	146	56	232	151	57	268	157	58
70	54	102	51	73	112	53	94	122	55	119	132	57	148	142	59	178	148	61	212	154	62	251	160	64	289	165	66
80	57	107	54	78	117	57	101	127	59	128	138	61	158	148	64	191	154	66	227	160	68	268	166	70	309	172	72
90	61	110	56	83	121	59	107	132	62	135	142	65	168	153	68	202	159	70	241	165	72	284	171	75	328	177	77
100	64	113	58	87	124	61	113	135	65	143	146	68	177	157	71	213	163	73	254	169	76	300	176	79	346	182	82
110	67	115	60	91	126	63	118	137	66	150	148	70	186	160	73	224	166	76	266	172	79	314	179	82	363	185	85
120	70	116	61	95	127	64	124	139	68	156	150	72	194	161	75	234	168	78	278	175	81	328	181	84	379	188	87

XLR 4	4 No	zzle	Thro	w Ra	nge /	/ Fixe	d 44	° Tra	jecto	ory																MET	RIC
		12 mr	n		14 mr	n		16 mr	n		18 mn	n		20 mr	n		22 mr	n		24 mr	n		26 mr	n		28 mr	n
Pressure bar			Height m		Radius m	Height m	Flow m³/h	Radius m	Height m		Radius m	Height m	Flow m³/h	Radius m	Height m	Flow m³/h	Radius m		Flow m³/h	Radius m	Height m	Flow m³/h	Radius m	Height m		Radius m	Heigh m
3.0	9.6	26.1	11.9	13.0	28.5	12.1	16.9	31.0	12.3	21.4	33.5	12.5	26.5	35.9	12.7	31.9	37.2	12.9	38.0	38.5	13.1	44.9	39.7	13.3	51.8	41.0	13.
3.5	10.3	27.7	13.1	14.1	30.3	13.4	18.2	33.0	13.7	23.1	35.6	14.0	28.7	38.2	14.4	34.5	39.7	14.6	41.1	41.1	14.9	48.5	42.6	15.1	56.0	44.0	15.3
4.0	11.1	29.3	14.3	15.1	32.1	14.7	19.5	34.9	15.1	24.7	37.8	15.6	30.7	40.6	16.0	36.9	42.2	16.3	43.9	43.8	16.6	51.8	45.5	17.0	59.8	47.1	17.3
4.5	11.7	30.4	15.1	16.0	33.4	15.6	20.7	36.3	16.1	26.2	39.3	16.7	32.5	42.2	17.2	39.1	43.9	17.6	46.6	45.6	18.1	55.0	47.3	18.5	63.5	49.0	18.9
5.0	12.4	31.5	15.9	16.8	34.6	16.5	21.8	37.7	17.1	27.6	40.8	17.8	34.3	43.9	18.4	41.2	45.7	19.0	49.1	47.4	19.5	58.0	49.2	20.0	66.9	51.0	20.5
5.5	13.0	32.4	16.4	17.7	35.6	17.2	22.9	38.7	17.9	29.0	41.9	18.6	35.9	45.1	19.4	43.2	46.9	20.0	51.5	48.7	20.6	60.8	50.5	21.2	70.2	52.3	21.8
6.0	13.5	33.3	17.0	18.4	36.5	17.8	23.9	39.8	18.7	30.3	43.0	19.5	37.5	46.3	20.3	45.2	48.1	21.0	53.8	50.0	21.7	63.5	51.8	22.3	73.3	53.6	23.0
6.5	14.1	33.9	17.4	19.2	37.2	18.3	24.9	40.5	19.2	31.5	43.8	20.1	39.1	47.1	21.0	47.0	49.0	21.8	56.0	50.9	22.5	66.1	52.7	23.3	76.3	54.6	24.
7.0	14.6	34.5	17.9	19.9	37.8	18.8	25.8	41.2	19.8	32.7	44.6	20.7	40.6	48.0	21.7	48.8	49.9	22.5	58.1	51.8	23.4	68.6	53.7	24.2	79.2	55.6	25.
7.5	15.1	34.8	18.1	20.6	38.2	19.1	26.7	41.7	20.2	33.8	45.1	21.2	42.0	48.5	22.2	50.5	50.4	23.1	60.1	52.4	24.0	71.0	54.3	24.9	82.0	56.3	25.8
8.0	15.6	35.2	18.4	21.3	38.7	19.5	27.6	42.1	20.6	34.9	45.5	21.6	43.4	49.0	22.7	52.2	51.0	23.6	62.1	53.0	24.6	73.3	55.0	25.5	84.6	57.0	26.

The performance data were obtained under ideal testing conditions and may be adversely affected by wind and other factors. Pressure refers to pressure at nozzle. A lowered trajectory angle improves the irrigation efficiency in windy conditions. For every 3° drop of the trajectory angle the throw is reduced by aprrox. 3 to 4% Radius = radius of throw in feet. Nozzle at 5 feet above ground level. Height = maximum stream height in meters above nozzle.

XLR ADJ Nozzle Throw Range | Adjustable Trajectory

• For every 3° drop of the trajectory angle, the throw is reduced by approximately 3 to 4%. • Use the XLR 24 Nozzle Throw Range Table for your pressure and nozzle diameter.

TSJ/TSJ-PRS Series

Swing Joints Connect $\frac{3}{4}$ " (1.9 cm) and 1" (2.5 cm) Rotors or Quick Coupler Valves to Lateral Pipes

Features

- Preassembled units save the contractor time and reduce installation costs
- Excellent structural integrity from the swept elbow design reduces the costs associated with fatigue related failures
- Double O Ring provides extra protection against leaks and keeps threads clean of debris making hand tightening easy
- The TSJ-PRS combines the great flow characteristics of the Rain Bird turf swing joint with an inline pressure regulating outlet elbow for controlling and maintaining constant pressure right at the rotor inlet

Operating Specifications

- Pressure rating: 315 psi at 73° F (21.7 bar at 22.8° C) (per ASTM D3139)
- 34" joint pressure loss: 0.3 psi at 6 gpm (0.02 bar at 0.4 l/s)
- 1 " joint pressure loss: 1.5 psi at 18 gpm; 2.5 psi at 23 gpm (0.1 bar at 1,1 l/s; 0.2 bar at 1.5 l/s)
- TSJ-PRS maximum flow: 22 gpm (1.41 l/s)

TSJ-PRS Application Information


- The TSJ-PRS is not recommended for use in systems where the pressure in the lateral lines is equal to or less than the nominal regulation pressure, as the increased pressure drop may adversely affect the performance of such systems
- To reduce the effects of water hammer, Rain Bird recommends flow rates in the supply line not exceed 5 ft/sec (1.5 m/s). The TSJ-PRS is not intended to function as a water hammer prevention device
- There are no user-serviceable parts inside. The internal spring is under compression. Do not open the PRS unit under any circumstances


Models

- TSJ-12075: 12" (30.5 cm) long, ³/₄" M NPT x M NPT swing joint
- TSJ-12: 12" (30.5 cm) long, 1" M NPT x M NPT swing joint
- TSJ-100-PRS: 1" swing joint with 70 psi pressure regulator, 12" (30.5 cm) long, 1" M NPT x M NPT inlet and outlet



TSJ-100-PRS







Valves

Major Products											
Primary Applications	DV	DVF	ASVF	HV	HVF	PGA	PEB	PESB/PESB-R	EFB-CP	BPES	QC
Manual Bleed	I/E	I/E	I/E	I/E	I/E	I	I/E	I/E	I/E	E	
Flow Control		•	•		•	•	•	•	•	•	
Bottom Inlet	DV-A		•			•				•	•
Low Flow		•	•		•		•	•	•		
PRS-Dial Compatible						•	•	•	•	•	
Dirty Water								•		•	
Non-Potable Water								•		•	
Sites Requiring Brass									•	•	
Sites Requiring Plastic								•			
Decoder System Compatible						•	•	•	•	•	

- $\bullet DV/DVF\ available\ in\ globe, angle,\ slip\ x\ slip,\ and\ male\ x\ barb\ configurations. \qquad \bullet Flows\ below\ 3\ gpm\ (0.68\ m^3/h;\ 0.19\ l/s)\ install\ 200\ mesh\ filter\ upstream. \qquad \bullet l/E=Internal/External$
- The PESB-R and EFB-CP are specifically designed with chlorine-resistant components for reclaimed water applications.



Water Saving Tips

- The PRS-Dial is an excellent means of regulating outlet pressure at the valve regardless of incoming pressure fluctuations. It helps ensure optimal pressure performance at the head.
- Rain Bird valves provide excellent filtration characteristics for maximum reliability in a wide range of environments.
- PESB-R and EFB-CP reclaimed valves provide reliable operation in all water conditions. Valve diaphragms are composed of EPDM, a rubber material which is chlorine and chemical resistant.

DV / DVF Series

Diaphragm Valve - The Industry Leader for Over 25 Years

- · Double-filtered (diaphragm and solenoid) pilot-flow design for maximum reliability and grit resistance
- Buna-N, balanced pressure diaphragm with self-cleaning 90 mesh (200 micron) pilot water filter and captive spring
- Energy-efficient, low-power encapsulated solenoid with captured plunger and 90-mesh (200 micron) solenoid filter
- Unique, easy-to-turn pressure assisted flow control mechanism (DVF models only)
- · External bleed to manually flush system of dirt and debris during installation and system start-up
- · Internal bleed for spray-free manual operation
- · Accepts Rain Bird TBOS latching solenoid for use with most batteryoperated controllers
- Operates in low-flow and Landscape Drip applications when a 200 mesh filter is installed upstream
- · Not recommended for use with two-wire control systems

Specifications

- Pressure: 15 to 150 psi (1,0 to 10,4 bar)
- 075-DV Non-Flow Control Model: 0.2 to 22 GPM (0,05 to 5,0 m³/h; 0,01 to 1,39 l/s). For flows below 3 GPM (0,68 m³/h; 0,19 l/s) or any Landscape Drip application, use a 200 mesh filter installed upstream
- 100-DV Non-Flow Control Model: 0.2 to 40 gpm (0,05 to 9,085 m³/h; 0.01 to 2.52 l/s). For flows below 3 gpm (0.68 m³/h; 0.19 l/s) or any Landscape Drip application, use a 200 mesh filter installed upstream
- 100-DVF Flow Control Model: 0.2 to 40 gpm (0,05 to 9.085 m³/h; 0,01 to 2,52 l/s); For flows below 3 gpm (0,68 m³/h; 0,19 l/s) or any Landscape Drip application, use a 200 mesh filter installed upstream
- Water Temperature: Up to 110° F (43° C)
- Ambient air temperature: Up to 125° F (52° C)
- 24 VAC 50/60 Hz (cycles per second) solenoid power requirement: 0.450A inrush current; 0.250A holding current
- · Solenoid coil resistance: 38 Ohms








100-DVF-MB



100-DV-A





DVF Cutaway

How to Specify



. Optional Configuration: MB: Male x Barb A: Angle SS: Slip x Slip

DV: Remote Control Valve DVF: Remote Control Valve with Flow Control

Size 075: ³/₄" 100: 1"

This specifies a 100-DV valve; 1" (26/34) male x barb.

Note: For non-U.S. applications it is necessary to specify
NPT or BSP thread type (1" only).



DV / DVF Series (cont.)

Dimensions

DV Valves

• Height: 4½" (11.4 cm)

• Height (Angle): 5½" (14 cm)

• Length: 43/8" (11.1 cm)

• Length (Angle): 3³/₄" (9.5 cm)

• Length (MB): 53/4" (14.6 cm)

• Width: 31/3" (8.4 cm)

DVF Valves

• Height: 5³/₅" (14.2 cm)

• Length: 43/8" (11.1 cm)

• Length (MB): 53/4" (14.6 cm)

• Width: 31/3" (8.4 cm)

DV and DVF Valve Pressure Loss (psi)									
Flow gpm	075-DV ³ ⁄4" psi	100-DV/100-DVF 1" psi							
1	3.2	3.3							
3	3.9	3.6							
5	4.2	3.8							
10	5.0	3.8							
20	7.7	5.1							
30	-	6.4							
40	-	8.6							

DV and	DVF Valve Pres	ssure Loss (bar)	METRIC
Flow m³/h	l/m	075-DV ³⁄4" bar	100-DV/100-DVF 1" bar
0.23	4	0.22	0.23
0.60	10	0.26	0.24
1.20	20	0.29	0.26
3.60	60	0.45	0.32
4.50	75	0.53	0.35
6.00	100	-	0.41
9.00	150	-	0.59

100-DV Angle, MxB Valve Pressure Loss (psi)									
Flow gpm	075-DV ³ ⁄4" psi	100-DV/100-DVF 1" psi							
1	2.8	2.5							
3	3.0	2.9							
5	3.2	3.0							
10	3.9	3.1							
20	4.3	4.3							
30	5.4	7.4							
40	8.2	12.7							

100-DV A	Angle, MxB Va	lve Pressure Los	s (bar)	METRIC
Flow m³/h	l/m	075-DV ³ ⁄4" bar	100-DV 1" bar	/100-DVF
0.23	4	0.19	0.17	
0.60	10	0.20	0.19	
1.20	20	0.22	0.21	
3.60	60	0.28	0.26	
4.50	75	0.30	0.30	
6.00	100	0.35	0.44	
9.00	150	0.56	0.86	

Note: DV/DVF Male x barb not recommended for flows exceeding 30 gpm (6.81 m^3/h , 113.56 l/m)

Models

• 075-DV: 3/4" NPT

• 100-DV: 1" NPT female x female*

• 100-DV-SS: 1" slip x slip

• 100-DV-A: 1" NPT female x female

• 100-DV-MB: 1" male x barb

• 100-DVF: 1" NPT female x female*

• 100-DVF-SS: 1" slip x slip

• 100-DVF-MB: 1" male x barb

* Available with BSP threads

Recommendations

1. Rain Bird recommends flow rates that result in discharge velocities in the supply line not to exceed 7.5 ft/sec (2.3 m/s) in order to reduce the effects of water hammer.

2. Rain Bird residential valves cannot be used with PRS pressure regulating modules.

3. Not recommended for use with two-wire systems.

ASVF Series

Anti-siphon Valve with Flow Control – The Industry Leader for Over 20 Years

Features

- Combination of the reliable DVF Angle valve and atmospheric backflow preventer in one unit
- Incorporates all features of DV/DVF Series valves
- · Not recommended for use with two-wire control systems

Specifications

- Pressure: 15 to 150 psi (1,0 to 10,4 bar)
- 075-ASVF Flow: 0.2 to 22 GPM (0,05 to 5,0 m³/h; 0,01 to 1,39 l/s). For flows below 3 GPM (0,68 m³/h; 0,19 l/s) or any Landscape Drip products application, use a 200 mesh filter installed upstream
- 100-ASVF Flow: 0.2 to 40 GPM (0,05 to 9,085 m³/h; 0,01 to 2,52 l/s). For flows below 3 GPM (0,68 m³/h; 0,19 l/s) or any Landscape Drip products application, use a 200 mesh filter installed upstream
- Water temperature: Up to 110° F (43° C)
- Ambient air temperature: Up to 125° F (52° C)
- 24 VAC 50/60 Hz (cycles per second) solenoid power requirement:
 0.450A inrush current;
 0.250A holding current
- Solenoid coil resistance: 38 Ohms

Installation Notes

- · Anti-siphon valve must be installed upright
- Anti-siphon unit must be installed at least 6" (15,2 cm) above the highest point of water in the pipe and sprinklers it serves
- · No valve can be located downstream of the anti-siphon valve
- Anti-siphon valves must not be subjected to operating pressure for more than twelve (12) hours in any twenty-four (24) hour period
- Uniform Plumbing Code Table 603.2 Consult local codes

Dimensions

- Height: 61/4" (15.8 cm)
- Length: 6¹/₁₀" (15.5 cm)
- Width: 31/5 " (8.1 cm)

Models

- 075-ASVF: 3/4"
- 100-ASVF: 1"

Models available in NPT threads only

Recommendations

- 1. Rain Bird recommends flow rates that result in discharge velocities in the supply line not to exceed 7.5 ft/sec (2.3 m/s) in order to reduce the effects of water hammer.
- 2. Rain Bird residential valves cannot be used with PRS pressure regulating modules.
- 3. Not recommended for use with two-wire systems.



100-ASVF



ASVF Cutaway

ASVF Valve Pressure Loss (psi)										
Flow gpm	075-ASVF ³ ⁄4" psi	100-ASVF 1" psi								
1	2.8	2.9								
3	3.4	3.1								
5	3.8	3.3								
10	4.6	3.9								
20	6.5	5.0								
30	-	7.8								
40	-	13.4								

ASVF Va	ve Pressure Lo	oss (bar)		METRIC
Flow m ³ /h	I/m	075-ASVF ³ ⁄4" bar	100-ASVF 1" bar	
0.23	3.8	0.19	0.20	
0.6	10	0.23	0.21	
1.2	20	0.26	0.23	
3.6	60	0.39	0.31	
4.5	75	0.45	0.34	
6.0	100	-	0.47	
9.0	150	-	0.91	

^{*} Rain Bird recommends flow rates in the supply line not to exceed 7.5 ft/sec (2.3 m/s) in order to reduce the effects of water hammer



HV Series

High Value Valve. High Performance. Big Savings.

Features

- Patented, eccentric, balanced pressure, Buna-N diaphragm with selfcleaning 90-mesh (200 micron) pilot water filter and captured stainless steel spring – Eccentric design provides smoother closing, less water hammer
- Only four durable, captured multi-drive bonnet screws that come out with half the number of turns for fast and easy servicing – at least twice as fast as the competition
- Glass-filled polypropylene body for strength (slip by slip model bodies are PVC)
- All popular model configurations available
- Compact design, 2.54" spin radius for tight installations
- · Reverse flow, normally closed design
- External bleed to manually flush system of dirt and debris during installation and system start-up
- · Internal bleed for spray-free manual operation
- Operates in low-flow and Landscape Drip applications when a 200 mesh filter is installed upstream

Specifications

- Pressure: 15 to 150 PSI (1,0 to 10,3 bar)
- Flow: 0.2 to 30 GPM (0,05 to 6,82 m³/h; 0,01 to 1,89 l/s); for flows below 3 GPM (0,68 m³/h; 0,19 l/s) or any Landscape Drip application, use a 200 mesh filter installed upstream
- Operating Temperatures: Water temperature up to 110° F (43° C); ambient temperature up to 125° F (52° C)
- 24 VAC 50/60 Hz (cycles/sec.) solenoid
- · Inrush current: 0.290A at 50/60 Hz
- Holding current: 0.091A at 50/60 Hz
- Solenoid Coil resistance: 70-85 Ohms (40° F 110° F)



100-HV-SS

HV Valve Pres	HV Valve Pressure Loss (psi)										
Flow gpm	1" HV psi	1" HV-MB psi									
1	1.57	1.73									
3	2.07	2.03									
5	2.38	2.25									
10	3.33	2.80									
20	4.59	4.45									
30	6.14	7.85									
40	8.23	13.68									

HV Valve	Pressure Loss	(psi)	METRIC
Flow m³/h	l/s	1" HV bar	1" HV-MB bar
0.25	0.06	0.11	0.12
0.75	0.21	0.14	0.14
1.00	0.28	0.16	0.16
2.00	0.56	0.23	0.19
5.00	1.39	0.32	0.31
7.50	2.08	0.42	0.54
9.10	2.52	0.57	0.94

^{*} Rain Bird recommends flow rates in the supply line not to exceed 7.5 ft/sec (2.3 m/s) in order to reduce the effects of water hammer

Dimensions


- Height: 4.62" (11.7 cm)
- Height (F): 5.62" (14.3 cm)
- Height (MB): 4.50" (11.4 cm)
- Length: 4.4" (11.2 cm)
- Length (MB): 5.68" (14.4 cm)
- Width: 3.1" (7.9 cm)

Models

- 100-HV-NPT: 1" NPT female x female*
- 100-HV-SS: 1" slip x slip
- 100 HV-MB: 1" male x barb
- 100 HVF-SS: 1" slip x slip

Recommendations

- Rain Bird recommends flow rates that result in discharge velocities in the supply line not to exceed 7.5 ft/sec (2.3 m/s) in order to reduce the effects of water hammer.
- 2. Rain Bird residential valves cannot be used with PRS pressure regulating modules.
- 3. Not recommended for use with two-wire systems.



^{*} Available with BSP threads. Also available with 9V DC Latching Solenoid.

PGA Series

Plastic Globe and Angle Valves. The Toughest, Most Reliable Valves In their Class

Features

- · Water-tight seal between the body and bonnet for maximum confidence, even in the most extreme conditions
- Robust construction and electrical design for quiet performance you can count on
- · Filtered pilot flow to resist debris and clogging
- Slow closing to prevent water hammer and subsequent system damage
- Normally closed, forward flow design Accepts latching solenoid for use with Rain Bird battery-operated controllers
- · Multi-drive screws (Phillips, flathead, hexagonal) for easy maintenance*
- Manual internal bleed operates the valve without allowing water into the valve box. This allows the pressure regulator to be adjusted without turning the valve on at the controller
- One-piece solenoid design with captured plunger and spring for easy servicing. Prevents loss of parts during field service
- Three-year trade warranty
- Accommodates optional, field-installed PRS-D pressure regulating dial to ensure optimum sprinkler performance
- · Accepts latching solenoid for use with Rain Bird battery-operated controllers



PGA Cutaway



150-PGA



Extreme Durability

The PGA valve maintains a strong, worryfree seal between the body and bonnet, no matter the conditions. PGA valves were exposed to extreme temperature swings and intense pressures. The result—zero leaks.*



Pressure-Resistant Seal

The PGA valve's body-to-bonnet seal is built to overcome the intense water pressure typical of many commercial sites. Faced with repeated pressure surges well into the triple digits, our valves outlasted the nearest competitor more than 2 ½ times to 1.*

How to Specify

100 - PGA - PRS-D

PRS-Dial: pressure regulating module (must be ordered 100: 1" NPT 150: 1½" NPT 200: 2" NPT separately)

Note: Valve and PRS-Dial module must be ordered separately. For non-U.S. applications, it is necessary to specify NPT or BSP thread type.

Optional Feature

^{*} Based on 2013 testing conducted at Rain Bird's Product Research Facility in Tucson, AZ.



PGA Series (cont.)

Options

- Accommodates optional, field installed PRS-D pressure regulating module to ensure optimum sprinkler performance. Regulates up to 100 psi (6.9 bar)
- Accepts latching solenoid for use with Rain Bird battery-operated controllers up to 150 psi (10,35 bar)
- · Compatible with ESP-LXD decoders

Specifications

- Pressure: 15 to 150 psi (1.04 to 10.4 bar)
- Flow without PRS-D option: 2 to 150 gpm (0.45 to 34.05 m³/h; 7.8 to 568 l/m)
- Flow with PRS-D option: 5 to 150 gpm (1.14 to 34.05 m³/h; 19.2 to 568 l/m)
- Water temperature: Up to 110° F (43° C) refer to chart
- Ambient temperature: Up to 125° F (52° C)
- 24VAC 50/60Hz (cycles/sec) solenoid power requirement
- Inrush current: 0.41A (9.9VA) at 50/60Hz
- Holding current: 0.14A (3.43VA) at 50/60Hz
- · Solenoid coil resistance: 30-39 Ohms, nominal

Dimensions

Model	Height	Length	Width
• 100-PGA	7¼" (18.4 cm)	5½" (14.0 cm)	3 ¼" (8.3 cm)
• 150-PGA	8" (20.3 cm)	6¾" (17.2 cm)	3½" (8.9 cm)
• 200-PGA	10" (25.4 cm)	7¾" (19.7 cm)	5" (12.7 cm)

Note: PRS-Dial adds 2" (5.1 cm) to valve height

Models

- 100-PGA: 1" NPT
- 150-PGA: 11/2" NPT
- 200-PGA: 2" NPT

BSP threads available; specify when ordering

Recommendations

- 1. Rain Bird recommends flow rates in the supply line not to exceed 7.5 ft/sec (2.29 m/s) in order to reduce the effects of water hammer
- For flows below 5 gpm (1.14 m³/h; 19.2 l/m), Rain Bird recommends use of upstream filtration to prevent debris from collecting below the diaphragm
- 3. For flows below 10 gpm (2.27 m³h; 37.8 l/m) Rain Bird recommends the flow control stem be turned down two full turns from the fully open position

PGA Series Valve Pressure Loss (psi)						
Flow gpm	100- PGA Globe 1"	100- PGA Angle 1"	150- PGA Globe 1½"	150- PGA Angle 1½"	200- PGA Globe 2"	200- PGA Angle 2"
2	5.1	4.3	-	-	-	-
5	5.5	5.0	-	-	-	-
10	5.9	5.5	-	-	-	-
20	6.0	5.6	-	-	-	-
30	6.4	5.5	1.9	1.3	-	-
40	7.0	7.5	3.2	2.0	1.2	1.0
50	-	-	4.8	3.0	1.5	0.9
75	-	-	11.1	6.5	3.0	1.7
100	-	-	19.2	11.7	5.5	3.0
125	-	-	-	-	8.6	4.8
150	-	-	-	-	12.0	6.5

PGA Series Valve Pressure Loss (psi)							
Flow m³/h	Flow I/m	100- PGA Globe 2.5cm	100- PGA Angle 2.5cm	150- PGA Globe 3.8cm	150- PGA Angle 3.8cm	200- PGA Globe 5.1cm	200- PGA Angle 5.1cm
0.5	7.6	0.35	0.30	-	-	-	-
1.2	20	0.38	0.35	-	-	-	-
3	50	0.41	0.38	-	-	-	-
6	100	0.43	0.38	0.10	0.07	-	-
9	150	0.48	0.51	0.22	0.14	0.08	0.07
12	200	-	-	0.38	0.23	0.12	0.07
15	250	-	-	0.61	0.36	0.17	0.10
18	300	-	-	0.86	0.51	0.24	0.13
21	350	-	-	1.16	0.70	0.33	0.18
24	400	-	-	-	-	0.43	0.23
27	450	-	-	-	-	0.54	0.30
30	500	-	-	-	-	0.66	0.36
34	568	-	-	-	-	0.83	0.45

PGA Series Valve Pressure Loss (psi)					
Water Temperature	Continuous Pressure				
73° F	150 psi				
80° F	132 psi				
90° F	112 psi				
100° F	93 psi				
110° F	75 psi				

PGA Series Valve Pressur	METRIC	
Water Temperature	Continuous Pressu	re
23° C	10.4 bar	
27° C	9.1 bar	
32° C	7.7 bar	
38° C	6.4 bar	
43° C	5.2 bar	

PEB / PESB Series


Best-in-class Professional Series Plastic Irrigation Valves

Features


- Durable glass-filled nylon construction with fabric-reinforced rubber diaphragm for long life and reliable performance
- · Globe configuration
- · Normally closed, forward flow design
- Slow closing to prevent water hammer and subsequent system damage
- · Low flow capability for a wide range of applications
- One-piece solenoid design with captured plunger and spring for easy servicing. Prevents loss of parts during field service
- · Flow control handle adjusts water flows as needed
- Manual internal bleed manually operates the valve without allowing water into the valve box; allows pressure regulator to be adjusted without turning the valve on at the controller first
- Manual external bleed permits flushing debris from the system.
 Recommended for system start up and after repairs
- Stainless steel studs molded into the body. Bonnet can be attached and removed more easily and more often without damaging threads
- Nylon scrubber scrapes a stainless steel screen to clean and break down grit and plant material. Prevents debris build-up and clogging (PESB Series only)
- · Five-year trade warranty

Specifications

- Pressure: 20 to 200 psi (1.4 to 13.8 bar)
- Flow without PRS-D option: 0.25 to 200 GPM (0.06 to 45 m³/h; 0.02 to 12.60 l/s)
- Flow with PRS-D option: 5 to 200 GPM (1.14 to 45 m³/h; 0.32 to 12.60 l/s)
- Temperature: Up to 150° F (66° C)
- 24VAC 50/60Hz (cycles/sec) solenoid power requirement
- Inrush current: 0.41A (9.9VA) at 50/60Hz
- Holding current: 0.14A (3.43VA) at 50/60Hz
- Solenoid coil resistance: 30-39 Ohms, nominal



PEB Cutaway



PESB Cutaway





How to Specify

100 - PEB - PRS-D

Model PEB

Size 100: 1" NPT 150: 1½" NPT 200: 2" NPT Optional Feature PRS-Dial: pressure regulating module (must be ordered separately)

Note: Valve and PRS-Dial module must be ordered separately. For non-U.S. applications, it is necessary to specify NPT or BSP thread type.



PEB / PESB Series (cont.)

Options

- Accommodates optional, field installed PRS-D pressure regulating module to ensure optimum sprinkler performance. Regulates up to 100 psi (6.9 bar)
- Accepts latching solenoid for use with Rain Bird battery-operated controllers up to 150 psi (10,35 bar)
- · Compatible with ESP-LXD decoders
- Optional purple flow control handle for non-potable water applications PEB-NP-HAN1 (1"); PEB-NP-HAN2 (1 1/2" and 2")

Dimensions

Model	Height	Length	Width
• 100-PEB and 100-PESB:	6½" (16.5 cm)	4" (10.2 cm)	4" (10.2 cm)
• 150-PEB and 150-PESB:	8" (20.3 cm)	6" (15.2 cm)	6" (15.2 cm)
• 200-PEB and 200-PESB:	8" (20.3 cm)	6" (15.2 cm)	6" (15.2 cm)
Note: The PRS-Dial option adds 2"	(5.1 cm) to valve height		

Models

- 100-PEB and 100-PESB: 1" NPT
 150-PEB and 150-PESB: 1½" NPT
- 200-PEB and 200-PESB: 2" NPT

BSP threads available; specify when ordering

Recommendations

- 1. Rain Bird recommends flow rates in the supply line not to exceed 7.5 ft/sec (2.29 m/s) in order to reduce the effects of water hammer
- For flows below 5 gpm (1.14 m³/t; 19.2 l/m), Rain Bird recommends use of upstream filtration to prevent debris from collecting below the diaphragm
- 3. For flows below 10 gpm (2.27 m³/h; 37.8 l/m) Rain Bird recommends the flow control stem be turned down two full turns from the fully open position
- 4. For PRS-Dial applications, Rain Bird recommends the installation of a pressure-regulating master valve or inline pressure regulator when the inlet pressure exceeds 100 psi (6.9 bar)

PEB and PESB Series Valve Pressure Loss (psi)					
Flow gpm	100-PEB 1"	150-PEB 1½"	200-PEB 2"		
0.25 0.5	0.8 1.0	-	-		
1 5	1.3 1.7		-		
10	1.7	_	-		
20	2.9	3.9	-		
30	5.6	3.6	-		
40 50	10.0 15.6	3.5 3.6	4.8		
75	-	5.4	4.5		
100	-	9.6	5.2		
125	-	14.6	8.2		
150 175	-	21.2	11.8		
200	-	-	15.5 19.5		

PEB and P	METRIC			
Flow m³/h	Flow I/m	100-PEB 2.5cm	150-PEB 3.8cm	200-PEB 5.1cm
0.06	1	0.06	-	-
0.3	5	0.09	-	-
0.6	10	0.10	_	-
1.2	20	0.12	-	-
3	50	0.15	-	-
6	100	0.32	0.26	-
9	150	0.68	0.24	-
12	200	-	0.26	0.33
15	250	-	0.33	0.32
18	300	-	0.42	0.32
21	350	-	0.57	0.34
24	400	-	0.74	0.41
27	450	-	0.92	0.51
30	500	-	1.14	0.64
33	550	-	1.38	0.77
36	600	-	-	0.90
39	650	-	-	1.04
42	700	-	-	1.18
45	757	-	-	1.34

Notes

- 1. Loss values are with flow control fully open
- 2. PRS-Dial recommended for use in shaded area only

PESB-R Series Valves


Durable Plastic – chlorine resistant Professional Plastic Irrigation Valves for reclaimed water irrigation applications

Features

- Plastic diaphragm and scrubber components molded of chlorine- and chemical-resistant plastic material
- Durable glass-filled nylon construction for long life and heavy-duty performance at 200 psi (13.80 bars) pressure
- Stainless steel studs molded into the body. Bonnet can be attached and removed easily without damaging threads
- One-piece solenoid design with captured plunger and spring for easy servicing. Prevents loss of parts during field service
- External bleed protects the solenoid ports from debris when system is flushed
- Internal bleed operates the valve without allowing water into the valve box; allows pressure regulator to be adjusted without turning on the valve at the controller first
- · Slow closing to prevent water hammer and subsequent system damage
- Scrubber mechanism scrapes stainless steel screen clean to break down grit and plant material
- Purple flow control handle standard on PESB-R Series valves
- · Five-year trade warranty

Options

- Accommodates optional, field installed PRS-D pressure regulating module to ensure optimum sprinkler performance. Regulates up to 100 psi (6.9 bar)
- Accepts latching solenoid for use with Rain Bird battery-operated controllers up to 150 psi (10.35 bar)
- · Compatible with ESP-LXD decoders



PESB-R Cutaway



How to Specify 100 - PESBR - PRS-D Model PESR-R: scrubber model Size 100: 1" NPT 150: 1½" NPT 200: 2" NPT Note: Valve and PRS-Dial module must be ordered separately.



PESB-R Series (cont.)

Specifications

- Pressure: 20 to 200 psi (1.38 to 13.80 bar)
- Flow: 0.25 to 200 gpm (0.06 to 45.40 m³/h; 0.02 to 12.60 l/s)
- Flow with PRS-Dial: 5 to 200 gpm (1.14 to 45.40 m³/h; 0.32 to 12.60 l/s)
- Temperature: Up to 150° F (66° C)
- 24VAC 50/60Hz (cycles/sec) solenoid power requirement
- Inrush current: 0.41A (9.9VA) at 50/60Hz
- Holding current: 0.14A (3.43VA) at 50/60Hz
- · Solenoid coil resistance: 30-39 Ohms, nominal

Dimensions

Model	Height	Length	Width
• 100-PESB-R	6½" (16.5 cm)	4" (10.2 cm)	4" (10.2 cm)
• 150-PESB-R	8" (20.3 cm)	6" (15.2 cm)	6" (15.2 cm)
• 200-PESB-R	8" (20.3 cm)	6" (15.2 cm)	6" (15.2 cm)

Note: The PRS-Dial option adds 2" (5.1 cm) to valve height

Models

- 100-PESB-R: 1" NPT
- 150-PESB-R: 11/2" NPT
- 200-PESB-R: 2" NPT

BSP threads available, specify when ordering

Recommendations

- 1. Rain Bird recommends flow rates in the supply line not to exceed 7.5 ft/sec (2.29 m/s) in order to reduce the effects of water hammer
- For flows below 5 gpm (1.14 m³h; 19.21 l/m), Rain Bird recommends use of upstream filtration to prevent debris from collecting below the diaphragm
- 3. For flows below 10 gpm (2.27 m³h; 37.8 l/m) Rain Bird recommends the flow control stem be turned down two full turns from the fully open position

PESB-R Series Valve Pressure Loss (psi)					
Flow gpm	100-PESB-R 1"	150-PESB-R 1½"	200-PESB-R 2"		
0.25 0.5	1.6 3.0	-	-		
1	1.8	-	-		
5 10	2.9 2.9	_	-		
20	2.6	3.5	-		
30	5.8	3.1	-		
40 50	10.2 16.0	2.3 2.1	- 2.7		
75	10.0	4.3	3.7 3.3		
100	-	7.5	4.7		
125	-	11.9	8.6		
150 175	-	17.0	12.6 14.8		
200	-	-	18.9		

PESB-R	METRIC			
Flow m³/h	Flow I/m	100-PESB-R 2.5cm	150-PESB-R 3.8cm	200-PESB-R 5.1cm
0.06	1	0.11	-	-
0.3	5	0.13	-	-
0.6	10	0.15	-	-
1.2	20	0.20	-	-
3	50	0.19	-	-
6	100	0.32	0.22	-
9	150	0.69	0.16	-
12	200	-	0.16	0.25
15	250	-	0.24	0.24
18	300	-	0.33	0.25
21	350	-	0.45	0.30
24	400	-	0.59	0.38
27	450	-	0.75	0.53
30	500	-	0.91	0.67
33	550	-	1.10	0.82
36	600	-	=	0.92
39	650	-	-	1.00
42	700	-	-	1.13
45	757	=	=	1.30

Notes

- 1. Loss values are with flow control fully open
- 2. PRS-Dial recommended for use in shaded area only

EFB-CP Series Brass Valves

Highly durable Brass Irrigation Valves - Globe Configuration

Features

- Reliable performance even in dirty water applications. Self-flushing filter resists debris build-up
- Rugged red brass construction for longer life
- Durable, fabric-reinforced diaphragm composed of EPDM, a rubber material which is chlorine and chemical resistant
- Normally closed, reverse flow design ensures valve will fail in the closed position if a tear or rip in the diaphragm occurs. Prevents flooding, water waste and landscape damage
- · Slow closing to prevent water hammer and subsequent system damage
- One-piece solenoid design with captured plunger and spring for easy servicing. Prevents loss of parts during field service
- Manual internal bleed operates the valve without allowing water into the valve box. Allows pressure regulator adjustment without turning on the controller
- Manual external bleed permits flushing debris from the system. Recommended for system start up and other repairs
- · Contamination-proof, self-flushing filter screen resists debris build-up. Water flow continuously flushes the screen, dislodging particles and debris before they can accumulate and clog the filter
- Reclaimed water compatible: all models now feature EPDM diaphragms and chlorine-resistant parts as standard equipment
- · Three-year trade warranty

Options

- Accommodates optional, field installed PRS-D pressure regulating module to ensure optimum sprinkler performance. Regulates up to 100 psi (6.9 bar)
- Accepts latching solenoid for use with Rain Bird battery-operated controllers up to 150 psi (10.35 bar)
- · Compatible with ESP-LXD decoders

Specifications

- Pressure: to 200 psi (1.04 to 13.80 bar)
- Flow with/without PRS-D: 5 to 200 GPM (1.14 to 45.40 m³/h; 0.32 to 12.60 l/s)
- Temperature: up to 150° F (66° C)
- 24VAC 50/60Hz (cycles/sec) solenoid power requirement
- Inrush current: 0.41A (9.9VA) at 50/60Hz
- Holding current: 0.14A (3.43VA) at 50/60Hz
- Solenoid coil resistance: 30-39 Ohms, nominal

Dimensions

Model	Height	Length	Width
• 100-EFB-CP:	6" (15.2 cm)	4½" (11.4 cm)	31/4" (8.3 cm)
• 150-EFB-CP:	6½" (16.5 cm)	5½" (14 cm)	4½" (11.4 cm)
• 200-EFB-CP:	7" (17.8 cm)	6¾" (17.1 cm)	5¾" (14.6 cm)


Note: The PRS-Dial option adds 2" (5.1 cm) to the valve height

Models

- 100-EFB-CP: 1" NPT*
- 150-EFB-CP: 1½" NPT*

- 1. Rain Bird recommends flow rates in the supply line not to exceed 7.5 ft/sec (2.29 m/s) in order to reduce the effects of water hammer
- 2. For flows below 5 gpm (1.14 m³/h; 19.21 l/m), Rain Bird recommends use of upstream filtration to
- 3. For flows below 10 gpm (2.27 $\mathrm{m}^3\!h$; 37.8 $\mathrm{l/m}$) Rain Bird recommends the flow control stem be turned down two full turns from the fully open position





ordered separately.



EFB-CP Series (cont.)

EFB-CP Series Valve Pressure Loss (psi)					
Flow gpm	100-EFB-CP 1"	150-EFB-CP 1½"	200-EFB-CP 2"		
5	0.2	-	-		
10	0.7	-	-		
15	1.2	-	-		
20	2.1	2.3	0.5		
30	5	2.9	0.6		
40	8.2	2	0.8		
50	13	3.3	1.1		
60	-	4.6	1.8		
80	-	7.5	2.4		
100	-	11.8	3.8		
120	-	16.6	5.9		
140	-	-	7.8		
160	-	-	10		
180	-	-	12.5		
200	-	-	15.8		

EFB-CP Series Valve Pressure Loss (bar) METRIC					
Flow m³/h	Flow I/m	100-EFB-CP 2.5cm	150-EFB-CP 3.8cm	200-EFB-CP 5.1cm	
1	19	0.01	-	-	
3	50	0.07	-	-	
6	100	0.27	0.19	0.04	
9	150	0.56	0.14	0.05	
12	200	-	0.25	0.09	
15	250	-	0.38	0.14	
18	300	-	0.51	0.16	
21	350	-	0.70	0.23	
24	400	-	0.91	0.30	
27	450	-	1.13	0.40	
30	500	-	-	0.49	
33	550	-	-	0.58	
36	600	-	-	0.68	
39	650	-	-	0.79	
42	700	-	-	0.92	
45	757	-	-	1.09	

Notes

- 1. Loss values are with flow control fully open
- 2. PRS-Dial module recommended for all flow rates

300-BPES Brass Valves

3" Brass Master Valve - Globe and angle configuration

Feature


- Unique hybrid construction featuring durable red brass body and glassfilled nylon bonnet for long life at a value price
- · Normally closed, forward flow design
- Slow closing to prevent water hammer and subsequent system damage
- Robust solenoid provides dependable performance even during constant operation
- Flow control handle adjusts water flows as needed and incorporates a brass thread insert for longer life
- Manual internal bleed operates the valve without allowing water into the valve box. Allows pressure regulator adjustment without turning the valve on at the controller
- Manual external bleed permits flushing debris from the system.
 Recommended for system start up and repairs
- · Highly efficient operation with extremely low pressure loss
- Patented nylon scrubber scrapes a stainless steel screen to clean and break down grit and plant material. Prevents debris build-up and clogging
- · Three-year trade warranty

Options

- Accommodates field-installed PRS-D pressure regulating module to ensure optimum sprinkler performance
- Purple flow control handle for non-potable water applications (BPE-NP-HAN)
- Latching solenoid for use with Rain Bird battery-operated controllers up to 150 psi (10.4 bar)

Specifications

- Pressure: 20 to 200 psi (1.4 to 13.8 bar)
- Flow with/without PRS-D option: 60 to 300 gpm (13.6 to 68.1 m³/h; 3.78 to 18.90 l/s)
- Temperature: up to 140° F (60° C)
- Power: 24 VAC 50/60 Hz (cycles per second) solenoid
- Inrush current: 0.41 A (9.8 VA) at 50/60Hz
- Holding current: 0.28 A (6.7 VA) at 50/60Hz
- · Coil resistance: 28 Ohms, nominal





300-BPES

BPES 3" Va	BPES 3" Valve Pressure Loss (psi)					
Flow gpm	Globe	Angle				
60	6.6	6.8				
80	5.1	5.9				
100	3.2	3.5				
120	1.8	1.8				
140	1.8	2.1				
160	2.0	2.1				
180	2.2	2.0				
200	2.7	2.5				
250	4.0	3.4				
300	4.9	4.5				

BPES 3" Valve Pressure Loss (bar)				
Flow m³/h	l/s	Globe	Angle	
13.6	227	0.46	0.47	
24	400	0.19	0.21	
36	600	0.14	0.14	
48	800	0.21	0.19	
60	1000	0.29	0.26	
68	1136	0.34	0.31	

Notes

- 1. Loss values are with flow control fully open
- 2. PRS-Dial module recommended for all flow rates

Dimensions

Model	Height	Length	Width
• 300	13 ⁵ / ₈ " (34.61 cm)	8" (20.32 cm)	7" (17.78 cm)

Models

• 300-BPES: 3" NPT

BSP threads available; specify when ordering

Recommendations

- Rain Bird recommends flow rates in the supply line not to exceed 7.5 ft/sec (2.29 m/s) in order to reduce the effects of water hammer.
- 2. For flows below 5 gpm (1.14 m³/h; 19.2 l/m), Rain Bird recommends use of upstream filtration to prevent debris from collecting below the diaphragm.
- 3. For flows below 10 gpm (2.27 m3h; 37.8 l/m) Rain Bird recommends the flow control stem be turned down two full turns from the fully open position.



BPES Cutaway

WC Series Wire Connector

Connections Made Easy

Features and Benefits

- Install Faster the WC Series Wire Connectoris quick to install and provides reliable moisture sealing for controller and valve electrical connections you can count on
- Simplify Inventory This is the only wire connector you'll need! It is ideal for use on two wire decoder control systems
- Avoid Call Backs Locating and repairing a corroded wire splice costs your business time and money. Avoid unnecessary service call backs
- Use for standard controllers, valve boxes and soil moisture sensors
- · Wire combinations ranging from 22ga to 8ga
- Use on connections from 24 VAC to 600 VAC
- · UL 486D certified for direct burial
- The Strain Relief ensures wires are secure and won't pull apart
- Waterproof silicone sealant protects against corrosion
- UV-resistant material ensures product performance does not degrade even after long periods of exposure to sunlight

Models

• WC20: Direct Bury Silicone Tube, Red Yellow Wire Nut, Bag of 20



Wire Combinations (for solid and stranded wire)					
WC20					
2-3 #10	2#18				
2-5 #12	1 #8 w/2 #18				
2-5 #14	3 #10 w/1 #18				
4-6 #16	3 #12 w/3 #18				
3 #14 w/2 #18					

The combinations listed are only a sample of the most common wire combinations.



PRS-Dial

Pressure Regulating Module

Features

- The PRS-Dial is an excellent means of regulating outlet pressure at the valve regardless of incoming pressure fluctuations. The visible scale makes adjustment quick and easy. The regulator fits all Rain Bird PGA, PEB, PESB, PESB-R, EFB-CP, and BPES series valves
- Regulates and maintains constant outlet pressure between 15 and 100 psi (1.04 to 6.9 bar) within ±3 psi (±0.21 bar)
- Adjustment knob with detents permits fine-tune setting in 1/3 psi (0.02 bar) increments. Dial cartridge makes installation and adjustment quick, easy and accurate Improved spike reduction capabilities reduce water hammer
- Ergonomic design with snap-tight cover to prevent vandalism
- Waterproof dial cartridge eliminates fogging and binding
- · Dial cartridge retrofits into all existing PRS-D units
- Schrader valve connects pressure hose gauge, ordered separately
- Easy field installation. PRS-Dial threads underneath the solenoid and adapter
- · Corrosion-resistant glass-filled nylon for rugged performance

Operating Range

- Pressure: Up to 100 psi (6.9 bar)*
- Regulation: 15 to 100 psi (1.04 to 6.9 bar)
- Flow: Refer to chart
- * While the PRS-Dial unit can withstand pressures up to 200 psi (13.8 bar), accurate pressure regulation can be maintained only up to 100 psi (6.9 bar)

Model

• PRS-D

Application Information

- Proper operation requires inlet pressure to be a minimum of 15 psi (1.04 bar) higher than desired outlet pressure
- For areas with very high pressure or uneven terrain, install sprinklers with PRS pressure regulating stems and/or SAM check valves
- When inlet pressure exceeds 100 psi (6.9 bar), a pressure regulating master valve or inline pressure regulator is required
- Rain Bird does not recommend using the pressure regulating module for applications outside the recommended flow ranges
- To reduce the effects of water hammer, Rain Bird recommends flow rates in the supply line not to exceed 7.5 ft/sec (2.29 m/s)
- For flows below 10 gpm (2.27 m³/h; 37.8 l/m), Rain Bird recommends the flow control stem be turned down two full turns from the fully open position

† Note: Valve and PRS-Dial module must be ordered separately.

Valve Flow Ranges*					
Model	gpm	m³/h	l/m		
100-PGA	5-40	1.14-9.08	19.2-151		
150-PGA	30-100	6.81-22.70	113-378		
200-PGA	40-150	9.08-34.05	151-568		
100-PEB	5-50	1.14-11.35	19.2-189		
150-PEB	20-150	4.54-34.05	76-568		
200-PEB	75-200	17.03-45.40	284-757		
100-PESB/PESB-R	5-50	1.14-11.35	19.2-189		
150-PESB/PESB-R	20-150	4.54-34.05	76-568		
200-PESB/PESB-R	75-200	17.03-45.40	284-757		
100-EFB-CP	5-50	1.14-11.35	19.2-189		
125-EFB-CP	20-80	4.54-18.16	76-302		
150-EFB-CP	20-120	4.54-31.78	76-529		
200-EFB-CP	20-200	4.54-45.40	76-757		
300-BPES	60-300	13.62-68.10	227-1136		

^{*} These are the valve flow ranges.





PRS-Dial cutaway



150-PEB with PRS-Dial Installation†



300-BPES with PRS-Dial Installation†

Quick-Coupling Valves

Convenient water access in potable and non-potable systems

Features

- Optional locking cover on models 33-DLRC, 44-LRC, 5-LRC, 33-DNP, 44-NP, 44-NP ACME, and 5-NP (use 2049 key to unlock). Metal cover on model 7 only
- One-piece body design (models 3-RC, 5-RC and 7)
- Two-piece body design for easy servicing (models 33-DRC, 44-LRC, 44-RC, 44-NP ACME, 33-DNP, and 44-NP)
- Strong corrosion-resistant stainless steel spring prevents leakage
- Thermoplastic cover for durability
- 33-DNP, 44-NP, 44-NP ACME, and 5-NP covers marked with "Do Not Drink!" warnings in English and Spanish
- · Three-year trade warranty

Specifications

- Pressure: 5 to 125 psi (0.35 to 8.63 bar)
- Flow: 10 to 125 gpm (2.27 to 28.38 m³/n; 37.8 to 473 l/m)
- 33-DNP, 44-NP, 44-NP ACME and 5-NP flow: 10 to 70 gpm (2.27 to 15.89 m³h; 37.8 to 265 l/m)

Dimensions (height)

• 3-RC: 4 ¹ / ₄ " (10.8 cm)	• 44-RC: 6" (15.2 cm)	• 7:5%" (14.6 cm)
• 33-DRC: 43/8" (11.1 cm)	• 44-LRC: 6" (15.2 cm)	• 33-DNP: 4 ³ / ₈ " (11.1 cm)
• 33-DLRC: 45/8" (11.7 cm)	• 5-RC: 5½" (14.0 cm)	• 44-NP: 6" (15.2 cm)
	• 5-I RC: 51/2" (14.0 cm)	• 5-NP: 5 ¹ / ₂ " (14.0 cm)

Models

- 3-RC: 3/4" NPT Rubber Cover, 1-Piece Body
- 33-DRC: ¾" NPT Double Track Key Lug, Rubber Cover, 2-Piece Body
- 33-DLRC: ¾" NPT Double Track Key Lug, Locking Rubber Cover, 2-Piece Body
- 44-RC: 1" NPT Rubber Cover, 2-Piece Body
- 44-LRC: 1" NPT Locking Rubber Cover, 2-Piece Body
- 5-RC: 1" NPT Rubber Cover, 1-Piece Body
- 5-LRC: 1" NPT Locking Rubber Cover, 1-Piece Body
- 7: 1½" NPT Metal Cover, 1-Piece Body
- 5-RC-BSP: 1" BSP Rubber Cover, 1-Piece Body, BSP threaded
- 5-LRC-BSP: 1" BSP Locking Rubber Cover, 1-Piece Body, BSP threaded
- 33-DNP: ¾" NPT Non-potable, Purple Locking Rubber Cover, 2-Piece Body
- 44-NP: 1" NPT Non-potable, Purple Locking Rubber Cover, 2-Piece Body
- 44-NP ACME: 1" NPT Non-potable, Purple Locking Rubber Cover,
 2-Piece Body, ACME thread
- 5-NP: 1" NPT Non-potable, Purple Locking Rubber Cover, 1-Piece Body

Note: For non-US applications, it is necessary to specify NPT or BSP thread type

Quick-Coupling Valves Pressure Loss (psi)						
Flow	3-RC	33-DRC 33-DLRC 33-DNP	44-RC 44-LRC 44-NP 44-NP ACME	5-RC 5-LRC 5-NP	7	
gpm	3/4"	3/4"	1"	1"	1½"	
10	1.8	2	-	-	-	
15	4.7	4.3	2.2	-	-	
20	7.2	7.6	4.4	-	-	
30	-	-	11.5	4.1	-	
40	-	-	-	7.3	-	
50	-	-	-	11	1.7	
60	-	-	-	15.7	2.5	
70	-	-	-	21.5	3.6	
80	-	-	-	-	4.9	
100	-	-	-	-	8.4	
125	-	-	-	-	14	

Quick-Coupling Valves Pressure Loss (psi)						
Flow		3-RC	33-DRC 33-DLRC 33-DNP	44-RC 44-LRC 44-NP 44-NP ACME	5-RC 5-LRC 5-NP	7
m³/h	l/m	1.9 cm	1.9 cm	2.5 cm	2.5 cm	3.8 cm
2.3	38	0.12	0.12	-	-	-
4	67	0.41	0.42	0.23	-	-
5	83	0.57	0.62	0.4	-	-
6	100	-	-	0.62	-	-
7	117	-	-	0.83	0.3	-
8	133	-	-	-	0.4	-
9	150	-	-	-	0.5	-
10	167	-	-	-	0.61	-
12	200	-	-	-	0.85	0.13
14	233	-	-	-	1.15	0.18
16	267	-	-	-	1.5	0.25
22	367	-	-	-	-	0.54
28	473	-	-	-	-	0.97



Quick-Coupling Valve Cutaway



Quick Coupling Valves



Valve Keys

Quick-Coupling Keys

Features

• Key threads into top of quick-coupling valve to provide water access

Models

- 33-DK: 3/4" NPT • 44-K: 1" NPT • 44-KA: 1" NPT
- 55-K-1: 1" NPT *
- 7-K: 1½" NPT *
- * Available with BSP threads; specify when ordering



Corresponding Valve Keys						
Valve	Key	Top Pipe Threads Valve	S Valve			
3-RC	33-DK	3/4"	1/2"			
33-DRC/33-NP	33-DK	3/4"	1/2"			
44-RC/44-NP	44-K/44-KA	1"	3/4"			
5-RC/5-NP	55-K-1	1"	-			
7	7-K	11/2"	11/4"			

Corresponding	Valve Keys		METRIC
Value	Vov	Top Pipe Thr Valve	eads Valve
Valve 3-RC	Key 33-DK	20/27	15/21
33-DRC/33-NP	33-DK	20/27	15/21
44-RC/44-NP	44-K/44-KA	26/34	20/27
5-RC/5-NP	55-K-1	26/34	-
7	7-K	40/49	33/42

SH Series

Hose Swivel

Features

- · Attaches water hose to quick-coupling valve key
- Swivels up to 360°
- · Allows hose to be pulled in any direction
- Prevents hose damage

Specifications

- SH-0: 3/4" NPT female pipe thread x 3/4" NPT male hose thread
- SH-1: 1" NPT female pipe thread x 3/4" NPT male hose thread
- SH-2: 1" NPT female pipe thread x 1" NPT male hose thread
- SH-3: 1½" NPT female pipe thread x 1" NPT male hose thread

Models

- SH-0
- SH-1
- SH-2*
- SH-3

*Available with BSP threads



Locking Cover Key

Features

- Locks and unlocks the optional locking cover on quick-coupling valves
- Operates the valve marker compression lock
- · Compatible with models 33-DLRC, 33-DNP, 44-LRC, 44-NP, 44-NP ACME, 5-LRC, and 5-NP

Model

· 2049 Cover Key

Purple Valve Handle Assembly

Features

- Purple flow control handle identifies valve as part of a non-potable system
- · Easily field installed
- · Sizes for all Rain Bird Commercial Valves

Models

- PEB-NP-HAN1 (1" PEB/PESB
- PEB-NP-HAN2 (1½" and 2" PEB/PESB Valves)
- BPE-NP-HAN (3" BPE/BPES Valves)



2049



PEB-NP-HAN, BPE-NP-HAN

24 VAC Solenoid Valves Wire Sizing - 50Hz

90 pci /F					ners - Equ			
80 psi (5. Common	Control V	iter Pressur Vire Size						
Wire Size	18 *	16 •	14 •	12 •	10 🔍	8 🛡	6	4
18 16	3700	6000						
16	4600	6000	0600					
14	5400	7400	9600	15200				
12	6000	8600	11800	15200	24222			
10	6500	9600	13700	18700	24200			
8	6900	10400	15400	21800	29700	38500		
6	7100	10900	16600	24300	34600	47100	60600	0700
4	7300	11300	17500	26300	38800	55100	74600	97000
• •		later Pressu	ıre at Valve					
Common Wire Size	Control \	Nire Size 16 ●	14 ●	12 •	10 🗨	8 🗨	6	4
18	3200							
16	4000	5200						
14	4700	6400	8300					
12	5200	7400	10200	13200				
10	5600	8300	11900	16200	20900			
8	5900	9000	13300	18900	25700	33300		
6	6100	9500	14300	21100	29900	40700	52400	
4	6300	9800	15100	22800	33500	47700	64600	83900
125 psi (8	3.6 bar) W	later Pressu	ure at Valve	<u>}</u>				
Common Wire Size	Control \	Vire Size 16 ●	14 ●	12 •	10 •	8 •	6	4
18	2900	10 •	17 🛡	12 🛡	10	0		7
16	3500	4600						
14	4100	5700	7400					
12	4600	6600	9000	11700				
10	5000	7400	10500	14400	18600			
8	5300	8000	11800	16800	22800	20600		
6				18700		29600	46600	
4	5400 5600	8400 8700	12700 13400	20200	26600 29800	36200 42300	46600 57300	74600
•					29000	72300	37300	7 +000
150 psi (1 Common		Water Press Wire Size	sure at Valv	/e				
Wire Size	18 •	16 •	14 ●	12 •	10 🌑	8 🔵	6	4
18	2600	44.45						
16	3200	4100						
14	3700	5000	6600	40/				
12	4100	5900	8100	10400				
10	4500	6600	9400	12800	16600	_		
8	4700	7100	10500	15000	20400	26400		
6	4900	7500	11400	16700	23800	32300	41600	
4	5000	7800	12000	18100	26600	37800	51300	66600
		Water Press	sure at Valv	/e				
Common Wire Size	Control \	Nire Size 16 ●	14 ●	12 •	10 🌑	8	6	4
18	2400							
16	2900	3800						
14	3400	4700	6100					
	3800	5500	7500	9700				
12					15500			
12 10	4100	6100	8800	11900	13300			
10	4100 4400	6100 6600	9800 9800	13900	19000	24600		
						24600 30100	38700	

Commercial Valve Wire Sizing Procedure

Step 1

Determine actual distance, along wire run, from controller out to the first valve on a circuit and between each succeeding valve on a multiple valve circuit. Example: (Two watt solenoid, 26.5 volt transformer, 50Hz, at 150 psi water pressure at valves.)

Step 2

Calculate the equivalent circuit length for each valve circuit on the controller. (See chart to left)

Step 3

Selecting Common Wire Size: Using the longest equivalent length calculated above, go to the appropriate valve chart and select a common wire and a control wire that are as close to the same size as possible (the common wire size should always be equal to or one size larger than the control wire size.) In the example above, the circuit for station #3 has the longest equivalent length, 7000 feet. In the chart (for this example use the chart for 150 psi water pressure at the valve and a 26.5 volt transformer) select a wire size combination of size 14 and 12 wire. Select common wire as size 12 wire. Since one common wire shall be used for all valves on the controller, you have now established the common wire size for that controller as size 12 wire.

Step 4

Sizing Circuit Control Wires: Reading only from the row for the common wire size selected in Step 3 (size 12), proceed to select each control wire size from the chart using the calculated equivalent length for each circuit.

EXAMPLE:

Station #1: Equiv. Length = 1 valve x 2000 ft. = 2000 ft. select size 18 control wire

Station #2: Equiv. Length = (1 valve x 1000 ft.) + (2 valves x 2000 ft.) = 5000 ft. select size 16 control wire

Station #3: Equiv. Length = (1 valve x 500 ft.) + (2 valves x 1000 ft.) + (3 valves x 1500 ft.) = 7000 ft. select size 14 control wire



24 VAC Solenoid Valves Wire Sizing – 60Hz

9.8 VA V	alves (E	Z) with 2	6.5 Volt 1	ransforn	ners - Equ	uivalent F	eet of Cir	cuit
		ter Pressur	e at Valve					
Common Wire Size	Control V 18 °	Vire Size 16 •	14 ●	12 •	10 •	8 •	6 ●	4
18	3200							
16	4000	5200	0000					
14	4700	6400	8300	42200				
12	5200	7500	10200	13200	21000			
10	5700	8300	11900	16200	21000	22400		
8	6000 6200	9000 9500	13300 14400	18900 21100	25800 30100	33400 40900	52600	
4	6300	9800	15200	22900	33700	47800	64800	84200
					33700	17000	0 1000	0 1200
Common	Control V		ure at Valve					
Wire Size	18 •	16 •	14 ●	12 •	10 •	8 🗨	6	4
18	2900	4600						
16 14	3500 4100	4600 5600	7200					
14	4600	5600 6600	7300 9000	11700				
10	5000	7400	10500	14300	18600			
8	5300	8000	11800	16700	22800	29500		
6	5400	8400	12700	18700	26500	36100	46500	
4	5600	8700	13400	20200	29700	42200	57200	74400
125 psi (8	3.6 bar) W	/ater Pressi	ure at Valve	!				
Common	Control V	Vire Size			10.0			4.0
Wire Size	2400	16 ●	14 •	12 •	10 •	8 🔴	6	4
16	2400 3000	3900						
14	3500	4800	6300					
12	3900	5600	7700	9900				
10	4300	6300	9000	12200	15800			
8	4500	6800	10000	14300	19400	25200		
6	4600	7100	10800	15900	22700	30800	39700	
4	4700	7400	11400	17200	25400	36100	48800	63500
150 psi (1	0.4 bar)	Water Pres	sure at Valv	re				
Common Wire Size	Control V 18 •	Vire Size 16 ●	14 ●	12 •	10 •	8	6	4
18	2200							
16	2700	3500						
14	3100	4300	5600					
12	3500	5000	6800	8800				
10	3800	5600	8000	10900	14100			
8	4000	6000	8900	12700	17300	22400		
6	4100	6300	9600	14100	20100	27400	35300	
4	4200	6600	10200	15300	22600	32100	43400	56500
• •	3.8 bar) Control V		sure at Valv	<i>r</i> e				
Common Wire Size	18 •	Vire Size 16 ●	14 ●	12 •	10 🌑	8 •	6	4
18	1800							
16	2300	2900						
14	2600	3600	4700					
12	3000	4200	5800	7500				
10	3200	4700	6800	9200	12000	10000		
8	3400	5100	7600	10800	14700	19000	20000	
6	3500 3600	5400 5600	8200 8600	12000 13000	17100 19200	23300 27300	30000 36900	48000
4		2011(1	ADUU	15000	19700	7/500	ากฯแน	48000

Commercial Valve Wire Sizing Procedure

Step 1

Determine actual distance, along wire run, from controller out to the first valve on a circuit and between each succeeding valve on a multiple valve circuit. Example: (Two watt solenoid, 26.5 volt transformer, 60Hz, at 150 psi water pressure at valves.)

Step 2

Calculate the equivalent circuit length for each valve circuit on the controller. (See chart to left)

Step 3

Selecting Common Wire Size: Using the longest equivalent length calculated above, go to the appropriate valve chart and select a common wire and a control wire that are as close to the same size as possible (the common wire size should always be equal to or one size larger than the control wire size.) In the example below, the circuit for station #3 has the longest equivalent length, 7000 feet. In the chart (for this example use the chart for 150 psi water pressure at the valve and a 26.5 volt transformer) select a size 12 wire for both common and control wire. Since one common wire shall be used for all valves on the controller, you have now established the common wire size for that controller as size 12 wire.

Step 4

Sizing Circuit Control Wires: Reading only from the row for the common wire size selected in Step 3 (size 12), proceed to select each control wire size from the chart using the calculated equivalent length for each circuit.

EXAMPLE:

Station #1: Equiv. Length = 1 valve x 2000 ft. = 2000 ft. select size 18 control wire

Station #2: Equiv. Length = $(1 \text{ valve } \times 1000 \text{ ft.})$ + $(2 \text{ valves } \times 2000 \text{ ft.})$ = 5000 ft. select size 16 control wire

Station #3: Equiv. Length = (1 valve x 500 ft.) + (2 valves x 1000 ft.) + (3 valves x 1500 ft.) = 7000 ft. select size 12 control wire

PVB Professional Series Valve Boxes

The PVB Series valve box provides rugged, no-nonsense dependability, with a price tag that can meet any budget

Features

- · Light & durable construction
- Side ridges for additional side wall support
- Pre-molded pipe slots
- Bottom flanges to help prevent sinking
- Four colors: available in green, black, tan and purple
- Multiple configurations designed to provide tight seals and easy maintenance access
- Earth-friendly, LEED-compliant material made of 100% recycled materials (black boxes and black lids only)

















6" Round Valve Box	10" Round Valve Box	Mini Standard Valve Box	Standard Valve Box	Standard Extension	Jumbo Valve Box	Jumbo Extension				
	SIZE									
Top Opening: 6 %" diameter Bottom Opening: 8 %" diameter	Top Opening: 10" diameter Bottom Opening: 12 ½" diameter	Top Opening: 15" L x 9 ½" W Bottom Opening: 18" L x 12 ½" W x 10" H	Top Opening: 18 ¼" L x 13" W Bottom Opening: 21 ¼" L x 15 15/6" W x 12" H	Top Opening: 17" L x 11 ¾" W Bottom Opening: 18 %" L x 13 %" W x 6 ¾" H	Top Opening: 22 ¼" L x 16 ¾" W Bottom Opening: 25 ¼" L x 19 ¾" W x 12" H	Top Opening: 21 %" L x 15 %" W Bottom Opening: 22 %" L x 16 %" W x 6 %" H				
			ADDITIONAL FEA	TURES						
Snap-in overlapping lid Skid-resistant texture Body built with three ridges for additional sidewall support	Overlapping lid with bolt hole and twist lock Skid-resistant lid texture Body built with double ridges for additional sidewall support	Our compact alternative to a standard size box Drop-in lid Skid-resistant lid texture	Drop-in lockable lid Skid-resistant lid texture Double ledge lid support Ridge adds additional support to sidewalls	Overlapping lockable lid Skid-resistant lid texture Body can be used to extend the PVB Standard series Body can be used as a 6" deep box	Drop-in lockable lid Skid-resistant lid texture Double ledge lid support Ridge adds additional support to sidewalls	Overlapping lockable lid Skid-resistant lid texture Body can be used to extend the PVB Jumbo series Body can be used as a 6" deep box				
			MODELS							
PVB6RND: 6" round black body & overlapping green lid PVB6RNDP: 6" round black body & overlapping purple lid PVB6RNDT: 6" round black body & overlapping purple lid PVB6RNDT: 6" round black body & overlapping tan lid	PVB10RND: 10" round black body & overlapping green lid PVB10RNDP: 10" round purple body & overlapping purple lid PVB10RNDT: 10" round tan body & overlapping tan lid	PVBMST: 10" mini- standard black body & drop-in green lid	PVBSTD: 12" standard black body & drop-in green lid PVBSTDP: 12" standard purple body & drop-in purple lid PVBSTDT: 12" standard tan body & drop-in tan lid	STDEXT body can extend the Standard Valve box by 6" in height STDEXT body can be used as a 6" deep box to reduce digging PVBSTDEXT: 6" black body & overlapping green lid PVBSTDEXTT: 6" tan body & overlapping tan lid	PVBJMB: 12" black body & drop-in green lid PVBJMBP: 12" purple body & drop-in purple lid PVBJMBT: 12" tan body & drop-in tan lid	PVBJMBEXT: 6" black body & overlapping green lid PVBJMBEXTP: 6" purple body & overlapping purple lid PVBJMBEXTT: 6" tan body & overlapping tan lid				

6" Round Lids PVB6RNDGL: 6" round green lid 10" Round Lids PVB10RNDGL: 10" round green lid 12" Standard Lids

PVBSTDGL: 12" standard green lid

12" Jumbo Lids PVBJMBGL:

12" jumbo green lid




VB Series Valve Boxes

Commercial grade boxes that are loaded with a rich set of industry-leading features

Features

- Strength and Stability Multiple sizes and shapes are designed with corrugated sides and wide flange bases for maximum durability, compression strength, and stability
- Smart Lid Design Designed with no holes to keep out pests, beveled edges to minimize damage potential from turf equipment, and for easy hand and shovel access
- Flexible Installations Interlocking stacking capabilities, extension models and pipe hole knockouts support deeper and flexible installations
- Environmentally Friendly Earth-friendly, LEED-compliant material made of 100% recycled materials (black boxes and black lids only)



















7 Inch Round Valve Box	10 Inch Round Valve Box	Standard Valve Box	Standard Extension	Jumbo Valve Box	Jumbo Extension	Super Jumbo Valve Box	Maxi Jumbo Valve Box				
	SIZE										
Bottom Diameter: 9.9 inches (25,1 cm) Height: 9.0 inches (22,9 cm)	Bottom Diameter: 13.75 inches (34,9 cm) Height: 10.0 inches (25,4 cm)	Length: 21.8 inches (55,4 cm) Width: 16.6 inches (42,2 cm) Height: 12.0 inches (30,5 cm)	Length: 20.0 inches (50,8 cm) Width: 14.75 inches (37,5 cm) Height: 6.75 inches (17,1 cm)	Length: 26.3 inches (66,8 cm) Width: 19.8 inches (50,3 cm) Height: 12.1 inches (30,7 cm)	Length: 24.4 inches (62,0 cm) Width: 17.9 inches (45,5 cm) Height: 6.75 inches (17,1 cm)	Length: 33.1 inches (84,1 cm) Width: 23.8 inches (60,5 cm) Height: 15.0 inches (38,1 cm)	Length: 40.3 inches (102,4 cm) Width: 27.1 inches (68,8 cm) Height: 18.0 inches (45,7 cm)				
	'		ADDITIONAL	FEATURES							
Easily removable knock-outs simplify pipe placement and reduce installation time Four equally spaced knock-outs accommodate up to 2.0" diameter pipe	Easily removable knock- outs simplify pipe placement and reduce installation time Four equally spaced knock-outs accommodate up to 2.0" diameter pipe	Two large center knock- outs accommodate up to 3 1/2" (8.9 cm) diameter pipe and eleven knock- outs accommodate up to 2" (5.0 cm) diameter pipe	Extension models support deeper and more flexible installations	Easily removable knock- outs simplify pipe placement and reduce installation time Two large center knock- outs accommodate up to 3.5" diameter pipe. (Extensions do not have knock-outs)	Extension models support deeper and more flexible installations	Easily removable knock-outs simplify pipe placement and reduce installation time Thirteen large knock-outs accommodate up to 3.5" diameter pipe	Easily removable knock-outs simplify pipe placement and reduce installation time. Six large knock- outs on the ends accommodate up to 5.0" diameter pipe and 12 knock-outs on the sides accommodate up to 3.0" diameter pipe				
			MODE	LS							
VB7RND: 7" Round Body & Green Lid	VB10RND: 10" Round Body & Green Lid VB10RNDB: 10" Round Body Only VB10RNDGL: Green Lid VB10RNDPL: Purple Lid VB10RNDPL: Black Lid VB10RNDH: 10" Round Body & Locking Green Lid	VBSTD: Standard Body & Green Lid VBSTDB: Standard Body Only VBSTDGL: Green Lid VBSTDPL: Purple Lid VBSTDBKL: Black Lid VBSTDH: Standard Body & Locking Green Lid	VBSTD6EXTB: Standard Extension Body Only	VBJMB: Jumbo Body & Green Lid VBJMBB: Jumbo Body Only VBJMBGL: Green Lid VBJMBPL: Purple Lid VBJMBBKL: Black Lid VBJMBH: Jumbo Body & Locking Green Lid	VBJMB6EXTB: Jumbo Extension Body Only	VBSPRH: Super Jumbo Body & 2 Lock Green Lid VBSPRPH: Super Jumbo Body & 2 Lock Purple Lid	VBMAXH: Maxi-Jumbo Body & 2 Lock Green Lid VBMAXPH: Maxi- Jumbo Body & 2 Lock Purple Lid				

LOCKING SYSTEMS

- VB-LOCK-H: Hex head $\, \mbox{\ensuremath{\$''}} \, x \, 2 \mbox{\ensuremath{\$''}} \, (1.0 \, x \, 5.7 \, cm)$ bolt, washer, and clip
- + VB-LOCK-P: Penta head $^3\!\!/\!\!\!/ x$ 2 $^1\!\!/\!\!\!/ ^{"}$ (1.0 x 5.7 cm) bolt, washer, and clip





Controllers



Water Saving Tips

- A Seasonal Adjust feature is available on all Rain Bird AC-powered controllers, allowing users to easily adjust irrigation schedules to changing seasonal landscape water requirements. The ESP-LX Series Controllers also feature an automated Monthly Seasonal Adjust feature to help save water through automatic adjustments every month of the year. LNK WiFi Module compatible controllers can be adjusted daily with the Automatic Seasonal Adjustment feature in the Rain Bird App.
- Water savings can also be optimized through daily irrigation schedule adjustments which fine-tune watering based on current weather. All ESP-LX series controllers can easily be upgraded to include smart weather-based/ET or soil moisture irrigation control capability by adding a local rain sensor or soil moisture sensor.
- All Rain Bird controllers simplify conservation through a variety of flexible programming features.
 With the touch of a button, the ESP-ME3 and ESP-TM2 can recall a previously saved "Contractor Default" irrigation program; the ESP-LX Series "Delayed Recall" feature automatically reverts to typical watering programs after a user-set time period.



Major Products	Wi-Fi	Wi-Fi				0.5
Major Froducts	READY	READY				Bluetooth
Primary Applications	ESP-TM2	ESP-ME3 ESP-Me	ESP-LXME ESP-LXMEF	ESP-LXD	ESP-9V	TBOS BT
esidential	•	•			•	•
ight Commercial	•	•	•	•	•	•
ommercial/Industrial			•	•		•
ype of Controller						
łybrid	•	•	•	•		
olid State					•	•
attery Operated					•	•
ndoor Location	•	•	•	•		
Outdoor Location	•	•	•	•		
eatures						
tations (up to)	12	22	48	200	6	6
rograms (up to)	3	4	4	4	6	3
tation Timing (up to)	6 hr1	6 hr¹	12 hr1	12 hr1	12 hr	12 hr
lumber of Starts per Program (up to)	4	6	8	8	6	8
urge protection	•	•	•	•	-	-
30VAC Option	•	•	•	•		
laster Valve/Pump Start	•	•	2	2	Multi-station models	
·			_4	_4	only	
Vater Budgeting	•	•	•4		•	
ndividual Program/Zone Shut-Off	•	•	•	•		
ain Delay	•	•	•	•		
attery Programmable		•	•	•	•	•
ensor Terminals, Status Indicator and Override	•	•	•	•	•	
Pelay Between Stations (up to)	9 hrs	9 hrs	0 - 10 min.	0 - 10 min.		
low Sensing		ESP-ME3 only	6 5	•		
imultaneous Multi-Station Operation			•	•		•
ycle + Soak™		6	•	•		
verlapping Programs			•	•	•	
lanual On/Off	•	•	•	•	•	•
emote Control Compatible	•	•	•	•		
Piagnostic Test			•	•		
Piagnostic Valve Circuit Breaker	•	•	•	•		
Out-of-Valve Box Programming						•
ubmersible (up to)					3.3 ft (1 m)	3.3 ft (1 m)
andal/Tamper Resistant						•
elf-Cleaning Solenoid						•
ow Battery Indicator					•	•
ave / Restore Programs	•	•	•	•	•	•
Master Valve ON/OFF by Station	•	•	•	•		•
otal Run Time Calculator by Program		•	•	•		•
ypass Rain Sensor by Station	•	•	•	•		
rogramming Schedule						
Day-of-Week	•	•	•	•	•	•
-7 Variable Cycle	•	•	•	•	•	•
-31 Variable Cycle	•	•	•	•	•	•
Odd/Even Cycle	•	•	•	•	•	•
·	•	•	•	•		•
odd 31st 65-Day Calendar	•	•	•	•	•	
	•	•	•	•	•	
vent Day Off			•	•		
entral Control Compatibility						
[™] Upgradeable			•	•		
abinet						
astic-Indoor	•	•				
astic-Outdoor	•	•	•	•	•	•
owder-Coated Metal Outdoor			•	•		
tainless Steel Pedestal			•	•		
owder-Coated Metal Pedestal			•	•		
ardware/Accessories						
wo-Wire Decoders and Accessories				•		
ain Sensing (need Rain Sensor)	•	•	•	•	•	•
ow Sensing (need Flow Sensor)		ESP-ME3 only	ESP-LXMEF only	•		
MRT-Y Soil Moisture Sensor	•	•				

LNK WiFi Module

Irrigation System Control from Anywhere

Features

- Upgrades WiFi-ready controllers (ESP-ME3, ESP-Me and ESP-TM2) to make them fully accessible and programmable from iOS or Android compatible devices*
- Operates like a wireless remote control for your irrigation system while onsite or an internet-based monitoring and control system when offsite
- Streamlines and simplifies initial irrigation timer setup and seasonal adjustment
- Instant access allows for real-time system management and timer settings
- Compatible professional app features allow for simple multi-site management and remote diagnostics by landscape professionals
- Built-in mobile notifications provide troubleshooting access, simplify service calls, and warn of freezing conditions when expected
- Automatic weather adjustments provide daily run time changes, saving up to 50% in water
- Superior programming capabilities that are designed to meet the most stringent water restrictions

Specifications

- 2.4 GHz (only) WiFi router compatible with WEP and WPA security settings
- Compatible with iOS 8.0 and Android 4.4 (KitKat) or later mobile devices*
- Operating Temperature: 14° F (-10° C) to 149°F (65°C)
- Storage Temperature: -40°F (-40°C) to 150°F (66°C)
- Operating Humidity: 95% max @ 50°F to 120°F (10°C to 49°C) noncondensing environment

Electrical Specifications

• Input: 24VAC(RMS) 50/60Hz; 55mA max

Certifications

cULus, FCC Part 15c, ISED RSS-247, IFETEL, CE.
 For current certifications visit: www.rainbird.com/lnkwifi

Dimensions

Width: 1.13"(2.87 cm)Height: 1.83" (4.65 cm)Depth: 0.48"(1.22 cm)

Model

LNKWIFI





















ESP-TM2 Series Controller

Simple, Flexible, and Reliable for Residential Applications

Features

- Upgradeable for WiFi-based remote monitoring and control via iOS and Android mobile devices (with LNK WiFi Module sold separately).
- Internet-based weather information can be used to make daily adjustments to the irrigation schedule, saving up to 30% in water (with LNK WiFi Module sold separately).
- 4, 6, 8, and 12 station models to meet small or large residential irrigation needs
- Set Permanent Days Off per program to ensure watering never occurs on days when maintenance crews are on site (for Odd/Even/ Cyclic schedules)
- · Easy to install indoors or outdoors with pre-installed power cord
- · Quick programming in just 3 steps for ease of setup
- 3 available programs with up to 4 start times for each program to meet the needs of varied landscapes
- · One-touch manual watering capability for ease of use
- Large back-lit LCD display for improved visibility in low-light and direct sun conditions
- Contractor Default™ allows you to easily save and restore your custom schedule
- Delay Watering up to 14 days and automatically resume watering after the set delay has elapsed
- Bypass Rain Sensor for any station gives you the ability to customize which stations react to a rain sensor
- Seasonal Adjust by program allows you to easily reduce or increase watering by program

Specifications

- Operating Temperature: Up to 149°F (65°C)
- Storage Temperature: -40°F (-40°C) to 150°F (66°C)
- Operating Humidity: 95% max @ 50°F to 120°F (10°C to 49°C) noncondensing environment

Electrical Specifications

- Input required: 120VAC (±10%) @ 60Hz
- Output: 1A at 24VAC
- · Master Valve/Pump Start Relay
- External battery back-up not required. Nonvolatile memory permanently saves the current programming and a 10 year life lithium battery maintains the controllers time and date during power outages



cULus, FCC Part 15b, CAN ICES-3(B)/NMB-3(B), NOM-001-SCFI-1993, CE.
 For current certifications visit: www.rainbird.com/esptm2

Dimensions

- Width: 7.92 in. (20.1 cm)
- Height: 7.86 in. (20.0 cm)
- Depth: 3.51 in. (9.0 cm)

Models

- TM2-4-120V: 4-station 120VAC
- TM2-6-120V: 6-station 120VAC
- TM2-8-120V: 8-station 120VAC
- TM2-12-120V: 12-station 120VAC

Accessories

- LNKWIFI: LNK WiFi Module for remote control and notification via iOS or Android device
- WR2 Series Wireless Rain + Freeze Sensors
- RSD Series Rain Sensors





ESP-TM2



Look for the WaterSense labeled LNK WiFi Module and a Rain Bird Rain Sensor to improve the water efficiency capabilities of this controller

ESP-ME3 and ESP-Me Series Controllers

The industry's most flexible irrigation controller solution. Supports up to 22 stations

Features

- Upgradeable for WiFi-based remote monitoring and control via iOS and Android mobile devices (with LNK WiFi Module sold separately).
- Internet-based weather information can be used to make daily adjustments to the irrigation schedule, saving up to 30% in water (with LNK WiFi Module sold separately).
- · Large LCD display with easy to navigate user interface
- Master valve/pump start circuit
- Non-Volatile (100 year) storage memory
- Remotely Programmable under 9V battery power (not included)
- Program based scheduling allows 4 individual programs with 6 independent start times per program for 24 total start times
- Watering schedule options: By days of week, ODD calendar days, EVEN calendar days, or Cyclic (every 1 – 30 days) Advanced Features
- · Advanced diagnostics and short detection with LED alert
- Contractor Default™ Program Save/Restore saved program(s)
- · Rain Sensor bypass by Station
- Total Run Time Calculator by program
- Delay Watering up to 14 days (applies only to stations not set to ignore Rain Sensor)
- · Manual Watering option by program or station
- · Seasonal Adjust applied to all programs or individual program
- Adjustable delay between valves (default set to 0)
- · Master Valve on/off by station

ESP-ME3 Specific Features

- · Built-in flow-sensing capabilities
- Easy to install indoors or outdoors with pre-installed power cord
- Back-lit LCD display for improved visibility in low-light and direct sun conditions

Operating Specifications

- Station timing: 1 minute to 6 hours
- Seasonal Adjust: 5% to 200%
- Max operating temperature: 149°F (65°C)

Electrical Specifications

- Input Required: 120VAC ± 10%, 60Hz (International models: 230/240VAC ± 10%, 50/60Hz)
- · Master Valve/Pump Start Relay
- Operating Voltage: 24VAC 50/60Hz
- Max Coil Inrush: 11VA
- · Max Coil Holding: 5VA
 - Idle/Off power draw 0.06 amps at 120VAC
- Power back-up not required. Nonvolatile memory permanently saves the current programming and a 10 year life lithium battery maintains the controllers time and date during power outages.

Certifications

 cULus, FCC Part 15b, CAN ICES-3(B)/NMB-3(B), CE. For current certifications visit: www.rainbird.com/espme, www.rainbird.com/me3



Look for the WaterSense labeled LNK WiFi Module and a Rain Bird Rain Sensor to improve the water efficiency capabilities of this controller

Dimensions

- Width: 10.7" (27.2 cm)
- Height: 7.7" (19.5 cm)
- Depth: 4.4" (11.2 cm)

North America Models (120VAC)

- · Controller Base Models
 - ESP4MEI: 4 station indoor model
 - ESP4ME3: 4 station indoor / outdoor model
- Modules
 - ESPSM3: 3 station module
 - ESPSM6: 6 station module (compatible with ESP-ME3 and ESP-ME series controllers only)

Accessories

- LNKWIFI: LNK WiFi Module for remote control and notification via iOS or Android device
- WR2: Wireless Rain + Freeze Sensors
- RSD Series Rain Sensors
- MJ100B Flow Sensor and other wired flow sensors*

* ESP-ME3 only





ESP-9V Series

Battery-Operated Controller

Features

Controller Features

- Waterproof case ensures long life, even when installed in a valve box
- Common programming features are easily accessed on one screen, making programming quick and easy
- Operates for approximately one full year using one 9-volt alkaline battery, or two years with two 9-volt alkaline batteries
- Large LCD display with easy to navigate user interface
- · Sensor input with bypass override
- Mast valve/pump-start circuit (multi-zone units only)
- · Non-volatile (100-year) program memory
- IP68 certified for protection against dust and water intrusion
- Plastic controller case has outstanding resistance to weather, yellowing and aging

Scheduling Features

- · Dedicated manual watering button for easy operation
- Automatic zone-stacking ensures that only one valve irrigates at the same time. ESP-9V will automatically irrigate the lower number zone first if zones are scheduled to water at the same time
- Contractor Rapid Programming™ automatically copies the start times and watering days from zone 1 to all remaining zones at initial setup
- Run times, start times, and watering days are customizable by zone
- 6 start times per zone
- 4 watering day options per zone: Custom days of the week, Cyclic, and ODD or EVEN calendar days
- Delay watering (1 to 9 days)

Valve Compatibility

- Rain Bird K80920
- Hunter 458200
- · Irritrol DCL
- · Toro DCLS-P

Controller Dimensions

• Width: 5.35" (13.59 cm)

· Height: 4.04" (10.26 cm)

• Depth: 2.42" (6.15 cm)

• Weight: 2 lbs (907 g)

LCD Screen Size

• Width: 2.25" (5.72 cm)

• Height: 1.25" (3.18 cm)



With optional Wall Mount

Optional Wall Mount Dimensions

Width: 4.25"(10.76 cm)
Height: 6.930"(17.60 cm)
Depth: 1.965" (4.99 cm)
Weight: 3.6 oz (107 g)

Certifications

• cULus. For current certifications visit: www.rainbird.com/esp9v

Models

- ESP9V1: 1-Zone ESP-9V Controller
- ESP9V2: 2-Zone ESP-9V Controller
- ESP9V4: 4-Zone ESP-9V Controller
- ESP9V6: 6-Zone ESP-9V Controller
- ESP9V1SOL: 1-Zone + 9V Solenoid
- 9VMOUNT: Wall-mount kit



ESP-9V Series Battery-Operated Controller



ntrollers

TBOS-BT



Bluetooth Battery-Operated Controller. Install anywhere. Program from a Smartphone.

Features

Rain Bird App Features (TBOS-BT)

- · Create, review and transmit irrigation programs
- · Capability to set zones or programs to manually irrigate
- Basic programming includes 3 independent programs A,B and C, each with 8 start times per day
- Stations can be assigned to several programs with different watering run times
- Run time is from 1 minute to 12 hours in 1-minute increments
- Five watering day cycle modes (Custom, even, odd, odd-31, cyclical) selectable by program for maximum flexibility and watering
- Program and global Monthly Seasonal Adjust; 0% to 300% (1% increments)
- Built-in ID with naming capability. The control module and stations can be individually named.
- · Optional passcode
- Delay watering from 1 to 14 days
- Permanently turn the controller off to prevent irrigation
- Battery indicator reports the status of the control module's battery
- Capability to clear the control module's irrigation program

Controller Features

- Operates for approximately one full year using one 9-volt alkaline battery
- Completely potted to obtain IP68 conformity
- Independent station operation allows sequential start times (with stacking in case of overlap) restriction compliance
- Master valve output (on TBOS-II 2, 4, and 6 Control Modules)
- · No loss of irrigation program after a battery replacement
- · Backwardly compatible with the TBOS-II Field Transmitter

Valve Compatibility

- Rain Bird TBOS Potted Latching Solenoid (K80920)
 - DV, DVF, ASVF, PGA, PEB, PESB, GB, EFB-CP, BPE and BPES series
- · Hunter 458200
- · Irritrol DCL
- Toro DCLS-P

Certifications

cULus, FCC Part 15b, ISED RSS-247 Issue 2.0, CE, IP68.
 For current certifications visit: www.rainbird.com/tbosbt

TBOS-BT System Components

Rain Bird App (TBOS-BT)

· Available for Android and IOS devices

Models

- · TBOS-BT1 (1 Station)
- TBOS-BT2 (2 Station)
- · TBOS-BT4 (4 Station)
- · TBOS-BT6 (6 Station)

Accessories

- · TBOS Potted Latching Solenoid
- · RSD Series Rain Sensors
- The TBOS solenoid adapters will adapt the potted latching solenoid for use in retrofit applications with selected Irritrol® (Hardie/Richdel) and Buckner® valves or Champion® and Superior® valve actuators.

Bluetooth





Google Play





ESP-LXME/F Controllers

Modular - Easily expandable from 8 or 12 stations up to 48 stations with 8- and 12-station modules

Features

- Hot-swappable modules, no need to power down the controller to add/ remove modules
- 8- or 12-stations base unit expandable to 48 stations with 8- and 12-Station Modules
- Flow Smart Module[™] factory installed (ESP-LXMEF) or field upgradable (ESP-LXME)
- Dynamic station numbering eliminates station numbering gaps
- · Master valve/pump start circuit
- · Weather Sensor input with override switch
- · 6 user-selectable languages
- · Standard 10kV surge protection
- · Non-Volatile (100-year) program memory
- · Front panel is removable and programmable under battery power
- Compatible with Rain Bird Landscape Irrigation and Maintenance Remote
- Plastic, locking, UV resistant, wall-mount case, Optional Metal and Stainless Steel Case & Pedestal

Water Management Features

- Optional Flow Smart Module™ with Learn Flow utility and flow usage totalizer — standard on ESP-LXMEF
- FloWatch™ protection for high and low flow conditions with user defined reactions (requires flow sensor)
- FloManager™ manages hydraulic demand, making full use of available water to shorten total watering time
- SimulStations™ are programmable to allow up to 5 stations to operate at the same time
- Station sequencing by station numbers or station priorities
- · Water Windows by program plus Manual MV Water Window
- Cycle+Soak[™] by station
- · Rain Delay
- 365-Day Calendar Day Off
- Programmable Station Delay by program
- Normally Open or Closed Master Valve programmable by station
- Weather Sensor programmable by station to prevent or pause watering
- Program Seasonal Adjust
- · Global Monthly Seasonal Adjust

Operating Specifications

- Station run times: 0 min to 12 hrs
- Seasonal Adjust; 0% to 300% (16 hrs maximum station run time)
- 4 independent programs (ABCD)
- ABCD programs can overlap
- 8 start times per program

- Program Day Cycles include Custom days of the week, Odd, Odd31, Even, & Cyclical dates
- · Manual station, program, test program

Electrical Specifications

- Power Supply Voltage: 120 VAC \pm 10%, 60Hz (International models: 230 VAC \pm 10%, 50Hz; Australian models: 240 VAC \pm 10%,50Hz)
- Output: 26.5 VAC 1.9A
- Power back-up: Lithium coin-cell battery maintains time and date while nonvolatile memory maintains the programming
- Multi-valve capacity: Maximum five 24 VAC, 7VA solenoid valves simultaneous operation including the master valve, maximum two solenoid valves per station module

Certifications

 cULus, FCC Part 15b, CAN ICES-3(B)/NMB-3(B), CE, IPX4. For current certifications visit: www.rainbird.com/esplxme-esplxmef

Dimensions

- · Width: 14.32 in. (36.4 cm)
- Height:12.69 in. (32.2 cm)
- Depth: 5.50 in. (14.0 cm)

Models

- ESP8LXME: 8-Station Controller, 120VAC
- ESP12LXMEF: 12-Station Controller with Flow Smart Module, 120VAC
- IESP8LXME: 8-Station Controller for International Market, 230VAC
- FSMLXME: Flow Smart Module for ESPLXME/F Controller
- ESPLXMSM8: 8-Station Module for ESP-LXME/F Controller
- ESPLXMSM12: 12-Station Module for ESP-LXME/F Controller
- ESPLXMEFP: ESPLXME Controller Front Panel Only

Accessories

- Painted Metal and Stainless Steel Pedestal/Enclosure Options available (see page 91)
- IQ Communication Cartridge (see page 104)
- Rain Bird FS-Series Flow Sensors (see page 96)

For more information call the ESP-LX Hotline: 1-866-544-1406



ESP-LXME Controller

Works ...ith

ESP-LXD Decoder Controller

50 – 200 station capable Two-Wire Decoder Commercial Controller

Controller Features

- 50-station capability standard expandable to 200 stations with optional ESPLXD-SM75 modules
- Four available sensor inputs (one wired plus up to three decodermanaged) with override switch
- · Five flow sensors supported
- Supported decoders: FD-101TURF, FD-102TURF, FD-202TURF, FD-401TURF, FD-601TURF
- Supports SD-210TURF sensor decoders (flow sensing and weather sensor support) and LSP-1 line surge protectors (one per 500 feet of two-wire path required)
- Central Control capable with Rain Bird IQ Communications Cartridges and software (see pg. 104)
- Advanced Features From Cycle+Soak™ to Contractor Default Program™, the ESP-LXD offers innovative features proven to cut installation expenses, troubleshooting time and water use
- Program backup and barcode decoder address entry with the optional PBCLXD
- Six user-selectable languages
- · Removable front panel is programmable under battery power
- Plastic, locking, UV resistant, wall-mount case, Optional Metal and Stainless Steel Case & Pedestal
- Compatible with Rain Bird Landscape Irrigation and Maintenance Remote - Flow Smart Module™ factory installed or field upgradable
- Plastic, locking, UV resistant, wall-mount case, Optional Metal and Stainless Steel Case & Pedestal

Operating Specifications

- Station timing: 0 min to 12 hrs
- Program level and global Monthly Seasonal Adjust; 0% to 300% (16 hrs maximum station run time)
- 4 independent programs (ABCD); ABC programs stack, ABCD overlap
- 8 start times per program
- Program Day Cycles include Custom days of the week, Odd, Odd no 31st, Even, and Cyclical dates
- · Manual station, program, test program

Certifications

• cULus, CE, IPX4. For current certifications visit: www.rainbird.com/esplxd





ESP-LXD Decoder Controller



LXMMSSPED Shown with ESP-LXD in LXMMSS Stainless Steel Cabinet



ESP-LXD Decoder Controller (cont.)

Upgrade Options

- IQ-NCC Network Communication Cartridge
- ESP-LXD-SM75 75-station module
- PBCLXD Programming Backup Cartridge

Electrical Specifications

- Power Supply Voltage: 120 VAC \pm 10%, 60Hz (International models: 230 VAC \pm 10%, 50Hz; Australian Models: 240 VAC \pm 10%, 50Hz)
- Power back-up: Lithium coin-cell battery maintains time and date while nonvolatile memory maintains the schedule
- Multi-valve station capacity: up to 2 solenoid valves per station; simultaneous operation of up to eight solenoids and/or master valves

Dimensions (W x H x D)

• 14.32" x 12.69" x 5.50" (36.4 x 32.2 x 14.0 cm)

Model

- ESP-LXD: 50-station, 120 VAC
- IESPLXD: 50-station for international markets, 230 VAC
- IESPLXDEU: 50-station for Europe, 230 VAC
- IESPLXDAU; 50-station for Australia, 240 VAC

Accessories

- FD-TURF: two-wire decoders (see pg. 93)
- SD-210TURF: two-wire sensor decoder (see pg. 93)
- LSP1TURF: two-wire line surge protection (see pg. 93)
- DPU-210: two-wire decoder programming unit (see pg. 94)
- Painted Metal and Stainless Steel Pedestal/Enclosure Options available (see pg. 94)
- IQ-NCC: Network Communication Cartridge for ESP-LX Series Controllers (see page 104)
- See page 96 for information on Rain Bird FS-Series Flow Sensors 'FD-TURF decoders include peel-off barcode address labels
- ²Barcode scanning pen not included sold separately; Unitech MS100NRCB00-SG recommended (www.ute.com)

For more information call the ESP-LX Hotline: 1-866-544-1406



ESP-LXD interior with modules

Controllers

FD-TURF Two-Wire Decoders

SiteControl and ESP-LXD with Support for 1, 2, 4 or 6 Decoder Addresses

Features

- Five different decoder options let you choose the precise amount of landscape irrigation control you need. Select different two-wire decoders to operate one, two, four, or six valves.
- Installed out of sight and protected from the elements and vandalism
- Enables advanced diagnostic and sensor features

Specifications

• Mounting: In valve box (recommended) or direct burial

· Power Draw:

- FD-101TURF: 0.5 mA (idle) 18 mA (per active solenoid)
- FD-102TURF: 0.5 mA (idle) 18 mA (per active solenoid)
- FD-202TURF: 1 mA (idle) 18 mA (per active solenoid)
- FD-401TURF: 1 mA (idle) 18 mA (per active solenoid)
- FD-601TURF: 1 mA (idle) 18 mA (per active solenoid)

• Dimensions:

- FD-101TURF: Length: 2.77 in. (70 mm), Diameter: 1.5 in. (40 mm)
- FD-102TURF: Length: 3.35 in. (85 mm), Diameter: 1.77 in. (45 mm)
- FD-202TURF: Length: 3.35 in. (85 mm), Diameter: 1.97 in. (50 mm)
- FD-401TURF: Length: 3.94 in. (100 mm), Diameter: 2.56 in. (65 mm)
- FD-601TURF: Length: 3.94 in. (100 mm), Diameter: 2.56 in. (65 mm)

Solenoids:

- FD-101TURF: 1 with individual control
- FD-102TURF: 1 or 2 simultaneously
- FD-202TURF: 1 to 4 simultaneously
- FD-401TURF: 1 to 4 with individual control
- FD-601TURF: 1 to 6 with individual control

Wires:

- FD-101TURF: Blue to cable, white to solenoid
- FD-102TURF: Blue to cable, white to solenoid
- FD-202TURF: Blue to cable, white and brown to solenoids
- FD-401TURF: Blue to cable, color-coded to solenoids
- FD-601TURF: Blue to cable, color-coded to solenoids

Surge Protection: One of the following is required every 500 ft. along two-wire path (40 V, 1.5 kW transil)

- LSP-1 Line Surge Protector
- FD-401TURF with built in surge protection
- FD-601TURF with built in surge protection

Note: Minimum 10ohms resistance grounding required at controller and each surge protector

 Input Fuse (FD-401TURF and FD-601TURF only): 300-500 mA, thermal

• Electrical Input:

- Maximum voltage: 36 Vpp
- Maximum load:
- FD-101TURF: 1 Rain Bird solenoid (one per address)
- FD-102TURF: 2 Rain Bird solenoids (two per address)
- FD-202TURF: 4 Rain Bird Solenoids (two per address)
- FD-401TURF: 4 Rain Bird Solenoids (one per address)
- FD-601TURF: 6 Rain Bird solenoids (one per address)

· Decoder/Solenoid Wires:

- Electrical resistance: Max. 3 ohms

Maximum Distance Decoder/Solenoids:

- Cable length: 14 gauge, 456 feet
- Wiring: 2 x 14-gauge (1.5 mm2) solid copper, UF insulated type

• Environment:

- Working range: 32° to 122° F (0° to 50° C)
- Storage range: -4° to 158° F (-20 to 70° C)
- Humidity: 100%

Note: Rain Bird recommends using Rain Bird DB Series Wire Connectors (pg. 75) waterproof connectors for all connections.

Note: FD-Series Decoders are not compatible with residential valves like the Rain Bird HV, DV, DVF, ASVF, JTV, JTVF, and Drip Control Zone Kit with ASVF/DV valves

Models

- FD-101TURF: Field Decoder interfacing signal line and valve
- FD-102TURF: Field Decoder interfacing signal line and valve or one pair of valves
- FD-202TURF: Field Decoder interfacing signal line and 2 valves or 2 pair of valves
- FD-401TURF: Field Decoder interfacing signal line and up to 4 individual valves
- FD-601TURF: Field Decoder interfacing signal line and up to 6 individual valves
- LSP-1TURF: Line Surge Protection
- SD-210TURF: Sensor Decoder interfacing signal line and analog or digital decoders



Decoders



PBCLXD Programming Backup Cartridge for ESP-LXD

Provides program backup and restore and barcode scanning capability for the ESP-LXD controller (not compatible with ESP-LXME or ESP-LX Basic)

Upgrade Kit Features

- Provides 8 full backups, including all programs, flow information and decoder addresses – allows you to easily archive 8 different controllers – restoring all information typically takes two minutes or less
- Snaps into the back of the ESP-LXD front panel; installs without tools; no additional enclosures or external wiring required
- Kit includes cable for interface to barcode scanning pen (pen not included) – allows you to quickly scan decoder addresses into the ESP-LXD controller during installation to save you time

Model

· PBCLXD (works with all versions of the ESP-LXD controller)



PBCLXD Cartridge

Controller Pedestals

Pedestals for ESP-LX Series, ESP-MC, ESP-SAT, ESP-SITE, and CCU

Features

· Includes all necessary mounting bolts, nuts, and washers

Specifications

- · Material: Powder-coated steel and stainless steel
- · Field wiring connection: In controller

Dimensions

Model	Height	Width	Depth
• LXMM	12%" (32.7 cm)	14½" (36.8 cm)	7¾" (19.7 cm)
 LXMMPED 	28" (71.1 cm)	141/4" (36.2 cm)	7 ¼" (18.4 cm)
 LXMMSS 	12%" (32.7 cm)	14½" (36.8 cm)	7¾" (19.7 cm)
 LXMMSSPED 	28" (71.1 cm)	14¼" (36.2 cm)	7¼" (18.4 cm)

Model

- LXMM: Metal Cabinet for ESP-LX Series Controllers*
- LXMMPED: Metal Pedestal for ESP-LX Series Controllers*
- LXMMSS: Stainless Steel Metal Wall Mount Enclosure for ESP-LX Series Controllers
- LXMMSSPED: Stainless Steel Metal Pedestal for ESP-LX Series Controllers
- * Note: Metal cabinets and pedestals are not standard on ESP-LX Series controllers and must be purchased separately. LXMMPED requires LXMM, and LXMMSSPED requires LXMSS.



LXMMSSPED Shown with ESP-LXD in LXMMSS Stainless Steel Cabinet

DPU-210 Decoder Programming Unit

For ESP-LXD, MDC/MDC2 and SiteControl FD-Turf Two-Wire Decoders

 Decoder Programming Unit tests and verifies operation of the ESP-LXD, MDC/MDC2, or SiteControl FD Series Field Decoders. Also allows for re-programming decoder addresses for maximum site set-up flexibility



Internet Connected Water Meters (ICWM)

Advanced Single-Jet and Turbine Technology Water Meters

Features

- 5 year data plan works anywhere the Verizon 4G wireless network reaches avoiding costs of network integration
- Digital register with web interface for water usage data collection and analysis including monthly water budgeting and over-usage alerts
- Extreme low flow accuracy starting 0.1 gpm to easily identify leaks
- · Wide operating temperature range
- Lead free NSF61 compliant
- Low flow, backflow and high usage reports and alerts
- 5 year data service plan + 5 year warranty included
- Compact design for tight installations with no upstream or downstream straight pipe requirements
- Single moving element and no strainer requirement for low maintenance
- Brass, bronze, cast iron, or composite plastic body for durable, longlasting performance
- Unaffected by sand or small debris in line
- · High resistance to freezing

Certifications

- FM Approved (ICWM600S)
- NSF Standard 61 Compliant
- · AWWA C712 Standard





Operating	g Speci	fications											
Model	Size (in)	Description	Lay Length	Approx. weight w/ register (lbs.)	Initial Wireless Term	Body Material	End Connection	Max Op Press (PSI)	Min Test Flow (GPM)	Nor Op Ra Min (GPM)		Max Cont. Duty (GPM)	Head Loss @ SMOC (PSI)
ICWM075S	5/8" X 3/4"	5/8" Single-Jet Cellular IC Flow Meter	7.5"	1	5 years	Plastic	1" NPSM	230	0.0625	0.125	30	24	13
ICWM100S	1"	1" Single-Jet Cellular IC Flow Meter	10.75"	5.6	5 years	Low lead Bronze	1.25" NPSM	230	0.125	0.5	70	35	8
ICWM150S	1.5"	1.5" Single-Jet Cellular IC Flow Meter	7.87"	10	5 years	Low lead Brass	Oval Flange	230	0.250	0.500	105	88	7.25
ICWM200S	2"	2: Single-Jet Cellular IC Flow Meter	9.78"	12	5 years	Low lead Brass	Oval Flange	230	0.250	0.75	165	130	7.25
ICWM300S	3"	3" Single-Jet Cellular IC Flow Meter	11.8"	32	5 years	Low lead Brass	3" Flange	230	0.50	0.75	350	175	7.25
ICWM300SH	3"	3" High Flow Single-Jet Cellular IC Flow Meter	13.75"	48	5 years	Lead free Bronze	3" Flange	230	0.75	1.5	500	350	7.25
ICWM400S	4"	4" Single-Jet Cellular IC Flow Meter	13.75"	48	5 years	Lead free Bronze	4" Flange	230	0.75	1.5	500	350	7.25
ICWM400SH	4"	4" High Flow Single-Jet Cellular IC Flow Meter	17.75"	89	5 years	Lead free Bronze	4" Flange	230	1.00	2.00	1000	600	9.5
ICWM600S	6"	6" Single-Jet Cellular IC Flow Meter	17.75"	89	5 years	Lead free Bronze	6" Flange	230	1.00	2.00	1000	600	9.5
ICWM200T	2"	2" Turbine Cellular IC Flow Meter	7.87"	12	5 years		2" Flange	232	1.50	2.00	396	176	NA
ICWM300T	3"	3" Turbine Cellular IC Flow Meter	8.9"	32	5 years	Epoxy coated	3" Flange	232	2.00	3.00	880	440	NA
ICWM400T	4"	4" Turbine Cellular IC Flow Meter	9.8"	48	5 years	cast Iron	4" Flange	232	2.00	4.00	1320	700	NA
ICWM600T	6"	6" Turbine Cellular IC Flow Meter	11.8"	91	5 years		6" Flange	232	8.00	16.00	1540	1000	NA

Note: Spool connections are available to adjust lay length.





Flow Sensors



Flow Sensor Transmitters and Accessories

Flow Sensors and Transmitters

Maxicom,^{2®} SiteControl, IQ, ESP-LX or ESP-ME3 Series Controllers, or IQ[™]

Features (Sensors)

- Simple six-bladed impeller design
- Designed for outdoor or underground applications
- Available in PVC, brass or stainless steel construction
- Pre-installed in tee or saddle mounted insert versions

Operating Specifications (Sensors)

- Accuracy: +- 1% (full scale)
- Velocity: 1/2-30 feet (0.15 9.2 meters) per second depending on model
- Pressure: 400 psi (27.5 bars) (max) on metal models; 100 psi (6.9 bars) (max) on plastic models
- Temperature: 220° F (105° C) (max) on metal models; 140° F (60° C) (max) on plastic models

Features (Transmitters)

- Programmable from a computer (PT322 Maxicom and SiteControl Systems only – not required for ESP-LXMEF or ESP-LXD)
- Reliable solid-state design, available with or without LCD display
- Operates with MAXILink,™ and (hard-wire) two-wire satellite systems
- Easy-to-program, menu-driven design
- Mounted in optional NEMA enclosure (PT3002 only)

Operating Specifications (Transmitters)

- · Input required:
 - 12-30 VDC/VAC on PT322
 - 12-24 VAC/VDC on PT 3002
- · Output: Pulse output
- Operating Temp: -4° F-158° F (-20° C to 70° C)
- Units: Domestic and International units available on PT3002

Dimensions

- PT322: 3.65" x 1.75" x 1.0" (93mm x 44m x 25mm)
- PT3002: 3.78" x 3.78" x 2.21" (96mm x 96mm x 56mm)
- FS100P: 3.50" x 3.94" x 1.315" (89mm x 100mm x 33mm)
- FS150P: 5.0" x 5.16" x 2.38" (127mm x 131mm x 60mm)
- FS200P: 5.63" x 5.64" x 2.88" (143mm x 143mm x 73mm)
- FS300P: 6.50" x 6.83" x 4.23" (165mm x 173mm x 107mm)
- FS400P: 7.38" x 7.83" x 5.38" (187mm x 199mm x 137mm)
- FS100B: 5.45" x 4.94" x 2.21" (138mm x 126mm x 56mm)
- FS150B: 6.5" x 5.19" x 2.5" (165mm x 132mm x 64mm)
- FS200B: 4.25" x 8.35" x 2.94" (108mm x 212mm x 75mm)
- FS350B: 7.13" x 3"(diameter) (181mm x 76mm (diameter))
- FS350SS: 7.13" x 3"(diameter) (181mm x 76mm (diameter))

ntrollers

Configuration

- For ESP-LXD Decoder Systems, the Flow Sensor is installed with a Two-Wire Decoder Sensor Decoder (SD210TURF)
- For ESP-LXMEF Systems, the Flow Sensor is attached to the FSM-LXME Flow Smart Module
- For ESP-ME3 Controllers, the Flow Sensor is attached to flow sensor terminals in the controller
- For (Hard Wire) Two-Wire Satellite Systems (Maxicom²
 and SiteControl), the Flow Sensor is installed with a Pulse Transmitter and a Rain Bird Pulse Decoder (DECPULLR)
- For Link Radio Satellite Systems (Maxicom² and SiteControl), the Flow Sensor is installed with a Pulse Transmitter (no pulse decoder required)
- For ESP-SITE Satellite Systems (Maxicom²), the Flow Sensor is installed with a Pulse Transmitter (no decoder required)
- For SiteControl Decoder Systems, the Flow Sensor is installed with a Two-Wire Decoder Sensor Decoder (SD210TURF)
- Surge protection (FSSURGEKIT) is recommended for Maxicom &
 SiteControl systems One at the Pulse Transmitter, and if more than 50'
 of wire run, one at the Flow Sensor. FSSURGEKIT is not compatible with
 ESP-LXMEF and ESP-LXD Controllers

Models

- Brass Flow Sensor
- MJ100B: 1" Brass Flow Sensor for the ESP-ME3
- Brass TEE's
- FS200B: 2" (50mm) Brass Tee Flow Sensor
- FS150B: 1 1/2" (40mm) Brass Tee Flow Sensor
- FS100B: 1" (25mm) Brass Tee Flow Sensor
- Plastic TEE's
- FS400P: 4" (110mm) PVC Tee Flow Sensor
- FS300P: 3" (75mm) PVC Tee Flow Sensor
- FS200P: 2" (50mm) PVC Tee Flow Sensor
- FS150P: 1 1/2" (40mm) PVC Tee Flow Sensor
- FS100P: 1" (25mm) PVC Tee Flow Sensor
- Inserts
- FS350SS: 3" and higher, Stainless Steel Insert
- FS350B: 3" and higher, Brass Insert
- FSTINSERT: Replacement insert for Tee type sensors
- Pulse Transmitters (not necessary with ESP-LX Controllers)
- PT322: Pulse Transmitter, no display
- PT3002: Pulse Transmitter, LCD display
- Accessories
- PTPWRSUPP: Pulse Transmitter power supply
- NEMACAB: NEMA Enclosure for PT3002
- FSSURGEKIT: Flow Sensor surge protection kit
- DECPULLR: Pulse Decoder for two-wire satellites
- SD210TURF: Sensor Decoder for decoder systems
- FSMLXME: Flow Smart Module for ESP-LXME Series Controllers

Rain Bird Flow Sensor Suggested Operating Range

The following tables indicate the suggested flow range for Rain Bird Flow Sensors. Rain Bird Sensors will operate both above and below the indicated flow rates. However, good design practice dictates the use of this range for best performance. Sensors should be sized for flow rather than pipe size.

Model	Suggested Operating Range (Gallons / Minute)	Suggested Operating Range (Liters / Minute)	Suggested Operating Range (Cubic Meters / Hour)					
FS100P	5.4 - 54	20 - 200	1.2 - 12					
FS150P	5 - 100	19 - 380	1.1 - 23					
FS200P	10 - 200	40 - 750	2.3 - 45					
FS300P	20 - 300	75 - 1130	4.5 - 70					
FS400P	40 - 500	150 - 1900	9 - 110					
FS100B	2 - 40	7.6 - 150	0.5 - 9					
FS150B	4 - 80	15 - 300	1 - 18					
FS200B	10 - 100	38 - 380	2.3 - 23					
FS350B		Depends on Pipe Type and Size - please						
FS350SS	refe	erence Flow Sensors te	ch spec					





RSD-BEX

Wired Rain Sensor

Features and Benefits

- Automatic rain shutoff prevents overwatering due to natural precipitation
- · Robust, reliable design reduces service call backs
- · Moisture sensing disks work in a variety of climates
- · Different sensor mounts permit speed and flexibility on the job site
- · Latching hinge maintains alignment

Mechanical Properties

- Multiple rainfall settings from $\frac{1}{3}$ " (5 20 mm) are quick and easy with just the twist of a dial
- · Adjustable vent ring helps control drying time
- · High-grade, UV resistant polymer body resists the elements
- Comes with 5" latching aluminum bracket
- Not compatible with ESP-SMT or ESP-SMTe controllers

Electrical Specifications

- Application: Suitable for low voltage 24 VAC control circuits and 24 VAC pump start relay circuits*
- Switch electrical rating: 3A @ 125/250 VAC
- Capacity: Electrical rating suitable for use with up to ten 24 VAC,
 7 VA solenoid valves per station, plus one master valve
- Wire: 25' (7.6 m) length of #20, 2 conductor UV resistant extension wire
- * Not recommended for use with high voltage pump start, pump start relay circuits or devices.

Certifications


• cULus, CE, RCM. For current certifications visit: www.rainbird.com/rsd

Dimensions

- Overall length: 6.5" (16.5 cm)
- Overall height: 5.4" (13.7 cm)
- Bracket hole pattern: 1.25" (3.2 cm)

Model

• RSD-BEx: Rain sensor w/ latching bracket, extension wire



ntrollers

WR2 Series Wireless Rain + Freeze Sensors

Superior responsiveness to rainfall and cold temperatures, save up to 35% on water usage

Features & Benefits

- Enhanced antenna array provides superior signal reliability that overcomes most line-of-sight obstructions
- Sensor signal strength indicator enables one person set up, reducing installation time
- Convenient adjustment and monitoring of rain or freeze settings at the controller interface
- Simple battery replacement without the need to disassemble the sensor
- · Highly intuitive icon-driven controller interface simplifies programming
- Easy to install, self-leveling sensor bracket mounts to flat surfaces or rain gutters
- Antennas concealed within the units for greater visual appeal and product robustness
- "Quick Shut Off" interrupts active irrigation cycle during a rain event

Electrical Specifications

- Application: suitable for use with 24 VAC controllers (with or without pump start / master valve)
- Electrical rating suitable for use with up to six 24VAC 7VA solenoids plus an additional master valve or pump start that does not exceed 53VA
- Controller Interface Wire: 30" (76 cm) length of #22 gauge (0.64 mm) UV resistant extension wire
- FCC approved spread spectrum 2 way radio transceivers with FCC Class B approvals
- Signal transmission distance of 700' (213.4 m) Line of Sight
- Battery life: four or more years under normal operating conditions
- 6 KV surge / lighting protection

Certifications

cULus, FCC Part 15c, ISED RSS-210, CE.
 For current certifications visit: www.rainbird.com/wr2

Mechanical Properties

- Adjustable rainfall settings from 1/8" 1/2" (3 13 mm)
- Adjustable low temperature settings from 33°F 41°F (0.5° 5°C)
- Three irrigation modes to select: Programmed, Suspend Irrigation for 72 hours, Override sensor for 72 hours

Note: The WR2-48 model replaces the Suspend Irrigation for 72 Hours mode with 48-Hour Irrigation Hold Active mode.

- "Quick Shut Off" suspends active irrigation cycle within approximately
- High-grade, UV resistant polymer units resist harmful environmental effects

Models

- North America (916 MHz)
 - WR2-RFC: Rain + Freeze Combo
 - WR2-48: Rain + Freeze Combo with 48-hour hold
- International (868 MHz)
 - WR2-RFC-868: Rain + Freeze Combo



WR2 Series Wireless Rain/Freeze Sensors

Step 1



Program in seconds

Step 2



Determine best sensor location

Step 3



Install sensor easily using mounting bracket



SMRT-Y Soil Moisture Sensor Kit

Accurate • Reliable • Smart

Features and Benefits

- · Turns any controller into a water saving smart controller
- Healthier landscapes less prone to nutrient depletion, fungus and shallow root growth
- Typical water savings exceed 40%
- TDT digital sensor enables highly accurate readings that are independent of soil temperature and electrical conductivity (EC)
- · · Displays soil moisture content, soil temperature and EC
- Corrosion-resistant in-ground sensor made of high-grade 304 stainless steel

Operating Specifications

- · 25 Volts AC at 12W
- Operating temperature: -4°F to 158°F (-20°C to 70°C)
- Survival temperature: -40°F to 185°F (-40°C to 85°C)

Certifications

cULus, FCC Part 15b, CE.
 For current certifications visit: www.rainbird.com/smrty

Dimensions

Controller Interface

- W: 3.0" (76mm); H: 3.0" (76mm); D: 0.75" (19mm)

In-Ground Soil Moisture Sensor (without wires)

- W: 2.0" (50mm); L: 8.0" (200mm); D: 0.5" (12mm)
- 18 AWG wire leads @ 42 in. (106.7 cm) length

SMRT-Y Kit


Includes


- Controller Interface
- In-Ground Soil Moisture Sensor
- Anodized, rust-proof screws, 1.5"(two per package)
- Wire nuts 5 blue, 2 gray, 1 yellow
- Multilingual instruction manual, "Quick Start" Guide and Soil Moisture sticker


Models

• SMRT-Y: Soil Moisture Sensor Kit

Note: All SMRT-Y models are RoHS compliant









Central Controls



Water Saving Tips

- Maxicom², SiteControl, and IQ™ Systems provide fully-automated ET (evapotranspiration) adjustment of irrigation programs for maximum water savings.
- Maxicom² and IQ™ FloWatch™ utility monitors and records real-time flow and automatically diagnoses and eliminates flow problems caused by broken pipes, vandalism or stuck valves.
- The New Rain Bird® IQ™ Platform. The ultimate tool for remote water management. With no hidden fees, It's the perfect remote water management solution. With the new IQ-Cloud v. 3.0, you can control your irrigation system from any device, anywhere. With set up that takes less than five minutes, multi-user access and no recurring annual fees, you finally have the option you've been waiting for. Visit www.rainbird.com/iq and take control now.



	1079	ar. a		
System Name	IQ™ v3.0	SiteControl	Maxicom ®	
iystem Type	Modular multi-site central control system	Modular single site central control system	Multi-satellite central control system	
raditionally wired or two-wire decoder	Works with both	Works with both	Traditionally wired	
ypical applications	Multi-site management with modular features. Ideal solution for water managers, schools, parks, corporate campuses and transportation departments	Single site management with modular features. Ideal for large resorts, cemeteries, shopping centers, theme parks and sports stadiums	Multi-site commercial or industri irrigation applications. Ideal for municipalities, school districts, homeowner associations and pa and recreation departments	
Number of sites/system	999	1	200+	
ocal and/or remote site control	Local and remote	Local	Local and remote	
Maximum number of simultaneous tations per site/system	5 per ESP-LXME 8 per ESP-LXD	3,584 per site	112 per CCU	
lumber of ET (weather) sources	100	4	16	
Program adjustments by ET	Yes	Yes	Yes	
rogram adjustments by percentage	Yes	Yes	Yes	
rogramming by volume/gallons	No	No	Yes	
lumber of programs	4 per satellite	100 total per system	999 per CCU	
low management capabilities	Yes	Yes	Yes	
low monitoring/recording capabilities	Yes	Yes	Yes	
ligh-flow shutdown	Mainline and laterals	Mainline only	Mainline and laterals	
ow- or zero-flow shutdown	Mainline and laterals	No	Mainline and laterals	
larms/warnings	Yes	Yes	Yes	
ensor input and manual bypass	Yes	Yes	Yes	
lumber of weather sensor inputs	One per ESP-LXME Four per ESP-LXD	Up to 200 sensor inputs per system	Up to 56 per CCU	
lumber of flow sensor inputs	One per ESP-LXMEF Five per ESP-LXD	Up to 200 sensor inputs per system	Up to 6 (two wire) or 20 (Link) per CCU	
oftware/password log-on protection	Yes	N/A	Yes	
	Ves IO Mahila	Ver Freedom System	Van Franklaus Contant	
emote control capabilities ycle+Soak™	Yes, IQ Mobile Yes	Yes, Freedom System Yes	Yes, Freedom System Yes	
•	Yes			
Vater window by program/schedule	No	Yes Yes	Yes Yes	
Computer included with software				
omputer programming	Yes	Yes	Yes	
4/7 system monitoring	Yes, by the controller	Yes, by the computer	Yes, by the CCU	
4/7 communication & feedback	No	Yes, computer to satellites and decoders	CCU to satellite	
lemote site telephone, cellular, radio, thernet, Wi-Fi communication	All	No	All	
Automatic remote site communication	Yes	No	Yes	
Satellite controllers or decoders	ESP-LXME or ESP-LXD Satellites	ESP-SAT Satellites or FD-Series Decoders	ESP-SAT or ESP-SITE Satellites	
Modular station capacity	ESP-LXME: 8-48 ESP-LXD: 50-200	No	No	
lumber of site/system interfaces	N/A – No interfaces required	8	>200	
umber of satellites/system	16,000+	896	>5,600	
lumber of satellites/site interface	Up to 150 satellites per IQNet	Up to 112 per TWI	Up to 28 per CCU	
umber of satellite stations/site	ESP-LXME: Up to 7,200 per IQNet ESP-LXD: Up to 30,000 per IQNet	Up to 21,504 per system	Up to 672 per CCU	
lumber of decoder addresses per site	Up to 30,000 per IQNet	Up to 4,000	N/A	
nteractive map interface	No	Yes	No	
PS, CAD, SHP, BMP Import	N/A	Yes	BMP, PDF, JPEG	
alve control: stations or decoders	Both	Both	Satellite stations only	
stimated/actual water use report	Yes	Yes	Yes	
vent recording (station operation)	Yes	Yes	Yes	
Projected operation (dry/run) capability	Yes	Yes	Yes	
Supported by Global Services Plan	Yes	Yes	Yes	
Can also manage lighting and security systems	Yes	Yes	Yes	

IQ™ v3.0 Central Control Software

Modular Multi-Site Central Control

The IQ Platform offers state-of-the-art command and control features in an easy to learn and use interface. IQ provides advanced water management features saving money and time. The IQ Platform consists of three options: IQ-Desktop v. 3.0, IQ-Cloud v. 3.0, and IQ-Enterprise v. 3.0.

Applications

All IQ versions provide remote programming, management, and monitoring of ESP-LX Series Controllers from the computer in your office. IQ is the perfect irrigation control solution for parks departments, school districts, property managers, landscape maintenance contractors, and water managers. IQ can manage small single-controller sites as well as large multi-controller sites and supports both ESP-LX Series traditionally-wired and 2-wire decoder controllers.

IQ-Desktop is installed and operated on a single desktop computer. IQ-Desktop is ideal for organizations with one administrator who can control the system from their computer in their office. The IQ-Desktop software package provides 5-satellite controller capacity. IQ software satellite controller capacity can be upgraded in 5-satellite increments with the IQSSATSWU.

IQ-Cloud is a cloud based service allowing users to login and control their irrigation system from any internet connected device.

IQ-Cloud is ideal for organizations with multiple irrigation system administrators and/or users that require mobility. IQ-Cloud features IQ-Mobile which provides quick access to key features in an interface designed for touchscreen devices found in smartphones or tablets. Users are not restricted to an initial capacity and can add satellites at will. Internet access is required.

IQ-Enterprise is installed on a server and enables organizations with internet access security/restrictions and a robust local area network to install their own private IQ-Cloud. Users can get all the mobility benefits of IQ-Cloud and comply with IT restrictions. IQ-Enterprise software package provides 5-satellite controller capacity. IQ software satellite controller capacity can be upgraded in 5-satellite increments with the IQ5SATSWU.

IQ Platform Software Features

- Software 5-satellite controller capacity upgradable in 5-satellite increments (Desktop & Enterprise)
- Compatible with ESP-LXM & ESP-LXME traditionally-wired and ESP-LXD 2-wire decoder controllers

Visit www.rainbird.com/iq to learn more about the features included the IQ Platform.

Additional 5-Satellite Capacity Upgrade

- IQ Software satellite controller capacity can be upgraded in 5-satellite increments
- Additional capacity is added through a purchased software activation keycode

Recommended Computer Requirements for IQ-Desktop

- Operating System: Windows® XP, 7 or 8, 32-bit or 64-bit
- Processor: Intel I5-540M or equivalent
- RAM Memory: 3 GB
- Available Hard Disk Space: 10 GB
- CD-ROM Drive: 8X speed minimum
- Display Resolution: 1024 x 768 minimum
- Network Connection (for Ethernet, WiFi, GPRS
- Serial Port or USB to Serial Adapter (for Direct Connect and External Modem communication)
- Operating System: Windows® XP, 7 or 8, 32-bit or 64-bit



IQ v3.0 Cloud





IQ v3.0 Desktop

IQ v3.0 Enterprise





IQ V3.0 SOFTWARE

IQADVCEDCD: 5-Satellite Capacity with advanced feature packs included

IQ5SATSWU:

Software 5-Satellite Capacity Upgrade



IQ NCC Network Communication Cartridge

Upgrades any ESP-LX Series Controller to an IQ Central Control Satellite Controller

Features

- IQ is the perfect irrigation control solution for parks departments, school districts, property managers, landscape maintenance contractors and water managers. IQ can manage small single-controller sites as well as large multi-controller sites. IQ NCC cartridges are compatible with the ESP-LXME Controller with 1- to 48-station capacity and ESP-LXD Decoder Controller with 1- to 200-station capacity
- IQ NCC cartridges are initially configured through a setup wizard provided in the ESP-LX Series Controller IQ Settings dial position. Communication setting parameters are configured through the IQ software or the NCC Configurator Software designed for netbook/laptop use on the job site

Direct Satellites

 Single controller sites would use an IQ NCC cartridge configured as a Direct satellite. A Direct satellite has an IQ central computer communication connection but no network connections to other satellites in the system

Server & Client Satellites

- Multi-controller sites would use one IQ NCC cartridge configured as a Server satellite and the other NCC cartridges configured as Client satellites. The Server satellite has an IQ central computer communication connection and shares this communication connection with the Client satellites though high-speed data cable or radios. The communication connection between Server and Client satellites is called the IQNet™
- Satellites on a common IQNet can share weather sensors and master valves
- Server and Client satellites using high-speed data cable for IQNet communication require installation of an IQ CM Communication Module. Server and Client satellites using radio communication for IQNet communication require installation of an IQSSRADIO radio.
 Each cartridge kit includes cables to connect the NCC cartridge to connection module and/or radio

IQ NCC 3G Cellular Cartridge

- Includes embedded 3g/Cellular Data Modem with antenna connector
- Includes internal antenna for plastic controller enclosures (optional external antenna available for metal case controller enclosures)
- Requires Cellular data service plan with static IP address from Cellular Service Provider
- Available with 1st year of communication service included. Cartridge with included communication service not offered in all areas

IQ NCC-EN Ethernet Cartridge

- Includes embedded Ethernet Network Modem with RJ-45 port
- Includes RJ-45e patch cable (requires LAN network static IP address)

IQ NCC-RS RS232 Cartridge

- Includes RS-232 Port for IQ Direct Cable or External Modem communication connection to the IQ central computer, and external modem cable (IQ Direct Cable provided with IQ Software Package)
- Used for Direct or Server Satellite applications requiring direct cable connection or external modem (radio or other 3rd-party device) communication with the IQ central computer, and for Client Satellite applications requiring IQNet high-speed data cable or radio communication with the Server Satellite

IQ FSCM-LXME Flow Smart Connection Module

- Provides IQNet high-speed data cable connections for ESP-LXME Controller
- Includes Flow Smart Module and Base Module functions
- Replaces standard ESP-LXME Base Module

IQ CM-LXD Connection Module

- Provides IQNet high-speed data cable connections for ESP-LXD Controller
- · Installs in ESP-LXD 0 (zero) module slot

IQ SS-Radio Radio Modem

- Provides IQNet wireless radio communication between Server and Client satellite controllers
- Can also be used with the IQ NCC-RS RS232 Cartridge for IQ central computer to Direct or Server satellite radio communication
- Includes power supply and external antenna (programming software and cable provided separately)



LX Series Cartridge Panel with IQ-NCC-RS Cartridge Installed

SiteControl

SiteControl

A Full-Featured Central Control System for Single Site Applications

Features

- Advanced Graphical Tracking- Maps generated by GPS technology or AutoCAD recreate your site. Interactive mapping and on-screen graphics show your complete site with location of individual valves and sprinklers allows you to measure and calculate areas from your map
- Smart Weather™ is sesigned to take complete advantage of Rain Bird's
 most advanced line of weather stations, tracks ET and rainfall via a
 weather station and reacts to current weather conditions based on
 user-defined options. Advanced warning system accepts user-defined
 sensor thresholds. System operator is immediately alerted if thresholds
 are exceeded
- RainWatch™ uses tipping bucket rain can(s) to detect and suspend irrigation while measuring rainfall. When rain stops, irrigation resumes with run times reduced according to measured rain
- Minimum ET- allows setting minimum ET threshold values for irrigation to take place. Promotes deep watering for optimum turf conditions
- Automatic ET automatically adjust run times in relation to fluctuations in Evapotranspiration (ET) values
- Remote System Control allows you to take control of your system and operate SiteControl from anywhere on your site using the Rain Bird FREEDOM System. Phone (landline or cellular) or radio communication options
- Hybrid System operates Satellite Controllers and/or Two-Wire Decoders
- SiteControl Plus operates four Large Decoder Interfaces (LDI), each capable of operating up to 1,000 solenoids with Hybrid system, can further expand capabilities by combining Two-Wire Decoder and/or Satellite Controller options up to four total interface devices

Superior Monitoring and Scheduling

- Flo-Graph™ allows visibility of real-time graphics with individual station information presented in colorful charts
- Flo-Manager™ balances system demands and maximum capacities with efficiency helping to lower water demand, reduce system wear and tear and save energy
- Cycle + Soak™. Better control the application of water on slopes and in areas with poor drainage
- QuicklRR™ Quick and easy method to build irrigation schedules and programs based on your parameters

Other Features

- Up to 200 points of connection
- Up to 200 pulse sensors
- · Water usage logs
- · Station run-time logs
- · Posted and dry run logs
- ET spreadsheet
- 1 year Global Service Plan included

Models

 SCON: Desktop PC with SiteControl software, includes 1 year Global Support Plan (GSP)

Software Module Options

- · Smart Weather
- Rain Bird Messenger (for Smart Weather)
- Automatic ET
- · Hybrid Module
- Smart Sensor
- Map Utilities
- Freedom

- · 8 Additional Locations
- · Additional Wire-Path (2nd)
- Additional Wire-Path (3rd)
- · Additional Wire-Path (4th)
- · SiteControl Plus
- Smart Pump
- MI (Mobile Interface)

Global Service Plan (GSP)

• Visit rainbird.com/gsp/index.htm for more information.



SiteControl



SiteControl Hardware

TWI Satellite Interface

- Allows real-time, two-way communication between SiteControl Central Controller and field satellites
- Allows use of advanced in-field capabilities of ESP-SAT twowire or LINK versions
- · Modular capacity can grow with the site

Two-Wire Decoder Interface

- Allows real-time, two-way communication between SiteControl Central Controller and decoders
- Connects the powerful capabilities of SiteControl with the ease of installation and security of a two-wire decoder system
- System can be set up and expanded according to project needs

ESP-SAT Satellite Controller

- · 40 Stations Satellite Controller
- Field Satellite Controller for Maxicom² or SiteControl Central Control systems
- The power of an advanced water-management tool, in an easy-to-use package
- All the features and stand-alone capabilities of the Rain Bird ESP-MC Controller line

Spread Spectrum Radio

- · Frequency hopping to avoid interference
- · Reduced cost of ownership, no FCC license required
- No FCC restrictions on antenna height (User should check local laws)
- Radios can be set up as repeater to achieve great distances and overcome obstacles

Ethernet Devices

- · Use Ethernet networks to:
- Communicate from Central Control Computer to CCUs, SiteSats, TWIs and weather stations
- - Communicate from CCU and TWIs to ESP-Sats

WS-PRO Weather Stations

- Scientific accuracy sensors located three meters above the ground for added vandal-resistance
- Powerful, internal micro-logger for climatic data collection, logging and analysis, constant communication with weather sensors, and storage of 30 days of data
- · Rugged yet lightweight metal construction;

Sensor-Pulse Decoders

- · Complete feedback system
- · Extends central control system versatility
- · Color-coded wire leads for ease of installation
- Programmable address codes for individual operation

RAINGAUGE Rain Sensor

- · Accurate rain counter switch counts rainfall in 1/100th inch increments
- · Heavy-duty metal construction
- Mounting bracket
- · Debris screen

ANEMOMETER Wind Sensor

- Accurate wind speed measurement for high-wind shutdown or interrupt of irrigation programs
- · Heavy-duty metal mounting bracket
- Requires PT322 or PT3002 Pulse Transmitter for use with Maxicom² System

Maxi Interface Boards

- Upgrades an ESP-MC Controller (wall mount or pedestal) to an ESP-SAT Satellite Controller
- · No additional enclosures or external wiring required
- · Installs on stand-offs on controller output board

MSP-1 Surge Protection

- Protects central control components from electrical surges on a two-wire communication path
- Can be installed in satellite or CCU pedestal or in valve box in conjunction with MGP-1 (Maxicom² Grounding Plate)

MGP-1 Surge Grounding Plate

- Provides a mounting location for MSP-1 or other grounding wires directly to a grounding rod or pipe
- · Installed on grounding rod or pipe









Maxicom^{2®}

Maxicom[®] version 4.4 now available

Multi-Site Central Control Ideal for Large Commercial Systems

New for version 4.4

- Windows 8 compatibility
- Seek & Eliminate Low Flow (SELF) Automatically diagnose a low flow problem
- Station Lockout Quarantine zones that have had high/low flow alarms until the user takes action
- Station Priorities for Flow Manager allows the user to alter the sequence of irrigation zones by assigning priorities when flow manager is being used
- Queued irrigation max run time limit increased from 99 minutes to 999 minutes
- Adjustable rain can settings
- Seek & Eliminate Excessive Flow (SEEF) improvement to account for manual adjustments
- Database trim setting is no longer fixed and is user-selectable so users can decide how far back the records go
- Phone number/address field works with URL's and longer IP Addresses
- Field Device Configuration Report now includes satellite names and sensor names

System Features

- Maxicom^{2®} Central Controller Package comes with Maxicom² software, pre-configured computer, Global Service Plan (GSP), and training
- Control hundreds of ESP-SITE-SAT Satellites (single controller sites) and Cluster Control Units (CCUs) which can each control up to 28 individual ESP-SAT Satellite Controllers on multi-controller sites
- Monitor dozens of Weather Sources including WSPRO2 Weather Stations, ET Managers, or rain counting sensors (Raingauge)
- Freedom Remote Control allows manual operation of system through a cellular phone or radio
- Multiple log and water usage reports are generated automatically to track system operation and water savings

Water Management Features

- Cross satellite schedule operation; 999 separate schedules per CCU provides precision watering of areas and microclimates
- ET Checkbook™ manages Evapotranspiration (ET) and automatically adjusts Satellite Controller station run-time or day cycle intervals to match the landscapes water requirements
- FloManager™ manages the total flow demand placed on the water source(s), optimizing both the available water and watering window
- FloWatch™ monitors flow sensors at each water source, records flow, and automatically reacts to problem flows by shutting down the effected portion of the system (individual valve or mainline)
- RainWatch™ monitors rain counting sensors, records rainfall, and automatically reacts to rainfall by interrupting irrigation, waiting to see how much rain has fallen, and determines if the irrigation should be resumed or cancelled

Operational Features

- Communication Control Engine automatically sends updated programming to sites before watering begins and retrieves logs after irrigation is completed; manual operation can be performed at any time
- Start day cycles: Custom (day of the week), Odd/Even, Odd31, or Cyclical and include Event Day Off Calendar scheduling
- Station run-times programmable from 1 minute to 16 hours
- Cycle + Soak™ optimizes water application to soil infiltration rate, reducing runoff and puddling
- Control non-irrigation functions such as lighting, fountains, door locks and gates

Maxicom² Communications Options

- Central Controller to CCU: Phone, direct connect, radio, cellular, network (Ethernet, Wi-Fi, fiber-optics)
- · CCU to ESP-SAT2: Two-wire path
- CCU to ESP-SATL: Radio, MasterLink, network (Ethernet, Wi-Fi, fiber-optics)

Global Service Plan (GSP)

• Visit rainbird.com/gsp/index.htm for more information.

Models

- MC2GOLD1: New System Desktop PC with Maxicom software, includes 1 year Global Support Plan (GSP)
- GSPMCPL3: Current GSP Or Expired GSP Subscribers, Desktop PC with Maxicom software, includes 3 Years Platinum Plus Global Support Plan
- GSPMXPPCIA: Current GSP Subscribers, Desktop PC with Maxicom software, based on 3 Year Platinum Plus Global Support Plan, includes year 1 GSP, requires year 2 and 3 GSP to be purchased separately (M95543A2)
- GSPMXPPCIM: Current GSP Subscribers, Desktop PC with Maxicom software, based on 3 Years Platinum Plus Global Support Plan, includes month 1 GSP, requires month 2 - 36 GSP to be purchased separately (M95544M2)
- GSPMXPPNIA: New GSP or Expired GSP Subscribers, Desktop PC with Maxicom software, based on 3 Years Platinum Plus Global Support Plan, includes year 1 GSP, requires year 2 and 3 GSP to be purchased separately (M95541A2)
- GSPMXPPNIM: New GSP or Expired GSP Subscribers, Desktop PC with Maxicom software, based on 3 Years Platinum Plus Global Support Plan, includes month 1 GSP, requires month 2 - 36 GSP to be purchased separately (M95542M2)
- MC2UPG: Maxicom Upgrade Software CD Only, upgrade existing Maxicom 1.X, 2.X and 3.X system to latest Maxicom Version



Maxicom



Maxicom^{2®} Hardware

Cluster Control Unit CCU Interface

- · Runs real-time operations of a site consisting of up to 28 satellites
- · Adapts station sequence to changing conditions for maximum efficiency
- · Instantly responds to unexpected conditions and sensor inputs

ESP-SAT Satellite Controller

- · 40 Stations Satellite Controller
- Field Satellite Controller for Maxicom² or SiteControl Central Control
- The power of an advanced water-management tool, in an easy-to-use package
- All the features and stand-alone capabilities of the Rain Bird ESP-MC Controller line

ESP-SITE-SAT Satellite Controller

- · 24, 40 Stations Satellite Controller
- · Combines power of a Cluster Control Unit (CCU) with capabilities of a single ESP-Satellite controller for small Maxicom² sites
- · Advanced water-management tool, in an easy-to-use package
- All the features and stand-alone capabilities of the Rain Bird ESP-MC Controller line

Spread Spectrum Radio

- · Frequency hopping to avoid interference
- · Reduced cost of ownership, no FCC license required
- No FCC restrictions on antenna height (User should check local laws)
- · Radios can be set up as repeater to achieve great distances and overcome obstacles

Ethernet Devices

- · Use Ethernet networks to:
- - Communicate from Central Control Computer to CCUs, SiteSats, TWIs and weather stations
- Communicate from CCU and TWIs to ESP-Sats

WS-PRO Weather Stations

- · Scientific accuracy sensors located three meters above the ground for added vandal-resistance
- Powerful, internal micro-logger for climatic data collection, logging and analysis, constant communication with weather sensors, and storage of 30 days of data
- · Rugged yet lightweight metal construction

Sensor-Pulse Decoders

- Complete feedback system
- · Extends central control system versatility
- · Color-coded wire leads for ease of installation
- Programmable address codes for individual operation

RAINGAUGE Rain Sensor

- Accurate rain counter switch counts rainfall in 1/100th inch increments
- · Heavy-duty metal construction
- · Mounting bracket
- · Debris screen

ANEMOMETER Wind Sensor

- · Accurate wind speed measurement for high-wind shutdown or interrupt of irrigation programs
- · Heavy-duty metal mounting bracket
- Requires PT322 or PT3002 Pulse Transmitter for use with Maxicom² System

Maxi Interface Boards

- · Upgrades an ESP-MC Controller (wall mount or pedestal) to an ESP-SAT or ESP-SITE Satellite Controller
- · No additional enclosures or external wiring required
- · Installs on stand-offs on controller output board

MSP-1 Surge Protection

- · Protects central control components from electrical surges on a two-wire communication path
- · Can be installed in satellite or CCU pedestal or in valve box in conjunction with MGP-1 (Maxicom² Grounding Plate)

MGP-1 Surge Grounding Plate

- Provides a mounting location for MSP-1 or other grounding wires directly to a grounding rod or pipe
- · Installed on grounding rod or pipe



CCU-28-W



ESP-40SAT-2W Satellite



MSP-1



MGP-1



RAINGAUGE

WS-PRO Weather Stations

WS-PRO Weather Stations

Maxicom $^{2\circ}$ (WS-PRO2 only), SiteControl, IQ $^{\sim}$ v3.0 (WS-PRO2 and WSPROLT)

Features

- Scientific accuracy sensors located three meters above the ground for added vandal-resistance
- Powerful, internal micro-logger for climatic data collection, logging and analysis, constant communication with weather sensors, and storage of 30 days of data
- Rugged yet lightweight metal construction
- Self-diagnostic test mechanisms: internal moisture, battery voltage level, test port for local sensor check, and simple-to-service sensors and internal components
- State-of-the-art weather software calculates ET values, stores daily and historic ET values, monitors and displays current weather conditions, and graphically displays weather parameters

SiteControl Features

- WS-PRO2 and WS-PRO-LT Weather Station compatibility is standard for SiteControl v3.0 or later software
- SiteControl can interface with up to 6 weather stations
- Automatic communication between Central Controller and Weather Station requires SiteControl Automatic ET Software Module
- SiteControl Smart Weather Software Module enables automatic, user defined reactions to weather events (rain, freeze, high wind, etc.)



IQ™ v3.0 Features

- WS- PRO2 or WS-PRO-LT Weather stations are compatible with IQ™ v3.0 or later software with advanced ET Feature Pack (IQAETFP)
- Automatic communication between the IQ™ v3.0 central and weather station requires the communcation feature pack (IQACOMFP)
- Weather data retrieval hourly or custom retrieval times up to 5 per day
- IQ can interface with 100 weather stations

Maxicom^{2®} Features (WS-PRO2 only)

- WS-PRO2 Weather Station compatibility is standard for Maxicom^{2®} v3.6 or later software
- Each site can have its own Weather Station or can share between sites
- · Automatic communication standard
- Up to 24 automatic weather data retrievals can be configured per day

Weather Station Sensors

- Air Temperature
- · Solar Radiation
- · Relative Humidity
- · Wind Speed
- · Wind Direction
- Rainfall

System Compatibility

- Maxicom² (WS-PRO2 only)
- SiteControl (requires Automatic ET Software Module)
- IQ[™] v3.0 with Advanced ET Feature Pack
- ET Manager Weather Reach Server Software

Models

- WS-PRO2-DC Direct Connect model 2-pair wire connection with Central Controller via short-haul modem
- WS-PRO2-PH Phone Connect model dial-up phone modem for phone communication with Central Controller
- WS-PRO-LT-SH Short Haul model 2-pair wire connection with Central Controller via short-haul modem



Spread Spectrum Radio

Maxicom^{2®}, SiteControl or IQ™

Features

- · Frequency hopping to avoid interference
- · Reduced cost of ownership, no FCC license required
- No FCC restrictions on antenna height (User should check local laws)
- Radios can be set up as repeater to achieve great distances and overcome obstacles

Installation Requirements

- Site Survey required prior to ordering and must be submitted with order
- RADTN9MIB mounts directly onto ESP-SAT MIB; RADTN9TWI connects with ribbon cable
- Antenna and antenna cable required (sold separately by Rain Bird Production and Service Center)

Models

- Radios For IQ Primary & Secondary Communication and For Maxicom and Site Control Primary Communication
 - IQSSRADIO: 900 MHz Spread Spectrum radio Allows communication between Central Computer and IQ Direct or IQ Server Satellite, and between IQ Server Satellite and IQ Client Satellites. Also can be used for communication between Maxicom Central Computer and CCU or Site Satellite, between Site Control Central Computer and TWI / SDI or LDI, and between a Central Computer and weather station
- Radios For Maxicom and Site Control Secondary Communication
 - RADTN9MIB: license free wireless radio (902-928 MHz) between CCU and satellites
 - RB-SS-TN9B: Plastic Case Radio License free radio to communicate to IQ Satellites

ANEMOMETER Wind Sensor

Maxicom,^{2®} SiteControl, IQ[™], ESP-LXME, ESP-LXD

Features

- Accurate wind speed measurement for high-wind shutdown or interrupt of irrigation programs
- · Heavy-duty metal mounting bracket
- Requires PT322 or PT3002 Pulse Transmitter for use with Maxicom² System
- Requires PT3002 Pulse Transmitter for use with SiteControl, IQ Systems, ESP-LXME, ESP-LXD

Model

ANEMOMETER



ANEMOMETER



Drip Irrigation

Major Products						
Primary Applications	Single outlet emitter	Multi-outlet emitter	Bubbler emitter	Spray	Inline emitter (Dripline)	RWS
Thick bushes		•	•	•	•	
Single bush	•					
Small trees	•	•			•	•
Large trees	•	•	•			•
Ground cover		•		•	•	
Annuals			•	•	•	
Mixed vegetation	•	•			•	
Potted plants	•		•	•	•	
Hedges	•				•	
Vegetation on slopes	•				•	




Water Saving Tips

- Drip products deliver water directly to the root zone. Use dripline for dense plantings where it's cost effective to distribute lowvolume water evenly. Use a system of precise emitter devices for sparse plantings where it's cost effective to separately irrigate each plant.
- Use drip to eliminate overspray, and you'll eliminate waste. Eliminate unsightly spray stains on buildings and fences. Eliminate soil erosion, water runoff, and potential litigation. Walkways, roads, and vehicles stay dry.
- Ask your tax advisor about capital depreciation when calculating your return-on-investment for a drip retrofit. Save water, and save money at the same time.



Landscape Drip System Overview





- 1a. Low Flow Valve (pg. 157)
- 1b. Pressure Regulating Filter (pg. 158)
- 2. Easy Fit Female Adapter (pg. 141)
- 3. Easy Fit Coupling (pg. 141)
- 4. Xeriman Tool (pg. 114)
- 5. XF Series Blank Tubing (pg. 143)
- 6. Xeri-Bug Emitter (pg. 114)
- 7. 1/4" Tubing Stake (pg. 125)

- 9. ¼" Barb Tee (pg. 147)
- 10. Tie-Down Stake (pg. 147)
- 11. Easy Fit Elbow (pg. 141)
- 12. Diffuser Bug Cap (pg. 125)
- 13. PC Emitter Diffuser Cap (pg. 125)
- 14. PC Module-1032 (pg. 118)
- 15. PolyFlex Riser Assembly (pg. 126)
- 16. Xeri-Bug Emitter 1/2" FPT (pg. 114)

- 18. SQ Series Square Nozzle (pg. 120)
- 19. Xeri-Pop (pg. 122)
- 20. Xeri-Bubbler SPYK (pg. 123)
- 21. ARV050 Air Relief Valve Kit (pg. 142)
- 22. SEB-7X Emitter Valve Box (pg. 147)
- 23. XFD Dripline (pg. 130)
- 24. Tubing Cutter (pg. 147)
- 25. Xeri-Bird 8 (pg. 117)

Targeted Watering with Landscape Drip


Rain Bird Xerigation®/Landscape Drip products are made especially for low-volume irrigation systems. By delivering water at or near the plants' root zones, Rain Bird Xerigation® products offer targeted watering with the following advantages:


- Water conservation
- Greater efficiency (target each plant)
- Design flexibility; simple construction and easily expandable
- Healthier plants
- Reduced liability (e.g. no overspray, no runoff)
- · Minimization of weed growth
- Cost savings

Broadest Product Line in the Industry

With over 150 products, Rain Bird has the products needed for your application. Systems can be designed to meet any site requirements and offer many exclusive Rain Bird advances including:

- Flexible XF Series dripline with advanced polymers that provide kinkresistance and reduced coil memory for easier installation
- Compact Control Zones with combined pressure regulator and filter to reduce parts, potential leak problems, and allow for fitting more Control Zones in a valve box
- Precision low volume SQ spray nozzles that offer a square wetting pattern and adjust to either 2.5' or 4' throw distances
- Point-source emitters that provide pressure compensation with a wide selection of flow rates and three inlet options (Barb, 1032 threaded, and ½" FPT)
- XFS and XFS-CV dripline with Copper Shield Technology™ for use in sub-surface applications under turf or shrub and groundcover areas. The copper chip effectively protects the emitter from root intrusion





- 26. Retrofit Pressure Regulator (pg. 159)
- 27.6 Outlet Manifold (pg. 116)
- 28. SQ Series Nozzle Adapter (pg. 120)
- 29. Easy Fit Tee (pg. 141)
- 30. Easy Fit Flush Cap (pg. 141)
- 31. Purple XF Dripline (pg. 130)
- 32. Xeri- Bug Emitter 1032 (pg. 114)
- 33. XF Series Blank Tubing (pg. 143)
- 34. 1/4" Barb Connector (pg. 147)


- 35. Multi-Outlet Xeri-Bug (pg. 116)
- 36. ¼" Landscape Dripline (pg. 146)
- 37. XFS-CV Sub-Surface Dripline with Copper Shield Technology (pg. 136)
- 38. RETRO-1800 Spray-to-Drip Retrofit Kit (pg. 163)
- 39. XT-025 ½" FPT x Barb Grey Transfer Fitting (pg. 116)
- 40. XFF Coupling (pg. 140)
- 41. PCT Bubbler (pg. 118)

- 42. XFCV Dripline with Heavy-Duty check valve (pg. 132)
- 43. RWS (Root Watering System) (pg. 127)
- 44. XF Insertion Tool (pg. 142)
- 45. PEB Valve (pg. 69)
- 46. Quick-Check Pressure Regulating Filter (pg. 161)
- 47. QF Dripline Header (pg. 138)
- 48. XF Series Dripline (XFD/XFS/XFCV/XFS-CV) (pg. 130-136)
- 49. Operation Indicator (pg. 142)
- 50. Twist Lock Fittings (pg. 139)






XB-05PC, XB-10PC, XB-20PC



XB-05PC-1032, XB-10PC-1032, XB-20PC-1032

1032-threaded models are specifically designed to be used with PolyFlex Risers, 1032 thread adapters (1032-A), or 1800 Xeri-Bubbler Adapter (XBA-1800)



Xeriman[™] Tool

Features

- Provides fast, easy, one-step installation of Xeri-Bug[™] emitters and PC Modules directly into 1/2" or 3/4" drip tubing, XF Dripline or Landscape Dripline
- · Cuts emitter installation time
- All-in-one tool inserts emitters, removes emitters, inserts 1/4" barbed fittings and installs goof plugs

Model

XM-TOOI





Xeri-Bug[™]

Insertion











Goof Plug Insertion

Xeri-Bug[™] Emitters

Point-Source Low-Flow Emitters for Watering the Root Zones of Plants, Trees, and Container Plants

Features

- · The only emitters with self-piercing barbs, making them the easiest to install using the Xeriman[™] tool
- Widest selection of pressure-compensating emitters, with 3 flow rates and 3 inlet options
- Most compact and unobtrusive emitters
- Flow-rates of 0.5, 1.0 and 2.0 gph (1.89, 3.79 and 7.57 l/h)
- Pressure-compensating design delivers uniform flow throughout a wide pressure range (15 to 50 psi; 1.0 to 3.5 bar)
- · Available with 3 different inlets (1.0 and 2.0 models):
 - Self-piercing barb for quick, one-step insertion into 1/2" or 3/4" drip tubing
 - 10-32 threaded inlet that easily threads into a PolyFlex Riser (see page 126), 1032 Thread adapter (page 126) or 1800 Xeri-Bubbler Adapter (page 126)
 - 1/2" FPT inlet that easily threads onto a 1/2" PVC riser (1.0 and 2.0 gph models)
- Outlet barb securely retains 1/4" Distribution Tubing (XQ)
- Design makes installation and maintenance easy
- Self-flushing action minimizes clogging
- Robust design made from highly inert materials that are resistant to chemicals
- Durable plastic construction is UV-resistant
- · Color-coded to identify flow rate

Operating Range

- Flow: 0.5 to 2.0 gph (1.89 to 7.57 l/h)
- Pressure: 15 to 50 psi (1.0 to 3.5 bar)
- Required filtration: 150 to 200 mesh (100 to 75 micron see chart pg. 115)

Models: 10-32 thread inlet x barb outlet

- XB-05PC-1032: Blue, 0.5 gph (1.89 l/h)
- XB-10PC-1032: Black, 1.0 gph (3.79 l/h)
- XB-20PC-1032: Red, 2.0 aph (7.57 l/h)


Models: ½" FPT inlet x barb outlet

- XBT-10: Black, 1.0 gph (3.79 l/h)
- XBT-20: Red, 2.0 gph (7.57 l/h)

Models: barb inlet x barb outlet

- XB-05PC: Blue, 0.5 gph (1.89 l/h)
- XB-10PC: Black, 1.0 gph (3.79 l/h)
- XB-20PC: Red, 2.0 gph (7.57 l/h)

Xeri-Bug E	mitter Ba	g Quant	ities and Models
Flow Rate	Color	Bag Qty.	Model Number
0.5 GPH (1.89 l/h)	Blue	25 100 8000	XB05PC XB05PCBULK XB05MAXPAK
1.0 GPH (3.79 l/h)	Black	25 100 8000	XB10PC XB10PCBULK XB10MAXPAK
2.0 GPH (7.57 l/h)	Red	25 100 8000	XB20PC XB20PCBULK XB20MAXPAK




Xeri-Bug Emitter Specifications and Models									
Model	Inlet Type/Color	Nominal Flow gph	Filtration Required mesh						
XB-05PC	Barb/Blue	0.5	200						
XB-10PC	Barb/Black	1.0	150						
XB-20PC	Barb/Red	2.0	150						
XB-05PC1032	10-32T/Blue	0.5	200						
XB-10PC1032	10-32T/Black	1.0	150						
XB-20PC1032	10-32T/Red	2.0	150						
XBT-10PC	1/2" FPT/Black	1.0	150						
XBT-20PC	1/2" FPT/Black	2.0	150						


Xeri-Bug Emitte	METRIC		
Model	Inlet Type/Color	Nominal Flow I/h	Filtration Required micron
XB-05PC	Barb/Blue	1.89	75
XB-10PC	Barb/Black	3.79	100
XB-20PC	Barb/Red	7.57	100
XB-05PC1032	10-32T/Blue	1.89	75
XB-10PC1032	10-32T/Black	3.79	100
XB-20PC1032	10-32T/Red	7.57	100
XBT-10PC	1/2" FPT/Black	3.79	100
XBT-20PC	1/2" FPT/Black	7.57	100



Xeri-Bug™ Emitter, TS025-1/4" stake, and DBC025 Diffuser Bug Cap



(For reference numbers below, please see the System Overview page 112)




Installation Option 1*

Using a Xeriman Tool, insert an emitter directly into ½" or ¾" drip tubing or between dripline emitters as needed.

Installation For more preci ¼" distribution stake, and a bu

Installation Option 2*

For more precise water placement, use ¼" distribution tubing, a ¼" tubing stake, and a bug cap.



Installation Option 3

For precise water placement, a barbed connector can be punched into distribution tubing. The emitter is then placed at the end of the ¼" distribution tubing. NOTE: should the emitter become dislodged, unregulated flow will occur.



Installation Option 4*

The Xeri-Bird 8 provides a centralized location for up to eight emitters. A mix of Xeri-Bug and/ or PC emitters can be used to provide the flow rates needed for different plant materials. Tentacles of ¼" distribution tubing, ¼" tubing stakes, and bug caps allow for precise water placement.



Installation Option 5

The 6 Outlet Manifold provides a centralized water distribution connection for up to six emission devices. Connect the ¼" distribution tubing to one of the outlets. Use a ¼" tubing stake to ensure precise water placement. The emitter is placed on the end of the 1/4" distribution tubing to regulate the water flow. NOTE: should the emitter become dislodged, unregulated flow will occur.

* Preferred installation options, which provide flow regulation at the source.



Multi-Outlet Xeri-Bug™

Features

- Pressure compensating design delivers uniform flow throughout a wide pressure range (15 to 50 psi; 1.0 to 3.5 bar)
- Six-outlet emitter supplied with one outlet opened. Simply clip the outlet tips open with snips or clippers for additional operational ports
- Barbed outlets retain 1/4" Distribution Tubing (XQ)
- · Self-flushing action minimizes clogging
- Durable, UV-resistant color-coded plastic housing

Operating Range

- Flow: 0.5, 1.0 or 2.0 gph (1.89, 3.79 or 7.57 l/h)
- Pressure: 15 to 50 psi (1.0 to 3.5 bar)
- · Filtration: 150-mesh (100-microns)

Models: barb inlet x barb outlet

- XB-05-6: Blue, 0.5 gph (1.89 l/h)
- XB-10-6: Black, 1.0 gph (3.79 l/h)
- XB-20-6: Red, 2.0 gph (7.57 l/h)

Models: 1/2" FPT inlet x barb outlet


- XBT-05-6: Blue, 0.5 gph (1.89 l/h)
- XBT-10-6: Black, 1.0 gph (3.79 l/h)
- XBT-20-6: Red, 2.0 gph (7.57 l/h)



XB-05-6, XB-10-6, XB-20-6



XBT-05-6, XBT-10-6, XBT-20-6



6 Outlet Manifold - EMT-6XERI

Features

- ' $\frac{1}{2}$ " FPT inlet threads onto $\frac{1}{2}$ " riser and provides a manifold with six free-flowing $\frac{1}{4}$ " barb outlets
- Each barb outlet is sealed with a durable plastic cap
- Plastic caps remove easily, allowing for a drip area that can be customized with up to six different emission devices
- Attach ¹/₄" Distribution Tubing (XQ) onto each outlet for use with: Xeri-Bugs, PC Modules, Xeri-Pops, Xeri-Sprays, and Xeri-Bubblers

Operating Range

- Pressure: 15 to 50 psi (1.0 to 3.5 bar)
- · Required filtration: 150 mesh (100 microns)

Model

EMT-6XERI



1/4" Self-Piercing Barb Connector

Features

- Used to connect ¼" Distribution Tubing into ½" or ¾" distribution tubing
- Self-piercing barb inlet is easily inserted into ½" or ¾" distribution tubing using a Xeriman™ Tool (XM-Tool)
- Outlet barb accepts ¼"
 Distribution Tubing (XQ). Gray outlet barb indicates unit has unrestricted flow

Operating Range

• Pressure: 0 to 50 psi (0 to 3.5 bar)

Model

• SPB-025 Inlet Outlet

1/2" FPT x Barb Grey Transfer Fitting

Features

- Grey outlet to designate open flow
- ½" FPT inlet can be easily attached to a schedule 80 riser or the top of an 1800 Retro
- Barbed outlet so ¼" distribution tubing or ¼" drip tubing can be easily and securely attached

Operating Range

 Pressure: 0 to 50 psi (0 to 3.5 bar)

Model

XT025



Xeri-Bird[™] 8-Outlet Emission Device

The Most Flexible and Feature-Rich Multi-Outlet Device on the Market, Ideal for New Projects and Retrofit Applications

Features

- The only multi-outlet device on the market with 8 configurable ports and 10 flow options for each port for maximum flexibility
- XBD-80 and XBD-81 models each contain a built-in filter. Makes retrofitting easy when installed with the optional in-stem pressure regulator (PRS-050 page 159)
- · Easy to maintain, because body can be easily removed from riser
- Threads onto any ½" riser and delivers water to multiple locations for increased system flexibility
- Each port accepts a Xeri-Bug™ Emitter or PC Module for independent flows from 0.5 to 24 gph (1.89 to 90.84 l/h) or use a self-piercing barb connector (SPB-025) for unrestricted flow
- XBD-80 and XBD-81 models each feature an integral 200 mesh (75 micron) filter which is easily serviceable from the top of the unit
- Eight bottom-mounted, sure-grip barbed outlets securely retain ¼" Distribution Tubing (XQ)
- Unique union base nut allows removal of Xeri-Bird 8 body from riser for easy installation and maintenance
- Emitters must be installed inside the Xeri-Bird to prevent excess back pressure

Operating Range

- Flow: 0.5 to 24 gph (1.89 to 90.84 l/h) per outlet
- Pressure: 15 to 50 psi (1.0 to 3.5 bar)

Models

- XBD-80: Xeri-Bird 8 unit (includes 7 removable port plugs and filter)
- XBD-81: Xeri-Bird 8 unit (includes eight 1 gph (3.79 l/h) Xeri-Bug emitters factory installed, and filter)

Replacement Parts:

· XBD8SCRN: replacement screen and two o-rings



Helpful Hint: Always install emitters with the pointed end (inlet barb) or threaded end up, as shown



XBD-80



Each port can be configured on the Xeri-Bird™ by installing flow controlled emitters. Above shows a combination of 0.5, 1.0, and 2.0 gph Xeri-Bug emitters.

^{*} Must be installed second

^{**} Must be installed first










PC-05-1032, PC-07-1032, PC-10-1032

10-32-threaded models are specifically designed to be used with PolyFlex Risers, 10-32 thread adapters (1032-A), or 1800 Xeri-Bubbler Adapter (XBA-1800)



PCT-05, PCT-07, PCT-10

1/2" FPT inlet that easily threads onto a 1/2" PVC riser



Pressure-Compensating Modules

Point-Source Medium-Flow Emitters for Watering Larger Shrubs and Trees

Features

- The only emitters with self-piercing barbs, making them the easiest to install using the Xeriman™ tool
- Widest selection of pressure-compensating emitters, with 6 flow rates and 3 inlet options
- · Most compact and unobtrusive emitters
- Flow rates from 5 to 24 gph (18.93 to 90.84 l/h)
- Pressure-compensating design delivers uniform flow throughout a wide pressure range (10 to 50 psi; 0.7 to 3.5 bar)
- · Available with 3 different inlets:
 - Self-piercing barbs for quick one-step emitter insertion into $^1\!/\!_2$ or $^3\!/\!_1$ drip tubing
 - 10-32 threaded inlet that easily threads into a PolyFlex Riser (see page 126), 1032 Thread adapter (page 126) or 1800 Xeri-Bubbler Adapter (page 126)
 - $^{-1}$ /2" FPT inlet that easily threads onto a 1 /2" PVC riser
- Robust design durable plastic construction is UV-resistant and colorcoded to identify flow rate

Operating Range*

- Flow: 5 to 24 gph (18.93 to 90.84 l/h)
- Pressure: 10 to 50 psi (0.7 to 3.5 bar)
- Required filtration: 100 mesh (150 micron)
- * IMPORTANT NOTE: Use a PC Diffuser Cap to eliminate squirting water when using a PC Module staked at the end of 1/4" Distribution Tubing (XQ) or on a PolyFlex Riser (PFR/FRA)

Models: barb inlet x barb outlet

- PC-05: Light brown, 5 gph (18.93 l/h)
- PC-07: Violet, 7 gph (26.50 l/h)
- PC-10: Green, 10 gph (37.85 l/h)
- PC-12: Dark brown, 12 gph (45.42 l/h)
- PC-18: White, 18 gph (68.13 l/h)
- PC-24: Orange, 24 gph (90.84 l/h)

Models: 10-32 thread inlet x barb outlet

- PC-05-1032: Light brown, 5 gph (18.93 l/h)
- PC-07-1032: Violet, 7 gph (26.50 l/h)
- PC-10-1032: Green, 10 gph (37.85 l/h)

Models: 1/2" FPT thread Inlet


- PCT-05: Light Brown, 5 gph (18.93 l/h)
- PCT-07: Violet, 7 gph (26.50 l/h)
- PCT-10: Green, 10 gph (37.85 l/h)

Orip Irrigatio

Pressure-Compensating Modules

Pressure-Cor	Pressure-Compensating Module Models								
Model	Inlet Type/ Outlet/Color	Nominal Flow gph	Filtration Required mesh						
PC-05	Barb / light brown	5	100						
PC-07	Barb / violet	7	100						
PC-10	Barb / green	10	100						
PC-12	Barb / dark brown	12	100						
PC-18	Barb / white	18	100						
PC-24	Barb / orange	24	100						
PC-05-1032	10-32T / light brown	5	100						
PC-07-1032	10-32T / violet	7	100						
PC-10-1032	10-32T / green	10	100						
PCT-05	NPT / light brown	5	100						
PCT-07	NPT / violet	7	100						
PCT-10	NPT / green	10	100						

Pressure-Cor	METRIC		
Model	Inlet Type/ Outlet/Color	Nominal Flow I/h	Filtration Required micron
PC-05	Barb / light brown	18.93	150
PC-07	Barb / violet	26.50	150
PC-10	Barb / green	37.85	150
PC-12	Barb / dark brown	45.42	150
PC-18	Barb / white	68.13	150
PC-24	Barb / orange	90.84	150
PC-05-1032	10-32T / light brown	18.93	150
PC-07-1032	10-32T / violet	26.50	150
PC-10-1032	10-32T / green	37.85	150
PCT-05	NPT / light brown	18.93	150
PCT-07	NPT / violet	26.50	150
PCT-10	NPT / green	37.85	150



PC Diffuser Caps







PC-DIFFUSER

PC-DIFF-PPL

PC Diffuser Caps are designed to fit onto outlet of pressure-compensating drip modules

Models: (see page 125 for complete information)

- PC-DIFFUSER: Black
- PC-DIFF-PPL: Purple, to designate non-potable water

PC Module (PC-10-1032) with PC Diffuser Cap (PC-DIFFUSER) on PolyFlex Riser (PFR-PFA) (PolyFlex Risers available in 12" and 24" models - p. 126)





SQ Nozzle Installed on PolyFlex Riser with Nozzle Adapter



One Nozzle...Two Throws

With a simple turn of the nozzle to the next preset stop, the Rain Bird SQ Nozzle adjusts from a 2.5' (0.8 m) throw to a 4' (1.2 m) throw. It's like having two nozzles in one.



Can be used on...

The SQ Nozzle is an ideal solution for a wide range of difficult-to-design areas, thanks to its compatibility with popular irrigation products.



SQ Series, Square Pattern Nozzles

The Most Precise and Efficient, Low-Volume Spray Solution for Irrigation of Small Areas with Dense Plantings

Features

- Square spray pattern and pressure compensation offer increased efficiency and control, reducing overspray, property damage and liability
- Simplify design and installation with the flexibility of applications: one nozzle throws 2.5' or 4' (0.8 m or 1.2 m) and can be used on a variety of spray heads and risers
- Meets micro irrigation system requirement for less than 26 gph flow rate at 30 psi
- Square spray pattern with edge-to-edge coverage allows you to easily design and install in small spaces
- Pressure compensation design delivers uniform flow over the pressure range
- Available in 3 models—quarter, half and full patterns with matched precipitation rate
 - Virtually no-mist performance from 20 psi to 50 psi
 - Two throw distances in each nozzle. One simple click adjusts to 2.5' or 4' (0.8 m or 1.2 m)
 - Shipped with blue filter screen (0.02" x 0.02") to maintain precise distance of flow, and to prevent clogging
- Compatible with all 1800 Sprays, Xeri-Pops, New PolyFlex Riser Adapter, UNI-Spray and SCH 80 risers

Operating Range

- Pressure: 20 to 50 psi (1.4 to 3.5 bar)
- Flow rates: 6, 12 and 24 gph (22.7, 45.4 and 90.8 l/h)
- · Required filtration: 40 mesh

Models

- SQ-QTR: SQ Nozzle, quarter pattern (Purple)
- SQ-HLF: SQ Nozzle, half pattern (Brown)
- SQ-FUL: SQ Nozzle, full pattern (Red)
- SQ-ADP: SQ PolyFlex Riser Adapter only
- SQ-ADP12: SQ Nozzle Adapter with 12" PolyFlex Riser
- * Note: A PA-8S Plastic Shrub Adapter (see page 10) is needed when using an SQ Series Nozzle mounted on a SCH 80 riser.




SQ Nozzle Performance										
2.5 feet throw @ 6" height above grade										
Throw Precip.Rate Pressure Radius Flow Flow w/no over Nozzle psi ft. gph gpm in/h										
Q	20	2.5	6.0	0.10	1.64					
	30	2.5	7.0	0.12	1.90					
	40	3.0	7.2	0.12	1.32					
	50	3.0	7.2	0.12	1.32					
H	20	2.5	10.2	0.17	1.31					
	30	2.5	10.7	0.18	1.57					
	40	3.0	10.7	0.18	1.22					
	50	3.0	10.7	0.18	1.22					
F.	20	2.5	20.0	0.33	1.28					
	30	2.5	24.2	0.40	1.55					
	40	3.0	27.3	0.46	1.22					
	50	3.0	27.3	0.46	1.22					

SQ Nozz	SQ Nozzle Performance METRIC									
0.8 m thro	0.8 m throw @ 0.15 m height above grade									
Nozzle	Pressure bar	Flow lpm	Precip.Rate w/no overlap mm/h							
Q	1.4	8.0	23	0.38	42					
	2.1	8.0	27	0.44	48					
	2.8	0.9	27	0.45	34					
	3.4	0.9	27	0.45	34					
Н	1.4	0.8	39	0.65	33					
	2.1	0.8	41	0.68	40					
	2.8	0.9	41	0.68	31					
	3.4	0.9	41	0.68	31					
F	1.4	0.8	76	1.27	33					
	2.1	8.0	92	1.53	39					
•	2.8	0.9	103	1.72	31					
	3.4	0.9	103	1.72	31					

SQ Nozzle Performance										
4 feet throw @ 6" height above grade										
Nozzle	Precip.Rate w/no overlap in/h									
Q	20	4.0	6.0	0.10	0.64					
	30	4.0	7.2	0.12	0.74					
	40	4.5	7.2	0.12	0.59					
	50	4.5	7.2	0.12	0.59					
Н	20	4.0	10.2	0.17	0.51					
	30	4.0	10.7	0.18	0.61					
	40	4.5	10.7	0.18	0.54					
	50	4.5	10.7	0.18	0.54					
F	20	4.0	20.0	0.33	0.50					
	30	4.0	24.2	0.40	0.61					
•	40	4.5	27.3	0.46	0.54					
	50	4.5	27.3	0.46	0.54					

SQ Nozzle Performance METRIC									
1.2 m throw @ 0.15 m height above grade									
Nozzle	Pressure bar	Throw Radius m	Flow lph	Flow lpm	Precip.Rate w/no overlap mm/h				
Q	1.4	1.2	23	0.38	16				
	2.1	1.2	27	0.44	19				
,	2.8	1.4	27	0.45	15				
	3.4	1.4	27	0.45	15				
Н	1.4	1.2	39	0.65	13				
	2.1	1.2	41	0.68	16				
	2.8	1.4	41	0.68	14				
	3.4	1.4	41	0.68	14				
F	1.4	1.2	76	1.27	13				
	2.1	1.2	92	1.53	15				
•	2.8	1.4	103	1.72	14				
	3.4	1.4	103	1.72	14				

Performance data taken in zero wind conditions





Xeri-Pop[™] Micro-Spray

The Xeri-Pop Micro-Spray Makes It Easy to Integrate a Durable Micro-Spray into a Low-Volume Irrigation Design

Features

- The only pop-up spray that works in low-volume low-pressure application, and this is the perfect solution to vandal-prone areas
- Xeri-Pops can be installed and located in nearly any location and are ideal for small, odd-shaped planting beds; the 12" version is perfect for annual flower beds
- Xeri-Pops work with Rain Bird 5' and 8' MPR nozzles and SQ Series Nozzles — nozzles with square spray patterns and adjustable throws of 2.5' and 4'
- The Xeri-Pop can operate with 20 to 50 psi base pressure when water is supplied via ¹/₄" Distribution Tubing (XQ)
- The flexibility of 1/4" tubing allows the Xeri-Pop to be easily located and relocated as planting conditions dictate
- A durable, plastic snap-collar (on 4" and 6" models) secures the ¹/₄" tubing to the outside of the Xeri-Pop case
- The Xeri-Pop's ¼" Distribution Tubing can readily connect to ½" or ¾" polyethylene tubing or to a multi-outlet manifold (EMT-6XERI).
 Connections to polyethylene tubing are accomplished with either an SPB-025 ½" Self-piercing barb Connector or an XBF1CONN ¼" barb Connector
- External parts are UV-resistant and available in 4", 6" and 12" pop up heights

Operating Range

- Pressure: 20 to 50 psi (1.4 to 3.5 bar)
- Filtration: Depends on nozzle used with Xeri-Pop


Models


- XP-400X: 4-inch pop-up
- · XP-600X: 6-inch pop-up
- XP-1200X: 12-inch pop-up

Nozzle Options

- SQ Series Nozzles (page 120)
- 5 Series MPR Nozzle (all configurations)
- · 5 Series Plastic Bubbler
- 8 Series MPR Nozzle (8H, 8T and 8Q)

Installing the Xeri-Pop in 4 Easy Steps









Xeri-Bubblers™

Ideal for Shrub Plantings, Trees, Containers, and Flower Beds

Features


- · Adjust flow and radius by turning outer cap
- · Clean by completely unscrewing cap from base unit
- Three convenient installation connections available for design flexibility: 10-32 self-tapping thread, 1/4" barb, and 5" spike


Operating Range

- • Pressure: 15 to 30 psi (1.0 to 2.1 bar)
- SXB Series flow:
 - 0 to 13 gph (0 to 49.21 l/h) at 30 psi (2.1 bar)
 - 0 to 8.5 gph (0 to 30 l/h) at 15 psi (1 bar)
- UXB Series flow:
 - 0 to 35 gph (0 to 132.48 l/h) at 30 psi (2.1 bar)
 - 0 to 26 gph (0 to 98 l/h) at 15 psi (1 bar)
- · Max flow varies with inlet pressure


Models

- SXB-180: Half-circle, 5 streams, 10-32 thread
- SXB-180-025: Half-circle, 5 streams, 1/4" barb
- SXB-180-SPYK: Half-circle, 5 streams, 5" spike; includes barb x barb coupler
- SXB-360: Full-circle, 8 streams, 10-32 thread
- SXB-360-025: Full-circle, 8 streams, 1/4" barb
- SXB-360-SPYK: Full-circle, 8 streams, 5" spike includes barb x barb coupler
- UXB-360: Full-circle, umbrella, 10-32 thread
- UXB-360-025: Full-circle, umbrella, 1/4" barb
- UXB-360-SPYK: Full-circle, umbrella, 5" spike includes barb x barb coupler











Xeri-Bubb	Xeri-Bubbler Performance													
Pressure SXB Flow Rate 360° and 180°					360° neter	SXB 180)° Radius		360° Rate		360° neter			
psi	bar	gph	lph	ft.	m.	ft.	m.	gph	lph	ft.	m.			
30	2.1	0 - 13	0 - 49	0 - 3	0 - 0.9	0 - 2.2	0 - 0.67	0 - 35	0 - 132	0 - 2	0 - 0.58			
20	1.4	0 - 10.5	0 - 40	0 -2	0 - 0.6	0 - 1.5	0 - 0.46	0 - 30	0 - 113	0 -1	0 - 0.30			
15	1	0 - 8.5	0 - 32	0 -1.2	0 - 0.4	0 - 1.2	0 - 0.38	0 - 27	0 - 98	0 - 0.7	0 - 0.21			



Xeri-Sprays[™] and Misters

Ideal for Ground Cover, Mass Plantings, Annual Flower Beds, and Containers

Features

- · Adjust flow/radius by turning integral ball valve
- Uniform emission pattern provides excellent distribution
- 10-32 self-tapping threads fit into ½" x 10-32 adapter (10-32A); 1800 Xeri-Bubbler™ adapter (XBA-1800); and PolyFlex Riser (PFR-12)

Operating Range

- Flow: 0 to 31 gph (0 to 117.34 l/h)
- Pressure: 10 to 30 psi (0.75 to 2.1 bar)
- Radius: 0 to 13.4 feet (0 to 4.1 m) full-circle; 0 to 10.6 feet (0 to 3.2 m) quarter- and half-circle

Models

- · XS-090: Quarter-circle, spray
- XS-180: Half-circle, spray
- · XS-360: Full-circle, stream spray
- X360 ADJMST: Full-circle, mist

Xeri-Spray[™] 360° True Spray

Ideal for Mass Plantings, Ground Cover, Annual Flower Beds and Containers

Features


- True micro-spray with full-circle fan spray pattern
- · Adjust flow/radius by turning outer cap
- Three convenient installation connections for design flexibility: 10-32 self-tapping thread, $^1\!\!4''$ barb and 5" spike
- Easily cleaned by completely unscrewing cap from base unit

Operating Range

- Flow: 0 to 24.5 gph (0 to 92.7 l/h) at 30 psi (200 kpa)
- • Flow: 0 to 17 gph (0 to 64 l/h) at 15 psi (100 kPa)
- Pressure: 15 to 30 psi (1.0 to 2.1 bar)
- Radius: 0 to 6.7 feet (0 to 2.0 m)

Models

- · XS-360TS: 10-32 threads
- XS-360TS-025: ¼" barb
- XS-360TS-SPYK: 5" spike; includes barb x barb coupler





Xeri-Spra	Xeri-Sprays [™] and Misters Performance												
Pres	Pressure Flow		XS-90 Radius of throw		XS-180 Radius of throw		XS-360 Radius of throw		360 Mister Radius of throw				
psi	bar	gph	l/h	ft.	m.	ft.	m.	ft.	m.	ft.	m.		
10	0.7	0 - 16.7	0 - 63.21	0 - 6.4	0 - 2.0	0 - 6.7	0 - 2.0	0 - 9.2	0 - 2.8	0 - 1.5	0 - 0.46		
15	1.0	0 - 21.0	0 - 79.49	0 - 8.1	0 - 2.5	0 - 8.1	0 - 2.5	0 - 11.3	0 - 3.4	0 - 1.3	0 - 0.40		
20	1.4	0 - 24.5	0 - 92.73	0 - 9.4	0 - 2.9	0 - 9.5	0 - 2.9	0 - 12.9	0 - 3.9	0 - 1.5	0 - 0.44		
25	1.7	0 - 28.0	0 - 105.98	0 - 9.8	0 - 3.0	0 - 10.1	0 - 3.1	0 - 13.2	0 - 4.0	0 - 1.4	0 - 0.43		
30	2.1	0 - 31.0	0 - 117.34	0 - 10.3	0 - 3.1	0 - 10.6	0 - 3.2	0 - 13.4	0 - 4.1	0 - 1.3	0 - 0.40		

Diffuser Bug Cap

Features

- Prevents bugs and other debris from clogging 1/4" Distribution Tubing
- Barbed inlet fits into 1/4" Distribution Tubing (XQ)

Emission Devices and Distribution Components

Flanged shield diffuses water to minimize soil erosion at emission point

Operating Range

• Pressure: 0 to 50 psi (0 to 3.5 bar)

Models

• DBC-025: Black



PC Diffuser Cap

Features

- Cap snaps securely onto the PC Module and XB emitter outlet to create bubbler effect and prevent wash out
- · Designed for quick and easy installation
- · Made of UV-resistant polyethylene material

Models

- PC-DIFFUSER: Black
- PC-DIFF-PPL: Purple to designate non-potable water



Suggested Applications



- A. 1/4" tubing, 1/4" stake, PC Module, Diffuser Bug Cap. Used for runs greater than 5 feet from main line
- B. 1/4" tubing, 1/4" stake, Diffuser Bug Cap. Used for runs up to 5 feet from main line

(Drip emitter not shown – installed directly into lateral line)

Universal ¼" Tubing Stake

Features

- Holds ¼" Distribution Tubing and emitter or Diffuser Bug Cap firmly in place at the root zone of the plant
- Designed to securely hold Rain Bird and other manufacturers' ¼" Distribution Tubing — 0.16" to 0.18" I.D. and 0.22" to 0.25" O.D.
- Rigid stake featuring a flat enlarged head designed to withstand hammering into tough soil

Note: If emitter is installed at inlet to distribution tubing, use a Diffuser Bug Cap (DBC-025) at outlet of tubing to prevent bugs from clogging tubing and to help hold tubing in place

Model

• TS-025

gs 7 TS-025

1/4" Tubing Stake with Cap

Features

- Locking cap holds tubing in place
- Used for holding ¼" Distribution Tubing (XQ) in place at the plant root zone
- Accepts ¹/₄" Distribution Tubing from 0.19 O.D. to 0.256 O.D.
- Bug cap included
- Constructed of UV-resistant plastic material





12" PolyFlex Riser

Features

- 12" riser that is used with any 10-32 threaded emission device to deliver water directly to a plant. These include Xeri-Bugs, PC Modules, Xeri-Bubblers and Xeri-Sprays
- Extremely rugged and reliable – constructed of thick-walled, high-density polyethylene
- Can be used with a riser-stake (RS-025T)

Operating Range

 Pressure: 15 to 50 psi (1.0 to 3.5 bar)

Model

• PFR-12

PFR-12

PolyFlex Riser and Adapter Assemblies

Features

- 12" or 24" riser that is pre-assembled with a ½" male threaded base that simplifies installation
- Use with any 10-32 threaded emission device to deliver water directly to a plant. These include Xeri-Bugs, PC Modules, Xeri-Bubblers and Xeri-Sprays
- Newly-designed adapter with larger tabs makes installation quicker and easier; can be used on PVC laterals, or with any ½" female threaded adapter
- Adapter made of heavy-duty Marlex®, which requires no Teflon® tape, saving time during installation
- Extremely rugged and reliable PolyFlex Riser constructed of thick-walled, high-density polyethylene

Operating Range

• Pressure: 15 to 50 psi (1.0 to 3.5 bar)

Models

- PFR-FRA: 12" (30.5 cm) PolyFlex Riser and adapter
- PFR-FRA24: 24" (61.0 cm) PolyFlex Riser and adapter





PFR-FRA



PolyFlex Riser and Stake Assembly

Features

- 12" riser that is pre-assembled with a 7" (17.8 cm) stake
- Use with any 10-32 threaded emission device to deliver water directly to a plant. These include Xeri-Bugs, PC Modules, Xeri-Bubblers and Xeri-Sprays
- Saves time and money when installing a low-volume irrigation system
- Extremely rugged and reliable PolyFlex Riser constructed of thick-walled, high-density polyethylene

Operating Range

 Pressure: 15 to 50 psi (1.0 to 3.5 bar)

Model

PFR-RS

PFR-RS: 12" (30.5 cm)
 PolyFlex Riser and
 7" (17.8 cm) stake

Riser Stake-Threaded

Features

- Rugged 5" (12.7 cm) stake for use with PolyFlex Risers
- Constructed of UV-resistant plastic material
- Barbed side inlet accepts ¹/₄"
 Distribution Tubing (XQ)
- 10-32 threaded outlet permits easy threading of 12" (30.5 cm)
 PolyFlex Riser (PFR-12)

Operating Range

 Pressure: 15 to 50 psi (1.0 to 3.5 bar)

Model

RS-025T

RS-025T

10-32 Thread Adapter

Features

- Inlet: ½" FPT that screws onto any ½" MPT riser
- Outlet: 10-32 threads that accept Xeri-Bugs, PC Modules, Xeri-Bubblers and Xeri-Sprays with 10-32 threads
- Constructed of UV-resistant plastic material

Operating Range

 Pressure: 15 to 50 psi (1.0 to 3.5 bar)

Model

• 10-32A



1800 Xeri-Bubbler Adapter

Features

- Inlet: ½" female threads that screw onto a Rain Bird 1800 series or UNI-Spray or shrub adapter
- Outlet: 10-32 threads that accept any emission device with 10-32 threads including Xeri-Bugs, PC Modules, Xeri-Bubblers and Xeri-Sprays
- Sits at grade when installed on a spray head for a robust installation

Operating Range

• Pressure: 15 to 50 psi (1.0 to 3.5 bar)

Model

XBA-1800



Drip Irrigation

RWS (Root Watering System)

Root Watering System promotes deep root growth, healthy tree development, and accelerated growth

Features and Benefits

- Subsurface aeration and irrigation prevents tree and shrub transplant shock
- Highest efficiency solution for tree irrigation up to 95% emission uniformity with minimal wind, evaporation, or edge control losses
- Aesthetically designed subsurface bubbler contributes to a landscape's natural appearance
- · Locking grate at grade deters vandals
- · Helps prevent shallow root growth and hardscape damage
- Aesthetically attractive below grade installation
- Self-contained and factory assembled units for assured reliability (10", 18" and 36" sizes)

For the RWS Model:

- 4" (10.2 cm) retaining cap and vandal resistant locking grate tops a 36" (91.4 cm) semi-rigid mesh tube
- Factory installed swing assemblies (excluding RWS) with a 1401 (0.25 gpm; 0.95 l/m), 1402 (0.5 gpm; 1.9 l/m), or 1404 (1.00 gpm; 3.8 l/m) bubbler on a fixed riser makes connecting to lateral lines easy
- Options: Check valve to keep lines from draining (10 ft. min holdback)
 Sand sock for use in fine soils


For the RWS - Mini:

- 4" (10.2 cm) retaining cap and vandal resistant locking grate tops a 18" (45.7 cm) semi-rigid mesh tube
- Factory installed ½" spiral barb elbow with a 1401 or 1402 bubbler makes connecting to lateral lines easy
- Options: Check valve to keep lines from draining Sand sock for use in fine soils

For the RWS - Supplemental:

- 2" (5.1 cm) snap-on cap and base cap enclose a 10" (25.4 cm) semi-rigid mesh tube
- Factory installed ½" spiral barb elbow with PCT or 1401 bubbler makes connecting to lateral lines easy
- Options: Check valve to keep lines from draining
 Sand sock for use in fine soils







Model	Bubbler	Check Valve*	Swing Assembly w/ ½" (15/21) M NPT inlet	Spiral Barb Elbow w/ ½" (15/21) M NPT inlet
36" Root Watering System (with	4" (10.2 cm) vandal-resistant locking g	rate)		
RWS	Ideal for ¼" drip tubing or customer provided hardware	_	-	-
RWS-B-C-1401	0.25 gpm (0.95 l/m)	✓ (36")	✓	_
RWS-B-1401	0.25 gpm (0.95 l/m)	_	✓	_
RWS-B-X-1401	0.25 gpm (0.95 l/m)	_	✓ (18" with no elbow)	_
RWS-B-C-1402	0.50 gpm (1.9 l/m)	✓ (36")	✓	_
RWS-B-1402	0.50 gpm (1.9 l/m)	_	✓	_
RWS-B-C-1404	1.00 gpm (3.8 l/m)	✓ (36")	✓	_
18" Root Watering System - Mini	(with 4" (10.2 cm) vandal-resistant loc	king grate)		
RWS-M	Ideal for ¼ " drip tubing or customer provided hardware	_	-	-
RWS-M-B-C-1401	0.25 gpm (0.95 l/m)	✓ (18")	_	V
RWS-M-B-1401	0.25 gpm (0.95 l/m)	_	_	V
RWS-M-B-C-1402	0.50 gpm (1.9 l/m)	✓ (18")	_	V
RWS-M-B-1402	0.50 gpm (1.9 l/m)	_	_	V
10" Root Watering System - Sup	olemental (with 2" (5.1 cm) snap-on cap	and base)		
RWS-S-B-C-PCT5	5.0 gph (19 l/m)	✓ (10")	_	✓
RWS-S-B-C-1401	0.25 gpm (0.95 l/m)	✓ (10")	_	V
RWS-S-B-1401	0.25 gpm (0.95 l/m)	_	_	V
Root Watering - Accessories				
RWS-SOCK (Root Watering Sock)				
RWSGRATE (Root Watering System	Black Grate for RWS and RWS Mini)			
RWS- GRATE-P (Root Watering Syst	tem Purple Grate for RWS and RWS Mini)			

^{*} Check Valve is 14 ft. of holdback, or 6 PSI



Tubing	Application	Compatible Fittings	Flow Rates	Emitter Spacing	Coil Lengths	Tubing Diameter	Tube Colors	Special Notes
DRIPLINE								
¼" Landscape Dripline	Pots and Planter Boxes; Container and Vegetable Gardens; Shrubs; Flowers	XBF1CONN XBF2EL XBF3TEE	0.8 gph	6" 12"	100'	OD: 0.250" ID: 0.170"		Flexible tubing with clog- resistant built-in filtration
XFD On-Surface Dripline	On-surface; Shrubs; Flowers	XF Dripline Insert Fittings Easy Fit Compression Fittings	0.6 gph 0.9 gph	12" 18"	100' 250' 500'	OD: 0.634" ID: 0.536"	Reclaimed Water	Extra flexible tubing with clog resistant self-flushing emitter
XFCV; Check Valve; Dripline	On-Surface; Elevation Changes; Shrubs and Flowers	XF Dripline Insert Fittings Easy Fit Compression Fittings	0.6 gph 0.9 gph	12" 18"	100' 250' 500'	OD: 0.634" ID: 0.536"		Built-in Emitter Check Valves
XFS Sub-Surface Dripline	Sub-Surface; Narrow Planting Areas; Turf and Beds	XF Dripline Insert Fittings	0.4 gph 0.6 gph 0.9 gph	12" 18"	100' 500'	0D:0.634" ID: 0.536"	Reclaimed Water	Copper Shield' protects emitters from root intrusion
XFS-CV; Sub-Surface; Check Valve; Dripline	Sub-Surface; Elevation Changes; Turf and Beds	XF Dripline Insert Fittings	0.4 gph 0.6 gph 0.9 gph	12" 18"	100' 250' 500'	0D:0.634" ID: 0.536"	Reclaimed Water Reclaimed Water	Copper Shield' protects emitters from root intrusion 10' Emitter Check Valves
BLANKTUBING	G							
XQ ¼" Distribution Tubing	Extend emitter outlets to desired location	XBF1CONN XBF2EL XBF3TEE	_	_	100' 1,000' 1,000' (in bucket)	OD: 0.250" ID: 0.170"		Flexibility of Vinyl with hold of Poly
XBS Black Stripe Tubing	Five Color Stripe Choices Shrubs Flowers	1/2": Twist Lock Fittings – 3/4": Twist Lock Fittings – 800 Series	_	_	100' 500'	½" OD:0.700" ½" ID: 0.600" ½" OD: 0.705" ½" ID: 0.615" ¾" OD: 0.940" ¾" ID: 0.820"	Reclaimed Water	Black tube with colored stripes to differentiate zones
XT-700 Distribution Tubing	Thick-walled but Flexible Shrubs Flowers	1/2": Twist Lock Fittings – 600 Series	_	_	100' 500'	OD: 0.700" ID: 0.580"		Thick-walled, flexible tubing resists kinks
XF Series Blank Tubing	Shrubs Flowers	XF Dripline Insert Fittings Easy Fit Compression Fittings		_	100' 250' 500'	OD: 0.634" ID: 0.536"	Reclaimed Water Reclaimed Water	Extra Flexible
QF Dripline Header	Pre-fabricated header for dripline installations	Twist Lock Fittings - 800 Series (For QF Header - ¾") Twist Lock Fittings - 1000 Series (For QF Header - 1")	_	Elbow Spacing: 12" 18"	100'	3/4" OD: 0.940" 3/4" ID: 0.820" 1" OD: 1.200" 1" ID: 1.060"	Reclaimed Water	Elbows rotate 360° and incorporate a protective ring



XFD On-Surface Dripline

The Most Flexible, Pressure-Compensating In-line Emitter Tubing Available to Irrigate Ground Cover, Dense Plantings, Hedge Rows and More

Features

- Extra flexible tubing for fast, easy installation
- Dual-layered tubing (brown over black or purple over black) provides unmatched resistance to chemicals, UV damage and algae growth
- · Patent pending emitter design provides for increased reliability
- · Longer lateral runs than competition
- Unique material offers significantly greater flexibility, allowing tighter turns with fewer elbows for easier installation
- Choice of flow rates, spacing and coil lengths provides design flexibility for a variety of non-turfgrass applications
- Use an Air/Vaccum Relief Valve Kit when installation is below soil (pg 142)

Operating Range

- Pressure: 8.5 to 60 psi (0.58 to 4.1 bar)
- Flow rates: 0.6 gph and 0.9 gph (2.3 l/h and 3.5 l/h)
- Temperature: Water up to 100° F (37.8C); Ambient up to 125° F (51.7C)
- · Required filtration: 120 mesh

Specifications

- Outside diameter: 0.634" (16.1 mm)
- Inside diameter: 0.536" (13.6 mm)
- Wall thickness: 0.049" (1.2 mm)
- Spacing: 12" or 18"
- · Lengths: 100', 250', and 500' coils
- Use with XF Dripline Insert Fittings or Rain Bird Easy Fit Compression Fittings




XFD Dripline






XFD Dripline Offers Improved Flexibility for Kink Resistance and Easy Installation. The Dripline Can Bend Down to a 3" Radius Without Kinking.



Self-Dispensing Coil Reduces Layout Time and Improves Ease of Installation



XFD Dripline



Compatible Fittings



XF Dripline Insert Fittings (pg. 140)



Easy Fit Compression Fittings (pg. 141)

XFD On-Surface Dripline Models					
Model	Flow gph	Spacing in.	Coil Length ft.		
XFD-06-12-100	0.60	12	100		
XFD-06-12-250	0.60	12	250		
XFD-06-12-500	0.60	12	500		
XFD-06-18-100	0.60	18	100		
XFD-06-18-250	0.60	18	250		
XFD-06-18-500	0.60	18	500		
XFD-09-12-100	0.90	12	100		
XFD-09-12-250	0.90	12	250		
XFD-09-12-500	0.90	12	500		
XFD-09-18-100	0.90	18	100		
XFD-09-18-250	0.90	18	250		
XFD-09-18-500	0.90	18	500		
XFDP-06-12-500 (Purple)	0.60	12	500		
XFDP-06-18-500 (Purple)	0.60	18	500		
XFDP-09-12-500 (Purple)	0.90	12	500		
XFDP-09-18-500 (Purple)	0.90	18	500		

XFD On-Surface Dripline Models METRIC					
Model	Flow I/h	Spacing cm	Coil Length m		
XFD-06-12-100	2.30	30.5	30.5		
XFD-06-12-250	2.30	30.5	76.5		
XFD-06-12-500	2.30	30.5	152.4		
XFD-06-18-100	2.30	45.7	30.5		
XFD-06-18-250	2.30	45.7	76.5		
XFD-06-18-500	2.30	45.7	152.4		
XFD-09-12-100	3.40	30.5	30.5		
XFD-09-12-250	3.40	30.5	76.5		
XFD-09-12-500	3.40	30.5	152.4		
XFD-09-18-100	3.40	45.7	30.5		
XFD-09-18-250	3.40	45.7	76.5		
XFD-09-18-500	3.40	45.7	152.4		
XFDP-06-12-500 (Purple)	2.30	30.5	152.4		
XFDP-06-18-500 (Purple)	2.30	45.7	152.4		
XFDP-09-12-500 (Purple)	3.40	30.5	152.4		
XFDP-09-18-500 (Purple)	3.40	45.7	152.4		

Purple Stripe XFD also available.

For dripline applications requiring 0.4 gpm flow rate, use XF Series Dripline, page 134.

XFD On-Surface Dripline Maximum Lateral Lengths (Feet)					
Maximum Lateral Length (feet)					
Inlet 12" Spacing 18" Spacing				ng	
Pressure	Nominal	Flow (gph):	Nominal	Flow (gph):	
psi	0.6	0.9	0.6	0.9	
15	273	155	314	250	
20	318	169	353	294	
30	360	230	413	350	
40	395	255	465	402	
50	417	285	528	420	
60	460	290	596	455	

XFD On-Surface Dripline Flow(per 100 Feet of Tubing)						
Emitter Spacing	0.6 gph Er	nitter	0.9 gph En	nitter		
12"	61.0 gph	1.02 gpm	92.0 gph	1.53 gpm		
18"	41.0 gph	0.68 gpm	61.0 gph	1.02 gpm		
10	···o gpii	oloo gpiii	ono gpii	oz 9p		

XFD On-Surface Dripline Maximum Lateral Lengths (meters)						
	Maximum Lateral Length (meters)					
Inlet	30.5 cm		45.7 cm			
Pressure	Nominal F	low (I/h):	Nominal F	low (I/h):		
bar	2.3	3.4	2.3	3.4		
1.0	83.2	47.2	95.7	76.2		
1.4	96.9	51.5	107.6	89.6		
2.1	109.7	70.1	125.9	106.7		
2.8	120.4	77.7	141.7	122.5		
3.5	127.1	86.9	160.9	128.0		
4.1	140.2	88.4	181.7	138.7		

XFD On-Surface Dripline Flow(per 100 meters of Tubing)					
Emitter Spacing	2.3 l/h Em	itter	3.4 l/h Emi	tter	
0.30 meter	757.9 l/h	12.6 l/m	1136.7 l/h	18.9 l/m	
0.46 meter	502.2 l/h	8.4 l/m	741.3 l/h	12.4 l/m	



XFCV Dripline with Check Valve

Rain Bird® XFCV Dripline with a heavy-duty 3.5 psi check valve for onsurface applications adds a valuable member to the Rain Bird XF Series of Dripline. The XFCV is the most effective dripline in the industry and is ideal for areas where no other dripline will work. When used in applications where elevation changes exist, the patent-pending check valve keeps the dripline charged, holding 8 feet of hold back. Rain Bird's XFCV offers better uniformity and helps to prevent over-watering at the low-point in the zone, avoiding puddling and water draining from the dripline.

It accepts Rain Bird Easy Fit Compression Fittings, XF Dripline Barbed Insert Fittings and other 17 mm barbed insert fittings.



Simple

- Rain Bird's patent-pending 3.5 psi check valve technology keeps
 the dripline charged with water at all times, increasing uniformity of
 watering, and conserves water by eliminating the need to recharge the
 line at the beginning of each watering cycle
- Through the use of a proprietary tubing material, the XFCV Dripline with heavy-duty check valve is the most flexible dripline tubing in the industry, making it the easiest dripline to design with and install
- Rain Bird's low-profile emitter design reduces in-line pressure loss, allowing longer lateral runs, simplifying design and reducing installation time
- Variety of emitter flow rates, emitter spacing and coil lengths provide design flexibility for on-surface areas with or without elevation changes

Made with Recycled Content

 All Rain Bird XF Dripline (XFD, XFS, XFCV, XFS-CV) qualify for LEED credit 4.2 because they contain at least 20% Polyethylene post consumer recycled material by cost. These come in an assortment of coil sizes, flow rates and emitter spacing

Reliable

 The pressure-compensating emitter design provides a consistent flow over the entire lateral length ensuring higher uniformity for increased reliability in the pressure range of 20 to 60 psi

Durable


 Dual-layered tubing (brown over black) provides unmatched resistance to chemicals, algae growth and UV damage


Grit Tolerant

 Rain Bird's proprietary emitter design resists clogging by use of an extra wide flow path combined with a self-flushing action



XFCV Dripline for Elevated Applications





Operating Range

- Opening Pressure: 14.5 psi
- Pressure: 20 to 60 psi (1.38 to 4.14 bar)
- Flow rates: 0.6 and 0.9 gph (2.3 l/hr and 3.5 l/hr)
- Temperature:
 - Water: Up to 100°F (37.8° C)
 - Ambient: Up to 125°F (51.7° C)
- Required Filtration: 120 mesh

Specifications

- · Dimensions:
 - OD: 0.634" (16mm)
 - ID: 0.536" (13.6mm);
- Thickness: 0.049" (1.2mm)
- 12" & 18" (30.5 cm, 45.7 cm) spacing
- Available in 100' and 500' (30.5 m and 152.4 m) coils
- · Coil Color: Brown
- Use with XF Dripline Insert Fittings or Rain Bird Easy Fit Compression Fittings

Compatible Fittings



XF Dripline Insert Fittings (pg. 140)



Easy Fit Compression Fittings (pg. 141)

XFCV Dripline Mode	ls		
Model	Flow gph	Spacing in.	Coil Length ft.
XFCV-06-12-100	0.60	12	100
XFCV-06-12-500	0.60	12	500
XFCV-06-18-100	0.60	18	100
XFCV-06-18-500	0.60	18	500
XFCV-09-12-100	0.90	12	100
XFCV-09-12-500	0.90	12	500
XFCV-09-18-100	0.90	18	100
XFCV-09-18-500	0.90	18	500

XFCV Dripline Maximum Lateral Lengths (Feet)					
Maximum Lateral Length (feet)					
Inlet	Inlet 12" Spacing 18" Spacing				
Pressure	Nominal	Flow (gph):	Nominal	Flow (gph):	
psi	0.6	0.9	0.6	0.9	
20	192	136	254	215	
30	289	205	402	337	
40	350	248	498	416	
50	397	281	573	477	
60	436	309	637	529	

XFCV Dripline Mod	els		METRIC
Model	Flow I/h	Spacing cm	Coil Length m
XFCV-06-12-100	2.30	30.5	30.5
XFCV-06-12-500	2.30	30.5	152.4
XFCV-06-18-100	2.30	45.7	30.5
XFCV-06-18-500	2.30	45.7	152.4
XFCV-09-12-100	3.40	30.5	30.5
XFCV-09-12-500	3.40	30.5	152.4
XFCV-09-18-100	3.40	45.7	30.5
XFCV-09-18-500	3.40	45.7	152.4

XFCV Dri	pline Max	imum Lateral	Lengths (Me	eters) METRIC
		Maximum L	ateral Length (meters)
Inlet	30.5 cm		45.7 cm	
Pressure	Nominal	Flow (I/h):	Nominal	Flow (I/h):
bar	2.3	3.4	2.3	3.4
1.4	59	41	77	66
2.1	88	63	123	103
2.8	107	76	152	127
3.5	121	86	175	145
4.1	133	94	194	161



XFS Sub-Surface Dripline with Copper Shield™ Technology

Sub-Surface Drip Irrigation (SDI) perfect for small, narrow and tight planting areas, switchbacks, as well as all turf landscapes

Rain Bird® XFS Sub-Surface Copper-Colored Dripline with Copper Shield™ Technology is the latest innovation in the Rain Bird Landscape Drip Family. Rain Bird's patent-pending Copper Shield Technology protects the emitter from root intrusion, creating a long-lasting, low maintenance sub-surface drip irrigation system for use under turf grass or shrub and groundcover areas

A proprietary tubing material makes the XFS Sub-Surface Dripline with Copper Shield the most flexible tubing in the industry, and the easiest subsurface dripline to design with and install.

Features

Simple

- Rain Bird's low-profile emitter design reduces in-line pressure loss, allowing longer lateral runs, simplifying design and reducing installation time
- Variety of emitter flow rates, emitter spacing and coil lengths provide design flexibility for either sub-surface turf or sub-surface shrub and groundcover applications

Reliable

- XFS Sub-Surface Dripline emitters are protected from root intrusion by Rain Bird's patent-pending Copper Shield™ Technology resulting in a system that does not require maintenance or replacement of chemicals to prevent root intrusion
- The pressure-compensating emitter design provides a consistent flow over the entire lateral length ensuring higher uniformity for increased reliability in the pressure range of 8.5 to 60 psi

Durable

- Dual-layered tubing (copper over black) provides unmatched resistance to chemicals, algae growth and UV damage
- Grit Tolerant: Rain Bird's proprietary emitter design resists clogging by use of an extra-wide flow path combined with a self-flushing action

Operating Range


- Pressure: 8.5 to 60 psi (0.58 to 4.14 bar)
- Flow rates: 0.4 gph, 0.6, and 0.9 gph (1.6 l/h, 2.3 l/hr and 3.5 l/hr)
- Temperature:
 - Water: Up to 100°F (37.8° C)
 - Ambient: Up to 125°F (51.7° C)
- · Required Filtration: 120 mesh

Specifications

- Dimensions: OD: 0.634" (16mm); ID: 0.536" (13.6mm);
 Thickness: 0.049" (1.2mm)
- 12" and 18" (30.5 cm and 45.7 cm) spacing
- Available in 100' and 500' (30.5 m and 152.4 m) coils
- · Coil Color: Copper
- Use with XF Dripline Insert Fittings



XFS Sub-Surface Dripline




XFS Sub-Surface Dripline with Copper Shield Technology



XFS Dripline offers increased flexibility for easy installation



Irrigation Association Show Winner



Orip Irrigatio

XF Dripline Insert Fittings

XF Dripline Insert Fittings offer a unique barb design to reduce insertion force and still retain a secure fit (p. 140)



XF Dripline Insert Fittings (pg. 140)

We recommend using the XF Insertion Tool (FITINS-TOOL) which lowers the effort required to insert each fitting by 50% (p. 142)



FITINS-TOOL

XFS Sub-Surface Dripline I	XFS Sub-Surface Dripline Models						
Model	Flow gph	Spacing in.	Coil Length ft.				
XFS-04-12-100	0.42	12	100				
XFS-04-12-500	0.42	12	500				
XFS-04-18-100	0.42	18	100				
XFS-04-18-500	0.42	18	500				
XFS-06-12-100	0.60	12	100				
XFS-06-12-500	0.60	12	500				
XFS-06-18-100	0.60	18	100				
XFS-06-18-500	0.60	18	500				
XFS-09-12-100	0.90	12	100				
XFS-09-12-500	0.90	12	500				
XFS-09-18-100	0.90	18	100				
XFS-09-18-500	0.90	18	500				
XFSP-04-12-500 (Purple)	0.42	12	500				
XFSP-04-18-500 (Purple)	0.42	18	500				
XFSP-06-12-500 (Purple)	0.60	12	500				
XFSP-06-18-500 (Purple)	0.60	18	500				
XFSP-09-12-500 (Purple)	0.90	12	500				
XFSP-09-18-500 (Purple)	0.90	18	500				

Purple	Stripe	XFD	also	available.
--------	--------	-----	------	------------

XFS Sub-Surface Dripline Maximum Lateral Lengths (Feet)

		Ma	ximum La	teral Leng	th (feet)		
Inlet	12" Spa	cing		18" Spa	cing		
Pressure	Nomina				Nominal Flow (gph):		
psi	0.42	0.6	0.9	0.42	0.6	0.9	
15	352	273	155	374	314	250	
20	399	318	169	417	353	294	
30	447	360	230	481	413	350	
40	488	395	255	530	465	402	
50	505	417	285	610	528	420	
60	573	460	290	734	596	455	

XFS Sub-Surface Dripline Flow(per 100 Feet of Tubing)

Emitter Spacing		0.42 gph 0.6 gph 0.9 Emitter Emitter Emitter						
	gph	gpm	gph	gpm	gph	gpm		
12"	42.0 gph	0.70 gpm	61.0 gph	1.02 gpm	92.0 gph	1.53 gpm		
18"	28.0 gph	0.47 gpm	41.0 gph	0.68 gpm	61.0 gph	1.02 gpm		

XFS Sub-Surface Dripline I	Models		METRIC
Model	Flow	Spacing	Coil Length
	I/h	cm	m
XFS-04-12-100	1.60	30.5	30.5
XFS-04-12-500	1.60	30.5	152.4
XFS-04-18-100	1.60	45.7	30.5
XFS-04-18-500	1.60	45.7	152.4
XFS-06-12-100	2.30	30.5	30.5
XFS-06-12-500	2.30	30.5	152.4
XFS-06-18-100	2.30	45.7	30.5
XFS-06-18-500	2.30	45.7	152.4
XFS-09-12-100	3.50	30.5	30.5
XFS-09-12-500	3.50	30.5	152.4
XFS-09-18-100	3.50	45.7	30.5
XFS-09-18-500	3.50	45.7	152.4
XFSP-04-12-500 (Purple)	1.60	30.5	152.4
XFSP-04-18-500 (Purple)	1.60	45.7	152.4
XFSP-06-12-500 (Purple)	2.30	30.5	152.4
XFSP-06-18-500 (Purple)	2.30	45.7	152.4
XFSP-09-12-500 (Purple)	3.50	30.5	152.4
XFSP-09-18-500 (Purple)	3.50	45.7	152.4

Purple Stripe XFD also available.

XFS Sub-Surface Dripline Maximum Lateral Lengths (meters)

	Maximum Lateral Length (meters)						
Inlet	30.5 cm	1		45.7 cm			
Pressure	Nomina	Nominal Flow (I/h):			Nominal Flow (I/h):		
bar	1.6	2.3	3.4	1.6	2.3	3.4	
1.0	107.2	83.2	47.2	114	95.7	76.2	
1.4	121.6	96.9	51.5	127.1	107.6	89.6	
2.1	136.2	109.7	70.1	146.6	125.9	106.7	
2.8	148.7	120.4	77.7	161.5	141.7	122.5	
3.5	153.9	127.1	86.9	185.9	160.9	128.0	
4.1	174.6	140.2	88.4	223.7	181.7	138.7	
3.5	153.9	127.1	86.9	185.9	160.9	128.0	

XFS Sub-Surface Dripline Flow(per 100 Meters of Tubing)

Emitter Spacing	1.6 l/h Emitter		2.3 l/h Emitter		3.4 l/h Emitter	
	l/h	l/m	l/h	l/m	l/h	l/m
0.30 meter	531.1 l/h	8.85 l/m	757.9 l/h	12.6 l/m	1136.7 l/h	18.9 l/m
0.46 meter	351.8 l/h	5.86 l/m	502.2 l/h	8.4 l/m	741.3 l/h	12.4 l/m



XFS-CV Dripline with Heavy-Duty Check Valve



Rain Bird® XFS-CV Dripline with an improved 4.3 psi check valve delivers 10 feet of hold-back – the highest in the industry.

With pure copper chips in every emitter to protect against emitter root intrusion, XFS-CV dripline is an all-in-one dripline suitable for any application – on-surface, sub-surface, sloped or level-grade.

When used in applications where elevation changes exist, the patent-pending check valve keeps the dripline charged with water, delivering better irrigation uniformity while preventing over-watering and puddling at the low-point in the zone.

It accepts Rain Bird XF Dripline Barbed Insert Fittings, RB 600 Series Twist Lock Fittings, and other 17 mm barbed insert fittings.

A proprietary tubing material makes the XFS Sub-Surface Dripline with Copper Shield the most flexible tubing in the industry, and the easiest sub-surface dripline to design with and install.

Features

Simple

- Rain Bird's patent-pending 4.3 psi check valve technology keeps
 the dripline charged with water at all times, increasing uniformity of
 watering, and conserves water by eliminating the need to recharge the
 line at the beginning of each watering cycle
- XFS-CV Sub-Surface Dripline emitters are protected from root intrusion by Rain Bird's patent-pending Copper Shield™ Technology resulting in a system that does not require maintenance or replacement of chemicals to prevent root intrusion• Through the use of a proprietary tubing material, the XFS-CV Dripline with heavy-duty check valve is the most flexible dripline tubing in the industry, making it the easiest dripline to design with and install
- Rain Bird's low-profile emitter design reduces in-line pressure loss, allowing longer lateral runs, simplifying design and reducing installation time
- Variety of standard emitter flow rates, emitter spacing and coil lengths provide design flexibility for sub-surface and on-surface areas with or without elevation changes

Made with Recycled Content

 All Rain Bird XF Dripline (XFD, XFS, XFCV, XFS-CV) qualify for LEED credit 4.2 because they contain at least 20% Polyethylene post consumer recycled material by cost. These come in an assortment of coil sizes, flow rates and emitter spacing

Reliable

 The pressure-compensating emitter design provides a consistent flow over the entire lateral length ensuring higher uniformity for increased reliability in the pressure range of 20 to 60 psi

Durable

 Dual-layered tubing (copper over black) provides unmatched resistance to chemicals, algae growth and UV damage

Grit Tolerant

• Rain Bird's proprietary emitter design resists clogging by use of an extra wide flow path combined with a self-flushing action




XFS-CV Dripline for Elevated Applications

With XFS-CV's built-in 4.3 check valve, all lines are kept charged and up to 10 feet of water is held back









Operating Range

- Opening Pressure: 14.5 psi
- Pressure: 20 to 60 psi (1.38 to 4.14 bar)
- Flow rates: 0.6 and 0.9 gph (2.3 l/hr and 3.5 l/hr)
- Temperature:
 - Water: Up to 100°F (37.8° C)
 - Ambient: Up to 125°F (51.7° C)
- Required Filtration: 120 mesh

Specifications

- · Dimensions:
 - OD: 0.634" (16mm)
 - ID: 0.536" (13.6mm);
- Thickness: 0.049" (1.2mm)
- 12" & 18" (30.5 cm, 45.7 cm) spacing
- Available in 100', 250' and 500' (30.5 m, 76.2 m and 152.4 m) coils
- Coil Colors: Copper, purple, purple stripe
- Use with XF Dripline Insert Fittings

XF Dripline Insert Fittings

XF Dripline Insert Fittings offer a unique barb design to reduce insertion force and still retain a secure fit (p. 140)



XF Dripline Insert Fittings (pg. 140)

We recommend using the XF Insertion Tool (FITINS-TOOL) which lowers the effort required to insert each fitting by 50% (p. 142)



FITINS-TOOL

XFS-CV D	XFS-CV Dripline Maximum Lateral Lengths (Feet)						
			_ateral Length				
Inlet	12" Spaci	ng	18" Spaciı	ng			
Pressure	Nominal	Flow (gph):	Nominal	Flow (gph):			
psi	0.6	0.9	0.6	0.9			
20	192	136	254	215			
30	289	205	402	337			
40	350	248	498	416			
50	397	281	573	477			
60	436	309	637	529			

XFS-CV D	Pripline Ma	ximum Later	al Lengths (N	Meters)		
	Maximum Lateral Length (meters)					
Inlet	30.5 cm		45.7 cm			
Pressure	Nominal	Flow (I/h):	Nominal I	Flow (I/h):		
bar	2.3	3.4	2.3	3.4		
1.4	59	41	77	66		
2.1	88	63	123	103		
2.8	107	76	152	127		
3.5	121	86	175	145		
4.1	133	94	194	161		





QF Dripline Header

A Quick and Flexible Solution to Dripline Headers

The QF Dripline Header is a patent pending product that is the landscape industry's first pre-fabricated header for dripline installations. A Quick and Flexible replacement for a site-built header, the QF Dripline Header saves time and labor expense. Using a proprietary blend of polyethylene, similar to Rain Bird's XF Series Dripline, the QF Dripline header allows installers to simply roll out the header and attach the dripline at guaranteed 12" or 18" spacing. Eliminating the need for measuring, cutting, gluing and taping, the QF Dripline Header saves time and money, making projects more profitable.

Features

- The QF Dripline Header elbows rotate 360° and incorporate a protective ring — preventing damage and ensuring a proper seal.
- The ring also provides leverage to make attaching the dripline easier.
- The rotating barb manages trenching misalignment. Move left or right to accommodate the dripline – no need to re-trench.
- Elbows utilize the same design as Rain Bird's popular XFF Fitting requiring 50% less insertion force, and are compatible with the XFF Fittings Tool.

Specifications

	QF Header - 3/4"	QF Header - 1"
• Outside Diameter:	0.940" (23.9mm)	1.200" (30.5mm)
• Inside Diameter:	0.820" (20.8mm)	1.060" (26.9mm)
 Wall Thickness: 	0.060" (1.5mm)	0.070" (1.8mm)

Models

- XQF7512100: XQF 3/4" Dripline Header (12" Spacing 100' Coil)
- XQF7518100: XQF 3/4" Dripline Header (18" Spacing 100' Coil)
- XQF1012100: XQF 1" Dripline Header (12" Spacing 100' Coil)
- XQF1018100: XQF 1" Dripline Header (18" Spacing 100' Coil)
- XQF101210P: XQF 1"Dripline Header (12"Spacing 100'Coil) Purple
- XQF101810P: XQF 1"Dripline Header (18"Spacing 100'Coil) Purple





QF Dripline Header



Compatible Fittings



Twist Lock Fittings 800 Series (pg. 139)


(For QF Header - 3/4")



Twist Lock Fittings 1000 Series (pg. 139)

(For QF Header - 1")





Orip Irrigatio

Twist Lock Fittings

Durable and Reliable. Rain Bird's NEW Twist Lock Fittings

- Complete line of Twist Lock Fittings to simplify installation of QF Header and Blank Distribution Tubing
- Fittings provide an even tighter seal on tubing by using high quality barbs and twist locking nuts
- Unique barb design reduces insertion force while maintaining a secure fit

Operating Range

• Pressure: 0 to 60 psi (0 to 4.1 bar)

Models

600 SERIES (1/2"):


- TLF-CUPL-0600: Twist Lock Fitting 1/2" Coupler
- TLF-TEE-0600: Twist Lock Fitting 1/2" Tee
- TLF-ELBW-0600: Twist Lock Fitting 1/2" Elbow
- TLF-MPT6-0600: Twist Lock Fitting ½" NPT to ½" Adaptor
- TLF-MPT8-0600: Twist Lock Fitting 3/4" NPT to 1/2" Adaptor

800 SERIES (3/4"):

- TLF-CUPL-0800: Twist Lock Fitting 3/4" Coupler
- TLF-TEE-0800: Twist Lock Fitting 34" Tee
- TLF-ELBW-0800: Twist Lock Fitting 3/4" Elbow
- TLF-MPT8-0800: Twist Lock Fitting ¾" NPT Adaptor
- TLF-CAP-0800: Twist Lock Fitting ¾"Cap







2 Step Installation

1000 SERIES (1"):

- TLF-CUPL-1000: Twist Lock Fitting 1" Coupler
- TLF-TEE-1000: Twist Lock Fitting 1"Tee
- TLF-ELBW-1000: Twist Lock Fitting 1" Elbow
- TLF-MPT8-1000: Twist Lock Fitting 1" NPT Adaptor

	600 Series		800 Series		1000 Series	
	Inches	mm	Inches	mm	Inches	mm
Acceptable Internal Diameter	0.590 to 0.630	15 to 16	0.790 to 0.845	20.0 to 21.5	1.025 to 1.085	26.0 to 27.6
Acceptable Wall Thickness	0.025 to 0.050	0.64 to 1.27	0.045 to 0.065	1.14 to 1.65	0.045 to 0.065	1.14 to 1.65
Compatible Tubing	XFD, XT70	0, ½" XBS	3/4" XBS, 3/4"	QF Header	1" QF H	leader





XF Dripline Insert Fittings

Features

- Complete line of 17mm insert fittings to simplify installation of XF Series Dripline
- · High quality barbs grab tubing for a secure fit
- Unique barb design to reduce insertion force and still retain a secure fit
- Non-obtrusive colored fittings to compliment natural earth tones


Operating Range

 Pressure: 0 to 50 psi (1.0 to 3.5 bar) if using 60 psi (4.1 bar) clamps will be required

Models

- XFF-COUP: 17mm Barb x Barb Coupling
- XFF-ELBOW: 17mm Barb x Barb Elbow
- XFF-MA-050: 17mm Barb x 1/2" MPT Male Adapter
- XFF-TEE: 17mm Barb x Barb x Barb Tee
- XFF-TMA-050: 17mm Barb x 1/2" MPT x 17mm Barb Tee Male Adapter
- XFF-MA-075: 17mm Barb x 3/4" MPT Male Adapter
- XFF-FA-050: Low profile barb elbow female adapter 17mm x 1/2" FPT
- XFF-TFA-050: Low profile barb tee female adapter 17mm x 1/2" FPT x 17mm
- XFD-CROSS: Barb cross 17mm x 17mm x 17mm x 17mm
- XFD-TFA-075: Barb tee female adapter 17mm x 3/4"FPT x 17mm
- LD16STK: 7 ¾" barbed tubing plastic stake
- FITINS-TOOL: XF Fitting Insertion Tool. Compatible with XFF-COUP, XFF-ELBOW, XFF-TEE, and QF Dripline Header





We recommend using the XF Insertion Tool (FITINS-TOOL) which lowers the effort required to insert each fitting by 50% (p. 142)



Drip Irrigation

Easy Fit Compression Fitting System

Complete system of compression fittings and adapters for all tubing connection needs in a low-volume system

Features

- Reduces inventory costs: Multi-diameter compression fittings work with a wide range of 16mm - 17mm tubing or dripline
- Saves time and effort: 50% less force is required to connect tubing and fittings versus competitive compression fittings. Adapters swivel for easy installation
- Provides increased flexibility: Just three Easy Fit Fittings and five Easy Fit Adapters are needed to make over 160 combinations of connections, accommodating countless installation and maintenance situations
- Works with all 16-17mm dripline and blank tubing
- Patented fittings and adapters are molded from UV-resistant and durable ABS materials
- Removable flush caps can be used to flush end of line and temporarily cap off lines for later expansion
 - Not recommended with subsurface irrigation

Operating Range

- Pressure: 0 to 60 psi (0 to 4.1 bar)
- Accepts tubing with an O.D. of 0.630" to 0.669" (16-17mm)
- · Recommended for use above surface only

Models

- · Easy Fit Fittings
 - MDCF-COUP: Coupling
 - MDCF-EL: Elbow
 - MDCF-TEE: Tee

· Easy Fit Adapters

- MDCF-50MPT: 1/2" Male Pipe Thread Adapter
- MDCF-75MPT: 3/4" Male Pipe Thread Adapter
- MDCF-50FPT: ½" Female Pipe Thread Adapter
- MDCF-75FPT: 3/4" Female Pipe Thread Adapter
- MDCF-75FHT: 3/4" Female Hose Thread Adapter
- MDCF-CAP: Removable Flush Cap For Easy Fit Fittings (Black)
- MDCF-PCAP: Removable Flush Cap For Easy Fit Fittings (Purple, to designate non-potable water)

Note: Easy Fit Adapters are not barbed fittings. They are to be used only with Easy Fit Compression Fittings.

Friction Loss per Fitting						
		METRIC				
Flow gpm	Loss psi	Flow I/h	Loss bar			
0.00	0.00	0.00	0.00			
1.00	0.3	227.1	0.03			
2.00	0.64	454.3	0.04			
3.00	0.82	681.4	0.06			
4.00	1.45	908.5	0.10			
5.00	1.90	1135.6	0.13			
6.00	2.57	1362.8	0.18			





XF Insertion Tool

The XF Insertion Tool reduces the effort required to insert the fittings into the tube by 50%.

Features

- 50% Less effort required to install fittings than without a tool
- Firmly locks fittings into place while inserting Dripline
- Tool helps widen the dripline opening to make the fitting insertion easier
- Solid grip and comfortable fit in hand

Model

• FITINS-TOOL



The XF Insertion Tool works with the following XF Fittings:







XFF-COUP

XFF-ELBOW

XFF-TEE



The XF Insertion Tool securely locks fittings into place to make inserting dripline easier.



The tool also has a sloped valley to allow room for the dripline when inserting a fitting onto the second side.

Air/Vacuum Relief Valve Kit

Features

- Use with Rain Bird XF-Series or Landscape Dripline inline emitter tubing when installation is below soil*
- Made of quality rust-proof materials
- Fits inside an SEB 7XB emitter box

*Rain Bird recommends XFS dripline with Copper Shield™ for subsurface installations, including installations under turf grass.

Model

• ARV050: 1/2" Air Relief Valve



Maximum Length of Dripline Useable with the ARV						
1/2" ARV						
0.6 GPH	0.9 GPH					
639'	424'					
958'	636'					
1278'	848'					
Total Flow (GPM) 6.5						
ral Flow (GPH) 390						
	0.6 GPH 639' 958' 1278'					

Maximum Length of Dripline Useable with the ARV METRIC						
	1/2" ARV					
Emitter Spacing	2.3 l/h	3.4 l/h				
0.30 m	195	129				
0.46 m	292	194				
0.61 m	390 258					
ARV Capacity						
Total Flow (I/m) 24.6						
Total Flow (I/h)	1	1476				

Install Air/Vacuum Relief Valves correctly by:

Locate at the highest point(s) of the dripline zone. Install the valve in an exhaust header or a line that runs perpendicular to the lateral rows to ensure all rows of the dripline can take advantage of the air/vacuum relief valve

Drip System Operation Indicator

Features

- Stem rises 6" for clear visibility
- When stem is extended, drip system is charged to a minimum of 15 psi
- Operational Indicator Kit includes three different indication caps: potable, non-potable, or an adjustable 4-VAN spray nozzle
- Includes 16" of ¼" distribution tubing with connection fitting pre-installed



XF Series Blank Tubing

Features:

- · Greater flexibility is easier to install and saves time
- Brown color matches landscape and blends with mulch. Matches XF Series Dripline inline emitter tubing
- Compatible with XF Series Dripline (0.536" I.D. x 0.634" O.D.)
- · Accepts Rain Bird Easy Fit Compression Fittings, XF Dripline Insert Fittings, and 17mm insert fittings
- · Not compatible with 16 mm fittings

Specifications

- Outside Diameter: 0.634" (16.1mm)
- Inside Diameter: 0.536" (13.6mm)
- Wall Thickness: 0.049" (1.2mm)



XFD100

Models:

- XFD100: 100 ft. coil (30m)
- XFD250: 250 ft. coil (76m)
- XFD500: 500 ft. coil (152m)

XF Blank Tubing Friction Loss Characteristics								
O.D634" I.D536"				O.D. 16.1mm	I.D. 13.6mm	METRIC		
Flow gpm	Velocity fps	Loss psi		Flow I/h	Velocity m/s	Loss bar		
0.50	0.70	0.27		113.56	0.21	0.06		
1.00	1.40	0.97		227.12	0.43	0.22		
1.50	2.10	2.06		340.69	0.64	0.46		
2.00	2.80	3.50		454.25	0.85	0.79		
2.50	3.50	5.29		567.81	1.07	1.20		
3.00	4.20	7.42		681.37	1.28	1.68		
3.50	4.90	9.87		794.94	1.49	2.23		
4.00	5.60	12.64		908.50	1.71	2.86		
4.50	6.30	15.72		1022.06	1.92	3.56		
5.00	7.00	19.11		1135.62	2.13	4.32		
5.50	7.70	22.80		1249.19	2.35	5.16		
6.00	8.40	26.78		1362.75	2.56	6.06		

Psi Loss Per 100 Feet of Pipe (psi/100ft.)

bar Loss per 100 Meters of Pipe (bar/100m)

Note: Use of tubing at flows shown in dark shaded area is not recommended, as velocities exceed 5 ft/sec (1.5 m/s)

Note: Purple and Purple Stripe also available.

XT-700 Distribution Tubing

Durable, thick-walled distribution tubing stands up to harsh conditions and performs well in all climates

- Thick-walled, flexible tubing resists kinks and damage caused by routine landscape maintenance activities
- Extruded from UV-resistant polyethylene resin materials

Operating Range

• Pressure: 0 to 60 psi (0 to 4.1 bar)

Specifications

- Outside diameter: 0.700" (18 mm)
- Inside diameter: 0.580" (15 mm)
- Wall thickness: 0.06" (1.5 mm)



XT-700-100

Models

- XT-700-100: 100-foot coil (30 m)
- XT-700-500: 500-foot coil (152 m)

Note: For both water conservation and appearance, it is recommended that a 2" to 3" (5 to 8 cm) mulch cover be placed on top of the tubing

CT-700 Tubing Friction Loss Characteristics

O.D700"	I.D580"		O.D. 18 mm	I.D. 15 mm		METRIC
Flow gpm	Velocity fps	Loss psi	Flow m³/h	Flow I/h	Velocity m/s	Loss bar
0.50	0.61	0.19	0.11	0.03	0.19	0.01
1.00	1.21	0.69	0.23	0.06	0.37	0.05
1.50	1.82	1.45	0.34	0.09	0.56	0.10
2.00	2.43	2.47	0.45	0.13	0.74	0.17
2.50	3.03	3.74	0.57	0.16	0.92	0.26
3.00	3.64	5.24	0.68	0.19	1.11	0.36
3.50	4.24	6.97	0.79	0.22	1.29	0.48
4.00	4.85	8.93	0.91	0.25	1.48	0.62
4.50	5.46	11.10	1.02	0.28	1.67	0.77
5.00	6.06	13.50	1.14	0.32	1.85	0.93
5.50	6.67	16.10	1.25	0.35	2.03	1.11
6.00	7.28	18.92	1.36	0.38	2.22	1.31

psi Loss per 100 Feet of Pipe (psi/100ft.) bar Loss per 100 Meters of Pipe (bar/100m) **Note:** Use of tubing at flows shown in dark shaded area is not recommended, as velocities

Compatible Fittings



Twist Lock Fittings 600 Series (pg. 139) XT-700 & 1/2" XBS



exceed 5 ft/sec (1.5 m/s)

Twist Lock Fittings 800 Series (pg. 139) 34" XBS



XBS - Black Stripe Tubing

High quality, flexible tubing for use in any low-volume irrigation system

Features

- 1/2" & 3/4" blank tubing extruded from polyethylene resin materials for consistent durability
- 1/2" tubing is now available in two different sizes: 0.600" I.D. X 0.700"
 O.D. and 0.615" I.D. X 0.705" O.D.
- · Available in five color stripes to differentiate zones
- UV-resistant for installations at or below grade
- · Compact coils for easy storage and shipping

Operating Range

• Pressure: 0 to 60 psi (0 to 4.1 bar)

Models

XBS 700 - 1/2" Tubing Models - 600-700

- Outside diameter: 0.700" (17.8 mm)
- Inside diameter: 0.600" (15.2 mm)
- Wall thickness: 0.050" (1.3 mm)
- XBS700G100: 1/2" tubing, 100 foot (30 m) coil with green striping
- XBS700G500: 1/2" tubing, 500 foot (152 m) coil with green striping
- XBS700P100: 1/2" tubing, 100 foot (30 m) coil with purple striping
- XBS700P500: 1/2" tubing, 500 foot (152 m) coil with purple striping

XBS - 1/2" Tubing Models

- Outside diameter: 0.705" (18 mm)
- Inside diameter: 0.615" (15.6 mm)
- Wall thickness: 0.045" (1.2 mm)
- XBS100: 1/2" tubing, 100 foot (30 m) coil with green striping
- XBS500: 1/2" tubing, 500 foot (152 m) coil with green striping
- XBS500B: 1/2" tubing, 500 foot (152 m) coil with black striping
- XBS500R: 1/2" tubing, 500 foot (152 m) coil with red striping
- XBS500Y: 1/2" tubing, 500 foot (152 m) coil with yellow striping
- XBS500P: 1/2" tubing, 500 foot (152 m) coil with purple striping

XBS 940 - 34" Tubing Models

- · Outside diameter: 0.940" (24 mm)
- Inside diameter: 0.820" (21 mm)
- Wall thickness: 0.060" (1.5 mm)
- XBS940G500: 3/4" tubing, 500 foot (152 m) coil with green striping
- XBS940P500: 3/4" tubing, 500 foot (152 m) coil with purple striping



XBS 700 - 1/2" Tubing Friction Loss Characteristics								
O.D700" I.D.	.600"			O.D. 17.8mm I.D. 15.2mm METRIC				
Flow gpm	Velocity fps	Loss psi		Flow I/h	Velocity m/s	Loss bar		
0.50	0.57	0.16		1.89	0.17	0.04		
1.00	1.14	0.58		3.79	0.35	0.13		
1.50	1.70	1.22		5.68	0.52	0.27		
2.00	2.27	2.08		7.57	0.69	0.46		
2.50	2.84	3.15		9.46	0.87	0.70		
3.00	3.41	4.41		11.36	1.04	0.98		
3.50	3.97	5.87		13.25	1.21	1.30		
4.00	4.54	7.52		15.14	1.38	1.67		
4.50	5.11	9.35		17.03	1.56	2.07		
5.00	5.68	11.36		18.93	1.73	2.16		
5.50	6.24	13.55		20.82	1.90	3.01		
6.00	6.81	15.92		22.71	2.08	3.53		

XBS - Tubing Friction Loss Characteristics							
O.D705"	I.D615"			O.D. 18 mm I.D. 15.6 mm MET			
Flow gpm	Velocity fps	Loss psi		Flow I/h	Velocity m/s	Loss bar	
0.50	0.54	0.14		1.89	0.16	0.03	
1.00	1.08	0.51		3.79	0.33	0.11	
1.50	1.62	1.08		5.68	0.49	0.24	
2.00	2.16	1.85		7.57	0.66	0.41	
2.50	2.70	2.79		9.46	0.82	0.62	
3.00	3.24	3.91		11.36	0.99	0.87	
3.50	3.78	5.20		13.25	1.15	1.15	
4.00	4.32	6.66		15.14	1.32	1.48	
4.50	4.86	8.29		17.03	1.48	1.84	
5.00	5.40	10.08		18.93	1.65	2.23	
5.50	5.94	12.02		20.82	1.81	2.67	
6.00	6.48	14.12		22.71	1.98	3.13	

XBS 940 - ¾" Tubing Friction Loss Characteristics							
OD .940" I	.D. 820"			OD 23.9mr	METRIC		
Flow gpm	Velocity fps	Loss psi		Flow I/h	Velocity m/s	Loss bar	
0.50	0.30	0.03		1.89	0.09	0.01	
1.00	0.61	0.13		3.79	0.19	0.03	
1.50	0.91	0.27		5.68	0.28	0.06	
2.00	1.22	0.46		7.57	0.37	0.10	
2.50	1.52	0.69		9.46	0.46	0.15	
3.00	1.82	0.96		11.36	0.55	0.21	
3.50	2.13	1.28		13.25	0.65	0.28	
4.00	2.43	1.64		15.14	0.74	0.36	
4.50	2.74	2.04		17.03	0.84	0.45	
5.00	3.04	2.49		18.93	0.93	0.55	
5.50	3.34	2.96		20.82	1.02	0.66	
6.00	3.65	3.48		22.71	1.11	0.77	
6.50	3.95	4.04		24.61	1.20	0.90	
7.00	4.25	4.63		26.50	1.30	1.03	
7.50	4.56	5.27		28.39	1.39	1.17	
8.00	4.86	5.93		30.28	1.48	1.32	
8.50	5.17	6.64		32.18	1.58	1.47	
9.00	5.47	7.38		34.07	1.67	1.64	
9.50	5.77	8.16 8.97		35.96 37.85	1.76 1.85	1.81 1.99	
10.00	6.08	0.7/		37.63	1.05	1.77	

Psi Loss Per 100 Feet of Pipe (psi/100ft.) Bar Loss per 100 Meters of Pipe (bar/100m)

Note: Use of tubing at flows shown in dark shaded area is not recommended, as velocities exceed 5 ft/sec (1.5 m/s)

XQ 1/4" Distribution Tubing

The strongest and most flexible ¼" Distribution Tubing available to extend emitter outlets to desirable discharge locations

Features

- Unique blend of polymers that give it the flexibility of vinyl with hold of poly
- · New textured finish improves handling
- Self extracting coiling feature makes it easy to use, store and eliminates waste
- Fits over barbed outlet ports and all Xerigation® emission devices and ¼" transfer fittings
- Extruded from UV-resistant polyethylene resin materials

Specifications

- Outside Diameter: 0.25" (6.3 mm)
- Wall Thickness: .04" (1.0 mm)
- Inside Diameter: 0.17" (4.3 mm)
- Lengths: 100' and 1000' coils

Operating Range

• Pressure: 0 to 60 psi (0 to 4.1 bar)

Models

- XQ-100: 100-foot (30m) coil 1/4" distribution tubing
- XQ-1000: 1000-foot (305m) coil 1/4" distribution tubing
- XQ-1000-B: 1000-foot (305m) coil 1/4" distribution tubing in a bucket

XQ 1/4" Distribution Tubing Friction Loss Characteristics							
O.D25" I.D17"				O.D. 6.3n	nm I.D. 4.3mm		METRIC
Flow gpm	Velocity fps	Loss psi		Flow m³/h	Flow I/h	Velocity m/s	Loss bar
1	0.27	0.16		0.00	3.79	0.08	0.01
3	0.80	1.24		0.01	11.6	0.24	0.09
5	1.33	3.20		0.02	18.92	0.41	0.22
7	1.86	5.97		0.03	26.50	0.57	0.41
9	2.39	9.50		0.03	34.07	0.73	0.66
11	2.92	13.79		0.04	41.64	0.89	0.95
13	3.45	18.75		0.05	49.21	1.05	1.29
15	3.98	24.43		0.06	56.78	1.21	1.69
17	4.52	30.80		0.06	64.35	1.38	2.13
18	4.78	34.23		0.07	68.13	1.46	2.36
19	5.05	37.83		0.07	71.92	1.54	2.61
20	5.31	41.60		0.08	75.70	1.62	2.87
25	6.64	62.86		0.09	94.63	2.03	4.34
30	7.97	88.08		0.11	113.55	2.43	6.08

Psi Loss Per 100 Feet of tubing; C=150 Bar Loss per 100 Meters of tubing

Note: Use of tubing at flows shown in dark shaded area is not recommended, as velocities exceed 5 ft/sec (1.5 m/s)



XQ-100 and XQ-1000 1/4" Tubing



XQ-1000-B 1/4" Tubing



1/4" Landscape Dripline

Rain Bird ¼" Dripline is a perfect choice for small-sized areas such as planter boxes, container gardens, loops around trees, vegetable gardens and shrubs

Features

- Simple to use, as the flexible tubing makes watering pots and container gardens easy
 - Clog resistance through built-in filtration and two outlet holes, 180 degrees apart
- Brown tubing complements Rain Bird XF Dripline
- Works with Rain Bird 1/4" barbed Fittings

Operating Range


- 10 to 40 psi (0.7 to 2.7 bar)
- Flow rate at 30 psi (2.0 bar): 0.8gph (3.0 l/h)
- Required filtration: 200 mesh (75 micron)


Specifications

- Outside diameter: 0.250" (6 mm)
- Inside diameter: 0.170" (4 mm)
- Wall thickness: 0.040" (1 mm)
- Spacing: 6" or 12" (15.25 cm and 30.5 cm)
- Length: 100' (30.5 m) coils

Models

• LDQ0806100 • LDQ0812100





Maximum Ler	ngth of Run (Feet)	
Emitter Spacing	Maximum Length of Run	Flow per Ft. @ 15 psi
6"	19 feet	1 gph/ft.
12"	33 feet	0.5 gph/ft.



LDQ-08-06-100

Distribution Components, Tools

1/4" Barb Transfer Fittings

Features

- Used to connect $\frac{1}{4}$ " Distribution Tubing (XQ) in different configurations or attach $\frac{1}{4}$ " tubing to $\frac{1}{2}$ " or $\frac{3}{4}$ " tubing
- Newly designed connectors have self-piercing barbs that easily puncture ½" or ¾" tubing
- Stem on fittings allows simple, quick installation using Xeriman™Tool (XM-TOOL)
- Rugged plastic construction

Operating Range*

Pressure: 0 to 50 psi (0 to 3.5 bar)
 *with polyethylene tubing

Models

- XBF1CONN: 1/4" barb connector
- XBF2EL: ¹/₄" barb x barb elbow
- XBF3TEE: 1/4" barb x barb x barb tee







Subterranean Emitter Box

Features

- Provides convenient access to subsurface emitter while protecting against vandalism. Ideal for multi-outlet devices (such as Xeri-Bird 8) and Air Vacuum Relief Valve Kit
- New larger body allows more room for components and distribution tubing
- · Rugged, UV-resistant thermoplastic construction
- · Available with black top

Dimensions

- Height: 9.0" (22.9 cm)
- Top Diameter: 6.4" (16.3 cm)
- Base Diameter: 9.8" (24.9 cm)

Model

• SEB 7XB



SEB 7XB

Galvanized Tie-Down Stake

9-gauge galvanized steel stake to secure distribution tubing, XF Dripline or XBS Tubing to finished grade

Features

- **Durability:** Sturdy 9 gauge galvanized steel provides long-lasting and corrosion resistant hold strength for distribution tubing
- Easy installation: Sharp tips provide easy insertion into all soil types
- **Convenience:** robust packaging options provide ease of transportation and storage

Specifications:

- · Size: 6 inches
- Material: galvanized steel
- Thickness: 9 gauge

Models

- TDS-6050: 6 in. galvanized tie down stake (50 piece)
- TDS-6500: 6 in. galvanized tie down stake (500 pieces, pail)



Tubing Goof Plug

Features

- Used to plug unwanted holes in tubing
- New design works with Xeriman[™] Tool (XM-TOOL) for a quick, easy installation

Model

EMA-GPX

EMA-GPX

Tubing Cutter

Features

- Re-designed Xerigation® Tubing Cutter allows for easier and cleaner cuts of all low-volume tubing
- Unique design provides two different-sized wells (one for ½" -¾" tubing and one for ¼" tubing:, giving more leverage so less force is needed to cut any tubing
- Tubing Cutter is lightweight with stainless steel blades.
 Replacement blades available (PPC-200XBLD)

Models

- PPC-200X: Tubing cutter
- PPC-200XBLD: Replacement blades



Improved Dual-well Design Allows for Clean Cuts

Pages

Pages

Pages

151 - 152

153 - 154

155 - 152



Control Zone Kit Selection Guide



XCZ-150-LCS FLOW: 15 - 62 gpm



XCZ-150-LCDR FLOW: 15 - 62 gpm



XCZ-150-PRB-COM FLOW: 15 - 40 gpm

Commercial High Flow: 15 - 62 gpm



XCZ-100-PRB-COM FLOW: 0.3 - 20 gpm



XCZ-100-PRBR FLOW: 0.3 - 20 gpm



XCZ-100-PRB-LC FLOW: 0.3 - 20 gpm

Commercial Wide Flow: 0.3 - 20 gpm



XCZPGA-100-PRF FLOW: 3 - 15 gpm



XCZ-100-PRF FLOW: 3 - 15 gpm



XACZ-100-PRF FLOW: 3 - 15 gpm

Residential Medium Flow: 3 - 15 gpm



XCZLF-100-PRF FLOW: 0.2 - 10 gpm

Residential Low Flow: Flow: 0.2 - 10 gpm



XCZ-075-PRF FLOW: 0.2 - 5 gpm



Residential Low Flow: Flow: 0.2 - 5 gpm

Pages 150 - 151

Online Control Zone Kit Selection Guide

Rain Bird Control Zone Kits provide all of the components necessary for on/ off control, filtration and pressure regulation of a low-volume irrigation zone, making the kits simple to order and easy to install.

This quick selection tool will help you find the appropriate control zone kit for your application. By answering a few simple questions, the selection guide will provide recommended control zone kits best suited for your application. Simply click on the kit image for detailed information and specifications.

Features

- Includes detailed drawings and specifications for each kit
- Available at www.rainbird.com/CZK



Control Zone Kits

Rain Bird Control Zone Kits provide all of the components necessary for on/off control, filtration, and pressure regulation in a single package, making them simple to order and easy to install.

- Most reliable kits, and contain revolutionary products such as the Low Flow Valve and Quick Check Basket Filter
- All kits in every category use the innovative PR Filter which combines the filter and pressure regulator into one unit.
- Rain Bird offers the most complete line of Control Zone Kits, giving contractors and specifiers the flexibility to meet every need from 0.2 to 40 gpm. Choose from:
- 3/4", 1" or 11/2" inlet opening
- Low Flow Valve, Anti-Siphon Valve, DV Valve, or PESB Valve
- Pressure Regulating RBY Filter, Pressure Regulating Quick Check Basket Filter, or Quick Check Basket Filter

Use the chart below to identify the most appropriate kit or see pages 150 - 155 for specific detailed information on these kits and their individual components. Also available is the interactive Control Zone Kit Pyramid Selection Guide for selection and detailed specification information; found at www.rainbird.com/professionals/products/drip-control

Control Zone	Selectio	n Chart							
Model	Flow Rate	Flow rate capability (.9 gph dripline with 12" emitter spacing)	Valve Type	2-Wire Compatible	Filtration Type	Pressure Regulator	Inlet/ Outlet Size	Size	Minimal Valve Box Size
				Commercial	Control Zone Kits				
XCZ-150-LCS	15-62 GPM	1000 to 4000 feet of dripline	150-PEB	Yes	120 Mesh Disc Filter (130 Micron)		1.5" x 1.5"	20.5" Length	Jumbo
XCZ-150-PRB-COM	15-40 GPM	1000 to 2500 feet of dripline	150-PESB	Yes		40 psi	1.5" x 1"	17.5" or 11" Length	Rectangular
XCZ-100-PRB-COM	0.3-20	20 to 1300 feet	100-PESB	Yes	200 Mesh Stainless Steel (75 Micron)	200 Mesh Stainless	1" x 1"	14" Length	Mini- Standard
XCZ-100-PRB-LC	GPM	of dripline	100-PEB	Yes			1" x 1"	12" Length	Rectangular
			Comme	rcial Control Zo	ne Kits for Reclaimed W	ater			
XCZ-150-LCDR	15-62 GPM	1000 to 4000 feet of dripline	150-PESBR	Yes	120 Mesh Disc Filter (130 Micron)	40 pci	1.5" x 1.5"	23.5" Length	Jumbo Rectangular
XCZ-100-PRBR	0.3-20 GPM	20 to 1300 feet of dripline	100-PESBR	Yes	200 Mesh Stainless Steel (75 Micron)	40 psi	1" x 1"	10.5" Length	Mini- Standard Rectangular
				Residential (Control Zone Kits				
XCZPGA-100-PRF	3-15	200 to 1000 feet	100-PGA	Yes				11" Length	
XCZ-100-PRF	GPM	of dripline	100-DV			40 psi	1" x 1"		
XCZLF-100-PRF	0.2-10 GPM	13 to 650 feet of dripline	LFV-100	No	200 Mesh Stainless Steel (75 Micron)			10" Length	Mini- Standard or 10" Round
XCZ-075-PRF	0.2-5 GPM	13 to 300 feet of dripline	LFV-075			30 psi	3/4" x 3/4"		
			Resid	ential Control Z	one Kits with Anti-Sipho	on			
XACZ-100-PRF	3-15 GPM	200 to 1000 feet of dripline	100-ASV	Ne	200 Mesh Stainless	40 psi	1" x 1"	14"112:26:	
XACZ-075-PRF	0.2-5 GPM	13 to 300 feet of dripline	ASV- LFV-075	No	Steel (75 Micron)	30 psi	3/4" x 3/4"	14" Height	



Combine a Xerigation® Control Zone Kit with a Rain Bird controller product to precisely regulate zone watering times.



Low Flow Control Zone Kits with PR Filter

- Reliable Control Zone Kits that include the Low Flow Valve, the only valve on the market that can handle low flows (below 3 gpm) without weeping
- Shorter kits with only two components (valve plus pressure-regulating filter) mean that you can fit more Control Zone Kits in a valve box, saving time and money
- These PR Filter kits provide on/off control, filtration, and pressure regulation with fewer components; so there is less chance of leakage at the connections, both at installation and over the life of the system

Operating Range

- Flow: 0.20 to 10 gpm (0.8 to 37.85 l/m)
- Inlet pressure: 20 to 150 psi (1.4 to 10.3 bar)
- Regulated pressure: 30 psi (2.1 bar)
- Filtration: 200 mesh stainless steel screen (75 micron)

Models

- XCZ-075-PRF: 3/4" Low Flow Valve with 3/4" PR RBY Filter (Assembled)
- Flow: 0.2 to 5.0 gpm (0.8 to 18.91 l/m)
- XCZLF-100-PRF: 1" Low Flow Valve with 1" PR RBY Filter (Assembled)
- Flow: 0.2 to 10.0 gpm (0.8 to 37.85 l/m)

Replacement Screen

• RBY-200SSMX (200 mesh stainless steel screen)



Minimum Inlet Pressure for 30psi (2.1 bar) outlet pressure					
		XCZ-0	75-PRF		
Flow (gpm)	Flow (I/m)	Pressure (psi)	Pressure (bar)		
0.2	0.8	34.4	2.4		
1.0	3.8	36.1	2.5		
3.0	11.4	38.1	2.6		
5.0	18.9	43.4	3.0		

Minimum Inlet Pressure for 40psi (2.8 bar) outlet pressure					
		XCZLF-	100-PRF		
Flow (gpm)	Flow (I/m)	Pressure (psi)	Pressure (bar)		
0.2	0.8	44.4	3.1		
1.0	3.8	44.4	3.1		
3.0	11.4	45.0	3.1		
5.0	18.9	46.2	3.2		
10.0	37.9	52.2	3.6		



Four Control Zone Kits in a Standard Valve Box



XCZLF-100-PRF

Drip Irrigation

Low Flow Control Zone Kits with Anti-Siphon Valve and PR Filter

- Reliable Control Zone Kits that include the Low Flow Valve, the only valve on the market that can handle low flows (below 3 gpm) without weeping
- Complete, two-piece Control Zone Kits include the field-proven Low Flow Anti-Siphon Valve that has an atmospheric vacuum breaker for backflow prevention and an IAPMO rating
- These PR Filter kits provide on/off control, filtration, and pressure regulation with only two parts; so there is less chance of leakage at the connections, both at installation and over the life of the system

Operating Range

- Flow: 0.20 to 5.0 gpm (0.8 to 18.9 l/m)
- Inlet pressure: 20 to 150 psi (1.4 to 10.3 bar)
- Filtration: 200 mesh stainless steel screen (75 micron)
- Regulated pressure: 30 psi (2.1 bar)

Models

• XACZ-075-PRF: 3/4" Low Flow Anti-Siphon Valve with 3/4" PR RBY Filter

Replacement Screen



Minimum Inlet Pressure for 30psi (2.1 bar) outlet pressure

Flow		Inlet Pres	Inlet Pressure		
gpm	l/m	psi	bar		
0.2	0.8	37.4	2.6		
1.0	3.8	39.1	2.7		
3.0	11.4	40.0	2.8		
5.0	18.9	497	3.4		

XACZ-075-PRF

Medium Flow Control Zone Kits with Anti-Siphon Valve and PR Filter

- Complete, two-piece Control Zone Kits include the field-proven ASVF valve which has an atmospheric vacuum breaker for backflow prevention and an IAPMO rating
- These PR Filter kits provide on/off control, filtration, and pressure regulation with only two parts; so there is less chance of leakage at the connections, both at installation and over the life of the system

Operating Range

- Flow: 3.0 to 15.0 gpm (11.4 to 56.8 l/m)
- Inlet pressure: 20 to 150 psi (1.4 to 10.3 bar)
- Filtration: 200 mesh stainless steel screen (75 micron)
- Regulated pressure: 40 psi (2.8 bar)

Models

 XACZ-100-PRF: 1" ASVF with 1" PR RBY Filter

Replacement Screen

 RBY-200SSMX (200 mesh stainless steel screen)



Minimum Inlet Pressure for 40 psi Outlet Pressure					
Flow		Inlet Pres	sure		
gpm	l/m	psi	bar		
3.0	11.4	43.3	3.0		
5.0	18.9	44.7	3.1		
7.0	26.5	46.2	3.2		
9.0	34.1	47.3	3.3		
11.0	41.6	50.8	3.5		
13.0	49.2	55.4	3.8		
15.0	56.8	59.7	4.1		

XACZ-100-PRF



Medium Flow Control Zone Kits with PR Filter

- Reliable Control Zone Kit that includes an extra durable PGA valve
- These PR Filter kits provide on/off control, filtration, and pressure regulation with only two parts; so there is less chance of leakage at the connections, both at installation and over the life of the system
- 2-wire compatible residential Control Zone Kit

Operating Range

- Flow: 3 to 15 gpm (11.4 to 56.8 l/m)
- Inlet pressure: 20 to 150 psi (1.4 to 10.3 bar)
- Filtration: 200 mesh stainless steel screen (75 micron)
- Regulated pressure: 40 psi (2.8 bar)

Models

XCZPGA-100-PRF: 1" PGA Valve with 1" PR Filter

Replacement Screen

• RBY-200SSMX (200 mesh stainless steel screen)



Minimum Inlet Pressure for 40 psi outlet pressure					
Flow gpm	Inlet Pressure (psi) XCZPGA-100-PRF	Inlet Pressure (psi) XCZ-100-PRF			
3.0	45.8	42.9			
5.0	47.0	44.1			
10.0	50.7	48.5			
15.0	57.6	55.5			

Medium Flow Control Zone Kits with PR Filter

- Shorter kits with only two components (valve plus pressureregulating filter) mean that you can fit more Control Zone Kits in a valve box, saving time and money
- These PR Filter kits provide on/off control, filtration, and pressure regulation with only two parts; so there is less chance of leakage at the connections, both at installation and over the life of the system

Operating Range

- Flow: 3 to 15 gpm (11.4 to 56.8 l/m)
- Inlet pressure: 20 to 150 psi (1.4 to 10.3 bar)
- Filtration: 200 mesh stainless steel screen (75 micron)
- Regulated pressure: 40 psi (2.8 bar)

Models

• XCZ-100-PRF: 1" DV Valve with 1" PR Filter (Assembled)*
*Available with BSP threads

Replacement Screen

• RBY-200SSMX (200 mesh stainless steel screen)



XCZ-100-PRF

Minimum Inlet Pressure for 2.8 bar outlet pressure					
Flow I/m	Inlet Pressure (bar) XCZPGA-100-PRF	Inlet Pressure (bar) XCZ-100-PRF			
11.4	3.2	3.0			
18.9	3.2	3.0			
37.9	3.5	3.3			
56.8	4.0	3.8			

ip Irrigation

Wide Flow Commercial Control Zone Kit with Pressure Regulating, Basket Filter

- Industry wide flow range between 0.3 and 20 gpm (1.13 to 75.71 l/m) leading enables single SKU purchase for large projects
- Updated with the reliable, flexible and proven PEB valve with the rugged pressure regulating basket filter
- This PR Filter kit provides on/off control, filtration, and pressure regulation with only two parts; so there is less chance of leakage at the connections, both at installation and over the life of the system
- The "No Spill" feature of the basket filter ensures dirt does not fall back into the filter during cleanup operation. The threaded filter top with 0-ring makes it easy to remove and clean that stainless steel filter screen

Operating	Range
-----------	-------

- Flow: 0.3 to 20 gpm (1.13 to 75.71 l/m)*
- Inlet Pressure: 15 to 150 psi (1,0 to 10,3 bar)
- Regulating Pressure: 40 psi (2,7 bar)
- Filtration: 200 mesh (75 micron) stainless steel
- Temperature: Up to 150 degree F (66 degree C)

Model

 XCZ-100-PRB-LC: 1" PEB Valve with 1" Pressure Regulating (40 psi), Basket Filter

Replacement Filter Screens

- · QKCHK-100M: 100 mesh stainless steel screen, red
- · QKCHK-200M: 200 mesh stainless steel screen, white

Replacement Cap

• BFCAP (Complete cap with body o-ring)

*For flows below 5gpm Rain Bird recommends use of upstream filtration to prevent debris from collecting below the diaphragm

Minimum Inlet Pressure for 40 psi (2.8 bar) Outlet Pressure					
Flow Rate Inlet Pressure					
gpm	l/m	psi	bar		
0.3	1.14	41.0	2.82		
1.0	3.78	41.5	2.86		
5.0	18.9	43.0	2.9		
10.0	37.9	48.0	3.3		
15.0	56.8	56.0	3.8		
20.0	75.7	65.0	4.5		





Wide Flow Commercial Control Zone Kit with Scrubber Valve & Pressure Regulating, Basket Filter

- Complete kit is the simplest, smallest and most reliable Control Zone Kit for commercial applications between 0.3 and 20 gpm (1.13 and 76 l/m)
- Includes the reliable, proven PESB Valve which provides patented scrubbing action, making this kit ideal for commercial dirty water applications
- Includes the Pressure Regulating, Quick-Check Basket Filter that has a clear indicator which goes from green to red, telling you when to clean the filter. This reduces maintenance and takes the guesswork out of cleaning the filter. In addition, the threaded top makes it easy to remove and clean the stainless steel screen
- Basket Filter and Pressure Regulator have been combined for one smaller Pressure Regulating, Quick-Check Basket filter that is 24% smaller than the previous unit

0	ner	atin	n R	anc	10
v	νcι	aun	y n	alic	16

- Flow: 0.3 to 20.0 gpm (1.13 to 75.7 l/m)*
- Inlet Pressure: 15 to 150 psi (1,0 to 10,3 bar)
- Regulating Pressure: 40 psi (2,7 bar)
- Filtration: 200 mesh (75 micron) stainless steel
- Temperature: Up to 150° F (66° C)

Model


- XCZ-100-PRB-COM: 1" Ball Valve with 1" PESB Valve and 1" Pressure Regulating (40 psi), Quick-Check Basket Filter
- XCZ-100-PRBR: 1" PESBR Valve and 1" Pressure Regulating (40psi) Basket Filter

Replacement Screen

- · QKCHK100M (100 mesh stainless steel screen)
- QKCHK200M (200 mesh stainless steel screen)

Replacement Cap

- QKCHKCAP (Complete cap with body o-ring)
 - * For flows below 5gpm Rain Bird recommends use of upstream filtration to prevent debris from collecting below the diaphragm



Minimum Inlet Pressure for 2.8 bar Outlet Pressure					
Flow I/m	Inlet Pressure (bar) XCZ-100-PRB-COM	Inlet Pressure (bar) XCZ-100-PRBR			
1.136	2.82	2.82			
3.78	2.86	2.86			
11.4	2.9	2.9			
18.9	3.0	3.1			
37.9	3.3	3.4			
56.8	3.6	3.9			
75.7	4.3	4.3			



XCZ-100-PRBR



XCZ-100-PRB-COM

rip Irrigation

High Flow Commercial Control Zone Kit with 2 Pressure Regulating, Basket Filters

- Highest flow Control Zone Kit on the market for large, commercial drip zones 15.0 to 40.0 gpm (56,8 to 151,4 l/m)
- Includes the reliable, proven 1 ½"PESB Valve which provides patented scrubbing action, making this kit ideal for commercial dirty water applications
- Includes 2 Pressure Regulating, Quick-Check Basket Filter that have a clear indicator which goes from green to red, telling you when to clean the filter. This reduces maintenance and takes the guesswork out of cleaning the filter. In addition, the threaded top makes it easy to remove and clean the stainless steel screen
- Basket Filter and Pressure Regulator have been combined for one smaller Pressure Regulating, Quick-Check Basket filter that is 22% smaller than the previous unit
- Comes partially assembled for convenience and ease of installation

Operating Range

- Flow: 15.0 to 40.0 gpm (56,8 to 151,4 l/m)
- Inlet Pressure: 20 to 150 psi (1,4 to 10,3 bar)
- Regulating Pressure: 40 psi (2,7 bar)
- Filtration: 200 mesh (75 micron) stainless steel
- Temperature: Up to 150° F (66° C)

Models


 XCZ-150-PRB-COM: 1 1/2" PESB Valve with two 1" Pressure Regulating (40 psi), Quick-Check Basket Filters

Replacement Screen

- · QKCHK100M (100 mesh stainless steel screen)
- · QKCHK200M (200 mesh stainless steel screen)

Replacement Cap

• QKCHKCAP (Complete cap with body o-ring)



Minimum I	Minimum Inlet Pressure for 2.8 bar Outlet Pressure					
Flow I/m	Inlet Pressure (bar) XCZ-150-PRB-COM					
56.8	2.8					
75.7	3.4					
94.7	3.5					
113.6	3.7					
132.5	3.9					
151.4	4.2					





1.5" Inline Commercial Control Zone Kit

Run Up to 62 gpm for Large Zones

- High Flow Range: Allows for larger drip zone coverage with one control zone kit, saving labor cost, material cost and installation hassle.
- Low Friction Loss: Allows usage in zones with lower head pressure.
- Fully Assembled: Saves installation labor cost by ensuring all key components are included and that the direction of flow in individual components is assembled properly.
- Inline Configuration: Fewer connection points, which fits two kits instead of just one in a jumbo valve box. Also provides more access for maintenance and components.

- Flow Range: 15 to 62 gpm (56.8 l/min to 234.69 l/min)
- Inlet Pressure: 15 to 115 psi (1.03 to 7.9 bar)
- Regulated Pressure: 40 psi (2.8 bar)
- Filtration: 120 mesh (130 micron)
- Water Temperature: 33° F up to 110° F (0.5° C to 43° C)
- Ambient Temperature: 33° F up to 125° F (0.5° C to 52° C)

Specifications

Dimensions

- XCZ-150-LCS: 20 3/4" L x 5 3/4" W x 9½" H
- XCZ-150-LCDR: 231/2" L x 5 3/4" W x 91/2" H

Filtration

- XCZ-150-LCS: 1½" (3.81 cm) Stainless Steel Screen Filter, 120 Mesh (130 Micron); Surface Area: 42 in² (270 cm²)
- XCZ-150-LCDR: 1½" (3.81 cm) Disc Filter, 120 Mesh (130 Micron);
 Surface Area: 48 in² (310 cm²)

Valve Type

- XCZ-150-LCS: 1.5" PEB
- XCZ-150-LCDR: 1.5" PESB-R
- Power: 24 VAC 50/60 Hz (cycles/sec) solenoid
- Inrush Current: 0.41A (9.84 VA) at 50/60Hz
- Holding Current: 0.14A (3.43VA) at 50/60Hz
- · Coil Resistance: 30-39 Ohms
- · Two-wire compatible with ESP-LXD Decoders

Models

- XCZ-150-LCS
- XCZ-150-LCDR


Replacement Filters

Disc

• LGFC120MD

Screen

· LGFC120MS



Pressure Loss Characteristics						
Flow Rate (I/h)	XCZ-150-LCS	XCZ-150-LCDR				
56.8	0.13	0.16				
75.7	0.17	0.23				
94.7	0.28	0.34				
113.6	0.37	0.37				
151.4	0.51	0.55				
189.3	0.94	0.99				
227.1	1.43	1.43				



XCZ-150-LCS



XCZ-150-LCDR

Low Flow Valves

Valves designed exclusively for the low flow rates of a drip irrigation system (0.2 - 10.0 gpm; 0.6 to 37.8 l/m)

Features

- The only valves in the industry made specifically for drip irrigation systems, making these the only valves that can effectively handle particles at low flow rates patented design
- These valves contain all of the features of reliable Rain Bird DV valves, coupled with a unique diaphragm design that allows particles to pass through at extremely low flow rates, thereby preventing weeping of the valve
- Allows the filter to be safely placed downstream of the valve since these valves handle all sizes of particles
- Unique "double-knife" diaphragm coupled with $\, 1\!\!/\!\! 2$ " diameter seat for flawless operation at low flow rates
- Low Flow Valve is available in 3/4" In-line model
- · Double-filtered pilot flow design for maximum reliability
- External bleed to manually flush the system of dirt and debris during installation and system start-up
- Internal bleed for spray-free manual operation.

Operating Range


- Flow: 0.20 to 10.0 gpm (0.6 to 37.8 l/m)
- Pressure: 15 to 150 psi (1.0 to 10.3 bar)

Electrical Specifications


- 24 VAC 50/60 Hz (cycles/sec) solenoid
- Inrush current: 0.30 (7.2 VA) at 50/60 Hz
- Holding current: 0.19 A (4.56 VA) at 50/60 Hz

Models

- LFV-075: 3/4" Low Flow DV Valve
- LFV-100*: 1" Low Flow DV Valve



Pressure Loss	METRIC		
Flow I/m	LFV-075 bar	LFV-100 bar	
0.6	0.21	0.21	
3.6	0.22	0.23	
7.8	0.23	0.26	
15.0	0.25	0.34	
22.8	0.28	0.44	
30.0	0.47	0.52	



Unique Diaphragm Design



LFV-075

Note: Also available as part of XCZLF-100-PRF (p. 150)

^{*}Available with BSP threads



Inline RBY Filter

Static filter helps prevent plugging in a drip irrigation system

Features

- A simple and reliable filter for low-volume irrigation systems
- Simple to clean, as cap has a sealing O-ring and unthreads to provide access to the stainless steel filter element
- Strong and reliable due to its robust design and glass-filled polypropylene construction
- Male x Male threaded connections for direct connection to valves and pressure regulators
- Replacement stainless steel elements are available in 200 mesh (75 micron)

Operating Range

- · Flow:
 - 3/4" units: 0.20 to 12.0 gpm (0.8 to 45.4 l/m)
 - 1" units: 0.20 to 18.0 gpm (0.8 to 68.1 l/m)
- Pressure: 20 to 150 psi (1.4 to 10.3 bar)
- · Filtration: 200 mesh (75 micron)

Models

- RBY075MPTX: 3/4" Inline RBY Filter with 200 Mesh Screen
- RBY100MPTX: 1" Inline RBY Filter with 200 Mesh Screen*

Replacement screen:

RBY-200SSMX (200 mesh stainless steel screen)

Note: Filter must be installed downstream of a control valve and not under constant pressure.



RBY075MPTX

Pressure Loss Characteristics							
Flow Rate gpm I/m		RBY075MPTX psi bar		RBY100MPTX psi bar			
1.00	0.8	0.1	0.00	0.1	0.00		
3.00	3.8	0.4	0.01	0.3	0.01		
5.0	11.4	1.1	0.03	0.5	0.02		
7.0	18.9	1.6	0.08	0.8	0.03		
9.0	26.5	2.7	0.11	1.4	0.06		
12.0	34.1	4.5	0.19	2.2	0.10		
14.0	45.4	_	0.31	3.0	0.15		
16.0	53.0	_	_	3.8	0.21		
18.0	60.6	_	_	4.7	0.26		
	68.1	_	_	_	0.32		

Note: Pressure loss for 200 mesh filter screen

Pressure-Regulating Filter (RBY)

Unique, compact unit that works with all valves to create a simple, efficient control zone. Combines filtration and pressure regulation in one piece for protection of downstream components in a low-volume irrigation system

Features

- Reduces the number of components in a control zone, making it smaller and easier to install. More control zones can fit in one valve box!
- Combination unit comes with 200 mesh (75 micron) stainless steel reduces the number of connections, making installation easier and faster
- Static RBY filter regulates pressure to a nominal 30 or 40 psi (2.0 or 2.8 bar) PR RBY Filter Cap has sealing O-ring and unthreads to provide access to the filter element for easy cleaning
- 30 or 40 psi pressure regulator is integrated into the filter body
- Robust body and cap are made of glass-filled polypropylene and provide 150 psi (10.3 bar) pressure rating

Operating Range

- Flow 3/4" units: 0.20 to 5.0 gpm (0.8 to 18.9 l/m)
 - 1" units: 3.0 to 15.0 gpm (11.4 to 56.8 l/m)
- Inlet pressure: 20 to 150 psi (1.4 to 10.3 bar)
- Regulated pressure: 3/4" units: 30 psi (2.1 bar)
 - 1" units: 40 psi (2.8 bar)

Models

- PRF-075-RBY: 3/4" PR RBY Filter
- PRF-100-RBY: 1" PR RBY Filter

Replacement Screen

• RBY-200SSMX (200 mesh stainless steel screen)

Note: When installing with emission points more than 5 ft. above the pressure regulating filter, a check valve should be installed after the regulator.

Note: Filter must be installed downstream of a control valve and not under constant pressure.





Components

of Control Zone

Kits Found on

pg. 150-162

Stainles: Steel

Screen

PRF-075-RBY and PRF-100-RBY

Pressure Loss Characteristics						
Flow Rate PRF-075-RBY PRF-100-RBY						
gpm	l/m	psi	bar	psi	bar	
0.2	0.8	3.0	0.21	N/A	N/A	
1.0	3.8	4.0	0.28	N/A	N/A	
3.0	11.4	6.1	0.42	0.8	0.06	
5.0	18.9	10.0	0.69	2.0	0.14	
8.0	30.3	N/A	N/A	3.8	0.26	
10.0	37.9	N/A	N/A	5.2	0.36	
15.0	56.8	N/A	N/A	12.0	0.83	

Note: Pressure loss for 200 mesh filter screen

Quick-Check Basket Filter

The only commercial-grade filter with a clean/dirty indicator for low-volume irrigation zones

Features

- Reduces maintenance and labor costs the indicator tells you when to clean the filter, taking the guesswork out of cleaning the filter
- Provides increased reliability "No-spill" feature ensures dirt does not fall back into the filter during cleanup operation
- Simplifies installation and maintenance threaded top with O-ring makes it easy to remove and clean the screen
- · Available in 1" model
- Comes pre-assembled with 200 mesh (75 micron) stainless steel screen (other screen sizes available)

Operating Range

- Flow: 3.0 to 20.0 gpm (11.4 to 75.7 l/m)
- Pressure: 0-150 psi (0 to 10.3 bar)

Models

QKCHK-100*: 1" Basket Filter with 200 mesh stainless steel screen
 * Available with BSP threads

Pressure Loss Characteristics - QKCHK-100							
Flow Rate 100 mesh screen 200 mesh screen							
gpm	l/m	psi	bar	psi	bar		
3	11.4	0.1	0.0	0.0	0.0		
5	18.9	0.2	0.0	0.0	0.0		
7	26.5	0.4	0.0	0.4	0.0		
9	34.1	0.7	0.0	0.7	0.0		
11	41.6	0.9	0.1	1.1	0.1		
14	53.0	1.3	0.1	1.6	0.1		
20	75.7	2.9	0.2	3.2	0.2		

Note: Pressure loss for 200 mesh filter screen

Replacement Filter Screens

• QKCHK-100M: 100 mesh screen, red

• QKCHK-200M: 200 mesh stainless steel screen, white

Replacement Cap

QKCHKCAP (Complete cap with body o-ring)





Inline Pressure Regulators

Features

- Can be installed above or below grade
- Preset outlet pressure: 30 psi (2.0 bar) and 40 psi (2.8 bar)
- 3/4" NPT female-threaded inlet and outlet

Operating Range

- Flow
 - PSI-L30X-075: 0.20 to 5.0 gpm; 12 to 300 gph (0.8 to 18.9 l/m)
 - PSI-M30X-075, PSI-M40X-075: 2.0 to 10.0 gpm; 120 to 600 gph (7.8 to 37.9 l/m)
- Inlet Pressure: 10-150 psi (0.7 to 10.3 bar)

Models

- PSI-L30X-075: ³/₄" 30 psi (2.1 bar) regulator for low flow (red label)
- PSI-M30X-075: ³/₄" 30 psi (2.1 bar) regulator for medium flow (yellow label)
- PSI-M40X-075: 3/4" 40 psi (2.8 bar) regulator for medium flow (yellow label)



PSI-L30X-075, PSI-M30X-075 PSI-M40X-075

Retrofit Pressure Regulators

Features

- Provides convenient 30 psi (2.1 bar) pressure regulation at the riser for any ½" FPT emission device or compression adapter
- · Can be installed above or below grade
- Can be used with Xeri-bird[™] 8 Multi-Outlet Emission Device (see page 117)

Operating Range

- Flow: 0.50 to 4.00 gpm; 30 to 240 gph (1.9 to 15.1 l/m)
- Inlet Pressure: 15 to 70 psi (1.0 to 4.8 bar)

Dimensions

- ½" female-threaded inlet
- Height: 4" (10 cm)

Model

• PRS-050-30





1" & 1½ " High Flow Inline Pressure Regulators



High flow Pressure Regulator family that delivers pre-set regulation for a wide flow range (0.5 -70 gpm) providing a solution for most irrigation applications.

Features

Flexibility

- Its high flow range (0.5 gpm to 70 gpm) capacity allows usage in a wide range of applications, making it ideal for drip or spray applications. It can be installed above or below grade.
 - 1" Pressure Regulators flow range: 0.5-35 gpm (1.9 to 132.5 l/min)
 - 1 ½" Pressure Regulator flow range: 15-70 gpm (56.8 to 265.0 l/min)

Reliable Performance:

 Pre-set outlet pressure regulation at either 40 psi (2.8 bar) or 50 psi (3.4 bar) provides worry-free protection for your irrigation installations.

Durability:

 Tested to meet Rain Bird's high-quality standards. High Strength ABS construction and stainless steel springs provide the durability to withstand any job.

Operating Range

- Pressure Regulation:
 - PSI-H40X-100: 40 psi (2.8 bar)
 - PSI-H50X-100:50 psi (3.4 bar)
 - PSI-H40X-150: 40 psi (2.8 bar)
- · Flow Range:
 - PSI-H40X-100 & PSI-H50X-100: 0.5 gpm (1.9 l/min) to 35 gpm (132.5 l/min)
 - PSI-H40X-150: 15 gpm (56.8 l/min) to 70 gpm (265.0 l/min)
- Inlet pressure: 15 psi (1.0 bar) to 150 psi (10.3 bar)

Specifications

- PSI-H40X-100 & PSI-H50X-100: 1" Female NPT X 1" Female NPT
- PSI-H40X-150: 1 ½" Female NPT X 1 ½" Female NPT

Dimensions:


- PSI-H40X-100 & PSI-H50X-100: 5.8" (14.7 cm) in Length x 2.7" (6.8 cm) in Width
- PSI-H40X-150: 6.3" (16.0 cm) in Length x 3.3" (8.4 cm) in Width

Models

- PSI-H40X-100: 1" 40 psi inline Pressure Regulator
- PSI-H50X-100: 1" 50 psi inline Pressure Regulator
- PSI- H40X-150: 11/2" 40 psi inline Pressure Regulator



1" & 1½ " High Flow Inline Pressure Regulators



Orip Irrigatio

Pressure Regulating, and Quick-Check Pressure Regulating Basket Filters

The only commercial-grade filter with built in pressure regulator for low-volume irrigation zones. Also available with a clean/dirty indicator.

Features

- Reduces maintenance and labor costs 40% larger filter surface than standard filters means less frequent cleaning
- Provides increased reliability "No Spill" feature ensures dirt does not fall back into the filter during cleanup operation
- Simplifies installation and maintenance threaded top with 0-ring makes it easy to remove and clean that stainless steel filter screen
- Efficient design combines filtration and pressure regulation in one compact unit with fewer connections
- · Available in 1" model
- Comes pre-assembled with 200 mesh (75 micron) stainless steel screen (other screen sizes available)
- Built-in 40 psi (2,7 bar) pressure regulator
- Also available in Light Commercial Control Zone Kits:
 - XCZ-100-PRBR (without Quick-Check feature)
 - XCZ-100-PRB-LC (without Quick-Check feature)
 - XCZ-PRB-100-COM (with Quick-Check)
 - XCZ-PRB-150-COM (with Quick-Check)

Operating Range

- Flow: 5.0 to 20 gpm (18.9 to 75.7 l/m)
- Inlet Pressure: 15 to 150 psi (1,0 to 10,3 bar)
- Regulating Pressure: 40 psi (2,7 bar)
- Filtration: 200 mesh (75 micron) stainless steel
- Temperature: Up to 150 degree F (66 degree C)

Models

- PRB-100: 1" Basket Filter with built-in Pressure Regulator (40 psi) and 200 mesh (75 micron) stainless steel screen
- PRB-QKCHK-100: 1" Basket Filter with built-in Pressure Regulator (40 psi) and 200 mesh (75 micron) stainless steel screen

Replacement Filter Screens

- · QKCHK-100M: 100 mesh stainless steel screen, red
- · QKCHK-200M: 200 mesh stainless steel screen, white

Replacement Cap

• QKCHKCAP (Complete cap with body o-ring)

Note: When installing with the emission points more than 5 feet above the pressure regulating filter, a check valve should be installed after the regulator.



Flow Rate		Inlet Pres PRB-100	sure / PRB-QKCHK-100	Inlet Pressure PRB-QKCHK-200	
gpm	l/m	psi	bar	psi	bar
3	11.4	41	2.8	43	2.9
5	18.9	42	2.9	48	3.3
10	37.9	48	3.3	52	3.6
15	56.8	52	3.6	54	3.7
20	75.7	64	4.4	66	4.5



PRB-100



PRB-QKCHK-100



OKCHK-200M

www.rainbird.com 161

Components

of Control Zone Kits Found on

pg. 150-162



Large-Capacity Filters

Large-Capacity high flow and low maintenance with a solid build

Features

- Provides extra large filtration capacity for residential, commercial, and municipal applications
- Durable filters can be easily removed for cleaning, significantly reducing cleaning time
- · Disc filters can decompress for easy cleaning
- Auxiliary connection with a threaded cap can be drilled to allow draining or depressurization

Operating Range

- 1" Model: Maximum flow: Up to 26 gpm (6 m³/hr)
 - Filtering surface (disc): 28 in² (180cm²)
- 1.5" Models: Maximum flow: Up to 62 gpm (14 m3/hr)
 - Filtering surface (disc): 48 in² (310 cm²)
 - Filtering surface (screen): 42 in2 (270 cm2)
- 2" Models: Maximum flow: Up to 110 gpm (25 m3/hr)
 - Filtering surface (disc): 81 in² (525 cm²)
 - Filtering surface (screen): 75 in² (485 cm²)
- Maximum Pressure: 116 psi (8 bar)
- Maximum Temperature: Up to 140° F (60° C)

Models

- LCRBY100D 1" Large-Capacity Disc Filter
- LCRBY150S 1.5" Large-Capacity Screen Filter
- · LCRBY150D 1.5" Large-Capacity Disc Filter
- · LCRBY200S 2" Large-Capacity Screen Filter
- LCRBY200D 2" Large-Capacity Disc Filter

Specifications

- Inlet / Outlet Size:
 - 1" Models: 1" NPT
 - 1.5" Models: 1.5" NPT
 - 2" Models: 2" NPT

Dimensions

- 1": (6.8" H x 7.5" W x 3.3" D)
- 1.5": (9.5"H x 10.3"W x 5.7" D)
- 2": (9.7"H x 10.6" W x 5.7"D)

Filtration

- Stainless Steel Screen Filter: 120 Mesh (130 Micron)*
- Plastic Filter Discs: 120 Mesh (130 Micron)
- * Screen not available in 1" model

Replacement Filters

Disc Screen

• LGFC120MD • LGFC120MS





Disc & Screen Filters

Pressu	Pressure Loss Characteristics - Disc FIlter						
Flow R	ate	1" Filte	1" Filter		1.5" Filter		r
gpm	l/m	psi	bar	psi	bar	psi	bar
5	18.93	0.60	0.04	0.08	0.01	0.10	0.01
11	41.67	1.16	0.08	0.18	0.01	0.10	0.01
22	83.33	2.61	0.18	0.40	0.03	0.10	0.01
33	125.0	4.35	0.30	0.73	0.05	0.24	0.02
44	166.67	_	_	1.05	0.07	0.40	0.03
55	208.33	_	_	1.50	0.10	0.60	0.04
66	250.00	_	_	2.18	0.15	0.82	0.06
77	291.67	_	_	3.10	0.21	1.10	0.08
88	333.33	_	_	3.95	0.27	1.60	0.11
99	375.00	_	_	_	_	2.03	0.14
110	416.67	_	_	_	_	2.47	0.17

Pressu	Pressure Loss Characteristics - Screen Filter						
Flow Rate 1" Filter 1.5" Filter 2" Filter							
gpm	l/m	psi	bar	psi	bar	psi	bar
5	18.93	0.80	0.06	0.00	0.00	0.00	0.00
11	41.67	1.74	0.12	0.00	0.00	0.00	0.00
22	83.33	2.90	0.20	0.50	0.03	0.20	0.01
33	125.0	4.06	0.28	0.95	0.07	0.25	0.02
44	166.67	_	_	1.45	0.10	0.44	0.03
55	208.33	_	_	1.89	0.13	0.60	0.04
66	250.00	_	_	2.32	0.16	0.87	0.06
77	291.67	_	_	2.76	0.19	1.16	0.08
88	333.33	_	_	3.19	0.22	1.45	0.10
99	375.00	_	_	_	_	1.89	0.13
110	416.67	_	_	_	_	2.32	0.16

Note: Body dimensions are available on the Rain Bird website.

Note: Filter must be installed downstream of the valve, to prevent the filter from being under constant pressure.

Drip Irrigat

Spray-to-Drip Retrofit Kit

Simple kit that easily converts a conventional spray zone to a low-volume irrigation zone

Features

- Permits convenient conversion to drip tubing when used with barbed adapter
- Provides 30 psi (2,0 Bars) pressure regulation and a 200-mesh (75 micron) screen that is easily accessible
- Supports flow rates of 0.5 to 6 gpm
- Internal assembly drops into 1804 spray head bodies to easily retrofit existing system to Xerigation® products
- · Comes with 1 low profile Barb Tee and 1 Elbow Fitting
- Includes (1) ½" FPT x Elbow Fitting and (1) ½" FPT x Tee Fitting for easy connection to drip tubing

Operating Range

- Flow: 0.5 to 6 gpm (0.11 to 1.36 l/m)
- Inlet pressure: 15 to 70 psi (1.0 to 4.8 bar)
- Regulated pressure: 30 psi (2.1 bar)
- Filtration: 200 mesh (75 micron)

Model

• 1800-RETRO

Dimensions

- ½" (15/21) female-threaded inlet
- ½" (15/21) male-threaded swivel outlet
- •Width:
 - Cap: 2.25" (5.70 cm)
 - Body: 1.5" (3.80cm)

Replacement Screen

• RBY-200SSMX (200 mesh stainless steel screen)






Model# 1800XC

Can be used to cap
off unused Rain Bird

1800 Series spray bodies.
(Sold seperately)










Designed specifically for areas with water restrictions, our Spray-to-Drip Retrofit Kit allows use of existing 1800 Series Spray Bodies as drip irrigation connection points.



Pump Stations



Water Saving Tips

- Newer high-efficiency motors are able to convert a higher percentage of their electric input to useful mechanical work resulting in energy and cost savings.
- Rain Bird Variable Frequency Drive (VFD) pump stations save energy while delivering the water pressure necessary to ensure maximum water use efficiency.
- Rain Bird designs pump stations specifically for the application, ensuring the pump runs at maximum efficiency.
 Delivering the right pressure as demanded by the system ensures your irrigation system is efficient and effective. For assistance call 520-806-5620 or email pumps@rainbird.com.

Rain Bird® ACLP Series



³/₄ to 3 hp; Up to 60 psi (4.1 bar); Up to 115 gpm (26.1 m³/h)


Rain Bird's ACLP series pump stations are UL listed packaged pump stations designed for boost, suction lift or flooded suction applications. The ACLP station features a marine-grade aluminum enclosure, professional-grade centrifugal pump, and powder coated carbon steel piping for efficient performance and maximum corrosion resistance. The ACLP stations feature variable speed controls to smoothly, efficiently, and reliably produce constant pressure at varying flow rates within a large envelope of operation. See individual pump performance curves for details.

At-A-Glance Description

- Variable Frequency Drive (VFD)
- Pump Start Relay included Flow Switch included
- · Bladder Tank included
- Marine-Grade Aluminum Enclosure with powder coated steel deck and exhaust fan
- Isolation Valves for easy maintenance and priming
- Auto-Off-Manual Switch provides the user full control and override capabilities
- Available in single and three phase 208V, 220V, 230V, VAC and three phase 480V VAC configurations
- Multiple options for boost, flooded suction, and suction lift applications (see options list)
- · External Fault / Alarm and Run lights

Features


- · Plumbing Configurations
 - Inlet and discharge piping on opposite sides of the enclosure (as shown)
 - 1/2" priming port



- Mechanical Features
 - Discharge and intake isolation valves
 - Liquid filled pressure gauges on intake and discharge piping
 - Rugged centrifugal pump

Optional Accessories

- Surge Suppression Kit
 - Single phase (208V,220V, or 230V AC)
 - Three phase (208V, 220V, 230V or 480V AC)
- Stainless steel piping to replace internal powder coated carbon steel piping
- Environmental package, includes space heater and enclosure insulation
- Passive intake strainer and foot valve assembly for suction lift applications
- Self-cleaning inlet strainer and foot valve assembly for improved suction lift performance





CLP Series



Compact Low Profile 5HP VFD Pump Station


Rain Bird's CLP Series pump station is designed for boost and flooded suction-lift applications. The CLP Series is a complete pump package that is simple to install and operate. It includes a professional-grade pump, a marine-grade aluminum enclosure, highest quality pump protection, and optional mounting for a Rain Bird controller. Home owner associations, small sports fields, schools, parks, and small agricultural projects are ideal applications. With this complete solution there is no need to deal with the hassle of stick building a pump station with non-compatible parts and a makeshift enclosure. Only Rain Bird provides a totally integrated irrigation solution with UL-listed components and a one-year warranty that dependably deliver healthy, beautiful landscapes, saving time and minimizing maintenance.

Features

- · Plumbing Configurations
 - Inlet and discharge piping on opposite sides of the enclosure (as shown)
 - 3/4" and 2" Priming Ports Included
- Mechanical Features
 - Isolation valve
 - Liquid filled pressure gauge
 - Rugged centrifugal pump (Suction Lift model is self-priming)

Enclosures / External Connections

- · Marine grade aluminum enclosure and deck
- · Stainless Steel piping
- · Fused main power disconnect
- Pump Control Runs based on signal from irrigation controller, or from optional Flow Start Switch (Boost model only)
- 24VAC Pump start relay included. Other voltages available as an accessory
- 130 °F Temperature cutout switch




At-A-Glance Description

- · Pump Start Relay included
- · Aluminum Deck and Enclosure
- · Stainless Steel Piping
- Isolation Valve for maintenance and priming
- · Manual Switch provides user full control and override capabilities
- 2" Discharge, 2" Intake NPT (Boost), 2 1/2" Suction Port NPT (Suction Lift)
- · Mounting options for Rain Bird Controllers

Accessories

- Surge Suppression Kit
 - Single Phase (208-230 VAC) p/n CLPSES1P
 - Three Phase (208-230 VAC) p/n CLPSES3P
- · Pump Start Relay
 - 6VDC p/n CLPPSR06DC
 - 12VDC p/n CLPPSR12DC
- · Boost Accessories (Boost Model Only
 - Flow Start Kit p/n CLPBSTSW
- Suction Lift Accessories (Suction Lift Model only)
 - Foot valve 4" Vertical Flanged p/n CLPFTVLV4VF



Low Profile Pump Stations – LP Series

Low Profile Pump Stations – LP Series

Rain Bird's LP Series Horizontal End Suction and Vertical multistage pump stations are designed for small to midsize boost, flooded suction and suction lift applications such as city parks and buildings, sports fields, commercial buildings, small home owner's associations and large residential sites. Its low profile design, durable centrifugal or vertical multistage pump configuration, and choice of options make it an ideal choice for Turf irrigation applications.

Standard Features


- Cost effective Standardized VFD driven pump system in enclosure delivers high performance with minimum investment
- Low Profile Compact aluminum enclosure with powder coated skid and piping
- Energy efficient Variable Frequency Drive (VFD) maintains constant pressure at varying flow demand
- Reliability Simple, standard design, easy installation and maintenance
- Mechanical Features
 - Inlet Butterfly Isolation Valve
 - Discharge Butterfly Isolation Valve
 - Silent Check Valve
- Enclosures / External Connections
 - Marine Grade Aluminum Enclosure
 - Polyester Powder-Coated Steel Deck and Piping
 - Thermostat and Fan on Mechanical Enclosure
- Pump Control
 - Pump Start Relay
 - VFD Variable Frequency Drive for Control of Pressure
- Display
 - Monochrome Touch Screen Display

Optional Features and Accessories

Visit: www.rainbird.com/professionals/products/pumps-pump-stations

Models

- Horizontal End Suction LP Series
 - 5 to 10 HP; Up to 100 psi (6.9 bar); Up to 200 gpm (12.6 lps, 45.4 m³/h)
- Vertical Multistage LP Series
 - 1 to 7.5 HP; Up to 120 psi (8.3 bar); Up to 0 gpm (5.7 lps, 20.4 m³/h)



Horizontal End Suction - LP Series Shown 5 to 10 HP; Up to 100 psi (6.9 bar); Up to 200 gpm (12.6 lps, 45.4 m³/h)

LP Series – Horizontal End Suction - 1 Pump – Aluminum Enclosure					
Motor Size	5 HP	7.5 HP	10 HP		
Pump Type	Horizontal End Suction				
		480/60/3 V/HZ/PH	l		
Power Requirement	208-230/60/3 V/HZ/PH				
	208-230/60/1 V/HZ/PH				
Inlet Pressure Requirement	Suction Lift or Boost Applications				
Outlet Pressure	Up	to 100 psi (6.9 ba	r) ⁽¹⁾		
Outlet Flow	Up to 200	gpm (12.6 lps, 45	.4 m ³ /h) ⁽¹⁾		
Concrete Slab Dimensions (min)	65" x	49" (165 cm x 12	5 cm)		
Platform Skid Dimensions (min)	53" x 3	9.75" (135 cm x 1	01 cm)		
Inlet / Discharge Size	2" Flange Fitting (adapter)	3" Flange Fitting	4" Flange Fitting (adapter)		
Cabinet Height (from slab)	35" (89 cm)				

LP Series – Vertical Multistage – 1 Pump – Aluminum Enclosure											
Motor Size	1 HP	1.5 HP	2 HP	5 HP	7.5 HP						
Pump Type		Vert	ical Multis	tage							
		480,	/60/3 V/HZ	Z/PH							
Power Requirement		208-23	30/60/3 V/I	HZ/PH							
	208-230/60/1 V/HZ/PH										
Inlet Pressure Requirement		Suction Lift	or Boost A	Application	S						
Outlet Pressure		Up to 1	20 psi (8.3	bar) (1)							
Outlet Flow		Up to 90 gpi	m (5.7 lps,	20.4 m ³ /h)	(1)						
Concrete Slab Dimensions (min)		65" x 49"	(165 cm x	(125 cm)							
Platform Skid Dimensions (min)		53" x 39 3/4	4" (135 cm	x 101 cm							
Inlet / Discharge Size	2" flange fitting standard - 3" and 4" adapters available										
Cabinet Height (from slab)		35" (89 (m) or 47"	(107 cm)							

 $(1) \ Refer to pump performance curves, provided upon request from pumps @rainbird.com$



Low to Medium Flow Pump Stations – D-Series

Rain Bird's single pump, Vertical Multi-Stage and Horizontal End Suction stations in powder-coated green enclosures are designed for small to midsize boost, flooded suction and suction lift applications such as city parks and buildings, sports fields, commercial buildings, small home owner's associations and large residential sites. Its small footprint, durable centrifugal or multistage pump configuration, and choice of options make it an ideal choice for Turf irrigation applications.

Standard Features


- Reliability Integrated Plug-n-Pump provide single source responsibility for the entire pumping system insuring trouble-free installation and operation
- Energy efficient Variable Frequency Drive (VFD) maintains constant pressure at varying flow demand
- · Inlet and discharge isolation valves for easier mechanical serviceability
- Easy Start-up All stations are water-tested at the factory prior to shipment.
- Mechanical Features
 - Inlet Butterfly Isolation Valve
 - Discharge Butterfly Isolation Valve
 - Silent Check Valve
- · Pressure / Flow
 - Stainless Steel Pressure Transducer
 - Flow Switch
- Enclosures / External Connections
 - Polyester Powder Coated Steel Enclosure
 - Polyester Powder-Coated Steel Deck and Piping
 - Re-Prime Piping (Suction Lift only)
 - Thermostat and Fan on Mechanical Enclosure
- Pump Control
 - Pump Start Relay
 - VFD Variable Frequency Drive for Control of Pressure
- Display
 - Monochrome Touch Screen Display
 - Optional Color Touch Screen Display with Remote Communication Capability

Optional Features and Accessories

Visit: www.rainbird.com/professionals/products/pumps-pump-stations

Models

- Horizontal End Suction 1 Pump D Series
 - 5 to 20 HP; Up to 130 psi (9.0 bar); Up to 180 gpm (11.4 lps, 40.9 m³/h)
- Vertical Multistage 1 Pump D Series
 - 3 to 15 HP; Up to 120 psi (8.3 bar); Up to 200 gpm (12.6 lps, 45.4 m³/h)



Horizontal End Suction - 1 Pump - D Series shown 5 to 20 HP; Up to 130 psi (9.0 bar); Up to 350 gpm (22.1 lps, 79.5 m³/h)

D-Series – Horizontal End Suction – 1 Pump – Green Enclosure										
Motor Size	5 HP	7 ½ HP	10 HP	15 HP	20 HP					
Pump Type	Horizontal End Suction									
		480)/60/3 V/HZ/	PH .						
Power Requirement		208-2	30/60/3 V/H	Z/PH						
	230/60/1 V/HZ/PH 208/60/1 V/HZ/P									
Inlet Pressure Requirement	Sucti	on Lift (up to	3 ft. lift), or E	Boost Applic	ations					
Outlet Pressure		Up to	130 psi (9.0	bar) ⁽¹⁾						
Outlet Flow		Up to 350 gp	m (22.1 lps,	79.5 m ³ /h) ⁽¹)					
Concrete Slab Dimensions (min)		90" x 48	" (229 cm x	122 cm)						
Platform Skid Dimensions (min)		78" x 36	5" (198 cm x	91 cm)						
Inlet / Discharge Size	4" standard - 2", 3" and 6" adapters are external accessories									
Cabinet Height (from slab)		52" (132	cm) or 64" ((163 cm)						

D-Series – Vertical Multistage – 1 Pump – Green Enclosure										
Motor Size	3 HP	5 HP	7 ½ HP	10 HP	15 HP					
Pump Type		Vei	rtical Multi-St	age						
		48	0/60/3 V/HZ/	PH .						
Power Requirement		208-	230/60/3 V/H	IZ/PH						
	208-230/60/1 V/HZ/PH									
Inlet Pressure Requirement		Suction Li	ft or Boost Ap	oplications						
Outlet Pressure		Up to	120 psi (8.3	bar) (1)						
Outlet Flow		Up to 180 g	pm (11.4 lps,	40.9 m3/h) ⁽	1)					
Concrete Slab Dimensions (min)		90" x 48	8" (229 cm x	122 cm)						
Platform Skid Dimensions (min)		78" x 3	6" (198 cm x	91 cm)						
Inlet / Discharge Size	4" Standard - 2", 3", and 6" adapters available									
Cabinet Height (from slab)		52" (132	2 cm) or 64" ((163 cm)						

 $(1) \, Refer \, to \, pump \, performance \, curves, \, provided \, upon \, request \, from \, pumps @rainbird.com$

Pump Station

Medium Flow Pump Station

Rain Bird's single pump, Vertical Multi-Stage Enhanced station in a compact enclosure is designed for medium-flow boost, flooded suction and suction lift applications, such as; parks, sports complexes, golf courses, turf farms and other agricultural projects. Its compact design, durable centrifugal pump configuration, choice of options and enclosures make it an ideal choice for Turf irrigation applications with flows up to 500 gpm (31.5 lps, 114 m³/h).

Standard Features

- · Entry Level through High Performance
- Control Package With either a cost-effective monochrome touch-panel display or high resolution color touch-panel display for improved user interfaced and remote monitoring via VNC (Virtual Network Computing)
- Energy efficient Variable Frequency Drive (VFD) maintains constant pressure at varying flow demand
- Enhanced Serviceability Modern electrical design utilizing industrial breaker motor protection instead of fuses. Industrial circuit breakers are quickly reset and designed for an extended service life
- Inlet and discharge isolation valves for easier mechanical serviceability
- Plumbing Configurations
 - Inlet and Discharge Piping on same side of the enclosure (as shown)
- · Mechanical Features
 - Inlet Butterfly Isolation Valve
 - Discharge Butterfly Isolation Valve
 - Pump Isolation Valve
 - Silent Check Valve
- · Pressure / Flow
 - Stainless Steel Pressure Transducer
 - Flow Switch
- · Enclosures / External Connections
 - Marine Grade Aluminum Enclosure
 - Polyester Powder-Coated Steel Deck and Piping
 - Thermostat and Fan on Mechanical Enclosure

Optional Features

Visit: www.rainbird.com/professionals/products/pumps-pump-stations

Models

- Vertical Multi-Stage 1 Pump Enhanced Aluminum Enclosure
 - 5 to 50 HP; Up to 150 psi (10.3 bar); Up to 500 gpm (31.5 lps, 114 m³/h)



Vertical Multi-Stage – 1 Pump Enhanced – Aluminum Enclosure shown
5 to 50 HP; Up to 150 psi (10.3 bar);
Up to 500 gpm (31.5 lps, 114 m³/h)

Vertical Multi-Stage – 1 Pump Enhanced – Aluminum Enclosure										
Motor Size	5 HP	7.5 HP	10 HP	15 HP	20 HP	20 HP	25 HP	30 HP	40 HP	50 HP
Pump Type				Ver	tical N	lulti-S	age			
		20	8-230	/1/60	V/PH/I	ΗZ				
Power Requirement				208-2	230/3/	60 V/F	H/HZ			
(Other power configurations available upon request)				480	0/3/60	V/PH	/HZ			
available apoliticquest,	575/3/60 V/PH/HZ									
Inlet Pressure Requirement			Suct	ion Lif	t or Bo	oost A	pplica	tions		
Outlet Pressure				Jp to	150 ps	i (10.3	bar) (1)		
Outlet Flow			Up to	500 gj	om (31	1.5 lps	, 114 n	n³/h) (1)	
Concrete Slab Dimensions (min)			10′3	" x 4′	9" (31:	2.4 cm	x 145	cm)		
Platform Skid Dimensions (min)			9′3	' x 3′9	" (281	cm x	114.3	cm)		
Inlet / Discharge Size	4" Flanges Standard, 6" Inlet Flange (Suction Lift), 3", 4", 6", 8" Adapters Available									

(1) Refer to pump performance curves, provided upon request from pumps@rainbird.com



Main Irrigation Pump Stations

Flows Up to 5000 GPM

Reliable Variable Frequency Drive Pump Stations designed to serve as the main irrigation pump station for golf courses and large commercial sites. Rain Bird's Pump Station Platforms are designed for both new construction projects and renovation projects

Available in the following configurations:

- · Vertical Turbine Pump Stations for Wet-well Applications
- Horizontal End Suction for Flooded Suction and Pressure Boosting Applications
- Vertical Multistage Pumps for Flooded Suction, Suction Lift, and Pressure Boosting Applications

Benefits:

- Enhanced Serviceability: Modern electrical design utilizing industrial breaker motor protection instead of time-wasting fuses. Industrial circuit breakers are quickly reset and designed for an extended service life
- Reduced Downtime: Industrial circuit breakers are good for thousands of trips
- Easy Operator Training: Multi-language color touch-screen that is easy to learn
- Superior Corrosion Resistance; Choice of Polyester Powder Coated or Marine Grade Aluminum deck for the highest level of corrosion resistance. Less corrosion equals longer pipe, skid, and manifold life, reducing cost
- No-Hassle Buying: Get everything you need for your irrigation system construction or renovation from the only manufacturer dedicated to irrigation for over seven decades
- Real-Time Communication: The pump station communications in realtime with the central, allowing the central to make immediate decisions to maximize the efficiency of the entire irrigations systems

Electrical Power Specifications:

- 60 Hz, 3-Phase Power: 208V 230V (up to 60HP per pump), 460V, 575V
- 50 Hz, 3-Phase Power: 380V, 415V
- · Other power configurations available upon request

Many options to choose from include:

- · Air Conditioned Electrical Panel Cooling System
- · Enclosures: Aluminum, Painted Steel (Government Specified Colors)
- · Fertigation Systems
- Filtration: Backwashing Screen Filters and Suction Scan Filters (Hydraulic or Electric)
- · Heater, Skid Mounted 5KW
- Intake Box Screen with 3 Stainless Steel Screens
- Intermediate Pump, 10-25HP
- · Lake Level Control: Float Switches and Level Transducer
- · Magnetic Flow Meter
- · Modem, Radio, Hard-wired or Cellular Gateway connection
- Power Zones: 3, 5, or 10KVA
- Premium Efficient Motors
- VFD per pump
- · Wye Strainer with Auto Back-flush
- · Z Discharge Pipe



Pump Manager with SmartPump™

- Combine a Rain Bird Pump Station and central control software to fully integrate pump station operation with
 your central control. This combination allows the pump station and central control to respond to changes in
 the system and irrigation immediately, providing the highest level of efficiency
- Smart Pump™ matches the irrigation system operation with the real capacity of the pump station, shortening
 the water window by an average of 20 percent and decreasing energy consumption. In addition, Smart Pump
 alerts the superintendent in real time of irrigation and pump station problems via cell phone text messaging.
 When an issue occurs such as an irrigation pipe break, the system verifies the break, shuts down the system
 and notifies the superintendent. Other systems cannot respond in a timely manner and can lose an hour of
 irrigation time trying to recover from a system fault

Need Help Specifying a Pump?

• Email pumps@rainbird.com or call 520-806-5620 for assistance with quotes and specifications



Pump Start Relays

For Optimum Pump Performance and Protection

Rain Bird Pump Start Relays (PSRs) provide worry free performance for your irrigation system and are compatible with Rain Bird and other reliable irrigation controllers.

Dual Voltage Pump Start Relay Features

- Works with a lawn controller's start/stop command to facilitate the electrical path from the breaker box to the pump motor
- Provides "pilot duty" operation for all types of electrically driven pump equipment with available coil voltages of 24, 110 and 220 VAC
- · 40 AMP certified relay
- · Quick connect terminals with wire nuts
- · Grounding provision
- · Compatible with 24 VAC timed lawn controllers
- Compatible with 110 or 220 VAC 3/4 HP thru 5 HP* single phase pumps
- Grey "baked-on" powder coating, for long life in difficult environments
- UL Listed as "Enclosed Industrial Control Panels" and backed by a oneyear warranty
- · Housed in compact NEMA3R weather-tight enclosures
- Not recommended for use with 2-wire controller/decoder systems

Model

• PSR110220

2-Wire Pump Start Relay Features

- Works with a lawn controller's start/stop command to facilitate the electrical path from the breaker box to the pump motor
- Provides "pilot duty" operation for all types of electrically driven pump equipment with available coil voltages of 24, 110 or 220 VAC
- · 40 AMP certified relay
- · Quick connect terminals with wire nuts
- · Grounding provision
- · Compatible with 24 VAC timed lawn controllers
- Compatible with 110 or 220 VAC 3/4 HP thru 5 HP* single phase pumps
- Grey "baked-on" powder coating, for long life in difficult environments
- UL Listed as "Enclosed Industrial Control Panels" and backed by a oneyear warranty
- · Housed in compact NEMA3R weather-tight enclosures
- Includes an additional ice cube relay for 2-wire controller/decoder systems

Models

- PSR110IC or PSR220IC
- *when thermal protection is present

Pump Start Relays Specifications									
Model	Line Voltage	Coil Voltage	hp						
PSR110IC	110	24	3/4 through 2*						
PSR220IC	220	24	3/4 through 5*						
PSR110220	110 or 220	24	3/4 through 5*						

* National electrical code (nec) states all motors will be thermally protected from excessive "amperage draw." Most motors under 2 hp are supplied with thermal protection from the motor manufacturer. For motors over 2 hp, code-compliant PSRB pump protection is recommended. NOTE: Circuit breakers are never classified as motor protection

 ${\it NOTE: Check with your local health department for regulations and requirements for backflow prevention.}$



PSR110220



PSR110IC or PSR220IC



Drainage



Water Saving Tips

- Installing a well-designed drainage system will result in the collection and capture of rain, runoff water and standing water from the site.
- The collected water can then be directed to an on-site storage tank, treated (if required) and pumped on an "as needed" basis to feed a Rain Bird water efficient irrigation system.
- Drainage systems can reduce damage to structures by directing water away from the foundation of the structure to a more desirable area on the site.
- A Rain Bird Drainage Pop-Up Valve (DPUV) can be installed at the lowest point of the piping network to allow for the collected water to slowly percolate into the soil and recharge the ground water supply.
- A properly installed drainage system can eliminate issues on the site caused by rushing or standing water which can result in soil erosion, plant disease and structural damage.
- Remember, water always runs downhill. Make sure that there is at least a 2% elevation difference between the high-end and the lowend of the drainage system.

Rain Bird Drainage Products

Ruggedly constructed and designed to work together, these drainage grates, basins, adapters, pipe, and accessories can help you efficiently manage water run-off for virtually any residential, light commercial or municipal site.

Three-Year Warranty

You need products that will last long after the job's done. That's why we stand behind our drainage products with the longest warranty in the drainage product category.

All Rain Bird drainage purchases qualify for valuable Rain Bird Rewards points.

Round Catch Basin 6" Round Atrium Grate (pg 177) 6" Coupling — optional 6" Pipe to Extend Basin Height — optional 6" Round Flat Grate (pg 177) 6" Round Catch Basin (pg 174)

Compatible Drainage Pipe



Color, Size and Style are Optional. Loose Fits are Not.

No matter the job, you'll have the equipment you need to do it right. We offer grates and basins of varying dimensions, shapes and colors—all designed to fit together for tight, worry-free connections.


Recycled Plastics

All drainage models are constructed from 100% recycled plastic and therefore qualify for points on LEED projects.

Full Compatibility

Any way you put them together, our grates and basins will give you the best fit. For easy upgrades and quick replacements, our products are also compatible with components from most other drainage manufacturers.

Low-Profile Basin



Square Catch Basin



Drainage Products



Round Catch Basins

Features

- Manufactured from High-Impact Polystyrene (HIPS)
- UV stabilized to protect from sun degradation
- Universal outlet(s) used to connect to 3" or 4" Sewer and Drain Pipe (ASTM D2729), 3" or 4" Corrugated Pipe and 3" or 4" Triple Wall Pipe
- Includes a sump to minimize clogging of pipes
- To extend height of basin, use 6" PVC Pipe (ASTM D2729 and ASTM D3034, SDR 35) as a riser



Model Number	Number of Outlets	Inlet (Top) Accepts	Outlet (Side) Fits	Capacity	Sump Capacity
6" Round, 1 Out	let or 6" Round, 2 O	utlets			
DB6R1	1	•6" Round Flat and Atrium Grates	• 3" or 4" Corrugated Pipe	0.00	0.20 mala
DB6R2	2	7" Universal Square Grates6" PVC Pipe (ASTM D2729, ASTM D3034, SDR 35)	3" or 4" Triple Wall PipeS & D Pipe (ASTM D2729)	0.80 gals	0.20 gals

Square Catch Basins

Features

- Manufactured from High-Density Polyethylene (HDPE)
- · UV stabilized to protect from sun degradation
- Use a 3" and 4" Basin Adapter to connect basin to 3" or 4" Corrugated Pipe and 3" or 4" Triple Wall Pipe
- Use a 6" Basin Adapter to connect basin to 6" PVC Pipe (ASTM D2729 and ASTM D3034, SDR 35) and 6" Corrugated Pipe
- Use 9" or 12" Square Basin Riser(s) to extend height of 9" and 12" Square Catch Basins by 6" in height, respectively
- Accepts 9", 12" or 18" Square Flat and Square Atrium grates



Model Number	Number of Outlets	Inlet (Top) Accepts	Outlet (Side) Fits	Capacity	Sump Capacity
9" Square	, 2 Outlets				
DB9S2	2	9" Square Flat Grates9" Square Atrium Grates9" Square Basin Riser (DBRE9)	 Basin Plug (DBAAP) 3" & 4" Basin Adapter (DBAA34 or DBAAO34) 6" Basin Adapter (DBAA6) 	2.20 gals	0.45 gals
12" Squar	e, 2 Outlets				
DB12S2	2	12" Square Flat Grates12" Square Atrium Grates12" Square Basin Riser (DBRE12)	 Basin Plug (DBAAP) 3" & 4" Basin Adapter (DBAA34 or DBAAO34) 6" Basin Adapter (DBAA6) 	5.10 gals	1.25 gals
18" Squar	e, 2 Outlets				
DB18S2	2	•18" Square Flat Grates	 Basin Plug (DBAAP) 3" & 4" Basin Adapter (DBAA34 or DBAAO34) 6" Basin Adapter (DBAA6) 	16.70 gals	4.90 gals

Square Low-Profile Basins

Features

- Manufactured from High-Impact Polystyrene (HIPS)
- UV stabilized to protect from sun degradation
- One bottom outlet designed to accept all Basin Adapters
- Use a 3" and 4" Basin Adapter to connect to 3" or 4"
 Corrugated Pipe and 3" or 4" Triple Wall Pipe
- Use a 6" Basin Adapter to connect to 6" PVC Pipe (ASTM D2729 and ASTM D3034, SDR 35) and 6" Corrugated Pipe
- Accepts 12" Square Flat and Atrium Grates
- Includes two screw holes to enable grates to be secured to Low-Profile Basin
- · Made in the USA



Model Number	Inlet (Top) Accepts	Outlet (Side) Fits
12" Square		
DB12SLP	12" Square Flat Grates12" Square Atrium Grates12" Square Basin Riser (DBRE12)	•3" & 4" Basin Adapter (DBAA34 or DBAAO34) •6" Basin Adapter (DBAA6)

Square Basin Kits

For your convenience, Basin Kits are available with the most popular basin, grate and adapter components required on most jobs.

Model Number	Each Kit Includes									
9" Square Basin Kit										
DB9KITG	9" Square Basin with two outlets (DB9S2)Two 3" and 4" Adapters (DBAA34)	Basin Plug (DBAAP)9" Square Flat Grate, GREEN (DG9SFG)								
DB9KITB	9" Square Basin with two outlets (DB9S2)Two 3" and 4" Adapters (DBAA34)	Basin Plug (DBAAP)9" Square Flat Grate, BLACK (DG9SFB)								
12" Square Bas	sin Kit (not shown)									
DB12KITG	•12" Square Basin with two outlets (DB12S2) •Two 3" and 4" Adapters (DBAA34)	• Basin Plug (DBAAP) • 12" Square Flat Grate, GREEN (DG12SFG)								
DB12KITB	• 12" Square Basin with two outlets (DB12S2) • Two 3" and 4" Adapters (DBAA34)	• Basin Plug (DBAAP) • 12" Square Flat Grate, BLACK (DG12SFB)								




Drainage Pro



Universal Square Grates

Features

- · Manufactured from structurally foamed High-Density Polyethylene (HDPE)
- UV stabilized to protect from sun degradation
- Textured anti-skid surface
- Load rated for pedestrian traffic¹
- · ADA compliant




Model Number	Color	Fits	Open Slot Width	Open Surface Area	Maximum Flow Rating	Maximum Load
7" Universal Squ	iare Flat					
DG7USG	Green	•6" Round Catch Basin (DB6R1, DB6R2) •3" or 4" S & D Pipe (ASTM D2729)	1/11	12 on in	11 CDM	250 lb -
DG7USB	Black	3" or 4" Corrugated Pipe3" or 4" Triple Wall Pipe3", 4" or 6" S & D Fittings (SDR 35)	1/4"	13 sq in	11 GPM	250 lbs

¹Maximum load rating based on basin encased in concrete and weight uniformly applied across entire grate surface

Plastic Square Grates

Features

- Manufactured from structurally foamed High-Density Polyethylene (HDPE)
- UV stabilized to protect from sun degradation
- Flat and atrium (domed) profiles, available in two colors, green and black
- Each grate has three stepped diameters to fit Sewer and Drain (S & D) Pipe and Fittings, Triple Wall Pipe and Corrugated Pipe
- Textured anti-skid surface¹
- Load rated for autos and light trucks at speeds less than 20 mph^{1,2}
- ADA compliant¹



Model Number	Color	Fits	Open Slot Width	Open Surface Area	Maximum Flow Rating	Maximum Load					
9" Square Flat											
DG9SFG	Green	9" Square Catch Basin (DB9S2)	3/8"	38 sg in	50 GPM	2,000 lbs					
DG9SFB	Black	5 Square Caterr basin (bb932)	-78	30 34 III	30 GI WI	2,000 103					
12" Square Flat											
DG12SFG	Green	12" Square Catch Basins (DB12S2 & DB12S4)	⁷ / ₁₆ "	53 sg in	70 GPM	3,000 lbs					
DG12SFB	Black	12" Low-Profile Basin (DB12SLP)	7 16	33 34 III	70 GI WI	3,000 103					
18" Square Flat											
DG18SFG	Green	18" Square Catch Basins (DB18S2 & DB18S4)	15/32"	92 sg in	120 GPM	4,000 lbs					
DG18SFB	Black	To Square Catch basins (DB1632 & DB1634)	732	92 3Q III	120 GFIVI	4,000 103					
12" Square Atriu	12" Square Atrium										
DG12SAG	Green	12" Square Catch Basins (DB12S2 & DB12S4)	⁷ / ₁₆ "	50 sq in	65 GPM	NA					
DG12SAB	Black	12" Low-Profile Basin (DB12SLP)	716	20 3Q III	OJ GFIVI	IVA					

¹Flat grate only ²Maximum load rating based on basin encased in concrete and weight uniformly applied across entire grate surface

Plastic Round Grates

Features

- Manufactured from structurally foamed High-Density Polyethylene (HDPE)
- UV stabilized to protect from sun degradation
- 3" and 6" available in two colors, green and black
- Each grate has three stepped diameters to fit Sewer and Drain (S & D) Pipe and Fittings, Triple Wall Pipe and Corrugated Pipe
- Textured anti-skid surface1
- Load rated for autos and light trucks at speeds less than 20 mph^{1,2}
- ADA compliant¹



DG3RFG





DG4RFG

DG6RFG

Model	Color		Each Diameter Fits	;	Open Slot	Open Surface	Maximum	Maximum	
Number	Color	Small Medium		Large	Width	Area	Flow Rating	Load	
3" Round Flat									
DG3RFG	Green	3" Triple	3" S & D Pipe (ASTM D2729)	3" S & D Fittings	3/16"	3 sq in	3 GPM	500 lbs	
DG3RFB	Black	Wall Pipe	3" Corrugated Pipe	(SDR 35) 3/16		5 54	5 5	200100	
4" Round Flat									
DG4RFG	Green	4" Triple Wall Pipe	4" S & D Pipe (ASTM D2729) 4" Corrugated Pipe	4" S & D Fittings (SDR 35)	1/4"	5 sq in	6 GPM	750 lbs	
6" Round Flat									
DG6RFG	Green	6" Sewer Pipe (ASTM D3034,	6" S & D Pipe (ASTM D2729)	6" S & D Fittings (SDR 35)	⁵ / ₁₆ "	13 sg in	16 GPM	1.000 lbs	
DG6RFB	Black	SDR 35)	6" Corrugated Pipe	6" Round Catch Basins (DB6R1 & DB6R2)	-/ 16	-/ 16 13 SQ III		1,000 105	

¹Flat grate only ²Maximum load rating based on basin encased in concrete and weight uniformly applied across entire grate surface

Basin Adapters and Accessories



Model Number	Description	Use
DBAAP	Basin Plug	• Blocks 9", 12" & 18" Square Basin side outlets
DBAA34	3" and 4" Basin Adapter	 Adapts 9", 12" and 18" Square Basin side outlets and 9" & 12" Low-Profile Basin outlets to 3" or 4" PVC and Corrugated Pipe
DBAAO34	3" and 4" Offset Basin Adapter	 Adapts 9", 12" & 18" Square Basin side outlets and 9" & 12" Low-Profile Basin outlets to 3" or 4" PVC and Corrugated Pipe
DBAA6	6" Basin Adapter	 Adapts 9", 12" & 18" Square Basin side outlets and 9" & 12" Low-Profile Basin outlets to 6" PVC and Corrugated Pipe
DPAFH34	Fitting Adapter	 Adapts 3" or 4" Triple Wall Pipe to 3" or 4" PVC and Corrugated Pipe
DBRE9	9" Square Basin Riser	 Extends height of 9" Square Basin or 9" Low-Profile Basin by 6"
DBRE12	12" Square Basin Riser	 Extends height of 12" Square Basin or 12" Low-Profile Basin by 6"



Flex Pipe

NEW

Ruggedly constructed and designed to work together, these drainage grates, basins, adapters, pipe, and accessories can help you efficiently manage water run-off for virtually any residential, light commercial or municipal site.

Solid Pipe Features

- Solid pipe is ideal for applications that involve diverting water from one point to another (i.e. away from downspouts). Does not allow water to seep in or out anywhere except pipe ends
- Available in 8', 12', 25' and 50' lengths
- Exceeds ASTM F-405 standards

Perforated Pipe Features

- A pipe with spaced slits, ideal for ground water drainage (French drains, dispersing water from flower beds) in applications where surrounding soil is coarse enough not to pose a clogging threat and/or surrounding debris is minimal
- Available in 8', 12', 25' and 50' lengths

Perforated with Sock Features

- A pipe with spaced slits, covered with removable polyester sock. Ideal for ground water drainage (French drains, dispersing water from flower beds) in applications where surrounding soil or sand is fine enough to require filtration and/or surrounding debris is considerable
- Available in 25' and 50' lengths

Madal Noveless	Description	18/: Jal-	Lawash
Model Number	Description	Width	Length
DFLXSOLID8	4 Inch Solid Flexible Drainage Pipe, From 2 Ft To 8 Ft	4"	8"
DFLXSOLID12	4 Inch Solid Flexible Drainage Pipe, From 3 Ft To 12 Ft	4"	12"
DFLXSOLID25	4 Inch Solid Flexible Drainage Pipe, Expands From 6 Ft To 25 Ft	4"	25"
DFLXSOLID50	4 Inch Solid Flexible Drainage Pipe, Expands From 12 Ft To 50 Ft	4"	50"
DFLXPERF8	4 Inch Perforated Flexible Drainage Pipe, Expands From 3 Ft To 8 Ft	4"	8"
DFLXPERF12	4 Inch Perforated Flexible Drainage Pipe, Expands From 3 Ft To 12 Ft	4"	12"
DFLXPERF25	4 Inch Perforated Flexible Drainage Pipe, Expands From 6 Ft To 25 Ft	4"	25"
DFLXPERF50	4 Inch Perforated Flexible Drainage Pipe, Expands From 12 Ft To 50 Ft	4"	50"
DFLXSOCK25	4 Inch Perforated Drainage Pipe With Filter Sock, Expands From 6 Ft To 25 Ft	4"	25"
DFLXSOCK50	4 Inch Perforated Drainage Pipe With Filter Sock, Expands From 12 Ft To 50 Ft	4"	50"









Drainage Produc

Flex Pipe Fittings and Accessories

Coupler

Female coupler is used to adapt flexible drainage pipe to other Rain Bird fittings, basins, channels, pop-ups, and 4" caps. It also connects the pipe to other standard 4" fittings to improve the fit and function of the overall system. Female coupler can also be used for joining 2 cut pieces of FLEXDrain together.

Connector

Expands up to 21" to connect 4" corrugated pipe, PVC and many other 4" pipes together. Creates any angle or turn, and expands to reach pipes that have been cut short, and is an excellent repair piece for damaged sections of pipe.

Model Number	Description	Width
DFLXCOUPL	Flexible Drainage Pipe Connector, Attaches Cut Pieces Of Flexible Pipe, And Connects Flexible Pipe To 4" Basins And Channel	4"
DFLXCONECT	4 Inch Flexible Drainage Pipe Elbow Connector	4"
DFLXSPOU3X4	Downspout Adaptor, Fits 3X4 Downspout, Connects To 4" Flex Pipe, Pvc And Corrugated Pipe	4"
DFLXSPOU2X3	Downspout Adaptor, Fits 2X3 Downspout, Connects To 4" Flex Pipe, Pvc And Corrugated Pipe	4"
DFLXTYCON	4 Inch Flexible Tee. Wye Fitting, Connects Flexible Drainage Pipe, Pvc, And Corrugated Pipe	4"

Flexible Tee/Wye

Bends to any shape and connects multiple pieces of pipe including Flexible Drainage Pipe, 4" PVC, and 4" corrugated pipe. Allows you to the ability to create multiple angles. Couplers are required to connect the male end or cut end of flexible drain pipe to the fitting.




Rain Bird Series Channel Drainage

Rain Bird Engineered Channel Drain Systems are designed with the professional in mind. 5" wide systems with the accessories you need designed to save time and money.

Features

- Lattice Sidewall Anchors the Channel Drain into Concrete providing increased strength
- Less concrete required vs. competitor products

- Manufactured from structurally foamed High-Density Polyethylene (HDPE)
- UV stabilized recycled plastic to protect from sun degradation
- Snap-in design for grates that require no screws
- · Ideal for sidewalks, driveways and patios
- Hold down feet to stop floatation during pouring of concrete
- · Available in 1m lengths, plus a wide range of accessories



NEW

Channel Drains

NEW

Rain Bird **Low Profile 5" Channel Drain** is our in line drainage solution perfect for sidewalks, driveways and pool decks because it is lightweight, durable and UV stabilized. The hold down feet and pipe cut–outs make it simple to install.

Rain Bird **Standard 5" Channel Drain** is the complete professional drainage system designed for sidewalks, driveways, and patios, with corners and tee sections. With a complete range of accessories, and our no-screws clip-in grate design, our product is designed to make life easy. 5" Channel Drains are 5 ton vehicle safe.

Rain Bird 10" Industrial Drainage is ideal for light commercial traffic or heavy, slow moving vehicles and has a complete range of accessories. 10 ton vehicle safe.

Model Number	Description	Width	Length
DCD1MX5SS	5" Standard Channel Drain, 1M Stainless Steel Grate	5"	40"
DCD1MX4B	5" Low Profile Straight Line Channel, 1M, Black Heel Guard	5"	40"
DCD1MX5G	5" Standard Channel Drain, 1M Gray Grate	5"	40"
DCD1MX5AR	5" Standard Channel Drain, 1M Architectural Grate	5"	40"
DCD1MX10ST	10" Industrial Grade Channel Drain, 1M Galvanized Steel Grate	10"	40"




Channel Drain In-Line Pits



- In-Line pit looks like an extension of the channel drain for a clean, uniform appearance
- In-Line pit has 4 outlet options
- Outlets allow for quick and easy gluing of 4" PVC pipe

Model Number	Description
DCDPIT5G	5" Standard Channel Drain Pit, Gray Grate
DCDPIT5SS	5" Standard Channel Drain Pit, Stainless Steel Grate
DCDPIT5AR	5" Standard Channel Drain Pit, Architectural Grate
DCDPIT10ST	10" Industrial Grade Drain Pit, Galvanized Steel Grate



End Caps, End Outlets and Leaf Guards

Drainage Prod

Channel Drain Corners and Tees



- Corners and Tees perfect for left or right extensions
- Designed to fit full length or cut channel drain sections
- Flexibility to change flow direction

Model Number	Description
DCDCOR5G	5" Standard Channel Drain Corner, Gray Grate
DCDCOR5SS	5" Standard Channel Drain Corner, Stainless Steel Grate
DCDTEE5G	5" Standard Channel Drain Tee, Gray Grate
DCDTEE5SS	5" Standard Channel Drain Tee, Stainless Steel Grate
DCDCOR5AR	5" Standard Channel Drain Corner, Architectural Grate
DCDCOR10ST	10" Industrial Grade Drain Corner, Galvanized Steel Grate



DCDCOR5AR



DCDCOR5G



DCDCOR5SS



DCDTEE5G



DCDTEE5SS

Channel Drain End Caps, End Outlets and Leaf Guards



- End caps can be sealed using silicone
- Use End Caps at the highest point of the Rain Bird Channel
- Use End Outlets at the low points of the Rain Bird Channel
- Connect to the low end of the channel or to the end of the In-Line Pit when using the bottom outlets

Model Number	Description
DCDENDOUT5	5" Standard Channel Drain Outlet
DCDENDCAP4	5" Low Profile Channel End Cap
DCDENDCAP5	5" Standard Channel Drain End Cap
DCDLEAFGD4	5" Low Profile Channel Drain Leaf Guard
DCDLEAFGD5	5" Standard Channel Drain Leaf Guard
DCDENDCAP10	10" Industrial Grade Channel Drain End Cap



DCDLEAFGD4



DCDLEAFGD5



DCDENDOUT5



DCDENDCAP4



DCDENDCAP5



DCDENDCAP10



Drainage Pop-Up Valves

Features

- Available in four configurations
- Pop-up valve body manufactured from structurally foamed High-Density Polyethylene (HDPE)
- Elbow (where applicable) manufactured from PVC
- Adapter (where applicable) manufactured from High Impact Polystyrene (HIPS)
- UV stabilized to protect from sun degradation
- Spring-loaded cover rises ½" to discharge excess water in system
- · Spring automatically retracts cover to closed position after excess water is discharged
- Can be used in both vertical and horizontal position
- · Stainless steel spring to prevent rusting
- PVC elbows (where applicable) include a 1/4" drain hole to eliminate standing water
- · Made in the USA



DPUV4EHUB

Model Number	Color	Description	Connects To
DPUV3E	Green	Drainage Pop-Up Valve with 3" PVC Elbow	• 3" S & D Pipe (ASTM D2729) • 3" Triple Wall Pipe
DPUV4EHUB	Green	Drainage Pop-Up Valve with 4" PVC Elbow and Adapter (DPAFHA34)	3" or 4" Corrugated Pipe3" or 4" Triple Wall Pipe3" or 4" S & D Pipe (ASTM D2729)

Accessories

Downspout Adapters

Available in both 3x4x4 and 2x3x4, it is used to connect your downspout to Rain Bird flexible drainage pipe, 4" standard corrugated pipe, 4" PVC, and most other 4" pipe. Perfect fit when flexibility is not required.

- Manufactured from structurally foamed High-Density Polyethylene (HDPE)
- · UV stabilized to protect from sun degradation
- Fits 3" or 4" PVC and Corrugated Pipe

Model Number	Description	Color
DDSA23	2" X 3" Downspout Adapter	Black
DDSA34	3" X 4" Downspout Adapter	Black

Soakwell

- · High strength reinforced polymer
- · Collects and reuses unwanted storm water runoff
- · Drainage slots provide maximum water flow to surrounding soil
- 3 Piece design makes for easier installation and transport
- Strong but lightweight lid replaces concrete lid for easier installation

Model Number	Description	Color
DSOAKWELL	26.75" Diameter x 31.75" H Soakwell Base	6.61
DSOAKLID	26.75" Diameter Soakwell Lid	3.09
DSOAKSOCK	Soakwell Sock	0.22



DDSA23



DDSA34



SOAKWELL



DSOAKLID



DSOAKSOCK



Rain Bird Online Resources and Contacts List	
Programs and Marketing Resources	Contacts/Information
Design and Specification Resources	www.rainbird.com/documents/professionals
Distributor Portal Website	www.rainbird.com/turfdistributor
Public and Non-Profit Agencies Portal	www.rainbird.com/agency
Facebook	www.facebook.com/RainBirdCorp
Intelligent Use of Water™	www.rainbird.com/corporate/intelligent-use-water
LEED Library	www.rainbird.com/LEED
Rain Bird Logo	www.rainbird.com/corporate/rain-bird-logo
Product Catalog	www.rainbird.com/catalog
Product Literature and Tech Specs	www.rainbird.com/documents/professionals
Rain Bird Agency Rewards (non-profits and government agencies)	www.rainbird.com/agency • E-mail: rewards@rainbird.com
Rain Bird Rewards	www.rainbird.com/Rewards • E-mail: rewards@rainbird.com
Rain Bird Training Services	www.rainbirdservices.com
Rain Bird Replacement Parts	www.rainbird.com/parts
Twitter	www.twitter.com/rainbirdcorp
Water Efficiency Calculators	www.rainbird.com/professionals/calculators
Site Reports	www.rainbird.com/sitereports
YouTube	www.youtube.com/rainbirdcorp



Rain Bird Training Services

Dedicated to the Development of Irrigation Professionals

Rain Bird Online Training

Rain Bird Basics Online

- For people with little to no irrigation experience
- · Non-manufacturer specific training, not just Rain Bird
- · The basics of irrigation adjustments, repairs and operation

Rain Bird Technical Online

- · In-depth technical irrigation training anytime, anywhere
- Best practices for installing, operating, and maintaining irrigation systems
- Pass the Factory Trained exam and you will earn a Factory Trained designation and certificate







Rain Bird Classroom Training

Rain Bird Academy

General Irrigation Skills Training

- Top quality training on many manufacturers' products
- Prepare for Irrigation Association (IA) exams
- The Rain Bird Academy Boot Camp delivers the basics of irrigation in one week
 - Boot Camp classes are part of the IA Select Program

Rain Bird Factory Trained

Comprehensive Training on Rain Bird Products

- · Training is exclusive to Rain Bird Products
- Be an expert on installing, managing and maintaining Rain Bird irrigation systems
- Get the designation that proves to your customers that you are the best choice to do the job







Rain Bird Customized and Private Training

Rain Bird Customized

We come to your facility with the materials, products and trainers

- Train your entire team
- · Classes based on your unique requirements
- · Maximize your training investment
- · From basic irrigation to central control, we do it all





Rain Bird Rewards

Supporting Your Business Success and Growth

You're working hard to build a successful business and Rain Bird Rewards is here to reward you. We have the benefits and tools you can use to attract new customers, train your employees and reduce costs. Reinvesting in your company and its future success has never been so easy.

Join today — and get the benefits you need to take your business to the next level.

Help Your Business Succeed

Tools to grow your business.

 Use Rain Bird marketing materials to align your business with the industry leader

Rewards you deserve.

 Points can be redeemed to reward your hard work and help you build a successful business

Training discounts.

 Receive 20% off professional-level training from Rain Bird Training Services

Enroll today at ww2.rainbird.com/rewards/enrollment.htm



Reward for Your Hard Work

Let Rain Bird reward your growing business now and in the future.

Customer Service

At Rain Bird, we believe that when you purchase our products, you should also receive the support you need to ensure that they perform as designed. Like our products, Rain Bird customer service is designed to exceed expectations. When you call with questions about orders or new products, you get the support you need from the top water management professionals in the industry, backed by our vast global network of distributor-partners.

Worry-Free Warranties

Our comprehensive product warranties make it even easier to choose Rain Bird and relax. Most Rain Bird Landscape Irrigation products are warranted to the trade for a period of either three or five years from the date of original purchase. A Rain Bird warranty is hassle-free support that enables maximum peak performance by irrigation system professionals. For you, it's the added peace of mind of knowing Rain Bird is there when you need it.

Rain Bird's Professional Customer Satisfaction Policy

Rain Bird will repair or replace at no charge any Rain Bird professional product that fails in normal use within the warranty period stated below. You must return it to the dealer or distributor where you bought it. Product failures due to acts of God including without limitation, lightning and flooding, are not covered by this warranty. This commitment to repair or replace is our sole and total warranty.

Implied Warranties of Merchantability and Fitness, if Applicable, are Limited to One Year from the Date of Sale.

We will not, under any circumstances be liable for incidental or consequential damages, no matter how they occur.

I. Landscape Irrigation and Drainage Products

1800 Series Pop-Up Spray Heads, U-Series Nozzles, PA-8S and PA-8S-PRS Shrub Adapters, 1300 and 1400 Bubblers, 5000 Series Rotors, 5500 Series Rotors, 8005 Series Rotors, Falcon* 6504 Series Rotors, PEB/PESB/PESB-R Plastic Valves, DV/DVF and ASVF Plastic Valves, VB Series Valve Boxes, Internet Connected Water Meters (ICWM), and XF Series Dripline* – 5 years

C2 Power Unit – 2 years

Pump Start Relays – 1 year for controls/electronics, 2 years for enclosure All other Landscape Irrigation and Drainage products – 3 years

II. Golf Products, Agricultural Products, and Pump Stations

For complete information and details please visit: http://www.rainbird.com/corporate/CustomerSatisfactionPolicy.htm

III. All Other Products - 1 year

* XF Series Dripline - 7 Years on Environmental Stress Cracking (ESCR)

For more information, see your Rain Bird Distributor. To find the nearest authorized distributor in your area, visit www.rainbird.com or call 1-800-RAINBIRD

Resource

How to Use This Catalog

Precipitation Rates

Rain Bird has calculated for you the precipitation rates for our comprehensive lines of impacts, sprays, and rotors. These rates are an indication of the approximate rate at which water is being applied. The equations used to calculate the precipitation rates are as follows:

Square Spacing

U.S.: Metric: PR=96.3 x gpm PR=1000 x m³/h SxS

- 4	
_	

Triangular Spacing											
U.S.:	Metric:										
PR=96.3 x gpm	PR=1000 x m ₃ /h										

SxL

SxL

96.3 = Constant (inches/square foot/hour)

1000 = Constant (millimeter/square meter/hour)

gpm = Gallons per minute (applied to area by sprinklers)

m³/h = Cubic meters per hour (applied to area by sprinklers)

S = Spacing between sprinklers

L = Spacing between rows (S x 0.866)

Specification Information

The information in this catalog was accurate at the time of printing and may be used for proper specification of each product. For the most up-todate information, go to the Rain Bird web site at www.rainbird.com.

ASABE Test Certification Statement

Rain Bird Corporation certifies that pressure, flow rate, and radius data for its products were determined and listed in accordance with ASABE/ICC 802-2014 or ASAE S398.1, Procedure for Sprinkler Testing and Performance Reporting, and are representative of performance of production sprinklers at the time of publication. Actual product performance may differ from the published specifications due to normal manufacturing variations and sample selection. All other specifications are solely the recommendations of Rain Bird Corporation.

Reference Charts

Information contained in this catalog is based upon generally accepted formulas, computations, and trade practices. Rain Bird Corporation, and its subsidiaries and affiliates, shall not be responsible or liable therefore if any problems, difficulties, or injuries should arise from or in connection with the use or application of this information, or if there is any error herein, typographical or otherwise.

Technical Support

Rain Bird Technical Support has the answers to your specific product and water-management questions. Call our toll-free Technical Service number, or for maximum convenience, access the Rain Bird web site. You'll get expert advice and the right solutions.

Technical Service

1-800-RAINBIRD (1-800-724-6247) **Internet Address** www.rainbird.com

Pressure Loss Through Water Meters

Nomina	5/8"	3/4"	1"	1 1/2"	2"	3"	4"
gpm	3/0	3/4	ļ'	1 1/2		3	7
1	0.2	0.1					
2	0.3	0.2					
3	0.4	0.3					
4	0.6	0.5	0.1				
5	0.9	0.6	0.2				
6	1.3	0.7	0.3				
7 8	1.8	0.8 1.0	0.4				
9	3.0	1.0	0.5				
10	3.7	1.6	0.7				
11	4.4	1.9	0.8				
12	5.1	2.2	0.9				
13	6.1	2.6	1.0				
14	7.2	3.1	1.1				
15	8.3	3.6	1.2				
16	9.4	4.1	1.4	0.4			
17	10.7	4.6	1.6	0.5			
18	12.0	5.2	1.8	0.6			
19	13.4	5.8	2.0	0.7			
20	15.0	6.5	2.2	0.8			
22		7.9	2.8	1.0			
24		9.5	3.4	1.2			
26		11.2	4.0	1.4			
28		13.0	4.6	1.6			
30		15.0	5.3	1.8	0.0		
32 34			6.0	2.1	0.8		
36			7.8	2.7	1.0		
38			8.7	3.0	1.0		
40			9.6	3.3	1.3		
42			10.6	3.6	1.4		
44			11.7	3.9	1.5		
46			12.8	4.2	1.6		
48			13.9	4.5	1.7		
50			15.0	4.9	1.9	0.7	
52				5.3	2.1		
54				5.7	2.2		
56				6.2	2.3		
58				6.7	2.5		
60				7.2	2.7		
65				8.3	3.2	1.1	
70				9.8	3.7	1.3	
75 80				11.2 12.8	4.3 4.9	1.5	0.7
90				16.1	6.2	2.0	0.7
100				20.0	7.8	2.5	0.9
110				20.0	9.5	2.9	1.0
120					11.3	3.4	1.2
130					13.0	3.9	1.4
140					15.1	4.5	1.6
150					17.3	5.1	1.8
160					20.0	5.8	2.1
170						6.5	2.4
180						7.2	2.7
190						8.0	3.0
200						9.0	3.2
220						11.0	3.9
240						13.0	4.7
260						15.0	5.5
280						17.3	6.3
300						20.0	7.2
350							10.0
400 450							13.0 16.2
500							20.0

(1120, 1220) SDR 26 C=150

psi Loss per 100 Feet of Pipe (psi/100 ft.)

Sizes 1" through 6" Flow 1 through 600 gpm Nominal Size 1" 1 1/4" 1 1/2" 2" 2 1/2" 3" 4" 6"																
Nominal Size			1 1/4"				2"		2 1/2"		3"		4"		6"	
Pipe OD	1.315		1.660		1.900		2.375 2.173		2.875 2.635		3.500		4.500		6.625 6.084	
Avg. ID Avg. Wall	1.175 0.070		1.512 0.074		1.734 0.083		0.101		0.120		3.21 0.145		4.134 0.183		0.271	
Tolerance	0.020		0.020		0.020		0.020		0.020		0.143		0.020		0.271	
Min. Wall	0.060		0.064			0.073			0.110		0.135		0.173		0.255	
Flow	Velocity	Loss	Velocity	Loss	Velocity	Loss	Velocity	Loss	Velocity	Loss	Velocity	Loss	Velocity	Loss	Velocity	Loss
(gpm)	(ft/s)	(psi)	(ft/s)	(psi)	(ft/s)	(psi)	(ft/s)	(psi)	(ft/s)	(psi)	(ft/s)	(psi)	(ft/s)	(psi)	(ft/s)	(psi)
2	0.30	0.02	0.18	0.01	0.14	0.00	0.09	0.00	0.06 0.12	0.00	0.04	0.00	0.02	0.00	0.01	0.00
3	0.89	0.07	0.54	0.02	0.27	0.01	0.17	0.00	0.12	0.00	0.08	0.00	0.03	0.00	0.02	0.00
4	1.18	0.15	0.71	0.07	0.54	0.02	0.35	0.01	0.10	0.00	0.16	0.00	0.10	0.00	0.04	0.00
5	1.48	0.38	0.89	0.11	0.68	0.06	0.43	0.02	0.29	0.01	0.20	0.00	0.12	0.00	0.06	0.00
6	1.77	0.54	1.07	0.16	0.81	0.08	0.52	0.03	0.35	0.01	0.24	0.00	0.14	0.00	0.07	0.00
7	2.07	0.71	1.25	0.21	0.95	0.11	0.60	0.04	0.41	0.01	0.28	0.01	0.17	0.00	0.08	0.00
8	2.36	0.91	1.43	0.27	1.09	0.14	0.69	0.05	0.47	0.02	0.32	0.01	0.19	0.00	0.09	0.00
9	2.66	1.14	1.61	0.33	1.22	0.17	0.78	0.06	0.53	0.02	0.36	0.01	0.21	0.00	0.10	0.00
10	2.96	1.38	1.78	0.40	1.36	0.21	0.86	0.07	0.59	0.03	0.40	0.01	0.24	0.00	0.11	0.00
11	3.25 3.55	1.65 1.94	1.96 2.14	0.48 0.57	1.49 1.63	0.25	0.95 1.04	0.08	0.65 0.71	0.03	0.44	0.01	0.26 0.29	0.00	0.12 0.13	0.00
14	4.14	2.58	2.50	0.76	1.90	0.29	1.21	0.10	0.82	0.05	0.55	0.02	0.23	0.01	0.15	0.00
16	4.73	3.30	2.86	0.97	2.17	0.50	1.38	0.17	0.94	0.06	0.63	0.02	0.38	0.01	0.18	0.00
18	5.32	4.10	3.21	1.20	2.44	0.62	1.56	0.21	1.06	0.08	0.71	0.03	0.43	0.01	0.20	0.00
20	5.91	4.99	3.57	1.46	2.71	0.75	1.73	0.25	1.18	0.10	0.79	0.04	0.48	0.01	0.22	0.00
22	6.50	5.95	3.93	1.74	2.99	0.90	1.90	0.30	1.29	0.12	0.87	0.04	0.53	0.01	0.24	0.00
24	7.09	6.99	4.28	2.05	3.26	1.05	2.07	0.35	1.41	0.14	0.95	0.05	0.57	0.02	0.26	0.00
26	7.68	8.11	4.64	2.38	3.53	1.22	2.25	0.41	1.53	0.16	1.03	0.06	0.62	0.02	0.29	0.00
28	8.27	9.30 10.57	5.00	2.73	3.80 4.07	1.40	2.42	0.47 0.53	1.65	0.18	1.11	0.07	0.67 0.72	0.02	0.31	0.00
30 35	8.87 10.34	14.06	5.35 6.25	3.10 4.12	4.07	1.59 2.12	3.02	0.53	1.76 2.06	0.21	1.19	0.08	0.72	0.02	0.33	0.00
40	11.82	18.00	7.14	5.28	5.43	2.71	3.46	0.90	2.35	0.25	1.58	0.11	0.95	0.03	0.39	0.00
45	13.30	22.39	8.03	6.56	6.11	3.37	3.89	1.12	2.64	0.44	1.78	0.17	1.07	0.05	0.50	0.01
50	14.78	27.21	8.92	7.98	6.78	4.10	4.32	1.37	2.94	0.53	1.98	0.20	1.19	0.06	0.55	0.01
55			9.82	9.52	7.46	4.89	4.75	1.63	3.23	0.64	2.18	0.24	1.31	0.07	0.61	0.01
60			10.71	11.18	8.14	5.74	5.18	1.91	3.53	0.75	2.38	0.29	1.43	0.08	0.66	0.01
65			11.60	12.97	8.82	6.66	5.62	2.22	3.82	0.87	2.57	0.33	1.55	0.10	0.72	0.01
70			12.49	14.88	9.50	7.64	6.05	2.55	4.11	1.00	2.77	0.38	1.67	0.11	0.77	0.02
75 80			13.38 14.28	16.90 19.05	10.18 10.86	8.68 9.78	6.48 6.91	2.89 3.26	4.41 4.70	1.13 1.28	2.97 3.17	0.43	1.79 1.91	0.13	0.83	0.02 0.02
85			14.20	19.03	11.53	10.94	7.34	3.65	4.70	1.43	3.37	0.49	2.03	0.14	0.88	0.02
90					12.21	12.16	7.78	4.06	5.29	1.59	3.56	0.61	2.15	0.18	0.99	0.03
95					12.89	13.45	8.21	4.48	5.58	1.76	3.76	0.67	2.27	0.20	1.05	0.03
100					13.57	14.79	8.64	4.93	5.88	1.93	3.96	0.74	2.39	0.22	1.10	0.03
110					14.93	17.64	9.50	5.88	6.46	2.30	4.36	0.88	2.63	0.26	1.21	0.04
120							10.37	6.91	7.05	2.71	4.75	1.04	2.86	0.30	1.32	0.05
130							11.23	8.02	7.64	3.14	5.15	1.20	3.10	0.35	1.43	0.05
140 150							12.10 12.96	9.20 10.45	8.23 8.81	3.60 4.09	5.54 5.94	1.38 1.57	3.34 3.58	0.40 0.46	1.54 1.65	0.06 0.07
160							13.82	11.77	9.40	4.61	6.34	1.76	3.82	0.52	1.76	0.07
170							14.69	13.17	9.99	5.16	6.73	1.97	4.06	0.58	1.87	0.09
180									10.58	5.73	7.13	2.19	4.30	0.64	1.98	0.10
190									11.16	6.34	7.52	2.42	4.54	0.71	2.09	0.11
200									11.75	6.97	7.92	2.67	4.77	0.78	2.20	0.12
225									13.22	8.67	8.91	3.32	5.37	0.97	2.48	0.15
250 275									14.69	10.53	9.90 10.89	4.03 4.81	5.97 6.57	1.18 1.40	2.76 3.03	0.18 0.21
300											11.88	5.65	7.16	1.65	3.31	0.21
325											12.87	6.55	7.76	1.91	3.58	0.29
350											13.86	7.52	8.36	2.19	3.86	0.33
375											14.85	8.54	8.95	2.49	4.13	0.38
400													9.55	2.81	4.41	0.43
425													10.15	3.14	4.68	0.48
450													10.74	3.50	4.96	0.53
475													11.34	3.86	5.24	0.59
500 550													11.94 13.13	4.25 5.07	5.51 6.06	0.65 0.77
600													14.32	5.96	6.61	0.77
500													17.32	5.50	0.01	0.71

Note: Dark shaded area of chart indicates velocities over 5' per second. Use with caution The velocity values were derived using the following equation: $\mathbf{V} = \frac{0.408 \times Q_{germ}}{d^2}$ Table are based upon the following Hazen-Williams equation: $\mathbf{H}_f = \mathbf{0.2083} \times \left(\frac{100}{C}\right)^{1.852} \times \frac{Q^{1.852}}{D^{1.8655}}$ for change in psi per foot of elevation. Pressure loss for uphill elevation and pressure gain for downhill elevation changes.

PVC Class 200 IPS Plastic Pipe

(1120, 1220) SDR 21 C=150

psi Loss per 100 Feet of Pipe (psi/100 ft.)

Sizes 3/4" through 6" Flow 1 through 600 gpm

		riow i thro	ougn 600 gp	om					2"									
Nominal Size	3/4"		1"								2 1/2"		3"		4"		6"	
Pipe OD	1.050		1.315		1.660		1.900		2.375		2.875		3.500		4.500		6.625	
Avg. ID	0.91		1.169		1.482		1.7		2.129		2.581		3.146		4.046		5.955	
Avg. Wall	0.070		0.073		0.089		0.100		0.123		0.147		0.177		0.227		0.335	
Tolerance	0.020		0.020		0.020		0.020		0.020		0.020		0.020		0.026		0.038	
Min. Wall	0.060		0.063		0.079		0.090		0.113		0.137		0.167		0.214		0.316	
Flow (gpm)	Velocity (ft/s)	Loss (psi)																
1	0.49	0.07	0.30	0.02	0.19	0.01	0.14	0.00	0.09	0.00	0.06	0.00	0.04	0.00	0.02	0.00	0.01	0.00
2	0.49	0.24	0.60	0.02	0.17	0.02	0.14	0.01	0.18	0.00	0.12	0.00	0.08	0.00	0.05	0.00	0.02	0.00
3	1.48	0.52	0.90	0.15	0.56	0.05	0.42	0.02	0.10	0.01	0.12	0.00	0.12	0.00	0.07	0.00	0.02	0.00
4	1.97	0.88	1.19	0.15	0.74	0.03	0.56	0.02	0.27	0.01	0.16	0.00	0.12	0.00	0.10	0.00	0.05	0.00
5	2.46	1.33	1.49	0.39	0.93	0.00	0.71	0.04	0.45	0.02	0.24	0.01	0.10	0.00	0.10	0.00	0.05	0.00
6	2.96	1.86	1.79	0.55	1.11	0.12	0.85	0.00	0.43	0.02	0.37	0.01	0.21	0.00	0.12	0.00	0.00	0.00
7	3.45	2.47	2.09	0.73	1.30	0.17	0.03	0.03	0.63	0.03	0.37	0.01	0.29	0.00	0.13	0.00	0.07	0.00
8	3.94	3.17	2.39	0.73	1.49	0.30	1.13	0.12	0.03	0.05	0.49	0.02	0.23	0.01	0.17	0.00	0.00	0.00
9	4.43	3.94	2.69	1.17	1.67	0.37	1.27	0.19	0.72	0.06	0.55	0.02	0.37	0.01	0.22	0.00	0.10	0.00
10	4.93	4.79	2.99	1.42	1.86	0.45	1.41	0.13	0.90	0.08	0.61	0.02	0.41	0.01	0.25	0.00	0.12	0.00
11	5.42	5.72	3.28	1.69	2.04	0.53	1.55	0.27	0.99	0.09	0.67	0.03	0.45	0.01	0.27	0.00	0.12	0.00
12	5.91	6.71	3.58	1.98	2.23	0.63	1.69	0.32	1.08	0.11	0.73	0.04	0.49	0.02	0.30	0.00	0.14	0.00
14	6.90	8.93	4.18	2.64	2.60	0.83	1.98	0.43	1.26	0.14	0.86	0.06	0.58	0.02	0.35	0.00	0.14	0.00
16	7.88	11.44	4.78	3.38	2.97	1.07	2.26	0.55	1.44	0.18	0.98	0.07	0.66	0.02	0.40	0.01	0.18	0.00
18	8.87	14.23	5.37	4.21	3.34	1.33	2.54	0.68	1.62	0.23	1.10	0.09	0.74	0.03	0.45	0.01	0.10	0.00
20	9.85	17.29	5.97	5.11	3.72	1.61	2.82	0.83	1.80	0.28	1.22	0.11	0.82	0.03	0.50	0.01	0.23	0.00
22	10.84	20.63	6.57	6.10	4.09	1.92	3.11	0.99	1.98	0.33	1.35	0.13	0.91	0.05	0.55	0.01	0.25	0.00
24	11.82	24.24	7.17	7.17	4.46	2.26	3.39	1.16	2.16	0.39	1.47	0.15	0.99	0.06	0.60	0.02	0.28	0.00
26	12.81	28.11	7.76	8.31	4.83	2.62	3.67	1.34	2.34	0.45	1.59	0.18	1.07	0.07	0.65	0.02	0.30	0.00
28	13.80	32.25	8.36	9.53	5.20	3.01	3.95	1.54	2.52	0.52	1.71	0.20	1.15	0.08	0.70	0.02	0.32	0.00
30	14.78	36.64	8.96	10.83	5.57	3.41	4.24	1.75	2.70	0.59	1.84	0.23	1.24	0.09	0.75	0.03	0.35	0.00
35	1 1.7 0	30.01	10.45	14.41	6.50	4.54	4.94	2.33	3.15	0.78	2.14	0.31	1.44	0.12	0.87	0.03	0.40	0.01
40			11.94	18.45	7.43	5.82	5.65	2.98	3.60	1.00	2.45	0.39	1.65	0.15	1.00	0.04	0.46	0.01
45			13.44	22.95	8.36	7.24	6.35	3.71	4.05	1.24	2.76	0.49	1.86	0.19	1.12	0.05	0.52	0.01
50			14.93	27.90	9.29	8.79	7.06	4.51	4.50	1.51	3.06	0.59	2.06	0.23	1.25	0.07	0.58	0.01
55			1 1155	27150	10.22	10.49	7.76	5.38	4.95	1.80	3.37	0.71	2.27	0.27	1.37	0.08	0.63	0.01
60					11.15	12.33	8.47	6.32	5.40	2.11	3.67	0.83	2.47	0.32	1.50	0.09	0.69	0.01
65					12.07	14.30	9.18	7.33	5.85	2.45	3.98	0.96	2.68	0.37	1.62	0.11	0.75	0.02
70					13.00	16.40	9.88	8.41	6.30	2.81	4.29	1.10	2.89	0.42	1.74	0.12	0.81	0.02
75					13.93	18.63	10.59	9.56	6.75	3.20	4.59	1.25	3.09	0.48	1.87	0.14	0.86	0.02
80					14.86	21.00	11.29	10.77	7.20	3.60	4.90	1.41	3.30	0.54	1.99	0.16	0.92	0.02
85							12.00	12.05	7.65	4.03	5.21	1.58	3.50	0.60	2.12	0.18	0.98	0.03
90							12.71	13.40	8.10	4.48	5.51	1.76	3.71	0.67	2.24	0.20	1.04	0.03
95							13.41	14.81	8.55	4.95	5.82	1.94	3.92	0.74	2.37	0.22	1.09	0.03
100							14.12	16.28	9.00	5.45	6.12	2.13	4.12	0.81	2.49	0.24	1.15	0.04
110									9.90	6.50	6.74	2.55	4.53	0.97	2.74	0.29	1.27	0.04
120									10.80	7.63	7.35	2.99	4.95	1.14	2.99	0.34	1.38	0.05
130									11.70	8.85	7.96	3.47	5.36	1.32	3.24	0.39	1.50	0.06
140									12.60	10.16	8.57	3.98	5.77	1.52	3.49	0.45	1.61	0.07
150									13.50	11.54	9.19	4.52	6.18	1.73	3.74	0.51	1.73	0.08
160									14.40	13.01	9.80	5.10	6.60	1.95	3.99	0.57	1.84	0.09
170											10.41	5.70	7.01	2.18	4.24	0.64	1.96	0.10
180											11.02	6.34	7.42	2.42	4.49	0.71	2.07	0.11
190											11.64	7.01	7.83	2.67	4.74	0.79	2.19	0.12
200											12.25	7.71	8.24	2.94	4.98	0.86	2.30	0.13
225											13.78	9.58	9.28	3.66	5.61	1.08	2.59	0.16
250											15.31	11.65	10.31	4.45	6.23	1.31	2.88	0.20
275													11.34	5.30	6.85	1.56	3.16	0.24
300													12.37	6.23	7.48	1.83	3.45	0.28
325													13.40	7.23	8.10	2.12	3.74	0.32
350													14.43	8.29	8.72	2.44	4.03	0.37
375															9.35	2.77	4.31	0.42
400															9.97	3.12	4.60	0.48
425															10.59	3.49	4.89	0.53
450															11.22	3.88	5.18	0.59
475															11.84	4.29	5.47	0.65
500															12.46	4.72	5.75	0.72
550															13.71	5.63	6.33	0.86
600															14.95	6.61	6.90	1.01

Note: Dark shaded area of chart indicates velocities over 5' per second. Use with caution

The velocity values were derived using the following equation $V = \frac{0.408 \times Q_{gpm}}{d^2}$

Table are based upon the following Hazen-Williams equation: $\mathbf{H_f} = \mathbf{0.2083} \times \left(\frac{100}{C}\right)^{1.852} \times \frac{Q^{1.852}}{D^{4.8655}}$ for change in psi per foot of elevation. Pressure loss for uphill elevation and pressure gain for downhill elevation changes.

PVC Class 315 IPS Plastic Pipe

(1120, 1220) SDR 13.5 C=150

psi Loss per 100 Feet of Pipe (psi/100 ft.)

Sizes 1/2" through 6" Flow 1 through 600 gpm

Sizes 1/2" th	rough 6"	Flow 1 thr		gpm	1													6"		
Nominal Size			1"		1 1/4"		1 1/2"		2"		2 1/2"				4"					
Pipe OD	0.840		1.050		1.315		1.660		1.900		2.375		2.875		3.500		4.500		6.625	
Avg. ID	0.6960		0.8740		1.1010		1.3940		1.5980		2.0030		2.4230		2.9510		3.7940		5.5840	
Avg. Wall	0.072		0.088		0.107		0.133 0.020		0.151		0.186		0.226		0.275		0.353		0.521	
Tolerance Min. Wall	0.020 0.020 0.062 0.078		0.020				0.020 0.141		0.020 0.176		0.026 0.213		0.031 0.259		0.040		0.059 0.491			
Flow	Velocity	Loss	Velocity	Loss	Velocity	Loss	0.123 Velocity	Loss	Velocity	Loss	Velocity	Loss	Velocity	Loss	Velocity	Loss	Velocity	Loss	Velocity	Loss
(gpm)	(ft/s)	(psi)	(ft/s)	(psi)	(ft/s)	(psi)	(ft/s)	(psi)	(ft/s)	(psi)	(ft/s)	(psi)	(ft/s)	(psi)	(ft/s)	(psi)	(ft/s)	(psi)	(ft/s)	(psi)
1	0.84	0.25	0.53	0.08	0.34	0.03	0.21	0.01	0.16	0.00	0.10	0.00	0.07	0.00	0.05	0.00	0.03	0.00	0.01	0.00
2	1.68	0.90	1.07	0.30	0.67	0.10	0.42	0.03	0.32	0.02	0.20	0.01	0.14	0.00	0.09	0.00	0.06	0.00	0.03	0.00
3	2.53	1.90	1.60	0.63	1.01	0.20	0.63	0.06	0.48	0.03	0.31	0.01	0.21	0.00	0.14	0.00	0.09	0.00	0.04	0.00
4	3.37	3.24	2.14	1.07	1.35	0.35	0.84	0.11	0.64	0.06	0.41	0.02	0.28	0.01	0.19	0.00	0.11	0.00	0.05	0.00
5	4.21	4.89	2.67	1.61	1.68	0.53	1.05	0.17	0.80	0.09	0.51	0.03	0.35	0.01	0.23	0.00	0.14	0.00	0.07	0.00
6	5.05	6.86	3.20	2.26	2.02	0.74	1.26	0.23	0.96	0.12	0.61	0.04	0.42	0.02	0.28	0.01	0.17	0.00	0.08	0.00
7	5.90	9.12	3.74	3.01	2.36	0.98	1.47	0.31	1.12	0.16	0.71	0.05	0.49	0.02	0.33	0.01	0.20	0.00	0.09	0.00
8	6.74	11.68	4.27	3.86	2.69	1.25	1.68	0.40	1.28	0.20	0.81	0.07	0.56	0.03	0.37	0.01	0.23	0.00	0.10	0.00
9	7.58	14.53	4.81	4.80	3.03	1.56	1.89	0.49	1.44	0.25	0.92	0.08	0.63	0.03	0.42	0.01	0.26	0.00	0.12	0.00
10	8.42	17.66	5.34	5.83	3.37	1.90	2.10	0.60	1.60	0.31	1.02	0.10	0.69	0.04	0.47	0.02	0.28	0.00	0.13	0.00
11	9.26	21.07	5.88	6.96	3.70	2.26	2.31	0.72	1.76	0.37	1.12	0.12	0.76	0.05	0.52	0.02	0.31	0.01	0.14	0.00
12	10.11	24.75	6.41	8.17	4.04	2.66	2.52	0.84	1.92	0.43	1.22	0.14	0.83	0.06	0.56	0.02	0.34	0.01	0.16	0.00
14	11.79	32.93	7.48	10.87	4.71	3.53	2.94	1.12	2.24	0.58	1.42	0.19	0.97	0.08	0.66	0.03	0.40	0.01	0.18	0.00
16	13.48	42.16	8.55	13.92	5.39	4.53	3.36	1.44	2.56	0.74	1.63	0.25	1.11	0.10	0.75 0.84	0.04	0.45	0.01	0.21	0.00
18 20	15.16	52.44	9.61 10.68	17.32 21.05	6.06 6.73	5.63 6.84	3.78 4.20	1.79 2.17	2.88 3.20	1.12	1.83	0.31	1.25	0.12	0.84	0.05	0.51	0.01	0.24	0.00
22			11.75	25.11	7.40	8.16	4.20	2.17	3.52	1.33	2.24	0.37	1.53	0.13	1.03	0.00	0.57	0.02	0.20	0.00
24			12.82	29.50	8.08	9.59	5.04	3.04	3.83	1.57	2.44	0.52	1.67	0.18	1.12	0.07	0.68	0.02	0.29	0.00
26			13.89	34.21	8.75	11.12	5.46	3.53	4.15	1.82	2.64	0.60	1.81	0.24	1.22	0.09	0.74	0.02	0.34	0.00
28			14.96	39.25	9.42	12.76	5.88	4.05	4.47	2.08	2.85	0.69	1.95	0.27	1.31	0.11	0.79	0.03	0.37	0.00
30			16.02	44.60	10.10	14.50	6.30	4.60	4.79	2.37	3.05	0.79	2.08	0.31	1.41	0.12	0.85	0.04	0.39	0.01
35					11.78	19.29	7.35	6.12	5.59	3.15	3.56	1.05	2.43	0.42	1.64	0.16	0.99	0.05	0.46	0.01
40					13.46	24.70	8.40	7.84	6.39	4.03	4.07	1.34	2.78	0.53	1.87	0.20	1.13	0.06	0.52	0.01
45					15.15	30.72	9.45	9.75	7.19	5.01	4.58	1.67	3.13	0.66	2.11	0.25	1.28	0.07	0.59	0.01
50					16.83	37.34	10.50	11.85	7.99	6.09	5.08	2.03	3.47	0.80	2.34	0.31	1.42	0.09	0.65	0.01
55							11.55	14.13	8.79	7.27	5.59	2.42	3.82	0.96	2.58	0.37	1.56	0.11	0.72	0.02
60							12.60	16.60	9.59	8.54	6.10	2.85	4.17	1.13	2.81	0.43	1.70	0.13	0.79	0.02
65							13.65	19.26	10.39	9.91	6.61	3.30	4.52	1.31	3.05	0.50	1.84	0.15	0.85	0.02
70							14.70	22.09	11.18	11.37	7.12	3.79	4.86	1.50	3.28	0.57	1.98	0.17	0.92	0.03
75							15.75	25.10	11.98	12.91	7.63	4.30	5.21	1.70	3.51 3.75	0.65	2.13	0.19	0.98	0.03
80 85							16.80	28.29	12.78 13.58	14.55 16.28	8.14 8.64	4.85 5.42	5.56 5.91	1.92 2.15	3.75	0.74	2.27	0.22	1.05	0.03
90									14.38	18.10	9.15	6.03	6.25	2.13	4.22	0.82	2.55	0.24	1.18	0.04
95									15.18	20.01	9.66	6.67	6.60	2.64	4.45	1.01	2.69	0.30	1.24	0.05
100									15.98	22.00	10.17	7.33	6.95	2.90	4.69	1.11	2.83	0.33	1.31	0.05
110											11.19	8.74	7.64	3.46	5.15	1.33	3.12	0.39	1.44	0.06
120											12.20	10.27	8.34	4.07	5.62	1.56	3.40	0.46	1.57	0.07
130											13.22	11.92	9.03	4.72	6.09	1.81	3.68	0.53	1.70	80.0
140											14.24	13.67	9.73	5.41	6.56	2.07	3.97	0.61	1.83	0.09
150											15.25	15.53	10.42	6.15	7.03	2.36	4.25	0.69	1.96	0.11
160											16.27	17.50	11.12	6.93	7.50	2.66	4.54	0.78	2.09	0.12
170													11.81	7.76	7.96	2.97	4.82	0.87	2.22	0.13
180													12.51	8.62	8.43	3.30	5.10	0.97	2.36	0.15
190													13.20	9.53	8.90	3.65	5.39	1.08	2.49	0.16
200													13.90 15.64	10.48 13.03	9.37 10.54	4.02 4.99	5.67 6.38	1.18 1.47	2.62 2.94	0.18
250													17.37	15.84	11.71	6.07	7.09	1.79	3.27	0.27
275													17.57	13.04	12.88	7.24	7.79	2.13	3.60	0.33
300															14.06	8.51	8.50	2.50	3.93	0.38
325															15.23	9.87	9.21	2.91	4.25	0.44
350															16.40	11.32	9.92	3.33	4.58	0.51
375															17.57	12.86	10.63	3.79	4.91	0.58
400															-		11.34	4.27	5.23	0.65
425																	12.05	4.77	5.56	0.73
450																	12.75	5.31	5.89	0.81
475																	13.46	5.87	6.22	0.89
500																	14.17	6.45	6.54	0.98
550																	15.59	7.70	7.20	1.17
600																	17.01	9.04	7.85	1.38

Note: Dark shaded area of chart indicates velocities over 5' per second. Use with caution The velocity values were derived using the following equation: $\mathbf{V} = \frac{0.408 \times Q_{germ}}{d^2}$ Table are based upon the following Hazen-Williams equation: $\mathbf{H}_f = \mathbf{0.2083} \times \left(\frac{100}{C}\right)^{1.852} \times \frac{Q^{1.852}}{D^{1.8655}}$ for change in psi per foot of elevation. Pressure loss for uphill elevation and pressure gain for downhill elevation changes.



PVC Schedule 40 IPS Plastic Pipe

(1120, 1220) C=150

psi Loss per 100 Feet of Pipe (psi/100 ft.)

Sizes 1/2" through 6" Flow 1 through 600 gpm

Sizes 1/2" thi	1	low I thro		gpm									1							
Nominal Size	1/2"		3/4"		1"		1 1/4"		1 1/2"		2"		2 1/2"		3"		4"		6"	
Pipe OD Avg. ID	0.840 0.602		1.050 0.804		1.315 1.029		1.660 1.36		1.900 1.59		2.375 2.047		2.875 2.445		3.500 3.042		4.500 3.998		6.625 6.031	
Avg. Wall	0.119		0.123		0.143		0.150		0.155		0.164		0.215		0.229		0.251		0.297	
Tolerance	0.020		0.020		0.020		0.020		0.020		0.020		0.024		0.026		0.028		0.034	
Min. Wall	0.109		0.113		0.133		0.140		0.145		0.154		0.203		0.216		0.237		0.280	
Flow	Velocity (ft/s)	Loss (psi)	Velocity (ft/s)	Loss (psi)	Velocity (ft/s)	Loss (psi)	Velocity (ft/s)	Loss (psi)	Velocity (ft/s)	Loss (psi)										
(gpm)	1.13	0.50	0.63	0.12	0.39	0.04	0.22	0.01	0.16	0.00	0.10	0.00	0.07	0.00	0.04	(psi) 0.00	0.03	(psi) 0.00	0.01	0.00
2	2.25	1.82	1.26	0.44	0.77	0.13	0.44	0.03	0.32	0.02	0.19	0.00	0.14	0.00	0.09	0.00	0.05	0.00	0.02	0.00
3	3.38	3.85	1.89	0.94	1.16	0.28	0.66	0.07	0.48	0.03	0.29	0.01	0.20	0.00	0.13	0.00	0.08	0.00	0.03	0.00
4	4.50	6.55	2.52	1.60	1.54	0.48	0.88	0.12	0.65	0.06	0.39	0.02	0.27	0.01	0.18	0.00	0.10	0.00	0.04	0.00
5	5.63	9.91	3.16	2.42	1.93	0.73	1.10	0.19	0.81	0.09	0.49	0.03	0.34	0.01	0.22	0.00	0.13	0.00	0.06	0.00
6	6.75	13.89	3.79	3.40	2.31	1.02	1.32	0.26	0.97	0.12	0.58	0.04	0.41	0.02	0.26	0.01	0.15	0.00	0.07	0.00
7	7.88	18.48	4.42	4.52	2.70	1.36	1.54	0.35	1.13	0.16	0.68	0.05	0.48	0.02	0.31	0.01	0.18	0.00	0.08	0.00
8	9.01	23.66	5.05	5.79	3.08	1.74	1.76	0.45	1.29	0.21	0.78	0.06	0.55	0.03	0.35	0.01	0.20	0.00	0.09	0.00
9	10.13	29.43	5.68	7.20	3.47	2.17	1.99	0.56	1.45	0.26	0.88	80.0	0.61	0.03	0.40	0.01	0.23	0.00	0.10	0.00
10 11	11.26 12.38	35.77 42.68	6.31 6.94	8.75 10.44	3.85 4.24	2.63 3.14	2.21	0.68	1.61	0.32	0.97 1.07	0.09	0.68	0.04	0.44	0.01	0.26	0.00	0.11	0.00
12	13.51	50.14	7.57	12.27	4.62	3.69	2.65	0.95	1.76	0.36	1.17	0.11	0.73	0.05	0.48	0.02	0.28	0.00	0.12	0.00
14	15.76	66.71	8.84	16.32	5.39	4.91	3.09	1.26	2.26	0.59	1.36	0.13	0.96	0.03	0.62	0.02	0.36	0.01	0.15	0.00
16	18.01	85.42	10.10	20.90	6.17	6.29	3.53	1.62	2.58	0.76	1.56	0.22	1.09	0.09	0.71	0.03	0.41	0.01	0.18	0.00
18	20.26	106.24	11.36	25.99	6.94	7.82	3.97	2.01	2.90	0.94	1.75	0.28	1.23	0.12	0.79	0.04	0.46	0.01	0.20	0.00
20			12.62	31.59	7.71	9.51	4.41	2.45	3.23	1.14	1.95	0.33	1.36	0.14	0.88	0.05	0.51	0.01	0.22	0.00
22			13.89	37.69	8.48	11.35	4.85	2.92	3.55	1.37	2.14	0.40	1.50	0.17	0.97	0.06	0.56	0.02	0.25	0.00
24			15.15	44.28	9.25	13.33	5.29	3.43	3.87	1.60	2.34	0.47	1.64	0.20	1.06	0.07	0.61	0.02	0.27	0.00
26			16.41	51.36	10.02	15.46	5.74	3.98	4.20	1.86	2.53	0.54	1.77	0.23	1.15	0.08	0.66	0.02	0.29	0.00
28			17.67	58.91 66.94	10.79	17.73 20.15	6.18	4.56	4.52	2.13	2.73	0.62	1.91 2.05	0.26	1.23	0.09	0.71	0.02	0.31	0.00
30 35			18.94	00.94	11.56 13.49	26.81	6.62 7.72	5.19 6.90	4.84 5.65	3.23	3.41	0.71 0.94	2.39	0.30	1.54	0.10	0.77	0.03	0.34	0.00
40					15.41	34.33	8.82	8.84	6.46	4.13	3.89	1.21	2.73	0.51	1.76	0.14	1.02	0.05	0.45	0.00
45					17.34	42.70	9.93	10.99	7.26	5.14	4.38	1.50	3.07	0.63	1.98	0.22	1.15	0.06	0.50	0.01
50					19.27	51.90	11.03	13.36	8.07	6.25	4.87	1.83	3.41	0.77	2.20	0.27	1.28	0.07	0.56	0.01
55							12.13	15.94	8.88	7.45	5.36	2.18	3.75	0.92	2.42	0.32	1.40	0.08	0.62	0.01
60							13.24	18.72	9.68	8.75	5.84	2.56	4.09	1.08	2.65	0.37	1.53	0.10	0.67	0.01
65							14.34	21.72	10.49	10.15	6.33	2.97	4.44	1.25	2.87	0.43	1.66	0.11	0.73	0.02
70							15.44	24.91	11.30	11.65	6.82	3.41	4.78	1.43	3.09	0.50	1.79	0.13	0.79	0.02
75 80							16.54 17.65	28.31 31.90	12.10 12.91	13.23 14.91	7.30 7.79	3.87 4.36	5.12 5.46	1.63 1.84	3.31 3.53	0.56	1.91 2.04	0.15 0.17	0.84	0.02
85							18.75	35.69	13.72	16.69	8.28	4.88	5.80	2.06	3.75	0.03	2.04	0.17	0.90	0.02
90							19.85	39.67	14.52	18.55	8.76	5.43	6.14	2.29	3.97	0.79	2.30	0.19	1.01	0.03
95							13.03	33.07	15.33	20.50	9.25	6.00	6.48	2.53	4.19	0.87	2.42	0.23	1.07	0.03
100									16.14	22.55	9.74	6.59	6.82	2.78	4.41	0.96	2.55	0.25	1.12	0.03
110									17.75	26.90	10.71	7.87	7.51	3.31	4.85	1.14	2.81	0.30	1.23	0.04
120									19.37	31.60	11.68	9.24	8.19	3.89	5.29	1.34	3.06	0.36	1.35	0.05
130											12.66	10.72	8.87	4.52	5.73	1.56	3.32	0.41	1.46	0.06
140											13.63	12.30	9.55	5.18	6.17	1.79	3.57	0.47	1.57	0.06
150 160											14.61 15.58	13.97 15.75	10.24 10.92	5.89 6.63	6.61 7.05	2.03	3.83 4.08	0.54 0.61	1.68 1.79	0.07
170											16.55	17.62	11.60	7.42	7.50	2.56	4.06	0.68	1.79	0.08
180											17.53	19.58	12.28	8.25	7.94	2.85	4.59	0.75	2.02	0.10
190											18.50	21.65	12.97	9.12	8.38	3.15	4.85	0.83	2.13	0.11
200											19.47	23.80	13.65	10.03	8.82	3.46	5.11	0.92	2.24	0.12
225													15.36	12.47	9.92	4.31	5.74	1.14	2.52	0.15
250													17.06	15.16	11.02	5.24	6.38	1.39	2.80	0.19
275													18.77	18.09	12.12	6.25	7.02	1.65	3.08	0.22
300															13.23	7.34	7.66	1.94	3.37	0.26
325															14.33	8.51	8.30 8.93	2.25	3.65	0.30
350 375															15.43 16.53	9.76 11.09	9.57	2.58 2.93	3.93 4.21	0.35
400															17.64	12.50	10.21	3.31	4.49	0.45
425															18.74	13.99	10.21	3.70	4.77	0.50
450															19.84	15.55	11.49	4.11	5.05	0.56
475																	12.12	4.55	5.33	0.62
500																	12.76	5.00	5.61	0.68
550																	14.04	5.97	6.17	0.81
600																	15.32	7.01	6.73	0.95

Note: Dark shaded area of chart indicates velocities over 5' per second. Use with caution

The velocity values were derived using the following equation $V = \frac{0.408 \times Q_{gpm}}{d^2}$

Table are based upon the following Hazen-Williams equation: $\mathbf{H_f} = \mathbf{0.2083} \times \left(\frac{100}{C}\right)^{1.852} \times \frac{Q^{1.852}}{D^{1.8655}}$ for change in psi per foot of elevation. Pressure loss for uphill elevation and pressure gain for downhill elevation changes.

PVC Schedule 80 IPS Plastic Pipe

(1120, 1220) C=150

psi Loss per 100 Feet of Pipe (psi/100 ft.)

Sizes 1/2" th	izes 1/2" through 6" Flow 1 through 600 gpm																			
Nominal Size Pipe OD Avg. ID	1/2" 0.840 0.526		3/4" 1.050 0.722		1" 1.315 0.935		1 1/4" 1.660 1.254		1 1/2" 1.900 1.476		2" 2.375 1.913		2 1/2" 2.875 2.289		3" 3.500 2.864		4" 4.500 3.786		6" 6.625 5.709	
Avg. Wall Tolerance	0.157 0.020		0.164 0.020		0.190 0.022		0.203 0.024		0.212 0.024		0.231 0.026		0.293 0.034		0.318 0.036		0.357 0.040		0.458 0.052	
Min. Wall	0.147	1	0.154	1	0.179	1	0.191	1	0.200	1	0.218	1	0.276	1	0.300	1	0.337	1	0.432	Less
Flow (gpm)	Velocity (ft/s)	Loss (psi)	Velocity (ft/s)	Loss (psi)	Velocity (ft/s)	Loss (psi)	Velocity (ft/s)	Loss (psi)	Velocity (ft/s)	Loss (psi)	Velocity (ft/s)	Loss (psi)	Velocity (ft/s)	Loss (psi)	Velocity (ft/s)	Loss (psi)	Velocity (ft/s)	Loss (psi)	Velocity (ft/s)	Loss (psi)
1	1.47	0.97	0.78	0.21	0.47	0.06	0.26	0.01	0.19	0.01	0.11	0.00	0.08	0.00	0.05	0.00	0.03	0.00	0.01	0.00
3	2.95 4.42	3.50 7.42	1.57 2.35	0.75 1.59	0.93	0.21	0.52	0.05	0.37	0.02	0.22	0.01	0.16	0.00	0.10	0.00	0.06	0.00	0.03	0.00
4	5.90	12.64	3.13	2.71	1.87	0.77	1.04	0.18	0.75	0.08	0.45	0.02	0.31	0.01	0.20	0.00	0.11	0.00	0.05	0.00
5	7.37	19.11	3.91	4.09	2.33	1.16	1.30	0.28	0.94	0.13	0.56	0.04	0.39	0.01	0.25	0.01	0.14	0.00	0.06	0.00
7	8.85 10.32	26.78 35.63	4.70 5.48	5.74 7.63	2.80 3.27	1.63 2.17	1.56 1.82	0.39	1.12	0.18 0.24	0.67	0.05	0.47	0.02	0.30	0.01	0.17	0.00	0.08	0.00
8	11.80	45.63	6.26	9.77	3.73	2.78	2.08	0.67	1.50	0.30	0.89	0.09	0.62	0.04	0.40	0.01	0.23	0.00	0.10	0.00
9	13.27 14.75	56.75 68.98	7.04 7.83	12.15 14.77	4.20 4.67	3.45 4.20	2.34	0.83 1.01	1.69	0.37 0.46	1.00	0.11	0.70 0.78	0.04	0.45	0.01	0.26 0.28	0.00	0.11	0.00
11	14./3	00.90	8.61	17.62	5.13	5.01	2.85	1.20	2.06	0.46	1.11	0.15	0.76	0.05	0.55	0.02	0.26	0.00	0.13	0.00
12			9.39	20.70	5.60	5.88	3.11	1.41	2.25	0.64	1.34	0.18	0.93	0.08	0.60	0.03	0.34	0.01	0.15	0.00
14 16			10.96 12.52	27.55 35.27	6.53 7.47	7.83 10.03	3.63 4.15	1.88	2.62 3.00	0.85 1.09	1.56 1.78	0.24	1.09	0.10	0.70	0.03	0.40	0.01	0.18	0.00
18			14.09	43.87	8.40	12.47	4.67	2.99	3.37	1.35	2.01	0.38	1.40	0.15	0.90	0.04	0.40	0.01	0.23	0.00
20			15.65	53.32	9.33	15.16	5.19	3.63	3.75	1.64	2.23	0.47	1.56	0.19	0.99	0.07	0.57	0.02	0.25	0.00
22 24					10.27 11.20	18.08 21.24	5.71 6.23	4.33 5.09	4.12 4.49	1.96 2.30	2.45	0.56 0.65	1.71 1.87	0.23	1.09	0.08	0.63	0.02	0.28	0.00
26					12.13	24.64	6.75	5.91	4.87	2.67	2.90	0.76	2.02	0.32	1.29	0.03	0.74	0.02	0.33	0.00
28					13.07	28.26	7.26	6.77	5.24	3.06	3.12	0.87	2.18	0.36	1.39	0.12	0.80	0.03	0.35	0.00
30 35					14.00 16.33	32.12 42.73	7.78 9.08	7.70 10.24	5.62 6.55	3.48 4.63	3.34	0.99	2.34	0.41	1.49	0.14	0.85 1.00	0.04	0.38	0.00
40					10.55	72.75	10.38	13.11	7.49	5.93	4.46	1.68	3.11	0.70	1.99	0.24	1.14	0.06	0.50	0.01
45							11.68	16.31	8.43	7.38	5.02	2.09	3.50	0.87	2.24	0.29	1.28	0.08	0.56	0.01
50 55							12.97 14.27	19.83 23.65	9.36 10.30	8.97 10.70	5.57 6.13	2.54 3.03	3.89 4.28	1.06 1.27	2.49	0.36	1.42 1.57	0.09	0.63	0.01
60							15.57	27.79	11.24	12.57	6.69	3.56	4.67	1.49	2.98	0.50	1.71	0.13	0.75	0.02
65									12.17	14.58	7.25	4.13	5.06	1.72	3.23	0.58	1.85	0.15	0.81	0.02
70 75									13.11 14.05	16.73 19.01	7.80 8.36	4.74 5.38	5.45 5.84	1.98 2.25	3.48 3.73	0.66 0.76	1.99 2.13	0.17 0.19	0.88	0.02
80									14.98	21.42	8.92	6.06	6.23	2.53	3.98	0.85	2.28	0.22	1.00	0.03
85									15.92	23.96	9.48	6.78	6.62	2.83	4.23	0.95	2.42	0.24	1.06	0.03
90 95											10.03 10.59	7.54 8.34	7.01 7.40	3.15 3.48	4.48 4.73	1.06 1.17	2.56	0.27	1.13	0.04
100											11.15	9.17	7.79	3.83	4.97	1.29	2.85	0.33	1.25	0.04
110 120											12.26 13.38	10.94 12.85	8.57 9.34	4.57 5.37	5.47 5.97	1.53 1.80	3.13 3.42	0.39 0.46	1.38	0.05
130											14.49	14.90	10.12	6.22	6.47	2.09	3.70	0.46	1.63	0.06
140											15.61	17.09	10.90	7.14	6.96	2.40	3.98	0.62	1.75	0.08
150 160													11.68 12.46	8.11 9.14	7.46 7.96	2.73 3.07	4.27 4.55	0.70 0.79	1.88	0.10
170													13.24	10.23	8.46	3.44	4.84	0.79	2.13	0.12
180													14.02	11.37	8.95	3.82	5.12	0.98	2.25	0.13
190 200													14.80 15.57	12.57 13.82	9.45 9.95	4.22 4.64	5.41 5.69	1.09 1.19	2.38	0.15
225													15.57	13.02	11.19	5.78	6.40	1.49	2.82	0.10
250															12.44	7.02	7.12	1.81	3.13	0.24
275 300															13.68 14.92	8.38 9.84	7.83 8.54	2.15	3.44	0.29
325															16.17	11.41	9.25	2.94	4.07	0.40
350																	9.96	3.37	4.38	0.46
375 400																	10.67 11.39	3.83 4.31	4.69 5.01	0.52 0.58
425																	12.10	4.82	5.32	0.56
450																	12.81	5.36	5.63	0.73
475 500																	13.52 14.23	5.93 6.52	5.95 6.26	0.80
550																	14.23	0.32	6.88	1.05
600																			7.51	1.24

Note: Dark shaded area of chart indicates velocities over 5' per second. Use with caution The velocity values were derived using the following equation: $\mathbf{V} = \frac{0.408 \times Q_{germ}}{d^2}$ Table are based upon the following Hazen-Williams equation: $\mathbf{H}_f = \mathbf{0.2083} \times \left(\frac{100}{C}\right)^{1.852} \times \frac{Q^{1.852}}{D^{1.8655}}$ for change in psi per foot of elevation. Pressure loss for uphill elevation and pressure gain for downhill elevation changes.

191



Polyethylene (PE) SDR Pressure Rated Tube

(2306, 3206, 3306) SDR 7, 9, 11.5, 15 C=140

psi Loss per 100 Feet of Pipe (psi/100 ft.)

Sizes 1/2" through 4" Flow 1 through 600 gpm

Nominal Size	1/2"		3/4"		1"		1 1/4"		1 1/2"		2"		2 1/2"		3"		4"	
Avg. I.D.	0.622 Velocity	1	0.824 Velocity	1	1.049 Velocity	1	1.380 Velocity	1	1.610 Velocity	1	2.067 Velocity	1	2.469	1	3.068 Velocity	1	4.026 Velocity	1
Flow (gpm)	(ft/s)	Loss (psi)	(ft/s)	Loss (psi)	(ft/s)	Loss (psi)	(ft/s)	Loss (psi)	(ft/s)	Loss (psi)	(ft/s)	Loss (psi)	Velocity (ft/s)	Loss (psi)	(ft/s)	Loss (psi)	(ft/s)	Loss (psi)
1	1.05	0.49	0.60	0.12	0.37	0.04	0.21	0.01	0.16	0.00	0.10	0.00	0.07	0.00	0.04	0.00	0.03	0.00
2	2.11	1.76	1.20	0.45	0.74	0.14	0.43	0.04	0.31	0.02	0.19	0.01	0.13	0.00	0.09	0.00	0.05	0.00
3	3.16	3.73	1.80	0.95	1.11	0.29	0.64	0.08	0.47	0.04	0.29	0.01	0.20	0.00	0.13	0.00	0.08	0.00
4	4.22	6.35	2.40	1.62	1.48	0.50	0.86	0.13	0.63	0.06	0.38	0.02	0.27	0.01	0.17	0.00	0.10	0.00
5	5.27 6.33	9.60 13.46	3.00 3.61	2.44 3.43	1.85	0.76 1.06	1.07	0.20	0.79	0.09	0.48	0.03	0.33	0.01	0.22	0.00	0.13	0.00
6 7	7.38	17.91	4.21	4.56	2.60	1.41	1.50	0.28	1.10	0.13	0.57	0.04	0.40	0.02	0.20	0.01	0.13	0.00
8	8.44	22.93	4.81	5.84	2.97	1.80	1.71	0.47	1.26	0.10	0.76	0.03	0.54	0.02	0.35	0.01	0.10	0.00
9	9.49	28.52	5.41	7.26	3.34	2.24	1.93	0.59	1.42	0.28	0.86	0.08	0.60	0.03	0.39	0.01	0.23	0.00
10	10.55	34.67	6.01	8.82	3.71	2.73	2.14	0.72	1.57	0.34	0.95	0.10	0.67	0.04	0.43	0.01	0.25	0.00
11			6.61	10.53	4.08	3.25	2.36	0.86	1.73	0.40	1.05	0.12	0.74	0.05	0.48	0.02	0.28	0.00
12			7.21	12.37	4.45	3.82	2.57	1.01	1.89	0.48	1.15	0.14	0.80	0.06	0.52	0.02	0.30	0.01
14			8.41	16.45	5.19	5.08	3.00	1.34	2.20	0.63	1.34	0.19	0.94	0.08	0.61	0.03	0.35	0.01
16			9.61	21.07	5.93	6.51	3.43	1.71	2.52	0.81	1.53	0.24	1.07	0.10	0.69	0.04	0.40	0.01
18 20			10.82	26.21 31.85	6.67	8.10	3.86 4.28	2.13	2.83 3.15	1.01	1.72	0.30	1.20	0.13	0.78 0.87	0.04	0.45	0.01
20			12.02	31.03	7.42 8.16	9.84 11.74	4.28	3.09	3.46	1.46	2.10	0.36	1.34	0.15	0.87	0.05	0.50	0.01
24					8.90	13.79	5.14	3.63	3.78	1.72	2.10	0.43	1.61	0.18	1.04	0.00	0.53	0.02
26					9.64	16.00	5.57	4.21	4.09	1.99	2.48	0.59	1.74	0.25	1.13	0.09	0.65	0.02
28					10.38	18.35	6.00	4.83	4.41	2.28	2.67	0.68	1.87	0.28	1.21	0.10	0.70	0.03
30					11.12	20.85	6.43	5.49	4.72	2.59	2.86	0.77	2.01	0.32	1.30	0.11	0.76	0.03
35					12.98	27.74	7.50	7.30	5.51	3.45	3.34	1.02	2.34	0.43	1.52	0.15	0.88	0.04
40							8.57	9.35	6.30	4.42	3.82	1.31	2.68	0.55	1.73	0.19	1.01	0.05
45							9.64	11.63	7.08	5.49	4.30	1.63	3.01	0.69	1.95	0.24	1.13	0.06
50							10.71	14.14	7.87	6.68	4.77	1.98	3.35	0.83	2.17	0.29	1.26	0.08
55 60							11.78 12.85	16.87 19.82	8.66 9.44	7.97 9.36	5.25 5.73	2.36	3.68 4.02	0.99 1.17	2.38	0.35	1.38	0.09
65							12.85	19.82	10.23	10.86	6.21	3.22	4.02	1.17	2.82	0.41	1.51	0.11
70									11.02	12.45	6.68	3.69	4.69	1.55	3.03	0.54	1.76	0.13
75									11.81	14.15	7.16	4.19	5.02	1.77	3.25	0.61	1.89	0.16
80									12.59	15.95	7.64	4.73	5.35	1.99	3.47	0.69	2.01	0.18
85									13.38	17.84	8.12	5.29	5.69	2.23	3.68	0.77	2.14	0.21
90											8.59	5.88	6.02	2.48	3.90	0.86	2.27	0.23
95											9.07	6.50	6.36	2.74	4.12	0.95	2.39	0.25
100											9.55	7.15	6.69	3.01	4.33	1.05	2.52	0.28
110 120											10.50 11.46	8.53 10.02	7.36 8.03	3.59 4.22	4.77 5.20	1.25 1.47	3.02	0.33
130											12.41	11.62	8.70	4.22	5.63	1.70	3.02	0.39
140											13.37	13.33	9.37	5.61	6.07	1.95	3.52	0.52
150												. 5.55	10.04	6.38	6.50	2.22	3.78	0.59
160													10.71	7.19	6.94	2.50	4.03	0.67
170													11.38	8.04	7.37	2.79	4.28	0.74
180													12.05	8.94	7.80	3.11	4.53	0.83
190													12.72	9.88	8.24	3.43	4.78	0.92
200													13.39	10.87	8.67	3.78	5.03	1.01
225 250															9.75 10.84	4.70 5.71	5.66 6.29	1.25 1.52
275															11.92	6.81	6.92	1.81
300															13.00	8.00	7.55	2.13
325															14.09	9.28	8.18	2.47
350																	8.81	2.84
375																	9.44	3.22
400																	10.07	3.63
425																	10.70	4.06
450																	11.33	4.52
475																	11.96	4.99
500 550																	12.59 13.84	5.49 6.55
600																	15.10	7.70
550																	13.10	7.70

Note: Dark shaded area of chart indicates velocities over 5' per second. Use with caution

The velocity values were derived using the following equation: $\mathbf{V} = \frac{0.406 \times Q_{gam}}{d^2}$ Table are based upon the following Hazen-Williams equation: $\mathbf{H}_f = 0.2083 \times \left(\frac{100}{C}\right)^{1.852} \times \frac{Q^{1.852}}{D^{4.8655}}$ for change in psi per foot of elevation. Pressure loss for uphill elevation and pressure gain for downhill elevation changes.

Schedule 40 Standard Steel Pipe

C=100

psi Loss per 100 Feet of Pipe (psi/100 ft.)

Sizes 1/2" through 6" Flow 1 through 600 gpm

Nominal Size Pipe OD Avg. ID Avg. Wall	1/2" 0.840 0.622 0.109		3/4" 1.050 0.824 0.113		1" 1.315 1.049 0.133		1 1/4" 1.660 1.380 0.140		1 1/2" 1.900 1.610 0.145		2" 2.375 2.067 0.154		2 1/2" 2.875 2.469 0.203		3" 3.500 3.068 0.216		4" 4.500 4.026 0.237		6" 6.625 6.065 0.280	
Flow (gpm)	Velocity (ft/s)	Loss (psi)	Velocity (ft/s)	Loss (psi)	Velocity (ft/s)	Loss (psi)	Velocity (ft/s)	Loss (psi)	Velocity (ft/s)	Loss (psi)	Velocity (ft/s)	Loss (psi)	Velocity (ft/s)	Loss (psi)	Velocity (ft/s)	Loss (psi)	Velocity (ft/s)	Loss (psi)	Velocity (ft/s)	Loss (psi)
1	1.05	0.91	0.60	0.23	0.37	0.07	0.21	0.02	0.16	0.01	0.10	0.00	0.07	0.00	0.04	0.00	0.03	0.00	0.01	0.00
2	2.11	3.28	1.20	0.84	0.74	0.26	0.43	0.07	0.31	0.03	0.19	0.01	0.13	0.00	0.09	0.00	0.05	0.00	0.02	0.00
3	3.16	6.95	1.80	1.77	1.11	0.55	0.64	0.14	0.47	0.07	0.29	0.02	0.20	0.01	0.13	0.00	0.08	0.00	0.03	0.00
5	4.22 5.27	11.85 17.91	2.40 3.00	3.02 4.56	1.48	0.93	0.86 1.07	0.25	0.63	0.12	0.38	0.03	0.27	0.01	0.17	0.01	0.10	0.00	0.04	0.00
6	6.33	25.10	3.61	6.39	2.22	1.97	1.07	0.52	0.79	0.16	0.48	0.03	0.33	0.02	0.22	0.01	0.15	0.00	0.00	0.00
7	7.38	33.40	4.21	8.50	2.60	2.63	1.50	0.69	1.10	0.33	0.67	0.10	0.47	0.04	0.30	0.01	0.18	0.00	0.08	0.00
8	8.44	42.77	4.81	10.88	2.97	3.36	1.71	0.89	1.26	0.42	0.76	0.12	0.54	0.05	0.35	0.02	0.20	0.00	0.09	0.00
9	9.49	53.19	5.41	13.54	3.34	4.18	1.93	1.10	1.42	0.52	0.86	0.15	0.60	0.06	0.39	0.02	0.23	0.01	0.10	0.00
10	10.55	64.65	6.01	16.45	3.71	5.08	2.14	1.34	1.57	0.63	0.95	0.19	0.67	80.0	0.43	0.03	0.25	0.01	0.11	0.00
11	11.60 12.65	77.14 90.62	6.61 7.21	19.63 23.06	4.08 4.45	6.06 7.12	2.36	1.60 1.88	1.73 1.89	0.75 0.89	1.05	0.22	0.74	0.09	0.48	0.03	0.28	0.01	0.12	0.00
14	12.03	90.02	8.41	30.68	5.19	9.48	3.00	2.50	2.20	1.18	1.13	0.35	0.94	0.11	0.52	0.05	0.35	0.01	0.15	0.00
16			9.61	39.29	5.93	12.14	3.43	3.20	2.52	1.51	1.53	0.45	1.07	0.19	0.69	0.07	0.40	0.02	0.18	0.00
18			10.82	48.87	6.67	15.10	3.86	3.97	2.83	1.88	1.72	0.56	1.20	0.23	0.78	0.08	0.45	0.02	0.20	0.00
20			12.02	59.40	7.42	18.35	4.28	4.83	3.15	2.28	1.91	0.68	1.34	0.28	0.87	0.10	0.50	0.03	0.22	0.00
22 24			13.22	70.87	8.16 8.90	21.89 25.72	4.71	5.76 6.77	3.46 3.78	2.72 3.20	2.10	0.81	1.47	0.34	0.95 1.04	0.12	0.55	0.03	0.24	0.00
26					9.64	29.83	5.14 5.57	7.85	4.09	3.71	2.29	1.10	1.74	0.46	1.04	0.14	0.65	0.04	0.27	0.01
28					10.38	34.22	6.00	9.01	4.41	4.25	2.67	1.26	1.87	0.53	1.21	0.18	0.70	0.05	0.23	0.01
30					11.12	38.88	6.43	10.24	4.72	4.83	2.86	1.43	2.01	0.60	1.30	0.21	0.76	0.06	0.33	0.01
35					12.98	51.72	7.50	13.62	5.51	6.43	3.34	1.91	2.34	0.80	1.52	0.28	0.88	0.07	0.39	0.01
40							8.57	17.44	6.30	8.24	3.82	2.44	2.68	1.03	1.73	0.36	1.01	0.10	0.44	0.01
45 50							9.64 10.71	21.69 26.36	7.08 7.87	10.25 12.45	4.30 4.77	3.04 3.69	3.01	1.28 1.55	1.95 2.17	0.44	1.13	0.12	0.50	0.02
55							11.78	31.45	8.66	14.86	5.25	4.40	3.68	1.85	2.17	0.54	1.38	0.14	0.55	0.02
60							12.85	36.95	9.44	17.45	5.73	5.17	4.02	2.18	2.60	0.76	1.51	0.20	0.67	0.03
65							13.93	42.86	10.23	20.24	6.21	6.00	4.35	2.53	2.82	0.88	1.64	0.23	0.72	0.03
70									11.02	23.22	6.68	6.88	4.69	2.90	3.03	1.01	1.76	0.27	0.78	0.04
75									11.81	26.39	7.16	7.82	5.02	3.29	3.25	1.14	1.89	0.31	0.83	0.04
80 85									12.59 13.38	29.74 33.27	7.64 8.12	8.82 9.86	5.35 5.69	3.71 4.15	3.47 3.68	1.29 1.44	2.01	0.34	0.89	0.05
90									13.30	33.27	8.59	10.96	6.02	4.62	3.90	1.60	2.14	0.43	1.00	0.05
95											9.07	12.12	6.36	5.10	4.12	1.77	2.39	0.47	1.05	0.06
100											9.55	13.33	6.69	5.61	4.33	1.95	2.52	0.52	1.11	0.07
110											10.50	15.90	7.36	6.70	4.77	2.33	2.77	0.62	1.22	0.08
120 130											11.46 12.41	18.68 21.66	8.03 8.70	7.87 9.12	5.20 5.63	2.73 3.17	3.02	0.73 0.85	1.33	0.10
140											13.37	24.85	9.37	10.47	6.07	3.64	3.52	0.83	1.55	0.12
150												2	10.04	11.89	6.50	4.13	3.78	1.10	1.66	0.15
160													10.71	13.40	6.94	4.66	4.03	1.24	1.77	0.17
170													11.38	15.00	7.37	5.21	4.28	1.39	1.89	0.19
180													12.05	16.67	7.80	5.79	4.53	1.54	2.00	0.21
190 200													12.72 13.39	18.43 20.26	8.24 8.67	6.40 7.04	4.78 5.03	1.71 1.88	2.11	0.23
225													13.33	20.20	9.75	8.76	5.66	2.33	2.50	0.20
250															10.84	10.64	6.29	2.84	2.77	0.39
275															11.92	12.70	6.92	3.38	3.05	0.46
300															13.00	14.92	7.55	3.98	3.33	0.54
325																	8.18	4.61	3.60	0.63
350 375																	8.81 9.44	5.29 6.01	3.88 4.16	0.72
400																	10.07	6.77	4.44	0.92
425																	10.70	7.58	4.71	1.03
450																	11.33	8.43	4.99	1.15
475																	11.96	9.31	5.27	1.27
500																	12.59	10.24	5.55	1.39
550 600																			6.10	1.66 1.95

Note: Dark shaded area of chart indicates velocities over 7' per second. Use with caution
The velocity values were derived using the following equation: $V = \frac{0.408 \times Q_{garm}}{d^2}$ Table are based upon the following Hazen-Williams equation: $H_f = 0.2083 \times \left(\frac{100}{C}\right)^{1.852}$ Table are based upon the following Hazen-Williams equation: $H_f = 0.2083 \times \left(\frac{100}{C}\right)^{1.852}$ Table are based upon the following Hazen-Williams equation: $H_f = 0.2083 \times \left(\frac{100}{C}\right)^{1.852}$ Table are based upon the following Hazen-Williams equation: $H_f = 0.2083 \times \left(\frac{100}{C}\right)^{1.852}$ Table are based upon the following Hazen-Williams equation: $H_f = 0.2083 \times \left(\frac{100}{C}\right)^{1.852}$



Type K Copper Water Tube

C=140

psi Loss per 100 Feet of Tube (psi/100 ft.)

Sizes 1/2" 1	through 3" F	low 1 thr	ough 600 gp	om														
Nominal Size Pipe OD Avg. ID Avg. Wall	1/2" 0.625 0.5270 0.049		5/8" 0.750 0.652 0.049		3/4" 0.875 0.745 0.065		1" 1.125 0.995 0.065		1 1/4" 1.375 1.245 0.065		1 1/2" 1.625 1.481 0.072		2" 2.125 1.959 0.083		2 1/2" 2.625 2.435 0.095		3" 3.125 2.907 0.109	
Flow (gpm)	Velocity (ft/s)	Loss (psi)	Velocity (ft/s)	Loss (psi)	Velocity (ft/s)	Loss (psi)	Velocity (ft/s)	Loss	Velocity (ft/s)	Loss (psi)	Velocity (ft/s)	Loss (psi)	Velocity (ft/s)	Loss	Velocity (ft/s)	Loss (psi)	Velocity (ft/s)	Loss (psi)
1	1.47	1.09	0.96	0.39	0.74	0.20	0.41	(psi) 0.05	0.26	0.02	0.19	0.01	0.11	(psi) 0.00	0.07	0.00	0.05	0.00
2	2.94	3.94	1.92	1.40	1.47	0.73	0.82	0.18	0.53	0.06	0.37	0.03	0.21	0.01	0.14	0.00	0.10	0.00
3	4.41	8.35	2.88	2.97	2.21	1.55	1.24	0.38	0.79	0.13	0.56	0.05	0.32	0.01	0.21	0.00	0.14	0.00
4	5.88	14.23	3.84	5.05	2.94	2.64	1.65	0.65	1.05	0.22	0.74	0.09	0.43	0.02	0.28	0.01	0.19	0.00
5	7.35	21.51	4.80	7.64	3.68	3.99	2.06	0.98	1.32	0.33	0.93	0.14	0.53	0.04	0.34	0.01	0.24	0.01
7	8.81 10.28	30.15 40.12	5.76 6.72	10.70 14.24	4.41 5.15	5.59 7.44	2.47 2.88	1.37 1.82	1.58 1.84	0.46	1.12 1.30	0.20	0.64 0.74	0.05	0.41	0.02	0.29	0.01
8	11.75	51.37	7.68	18.24	5.88	9.53	3.30	2.33	2.11	0.01	1.49	0.20	0.74	0.07	0.46	0.02	0.34	0.01
9	13.22	63.90	8.64	22.68	6.62	11.85	3.71	2.90	2.37	0.97	1.67	0.42	0.96	0.11	0.62	0.04	0.43	0.02
10	14.69	77.66	9.60	27.57	7.35	14.41	4.12	3.52	2.63	1.18	1.86	0.51	1.06	0.13	0.69	0.05	0.48	0.02
11			10.56	32.89	8.09	17.19	4.53	4.21	2.90	1.41	2.05	0.61	1.17	0.16	0.76	0.05	0.53	0.02
12			11.52	38.64	8.82	20.20	4.95	4.94	3.16	1.66	2.23	0.71	1.28	0.18	0.83	0.06	0.58	0.03
14 16			13.44 15.36	51.41 65.83	10.29 11.76	26.87 34.41	5.77 6.59	6.57 8.42	3.69 4.21	2.21	2.60 2.98	0.95 1.22	1.49 1.70	0.24	0.96 1.10	0.08	0.68 0.77	0.04
18			17.28	81.88	13.23	42.80	7.42	10.47	4.74	3.52	3.35	1.51	1.91	0.39	1.10	0.11	0.77	0.05
20			17.20	01.00	14.70	52.02	8.24	12.72	5.26	4.28	3.72	1.84	2.13	0.47	1.38	0.16	0.97	0.07
22					16.17	62.06	9.07	15.18	5.79	5.10	4.09	2.19	2.34	0.56	1.51	0.19	1.06	0.08
24					17.64	72.91	9.89	17.84	6.32	5.99	4.46	2.58	2.55	0.66	1.65	0.23	1.16	0.10
26							10.71	20.69	6.84	6.95	4.84	2.99	2.76	0.77	1.79	0.27	1.26	0.11
30							11.54 12.36	23.73 26.96	7.37 7.90	7.97 9.06	5.21 5.58	3.43 3.89	2.98 3.19	0.88 1.00	1.93 2.06	0.30	1.35 1.45	0.13
35							14.42	35.87	9.21	12.05	6.51	5.18	3.72	1.33	2.00	0.33	1.69	0.15
40							16.48	45.94	10.53	15.43	7.44	6.63	4.25	1.70	2.75	0.59	1.93	0.15
45									11.84	19.20	8.37	8.25	4.78	2.11	3.10	0.73	2.17	0.31
50									13.16	23.33	9.30	10.03	5.32	2.57	3.44	0.89	2.41	0.38
55									14.48	27.84	10.23	11.96	5.85	3.07	3.78	1.06	2.66	0.45
60									15.79 17.11	32.70 37.93	11.16 12.09	14.05 16.30	6.38 6.91	3.60 4.18	4.13 4.47	1.25 1.45	2.90 3.14	0.53
70									18.43	43.51	13.02	18.70	7.44	4.79	4.47	1.66	3.38	0.70
75									10.73	75.51	13.95	21.24	7.97	5.45	5.16	1.89	3.62	0.80
80											14.88	23.94	8.51	6.14	5.50	2.13	3.86	0.90
85											15.81	26.79	9.04	6.87	5.85	2.38	4.10	1.01
90											16.74	29.78	9.57	7.63	6.19	2.65	4.35	1.12
95											17.67	32.91	10.10	8.44	6.54	2.93	4.59	1.24
100 110											18.60	36.19	10.63 11.69	9.28 11.07	6.88 7.57	3.22 3.84	4.83 5.31	1.36
120													12.76	13.01	8.26	4.51	5.79	1.91
130													13.82	15.08	8.95	5.23	6.28	2.21
140													14.88	17.30	9.63	6.00	6.76	2.54
150													15.95	19.66	10.32	6.82	7.24	2.88
160 170													17.01 18.07	22.16 24.79	11.01 11.70	7.69 8.60	7.72 8.21	3.25 3.63
180													10.07	24./9	12.39	9.56	8.69	4.04
190															13.07	10.57	9.17	4.46
200															13.76	11.62	9.66	4.91
225															15.48	14.46	10.86	6.10
250															17.20	17.57	12.07	7.42
275															18.92	20.96	13.28	8.85
300 325																	14.48 15.69	10.40 12.06
350																	16.90	13.84
375																	18.11	15.72
400																	19.31	17.72
425																		
450																		
475 500																		
550																		

Note: Dark shaded area of chart indicates velocities over 7' per second. Use with caution The velocity values were derived using the following equation: $\mathbf{V} = \frac{0.406 \times Q_{girm}}{d^2}$ Table are based upon the following Hazen-Williams equation: $\mathbf{H}_{f} = 0.2083 \times \left(\frac{100}{C}\right)^{1.852} \times \frac{Q^{1.852}}{Q^{1.8055}}$ for change in psi per foot of elevation. Pressure loss for uphill elevation and pressure gain for downhill elevation changes.

Index

Resource

Index

1" & 1½ " High Flow Inline Pressure Regulators 160
. a 1/2 ingition illine i ressure negalaters i i i i i i
1/4" Barb Transfer Fittings147
1/4" Landscape Dripline
14" Self-Piercing Barb Connector
1/4" Tubing Stake with Cap
1.5" Inline Commercial Control Zone Kit 156
6 Outlet Manifold - EMT-6Xeri
10-32 Thread Adapter
12" PolyFlex Riser
24 VAC Solenoid Valves Wire Sizing – 50Hz79
24 VAC Solenoid Valves Wire Sizing – 60Hz
300-BPES Brass Valves
1300A-F
1400 Series
1800°-EXT
1800® NP Cover
1800 PCS
1800°-SAM-P45 Series
1800° Series
1800 Xeri-Bubbler Adapter
2045A Maxi-Paw™ and 2045-PJ Maxi-Bird™
3500 Series
5000 Series
5000 Series MPR Nozzles
8005 Series53
½" FPT x Barb Grey Transfer Fitting
Air/Vacuum Relief Valve Kit
Anemometer Wind Sensor
ASVF Series65
Basin Adapters and Accessories
Channel Drain Corners and Tees181
Channel Drain End Caps, End Outlets
and Leaf Guards181
Channel Drain In-Line Pits
Channel Drains
CLP Series
Commercial Valve Wire Sizing Procedure
Controller Pedestals
Control Zone Kits
Control Zone Kit Selection Guide
Customer Service
Diffuser Bug Cap
DPU-210 Decoder Programming Unit94
DPU-210 Decoder Programming Unit94 Drainage Pop-Up Valves
DPU-210 Decoder Programming Unit .94 Drainage Pop-Up Valves 182 Drip System Operation Indicator 142
DPU-210 Decoder Programming Unit. .94 Drainage Pop-Up Valves .182 Drip System Operation Indicator .142 DV / DVF Series .63
DPU-210 Decoder Programming Unit. .94 Drainage Pop-Up Valves .182 Drip System Operation Indicator .142 DV / DVF Series .63 Easy Fit Compression Fitting System .141
DPU-210 Decoder Programming Unit. .94 Drainage Pop-Up Valves .182 Drip System Operation Indicator .142 DV / DVF Series .63 Easy Fit Compression Fitting System .141 EFB-CP Series Brass Valves .73
DPU-210 Decoder Programming Unit .94 Drainage Pop-Up Valves .182 Drip System Operation Indicator .142 DV / DVF Series .63 Easy Fit Compression Fitting System .141 EFB-CP Series Brass Valves .73 ESP-9V Series .88
DPU-210 Decoder Programming Unit .94 Drainage Pop-Up Valves .182 Drip System Operation Indicator .142 DV / DVF Series .63 Easy Fit Compression Fitting System .141 EFB-CP Series Brass Valves .73 ESP-9V Series .88 ESP-LXD Decoder Controller .91
DPU-210 Decoder Programming Unit .94 Drainage Pop-Up Valves .182 Drip System Operation Indicator .142 DV / DVF Series .63 Easy Fit Compression Fitting System .141 EFB-CP Series Brass Valves .73 ESP-9V Series .88
DPU-210 Decoder Programming Unit. .94 Drainage Pop-Up Valves .182 Drip System Operation Indicator .142 DV / DVF Series .63 Easy Fit Compression Fitting System .141 EFB-CP Series Brass Valves. .73 ESP-9V Series. .88 ESP-LXD Decoder Controller .91 ESP-LXME/F Controllers .90
DPU-210 Decoder Programming Unit. .94 Drainage Pop-Up Valves .182 Drip System Operation Indicator .142 DV / DVF Series .63 Easy Fit Compression Fitting System .141 EFB-CP Series Brass Valves .73 ESP-9V Series .88 ESP-LXD Decoder Controller .91 ESP-LXME/F Controllers .90 ESP-ME3 and ESP-Me Series Controllers .87
DPU-210 Decoder Programming Unit. .94 Drainage Pop-Up Valves .182 Drip System Operation Indicator .142 DV / DVF Series .63 Easy Fit Compression Fitting System .141 EFB-CP Series Brass Valves .73 ESP-9V Series .88 ESP-LXD Decoder Controller .91 ESP-LXME/F Controllers .90 ESP-ME3 and ESP-Me Series Controllers .87 ESP-TM2 Series Controller .86
DPU-210 Decoder Programming Unit. .94 Drainage Pop-Up Valves .182 Drip System Operation Indicator .142 DV / DVF Series .63 Easy Fit Compression Fitting System .141 EFB-CP Series Brass Valves .73 ESP-9V Series .88 ESP-LXD Decoder Controller .91 ESP-LXME/F Controllers .90 ESP-ME3 and ESP-Me Series Controllers .87 ESP-TM2 Series Controller .86 Expanded Models .166
DPU-210 Decoder Programming Unit. .94 Drainage Pop-Up Valves .182 Drip System Operation Indicator .142 DV / DVF Series .63 Easy Fit Compression Fitting System .141 EFB-CP Series Brass Valves .73 ESP-9V Series .88 ESP-LXD Decoder Controller .91 ESP-LXME/F Controllers .90 ESP-MB3 and ESP-Me Series Controllers .87 ESP-TM2 Series Controller .86 Expanded Models .166 Falcon® 6504 Series .49
DPU-210 Decoder Programming Unit. .94 Drainage Pop-Up Valves .182 Drip System Operation Indicator .142 DV / DVF Series .63 Easy Fit Compression Fitting System .141 EFB-CP Series Brass Valves .73 ESP-9V Series .88 ESP-LXD Decoder Controller .91 ESP-MES and ESP-Me Series Controllers .90 ESP-MB3 and ESP-Me Series Controllers .87 ESP-TM2 Series Controller .86 Expanded Models .166 Falcon* 6504 Series .49 FD-TURF Two-Wire Decoders .93 Flex Pipe .178 Flex Pipe Fittings and Accessories .179
DPU-210 Decoder Programming Unit. .94 Drainage Pop-Up Valves .182 Drip System Operation Indicator .142 DV / DVF Series .63 Easy Fit Compression Fitting System .141 EFB-CP Series Brass Valves .73 ESP-9V Series .88 ESP-LXD Decoder Controller .91 ESP-LXME/F Controllers .90 ESP-MB3 and ESP-Me Series Controllers .87 ESP-TM2 Series Controller .86 Expanded Models .166 Falcon® 6504 Series .49 FD-TURF Two-Wire Decoders .93 Flex Pipe .178 Flex Pipe Fittings and Accessories .179 Flow Sensors and Transmitters .96
DPU-210 Decoder Programming Unit. .94 Drainage Pop-Up Valves .182 Drip System Operation Indicator .142 DV / DVF Series .63 Easy Fit Compression Fitting System .141 EFB-CP Series Brass Valves .73 ESP-9V Series .88 ESP-LXD Decoder Controller .91 ESP-LXME/F Controllers .90 ESP-ME3 and ESP-Me Series Controllers .87 ESP-TM2 Series Controller .86 Expanded Models .166 Falcon* 6504 Series .49 D-TURF Two-Wire Decoders .93 Flex Pipe .178 Flex Pipe Fittings and Accessories .179 Flow Sensors and Transmitters .96 Galvanized Tie-Down Stake .147
DPU-210 Decoder Programming Unit. .94 Drainage Pop-Up Valves .182 Drip System Operation Indicator .142 DV / DVF Series .63 Easy Fit Compression Fitting System .141 EFB-CP Series Brass Valves .73 ESP-9V Series .88 ESP-LXD Decoder Controller .91 ESP-LXME/F Controllers .90 ESP-ME3 and ESP-Me Series Controllers .87 ESP-TM2 Series Controller .86 Expanded Models .166 Falcon® 6504 Series .49 FD-TURF Two-Wire Decoders .93 Flex Pipe .178 Flex Pipe Fittings and Accessories .179 Flow Sensors and Transmitters .96 Galvanized Tie-Down Stake .147 HE-VAN Series Nozzles .21
DPU-210 Decoder Programming Unit. .94 Drainage Pop-Up Valves .182 Drip System Operation Indicator .142 DV / DVF Series .63 Easy Fit Compression Fitting System .141 EFB-CP Series Brass Valves .73 ESP-9V Series .88 ESP-LXD Decoder Controller .91 ESP-LXME/F Controllers .90 ESP-ME3 and ESP-Me Series Controllers .87 ESP-TM2 Series Controller .86 Expanded Models .166 Falcon* 6504 Series .49 FD-TURF Two-Wire Decoders .93 Flex Pipe .178 Flex Pipe Fittings and Accessories .179 Flow Sensors and Transmitters .96 Galvanized Tie-Down Stake .147 HE-VAN Series Nozzles .21 High Flow Commercial Control Zone Kit with 2
DPU-210 Decoder Programming Unit. .94 Drainage Pop-Up Valves .182 Drip System Operation Indicator .142 DV / DVF Series .63 Easy Fit Compression Fitting System .141 EFB-CP Series Brass Valves .73 ESP-9V Series .88 ESP-LXD Decoder Controller .91 ESP-LXME/F Controllers .90 ESP-ME3 and ESP-Me Series Controllers .87 ESP-TM2 Series Controller .86 Expanded Models .166 Falcon® 6504 Series .49 FD-TURF Two-Wire Decoders .93 Flex Pipe .178 Flex Pipe Fittings and Accessories .179 Flow Sensors and Transmitters .96 Galvanized Tie-Down Stake .147 HE-VAN Series Nozzles .21

low to Use This Catalog	18
IV Series	
nline Pressure Regulators	
nline RBY Filter	
nternet Connected Water Meters (ICWM)	
Q NCC Network Communication Cartridge	
Q™ v3.0 Central Control Software	
andscape Drip System Overviewarge-Capacity Filters	
NK WiFi Module	
ocking Cover Key	
ow Flow Control Zone Kits with Anti-Siphon Valve	
ow Flow Control Zone Kits with Anti-Siphon Valve and PR Filter	.15
ow Flow Control Zone Kits with PR Filter	15
ow Flow Valves	
ow Profile Pump Stations – LP Series	
ow to Medium Flow Pump Stations – D-Series	
Main Irrigation Pump Stations	
Maxicom ^{2®} Hardware	
Maxicom® version 4.4 now available Medium Flow Control Zone Kits with Anti-Siphon	.10
Valve and PR Filter	.15
Medium Flow Control Zone Kits with PR Filter	
Nedium Flow Pump Station	16
/IPR Spray Nozzles	
⁄lulti-Outlet Xeri-Bug™	
Online Control Zone Kit Selection Guide	
A	
'A-8S-PRS & PA-8S-P45 'A-80	
PBCLXD Programming Backup Cartridge for ESP-LXD	
C Diffuser Caps119	
PEB / PESB Series	
ESB-R Series Valves	7
GA Series	6
Plastic Round Grates	
lastic Square Grates	
PolyFlex Riser and Adapter Assemblies	
olyFlex Riser and Stake Assembly	
Pressure-Compensating Modules	. 110
Regulating Basket Filters	.16
ressure-Regulating Filter (RBY)	
RS-Dial	
ump Manager with SmartPump™	
ump Start Relays	
Purple Valve Handle Assembly	
VB Professional Series Valve Boxes	
NF Dripline Header Quick-Check Basket Filter	
Quick-Coupling Valves	
tain Bird® ACLP Series	
ain Bird Drainage Products	
ain Bird Rewards	
tain Bird Series Channel Drainage	
Rain Bird Training Services	
RD1800™ Series Spray Heads	
letrofit Pressure Regulators	
lotor Tool	
Round Catch Basins	
SD-BEx	
-VAN Nozzles	
M/C (Poot Matering System)	12

B Series Spiral Barb Fittings	1
H Series	
iteControl1	0
iteControl Hardware1	0
MRT-Y Soil Moisture Sensor Kit1	0
pray-to-Drip Retrofit Kit	6
pread Spectrum Radio1	1
PX Series Swing Pipe	
Q Series, Square Pattern Nozzles	2
quare Basin Kits1	7
quare Catch Basins1	
quare Low-Profile Basins	
ubterranean Emitter Box1	
uggested Applications	2
BOS-BT	
echnical Support13	
SJ/TSJ-PRS Series	
ubing Cutter1	
ubing Goof Plug1	
wist Lock Fittings1	
INI-Spray™ Series	
Iniversal ¼" Tubing Stake1	
Iniversal Square Grates	
l-Series Nozzles	
alve Keys	
AN Series Nozzles	
B Series Valve Boxes	
VC Series Wire Connector	7
Vide Flow Commercial Control Zone Kit with	_
Pressure Regulating, Basket Filter	
Vide Flow Commercial Control Zone Kit with Scrubber	
Valve & Pressure Regulating, Basket Filter	
Vorry-Free Warranties	
VS-PRO Weather Stations	
BS - Black Stripe Tubing	
eri-Bird™ 8-Outlet Emission Device	
eri-Bubblers TM	2
eri-Bug™ Emitters1	2
eri-Bug™ Emitters	2 1 1
eri-Bug™ Emitters	2 1 1 2
eri-Bug™ Emitters	1 1 2 2
eri-Bug™ Emitters	2 1 2 2
eri-Bug™ Emitters	1 1 2 2 3
eri-Bug™ Emitters	1 1 2 2 3
eri-Bug™ Emitters	1 1 2 2 3 4
eri-Bug™ Emitters	2 1 1 2 2 3 4 4
eri-Bug™ Emitters	2 1 1 2 2 3 3 4 4 3
eri-Bug™ Emitters	2 1 1 2 2 3 3 4 4 3
eri-Bug™ Emitters	2 1 1 2 2 2 3 3 4 4 3 4
eri-Bug™ Emitters	2 1 1 2 2 2 3 3 4 4 3 4 3
eri-Bug™ Emitters	2 1 1 2 2 2 3 3 4 4 3 4 3 5
eri-Bug™ Emitters	2 1 1 2 2 2 3 3 4 4 3 4 3 5 4

The Intelligent Use of Water.™

LEADERSHIP • EDUCATION • PARTNERSHIPS • PRODUCTS

At Rain Bird, we believe it is our responsibility to develop products and technologies that use water efficiently. Our commitment also extends to education, training and services for our industry and our communities.

The need to conserve water has never been greater. We want to do even more, and with your help, we can. Visit www.rainbird.com for more information about The Intelligent Use of Water."



Rain Bird Corporation

6991 E. Southpoint Road Tucson, AZ 85756 Phone: (520) 741-6100 Fax: (520) 741-6522

Rain Bird Technical Services

(800) RAINBIRD (1-800-724-6247) (U.S. and Canada)

Rain Bird Corporation

970 West Sierra Madre Avenue Azusa, CA 91702 Phone: (626) 812-3400 Fax: (626) 812-3411

www.rainbird.com

Rain Bird International, Inc.

1000 West Sierra Madre Azusa, CA 91702 Phone: (626) 963-9311 Fax: (626) 852-7343